

SAFETY DATA SHEET

1. Identification

Product identifier	Repair Compound Hardener	
Other means of identification		
SKU#	DM004H	
Recommended use	Not available.	
Recommended restrictions	Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.	
Manufacturer/Importer/Supplier/Distributor information		
Manufacturer		
Company name	ITW Performance Polymers	
Address	130 Commerce Drive Montgomeryville, PA 18936 United States	
Telephone	Customer Service	215-855-8450
Website	www.itwperformancepolymers.com	
E-mail	Not available.	
Contact person	EHS Department	
Emergency phone number	CHEMTREC	800-424-9300
	International	703-527-3887

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Acute toxicity, oral	Category 4
	Acute toxicity, dermal	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Sensitization, skin	Category 1
Environmental hazards	Hazardous to the aquatic environment, long-term hazard	Category 3
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Warning
Hazard statement	Harmful if swallowed. Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.
Precautionary statement	
Prevention	Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear eye protection/face protection. Wear protective gloves/protective clothing.
Response	If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth. If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
Storage	Not available.

Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	93.79356% of the mixture consists of component(s) of unknown acute oral toxicity. 96.09756% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 96.09756% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Talc		14807-96-6	30 - 60
Amidoamine	Fatty acids, tall-oil, reaction products with tetraethylenepentamine	Trade Secret	10 - 30
3,6,9-triazaundecamethylenediamine	3,6,9-triazaundecamethyleendiamine	112-57-2	1 - 5
Silicon Dioxide	Silica, amorphous, fumed, cryst.-free	112945-52-5	1 - 5
Quartz		14808-60-7	0.1 - 1
Other components below reportable levels			10 - 30

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical advice/attention if you feel unwell. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Use water spray to cool unopened containers.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	--

Methods and materials for containment and cleaning up

Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Following product recovery, flush area with water.

Small Spills: Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage**Precautions for safe handling**

Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Quartz (CAS 14808-60-7)	PEL	0.05 mg/m3

US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)

Components	Type	Value	Form
Quartz (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
Silicon Dioxide (CAS 112945-52-5)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Talc (CAS 14807-96-6)	TWA	0.8 mg/m3	
		0.1 mg/m3	Respirable.
		20 mppcf	
		2.4 mppcf	Respirable.

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value	Form
Quartz (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Components	Type	Value
Silicon Dioxide (CAS 112945-52-5)	IDLH	3000 mg/m3
Talc (CAS 14807-96-6)	IDLH	1000 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL)

Components	Type	Value	Form
Quartz (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
Silicon Dioxide (CAS 112945-52-5)	TWA	6 mg/m3	
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable.

US. OARS. Workplace Environmental Exposure Level (WEEL) Guide

Components	Type	Value	Form
3,6,9-triazaundecamethylenediamine (CAS 112-57-2)	TWA	5 mg/m3	Aerosol.
		1 ppm	Aerosol.
Biological limit values	No biological exposure limits noted for the ingredient(s).		
Exposure guidelines	Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled. Occupational Exposure Limits are not relevant to the current physical form of the product.		
US WEEL Guides: Skin designation			
3,6,9-triazaundecamethylenediamine (CAS 112-57-2)		Can be absorbed through the skin.	
Appropriate engineering controls	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.		
Individual protection measures, such as personal protective equipment			
Eye/face protection	Wear safety glasses with side shields (or goggles). Face shield is recommended.		
Skin protection			
Hand protection	Wear appropriate chemical resistant gloves.		
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.		
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.		
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.		
General hygiene considerations	Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.		

9. Physical and chemical properties

Appearance	Paste.
Physical state	Solid.
Form	Solid. Paste.
Color	Cream
Odor	Amine-like. Mild.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	>200.0 °F (>93.3 °C) Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	0.24 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.

Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	1.55 g/cm ³
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	1.55

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	No adverse effects due to inhalation are expected.
Skin contact	Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
---	---

Information on toxicological effects

Acute toxicity	Harmful in contact with skin. Harmful if swallowed.
-----------------------	---

Components	Species	Test Results
3,6,9-triazaundecamethylenediamine (CAS 112-57-2)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	0.66 g/kg
Silicon Dioxide (CAS 112945-52-5)		
<u>Acute</u>		
Oral		
LD50	Rat	> 22500 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	May cause an allergic skin reaction.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	

Carcinogenicity

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled. Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

Quartz (CAS 14808-60-7)	1 Carcinogenic to humans.
Silicon Dioxide (CAS 112945-52-5)	3 Not classifiable as to carcinogenicity to humans.
Talc (CAS 14807-96-6)	2B Possibly carcinogenic to humans.
	3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz (CAS 14808-60-7)	Cancer
-------------------------	--------

US. National Toxicology Program (NTP) Report on Carcinogens

Quartz (CAS 14808-60-7)	Known To Be Human Carcinogen.
-------------------------	-------------------------------

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

3,6,9-triazaundecamethylenediamine 1.503

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz (CAS 14808-60-7) Cancer
lung effects
immune system effects
kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

Yes

Classified hazard categories Acute toxicity (any route of exposure)
Skin corrosion or irritation
Serious eye damage or eye irritation
Respiratory or skin sensitization

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Phenol	108-95-2	0.1 - 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

California Proposition 65



WARNING: This product can expose you to chemicals including Talc, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Quartz (CAS 14808-60-7) Listed: October 1, 1988
Talc (CAS 14807-96-6) Listed: April 1, 1990

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	03-04-2014
Revision date	08-30-2024
Version #	13
HMIS® ratings	Health: 3 Flammability: 1 Physical hazard: 0 Personal protection: X
NFPA ratings	Health: 3 Flammability: 1 Instability: 0
Disclaimer	ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.
Revision information	Product and Company Identification: Product Registration Numbers Physical & Chemical Properties: Multiple Properties