# SAFETY DATA SHEET

## 1. Identification

Product identifier Repair Compound Resin

Other means of identification

SKU# DM004R

Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Performance Polymers
Address 130 Commerce Drive
Montgomeryville, PA 18936

**United States** 

**Telephone** Customer Service 215-855-8450

Website www.itwperformancepolymers.com

E-mail Not available.

Contact person EHS Department

Emergency phone number CHEMTREC 800-424-9300

International 703-527-3887

# 2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, dermal Category 4

Skin corrosion/irritation

Serious eye damage/eye irritation

Sensitization, skin

Category 2

Category 2

Sensitization, skin

Category 1

Hazardous to the aquatic environment,

Category 2

long-term hazard

OSHA defined hazards Not classified.

Label elements

**Environmental hazards** 



Signal word Warning

Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes

serious eye irritation. Toxic to aquatic life with long lasting effects.

**Precautionary statement** 

Prevention Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Contaminated

work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear

eye protection/face protection. Wear protective gloves/protective clothing.

**Response** If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take

off contaminated clothing and wash before reuse. Collect spillage.

**Storage** Store away from incompatible materials.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Material name: Repair Compound Resin

SDS US

93.12% of the mixture consists of component(s) of unknown acute oral toxicity. 98.22% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 39.18% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Epoxy Resin:reaction Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)		25068-38-6	30 - 60
Limestone		1317-65-3	10 - 30
Talc		14807-96-6	5 - 15
Cyclic ester		14228-73-0	1 - 5
Silicon Dioxide		112945-52-5	1 - 5
Carbon Black		1333-86-4	0.1 - 1
Quartz		14808-60-7	0.1 - 1
Other components below reportable levels			1 - 5

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. Get medical advice/attention if you feel unwell. In case of eczema or other skin disorders: Seek medical

advice/attention if you feel unwell. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical advice/attention if you feel unwell.

**Most important**Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis.

delayed

Indication of immediate medical attention and special treatment needed

**General information** 

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Use water spray to cool unopened containers.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

**General fire hazards** No unusual fire or explosion hazards noted.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: Repair Compound Resin

# Methods and materials for containment and cleaning up

Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

## **Environmental precautions**

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

Precautions for safe handling

Avoid contact with eyes, skin, and clothing. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

## Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	Form
Carbon Black (CAS 1333-86-4)	PEL	3.5 mg/m3	
Limestone (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction
		15 mg/m3	Total dust.
Quartz (CAS 14808-60-7)	PEL	0.05 mg/m3	
US. OSHA Table Z-3 (29 CFR 1910.1	1000)		
Components	Туре	Value	Form
Quartz (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
Silicon Dioxide (CAS 112945-52-5)	TWA	0.8 mg/m3	
		20 mppcf	
Talc (CAS 14807-96-6)	TWA	0.1 mg/m3	Respirable.
		20 mppcf	
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
Carbon Black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Quartz (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction
US. NIOSH: Pocket Guide to Chemi	cal Hazards		
Components	Туре	Value	Form
Carbon Black (CAS 1333-86-4)	TWA	0.1 mg/m3	
Limestone (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Quartz (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.

Material name: Repair Compound Resin

SDS US

DM004R Version #: 06 Revision date: 06-20-2018 Issue date: 10-14-2013

US. NIOSH: Pocket Guide to Chemical Hazards
Components Type

Silicon Dioxide (CAS TWA 6 mg/m3

112945-52-5)

Talc (CAS 14807-96-6) TWA 2 mg/m3 Respirable.

**Biological limit values**No biological exposure limits noted for the ingredient(s).

**Exposure guidelines**Occupational Exposure Limits are not relevant to the current physical form of the product.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Value

**Form** 

Individual protection measures, such as personal protective equipment

**Eye/face protection** Face shield is recommended. Wear safety glasses with side shields (or goggles).

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

**Respiratory protection** In case of insufficient ventilation, wear suitable respiratory equipment.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

## 9. Physical and chemical properties

Appearance Paste.
Physical state Solid.

Form Solid. Paste.

ColorBlueOdorSlight.

Odor thresholdNot available.pHNot available.Melting point/freezing pointNot available.

Initial boiling point and boiling

range

> 500 °F (> 260 °C)

Flash point > 400.0 °F (> 204.4 °C) Pensky-Martens Closed Cup

Evaporation rate < 1 BuAc
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 0.03 mm Hg

Vapor density > 1

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

**Decomposition temperature** Not available. **Viscosity** Not available.

Other information

Density12.08 lb/galExplosive propertiesNot explosive.Oxidizing propertiesNot oxidizing.

Specific gravity 1.45 VOC 0 g/l

## 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with

incompatible materials.

**Incompatible materials** Strong oxidizing agents.

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

## 11. Toxicological information

## Information on likely routes of exposure

**Inhalation** No adverse effects due to inhalation are expected.

**Skin contact** Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.

**Eye contact** Causes serious eye irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skip irritation. May cause redness and pain. May cause an allernic skip reaction.

vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis. Rash.

## Information on toxicological effects

Acute toxicity Harmful in contact with skin.

Components Species Test Results

Carbon Black (CAS 1333-86-4)

Acute Oral

LD50 Rat > 8000 mg/kg

Silicon Dioxide (CAS 112945-52-5)

Acute Oral

LD50 Rat > 22500 mg/kg

**Skin corrosion/irritation** Causes skin irritation.

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** May cause an allergic skin reaction.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure.

## IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon Black (CAS 1333-86-4) 2B Possibly carcinogenic to humans.

Quartz (CAS 14808-60-7) 1 Carcinogenic to humans.

Silicon Dioxide (CAS 112945-52-5)

3 Not classifiable as to carcinogenicity to humans.

Talc (CAS 14807-96-6) 2B Possibly carcinogenic to humans.

Material name: Repair Compound Resin

cinogenic to numaris.

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Quartz (CAS 14808-60-7)

US. National Toxicology Program (NTP) Report on Carcinogens

Quartz (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Not an aspiration hazard. **Aspiration hazard** 

**Chronic effects** Prolonged exposure may cause chronic effects.

12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

No data available. Mobility in soil

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

**IATA** 

UN3077 **UN number** 

UN proper shipping name Environmentally hazardous substance, solid, n.o.s. (Epoxy Resin)

Transport hazard class(es)

Class 9 Subsidiary risk Ш Packing group **Environmental hazards** Yes 9L **ERG Code** 

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

**IMDG** 

**UN number** UN3077

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Epoxy Resin), MARINE **UN proper shipping name** 

**POLLUTANT** 

Transport hazard class(es)

9 Class

Subsidiary risk Packing group Ш

**Environmental hazards** 

Marine pollutant Yes F-A, S-F **EmS** 


Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Not applicable.

Transport in bulk according to

Annex II of MARPOL 73/78 and the IBC Code

IATA; IMDG



## Marine pollutant



**General information** IMDG Regulated Marine Pollutant.

## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Cancer Quartz (CAS 14808-60-7) lung effects

immune system effects

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Yes

Classified hazard

Skin corrosion or irritation

categories

Serious eye damage or eye irritation Respiratory or skin sensitization

Acute toxicity (any route of exposure)

SARA 313 (TRI reporting)

Not regulated.

## Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

#### US state regulations

## **California Proposition 65**



WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of

California to cause cancer. For more information go to www.P65Warnings.ca.gov.

#### California Proposition 65 - CRT: Listed date/Carcinogenic substance

Carbon Black (CAS 1333-86-4) Listed: February 21, 2003 Ethyl Benzene (CAS 100-41-4) Listed: June 11, 2004 Quartz (CAS 14808-60-7) Listed: October 1, 1988

## US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Carbon Black (CAS 1333-86-4) Quartz (CAS 14808-60-7) Talc (CAS 14807-96-6)

#### **International Inventories**

**Philippines** 

**HMIS®** ratings

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI) Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

Philippine Inventory of Chemicals and Chemical Substances

## 16. Other information, including date of preparation or last revision

10-14-2013 Issue date 06-20-2018 Revision date

Version # 06

Health: 2

Flammability: 1 Physical hazard: 1

NFPA ratings Health: 2

> Flammability: 1 Instability: 1

DM004R Version #: 06 Revision date: 06-20-2018 Issue date: 10-14-2013

Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

#### **Disclaimer**

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

**Revision information** 

This document has undergone significant changes and should be reviewed in its entirety.

SDS US

DM004R Version #: 06 Revision date: 06-20-2018 Issue date: 10-14-2013