

Revision Date: 11/16/2022

# SAFETY DATA SHEET

#### 1. Identification

Material name: CONCRETE SURFACE RETARDER F

Material: 080A 05

Recommended use and restriction on use

Recommended use: Coatings Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

EUCLID CHEMICAL COMPANY 19218 REDWOOD ROAD CLEVELAND OH 44110

US

**Contact person:** EH&S Department **Telephone:** 216-531-9222

**Emergency telephone number:** 1-800-424-9300 (US); 1-613-996-6666 (Canada)

#### 2. Hazard(s) identification

#### **Hazard Classification**

#### **Physical Hazards**

Flammable liquids Category 3

#### **Health Hazards**

Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2B
Carcinogenicity Category 1B
Aspiration Hazard Category 1

#### **Unknown toxicity - Health**

Acute toxicity, oral 7.32 %
Acute toxicity, dermal 11.28 %
Acute toxicity, inhalation, vapor 72.63 %
Acute toxicity, inhalation, dust 73.62 %
or mist

#### **Environmental Hazards**

Acute hazards to the aquatic Category 3

environment

### **Unknown toxicity - Environment**

Acute hazards to the aquatic 76.4 %

environment



Revision Date: 11/16/2022

Chronic hazards to the aquatic 100 % environment

#### **Label Elements**

#### **Hazard Symbol:**



Signal Word: Danger

**Hazard Statement:** Flammable liquid and vapor.

Causes skin and eye irritation.

May cause cancer.

May be fatal if swallowed and enters airways.

Harmful to aquatic life.

Precautionary Statements

**Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical equipment. Use non-sparking tools. Take action to prevent static

discharges. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release

to the environment.

**Response:** IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation occurs: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. Do NOT induce vomiting. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Take off contaminated clothing. In case of fire:

Use... to extinguish.

Storage: Store in a well-ventilated place. Keep cool. Store locked up.

**Disposal:** Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

Static accumulating flammable liquid can become electrostatically charged

even in bonded and grounded equipment.



Revision Date: 11/16/2022

#### 3. Composition/information on ingredients

#### **Mixtures**

Chemical Identity	CAS number	Content in percent (%)*
Aromatic petroleum distillates	64742-95-6	10 - <20%
1,2,4-Trimethylbenzene	95-63-6	10 - <20%
Xylene	1330-20-7	5 - <10%
1,3,5-Trimethylbenzene	108-67-8	1 - <5%
Ethylbenzene	100-41-4	1 - <5%
1,2,3-Trimethylbenzene	526-73-8	1 - <5%
Methanol	67-56-1	0.1 - <1%
Cumene	98-82-8	0.1 - <1%

<sup>\*</sup> All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures

#### Description of necessary first-aid measures

**Inhalation:** Move to fresh air.

**Skin Contact:** Take off immediately all contaminated clothing. Immediately flush with

plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get

medical attention.

**Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy

to do, remove contact lenses. Get medical attention.

**Ingestion:** Call a physician or poison control center immediately. Rinse mouth.

Never give liquid to an unconscious person. If vomiting occurs, keep

head low so that stomach content doesn't get into the lungs.

**Personal Protection for First-**

aid Responders:

Firefighters must use standard protective equipment including flame

retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

#### Most important symptoms/effects, acute and delayed

Symptoms: Respiratory tract irritation. Prolonged or repeated contact with skin

may cause redness, itching, irritation and eczema/chapping.

**Hazards:** No data available.

#### Indication of immediate medical attention and special treatment needed

**Treatment:** Symptoms may be delayed.

## 5. Fire-fighting measures

**General Fire Hazards:** Use water spray to keep fire-exposed containers cool. Water may be

ineffective in fighting the fire. Fight fire from a protected location. Move

containers from fire area if you can do so without risk.



Revision Date: 11/16/2022

#### Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media:

Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from the chemical:

Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of

vapors or gases to explosive concentrations.

Special protective equipment and precautions for fire-fighters

Special fire-fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Accidental release measures:

In the event of a spill or accidental release, notify relevant authorities in

accordance with all applicable regulations.

Methods and material for containment and cleaning

up:

Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for

disposal according to local regulations.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe

to do so. Do not contaminate water sources or sewer.

#### 7. Handling and storage

#### Handling

Technical measures (e.g. Local and general ventilation):

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.



Revision Date: 11/16/2022

**Safe handling advice:** Do not handle until all safety precautions have been read and understood.

Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with skin.Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial

hygiene practices.

Contact avoidance measures: No data available.

**Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. When using do not smoke. Wash

contaminated clothing before reuse. Avoid contact with skin.

**Storage** 

Safe storage conditions: Store locked up. Store in a well-ventilated place. Store in a cool place.

Safe packaging materials: No data available.

#### 8. Exposure controls/personal protection

#### **Control Parameters**

**Occupational Exposure Limits** 

Chemical Identity	Туре	Exposure Limit Values		Source
1,2,4-Trimethylbenzene	REL	25 ppm	125 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	TWA	25 ppm	125 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	25 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
Xylene	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	STEL	150 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
	TWA	100 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
1,3,5-Trimethylbenzene	TWA	25 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
Ethylbenzene	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
1,2,3-Trimethylbenzene	TWA	25 ppm		US. ACGIH Threshold Limit Values, as amended (2011)
Methanol	PEL	200 ppm	260 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	200 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
	STEL	250 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
Cumene	PEL	50 ppm	245 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	5 ppm		US. ACGIH Threshold Limit Values, as



**EUCLID CHEMICAL** 

Version: 3.2

Revision Date: 11/16/2022

amended (01 2021)

Chemical name	Туре	Exposure Lim	it Values	Source
1,2,4-Trimethylbenzene	TWA	25 ppm	123 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm Canada. British Columbia OELs. (Occupationa Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)		
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Xylene	STEL	150 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Xylene	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	STEL	150 ppm	651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)



**EUCLID CHEMICAL** 

Version: 3.2

Revision Date: 11/16/2022

1,3,5-Trimethylbenzene	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,3,5-Trimethylbenzene	TWA	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
1,3,5-Trimethylbenzene	TWA	25 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Ethylbenzene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Ethylbenzene	TWA	20 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
1,2,3-Trimethylbenzene	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,3-Trimethylbenzene	TWA	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
1,2,3-Trimethylbenzene	TWA	25 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Methanol	TWA	200 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methanol	TWA	200 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	STEL	250 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	250 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Methanol	STEL	250 ppm	328 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	TWA	200 ppm	262 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Cumene	STEL	75 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)



Revision Date: 11/16/2022

Cumene	TWA	50 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Cumene	TWA	50 ppm	246 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA		0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA		0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA		0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Toluene	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Toluene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Toluene	TWA	50 ppm	188 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Benzene	STEL	2.5 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.5 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Benzene	TWA	0.5 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
	STEL	2.5 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Benzene	TWA	1 ppm	3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	STEL	5 ppm	15.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)

**Biological Limit Values** 

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)
Methanol (methanol: Sampling time: End of shift.)	15 mg/l (Urine)	ACGIH BEI (03 2013)

# Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment



Revision Date: 11/16/2022

**Eye/face protection:** Wear safety glasses with side shields (or goggles).

**Skin Protection** 

**Hand Protection:** Additional Information: Use suitable protective gloves if risk of skin contact.

**Skin and Body Protection:** Wear chemical-resistant gloves, footwear, and protective clothing

appropriate for the risk of exposure. Contact health and safety professional

or manufacturer for specific information.

**Respiratory Protection:** In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

**Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. When using do not smoke. Wash

contaminated clothing before reuse. Avoid contact with skin.

#### 9. Physical and chemical properties

**Appearance** 

Physical state: liquid
Form: liquid
Color: Tan

Odor: Mild petroleum/solvent
Odor threshold: No data available.

pH: No data available.

Melting point/freezing point: No data available.

Initial boiling point and boiling range: 160 °C 320 °F

Flash Point: 43 °C 110 °F(Setaflash Closed Cup)

**Evaporation rate:** Slower than Ether

Flammability (solid, gas):

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

1 %(V)

**Explosive limit - upper:**No data available. **Explosive limit - lower:**No data available.

Vapor pressure: 4.8 hPa

Vapor density: Vapors are heavier than air and may travel along the floor and

in the bottom of containers.

Relative density: 1.06

Solubility(ies)

Solubility in water: Practically Insoluble
Solubility (other): No data available.
Partition coefficient (n-octanol/water): No data available.

Auto-ignition temperature:No data available.Decomposition temperature:No data available.



Revision Date: 11/16/2022

**Viscosity:** < 20.5 mm2/s (40 °C 104 °F)

#### 10. Stability and reactivity

**Reactivity:** No data available.

**Chemical Stability:** Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

**Conditions to avoid:** Heat, sparks, flames.

Incompatible Materials: Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides

and chromates). Strong bases.

**Hazardous Decomposition** 

**Products:** 

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

#### 11. Toxicological information

#### Information on likely routes of exposure

**Inhalation:** In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

**Skin Contact:** Causes skin irritation.

**Eye contact:** Causes eye irritation.

**Ingestion:** May be ingested by accident. Ingestion may cause irritation and malaise.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation:** No data available.

**Skin Contact:** No data available.

**Eye contact:** No data available.

**Ingestion:** No data available.

#### Information on toxicological effects

#### Acute toxicity (list all possible routes of exposure)

Oral

**Product:** Not classified for acute toxicity based on available data.

**Dermal** 

**Product:** Not classified for acute toxicity based on available data.

Inhalation

**Product:** Not classified for acute toxicity based on available data.



Revision Date: 11/16/2022

Repeated dose toxicity

**Product:** No data available.

Skin Corrosion/Irritation

**Product:** No data available.

Serious Eye Damage/Eye Irritation

**Product:** No data available.

Respiratory or Skin Sensitization

**Product:** No data available.

Carcinogenicity

**Product:** May cause cancer. Suspected of causing cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Ethylbenzene Overall evaluation: Possibly carcinogenic to humans.

Cumene Overall evaluation: Possibly carcinogenic to humans.

**US. National Toxicology Program (NTP) Report on Carcinogens:** 

Reasonably Anticipated to be a Human Carcinogen. Cumene

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

**Germ Cell Mutagenicity** 

In vitro

**Product:** No data available.

In vivo

**Product:** No data available.

Reproductive toxicity

**Product:** No data available.

**Specific Target Organ Toxicity - Single Exposure Product:** 

No data available.

**Specific Target Organ Toxicity - Repeated Exposure** 

Product: No data available.

**Aspiration Hazard** 

**Product:** May be fatal if swallowed and enters airways.



Revision Date: 11/16/2022

Other effects: Constituents of this product may include crystalline silica which, if in

inhalable form, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimis exposure to these impurities in inhalable form may be carcinogenic

or cause other serious lung problems.

#### 12. Ecological information

#### **Ecotoxicity:**

Acute hazards to the aquatic environment:

Fish

**Product:** No data available.

**Aquatic Invertebrates** 

**Product:** No data available.

Chronic hazards to the aquatic environment:

**Fish** 

**Product:** No data available.

**Aquatic Invertebrates** 

**Product:** No data available.

**Toxicity to Aquatic Plants** 

**Product:** No data available.

**Persistence and Degradability** 

Biodegradation

**Product:** No data available.

**BOD/COD Ratio** 

**Product:** No data available.

Bioaccumulative potential

**Bioconcentration Factor (BCF)** 

**Product:** No data available.

Partition Coefficient n-octanol / water (log Kow)

**Product:** No data available.

**Mobility in soil:** No data available.

Other adverse effects: Harmful to aquatic organisms.

Revision Date: 11/16/2022

#### 13. Disposal considerations

**Disposal methods:** Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

**Contaminated Packaging:** No data available.

#### 14. Transport information

#### TDG:

UN1993, FLAMMABLE LIQUID, N.O.S. (Petroleum Distillates), 3, PG III

#### CFR / DOT:

UN1993, Flammable liquids, n.o.s. (Petroleum Distillates), 3, PG III

#### IMDG:

UN1993, FLAMMABLE LIQUID, N.O.S. (Petroleum Distillates), 3, PG III

#### **Further Information:**

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

#### 15. Regulatory information

#### **US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

<u>Chemical Identity</u> <u>Reportable quantity</u>

Sodium glucoheptonate De minimis concentration: TSCA 4% One-Time Export Notification only.

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.



Revision Date: 11/16/2022

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

Chemical IdentityOSHA hazard(s)Crystalline Silicakidney effects(Quartz)/ Silica Sandlung effects

immune system effects

Cancer

Benzene Blood

respiratory tract irritation Central nervous system

Flammability Cancer Skin Aspiration Eye

#### CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical IdentityReportable quantityXylene100 lbs.Ethylbenzene1000 lbs.Methanol5000 lbs.Cumene5000 lbs.Toluene1000 lbs.Benzene10 lbs.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### **Hazard categories**

Fire Hazard

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

Flammable (gases, aerosols, liquids, or solids)

Skin Corrosion or Irritation

Serious eye damage or eye irritation

Carcinogenicity
Aspiration Hazard

Hazards Not Otherwise Classified (HNOC)

# US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

#### US. EPCRA (SARA Title III Section 313 Toxic Chemical Release Inventory (TRI) Reporting

Chemical Identity% by weight1,2,4-Trimethylbenzene1.0%Xylene1.0%Ethylbenzene0.1%

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

#### Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

<u>Chemical Identity</u> <u>Reportable quantity</u>



Revision Date: 11/16/2022

Xylene Reportable quantity: 100 lbs.

#### **US State Regulations**

#### **US. California Proposition 65**

For more information go to www.P65Warnings.ca.gov.

#### International regulations

#### **Montreal protocol**

Not applicable

#### Stockholm convention

Not applicable

#### **Rotterdam convention**

Not applicable

#### **Kyoto protocol**

Not applicable

VOC:

Regulatory VOC (less water and

exempt solvent)

: 648 g/l

VOC Method 310 : 43.25 %



Revision Date: 11/16/2022

**Inventory Status:** 

Australia AICS: One or more components in this

product are not listed on or exempt

from the Inventory.

Canada DSL Inventory List: All components in this product are

listed on or exempt from the

Inventory.

EINECS, ELINCS or NLP: One or more components in this

product are not listed on or exempt

from the Inventory.

Japan (ENCS) List: One or more components in this

product are not listed on or exempt

from the Inventory.

China Inv. Existing Chemical

Substances:

One or more components in this product are not listed on or exempt

from the Inventory.

Korea Existing Chemicals Inv. (KECI): One or more components in this

product are not listed on or exempt

from the Inventory.

Canada NDSL Inventory: One or more components in this

product are not listed on or exempt

from the Inventory.

Philippines PICCS: One or more components in this

product are not listed on or exempt

from the Inventory.

US TSCA Inventory: All components in this product are

listed on or exempt from the

Inventory.

New Zealand Inventory of Chemicals: One or more components in this

product are not listed on or exempt

from the Inventory.

Japan ISHL Listing: One or more components in this

product are not listed on or exempt

from the Inventory.

Japan Pharmacopoeia Listing: One or more components in this

product are not listed on or exempt

from the Inventory.



Revision Date: 11/16/2022

## 16.Other information, including date of preparation or last revision

**Revision Date:** 11/16/2022

Version #: 3.2

Further Information: No data available.

**Disclaimer:** For Industrial Use Only. Keep out of Reach of Children. The hazard

information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.