



This is a kit that contains the following components:  
DURAL 340 NS 1:1 PART A  
DURAL 340 NS 1:1 PART B



# SAFETY DATA SHEET

## 1. Identification

**Product identifier:** DURAL 340 NS 1:1 PART A  
**Product Code:** TD5372104

### Recommended use and restriction on use

**Recommended use:** Sealant  
**Restrictions on use:** Not known.

### Manufacturer/Importer/Supplier/Distributor Information

EUCLID CHEMICAL COMPANY  
19218 REDWOOD ROAD  
CLEVELAND OH 44110  
US

**Contact person:** EH&S Department  
**Telephone:** 216-531-9222  
**Emergency telephone number:** 1-800-424-9300 (US); 1-613-996-6666 (Canada)

## 2. Hazard(s) identification

### Hazard Classification

#### Health Hazards

Skin Corrosion/Irritation	Category 1B
Serious Eye Damage/Eye Irritation	Category 1
Skin sensitizer	Category 1
Toxic to reproduction	Category 2

#### Unknown toxicity - Health

Acute toxicity, oral	16.06 %
Acute toxicity, dermal	24.03 %
Acute toxicity, inhalation, vapor	33.66 %
Acute toxicity, inhalation, dust or mist	33.66 %

### Environmental Hazards

Acute hazards to the aquatic environment	Category 2
Chronic hazards to the aquatic environment	Category 2

#### Unknown toxicity - Environment

Acute hazards to the aquatic environment	25.83 %
--	---------



Chronic hazards to the aquatic environment 25.83 %

## Label Elements

### Hazard Symbol:



**Signal Word:** Danger

**Hazard Statement:** Causes severe skin burns and eye damage.  
May cause an allergic skin reaction.  
Suspected of damaging fertility or the unborn child.  
Toxic to aquatic life with long lasting effects.

### Precautionary Statements

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Use personal protective equipment as required. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray.

**Response:** IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Collect spillage.

**Storage:** Store locked up.

**Disposal:** Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Hazard(s) not otherwise classified (HNO C):** None.

## 3. Composition/information on ingredients

### Mixtures

000000019464



Chemical Identity	Common name and synonyms	CAS number	Content in percent (%)*
Bisphenol A Polyglycidyl Ether Resin		25068-38-6	50 - <100%
4-Nonylphenol		84852-15-3	5 - <10%
Crystalline Silica (Quartz)/ Silica Sand		14808-60-7	1 - <5%
Talc		14807-96-6	1 - <5%
Trade Secret	Trade Secret	Trade Secret	0.1 - <1%
Magnesite		546-93-0	0.1 - <1%

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures

##### Description of necessary first-aid measures

- Inhalation:** Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
- Skin Contact:** Call a physician or poison control center immediately. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
- Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Call a physician or poison control center immediately.
- Ingestion:** Rinse mouth. Call a physician or poison control center immediately. Never give liquid to an unconscious person. Do not induce vomiting without advice from poison control center.
- Personal Protection for First-aid Responders:** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

##### Most important symptoms/effects, acute and delayed

**Symptoms:** Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping. Extreme irritation of eyes and mucous membranes, including burning and tearing.

**Hazards:** No data available.

##### Indication of immediate medical attention and special treatment needed

**Treatment:** Symptoms may be delayed.

#### 5. Fire-fighting measures

**General Fire Hazards:** No unusual fire or explosion hazards noted.

**Suitable (and unsuitable) extinguishing media**

**Suitable extinguishing media:** Use fire-extinguishing media appropriate for surrounding materials.

**Unsuitable extinguishing media:** Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical:** During fire, gases hazardous to health may be formed.

**Special protective equipment and precautions for firefighters**

**Special fire fighting procedures:** No data available.

**Special protective equipment for fire-fighters:** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

**6. Accidental release measures**

**Personal precautions, protective equipment and emergency procedures:** See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

**Accidental release measures:** In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

**Methods and material for containment and cleaning up:** Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

**Environmental Precautions:** Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

**7. Handling and storage****Handling**

**Technical measures (e.g. Local and general ventilation):** Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

**Safe handling advice:** Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Wash hands thoroughly after handling. Do not get in eyes. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not get in eyes, on skin, on clothing. Avoid contact with eyes, skin, and clothing.

**Contact avoidance measures:** No data available.



**Hygiene measures:** Observe good industrial hygiene practices. Do not get in eyes. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated clothing before reuse. Do not get this material in contact with skin. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

**Storage**

**Safe storage conditions:** Store locked up.

**Safe packaging materials:** No data available.

**8. Exposure controls/personal protection****Control Parameters****Occupational Exposure Limits**

Chemical Identity	Type	Exposure Limit Values	Source
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values, as amended (2011)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.05 mg/m <sup>3</sup>	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (03 2016)
	OSHA_AC T	0.025 mg/m <sup>3</sup>	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (03 2016)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	PEL	0.05 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (03 2016)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	TWA	0.1 mg/m <sup>3</sup>	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Talc - Respirable fraction.	TWA	2 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values, as amended (2011)
Talc	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Talc - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	TWA	0.1 mg/m <sup>3</sup>	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Trade Secret - Inhalable particles.	TWA	10 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values, as amended (03 2015)
Trade Secret - Respirable particles.	TWA	3 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values, as amended (03 2015)
Trade Secret - Respirable fraction.	PEL	5 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Trade Secret - Total dust.	PEL	15 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	15 mg/m <sup>3</sup>	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	TWA	50 millions of particles per	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)



		cubic foot of air	
Trade Secret - Respirable fraction.	TWA	5 mg/m <sup>3</sup>	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Magnesite - Total dust.	PEL	15 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Magnesite - Respirable fraction.	PEL	5 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)

Chemical name	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m <sup>3</sup>	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.10 mg/m <sup>3</sup>	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m <sup>3</sup>	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Talc - Respirable.	TWA	2 mg/m <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Talc - Respirable dust.	TWA	3 mg/m <sup>3</sup>	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Talc	TWA	2 Fibers/cc	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)
Talc - Respirable fraction.	TWA	2 mg/m <sup>3</sup>	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)



Chemical name	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Talc - Respirable.	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Talc - Respirable dust.	TWA	3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Talc	TWA	2 Fibers/cc	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)
Talc - Respirable fraction.	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)
Trade Secret - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Trade Secret - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Trade Secret - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Trade Secret - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Trade Secret - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Magnesite - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Stoddard solvent (Mineral Spirits)	STEL	580 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	290 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation





			296/97, as amended) (07 2007)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm 525 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
1-Methoxy-2-propanol acetate	TWA	50 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	75 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1-Methoxy-2-propanol acetate	TWA	50 ppm 270 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Epichlorohydrin	TWA	0.1 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Epichlorohydrin	TWA	0.5 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Epichlorohydrin	TWA	2 ppm 7.6 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)

**Appropriate Engineering Controls**

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

**Individual protection measures, such as personal protective equipment****Eye/face protection:**

Wear a full-face respirator, if needed. Wear safety glasses with side shields (or goggles) and a face shield.

**Skin Protection****Hand Protection:**

Additional Information: Use suitable protective gloves if risk of skin contact.

**Skin and Body Protection:**

Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.



<b>Respiratory Protection:</b>	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
<b>Hygiene measures:</b>	Observe good industrial hygiene practices. Do not get in eyes. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated clothing before reuse. Do not get this material in contact with skin. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

## 9. Physical and chemical properties

### Appearance

<b>Physical state:</b>	liquid
<b>Form:</b>	liquid
<b>Color:</b>	Off-white
<b>Odor:</b>	Mild
<b>Odor threshold:</b>	No data available.
<b>pH:</b>	No data available.
<b>Melting point/freezing point:</b>	No data available.
<b>Initial boiling point and boiling range:</b>	No data available.
<b>Flash Point:</b>	> 93 °C > 200 °F
<b>Evaporation rate:</b>	Slower than Ether
<b>Flammability (solid, gas):</b>	No
<b>Upper/lower limit on flammability or explosive limits</b>	
<b>Flammability limit - upper (%):</b>	No data available.
<b>Flammability limit - lower (%):</b>	No data available.
<b>Explosive limit - upper:</b>	No data available.
<b>Explosive limit - lower:</b>	No data available.
<b>Vapor pressure:</b>	No data available.
<b>Vapor density:</b>	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
<b>Relative density:</b>	1.16
<b>Solubility(ies)</b>	
<b>Solubility in water:</b>	Insoluble in water
<b>Solubility (other):</b>	No data available.
<b>Partition coefficient (n-octanol/water):</b>	No data available.
<b>Auto-ignition temperature:</b>	No data available.
<b>Decomposition temperature:</b>	No data available.
<b>Viscosity:</b>	No data available.

## 10. Stability and reactivity

<b>Reactivity:</b>	No data available.
<b>Chemical Stability:</b>	Material is stable under normal conditions.



<b>Possibility of hazardous reactions:</b>	No data available.
<b>Conditions to avoid:</b>	Avoid heat or contamination.
<b>Incompatible Materials:</b>	No data available.
<b>Hazardous Decomposition Products:</b>	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation:</b>	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
<b>Skin Contact:</b>	May be harmful in contact with skin. Causes severe skin burns. May cause an allergic skin reaction.
<b>Eye contact:</b>	Causes serious eye damage.
<b>Ingestion:</b>	May be harmful if swallowed.

### Symptoms related to the physical, chemical and toxicological characteristics

<b>Inhalation:</b>	No data available.
<b>Skin Contact:</b>	No data available.
<b>Eye contact:</b>	No data available.
<b>Ingestion:</b>	No data available.

### Information on toxicological effects

#### Acute toxicity (list all possible routes of exposure)

<b>Oral</b>	
<b>Product:</b>	ATEmix: 2,082 mg/kg
<b>Dermal</b>	
<b>Product:</b>	ATEmix: 2,232.48 mg/kg
<b>Inhalation</b>	
<b>Product:</b>	
<b>Specified substance(s):</b>	
Bisphenol A Polyglycidyl Ether Resin	LC 50: > 20 mg/l LC 50: > 5 mg/l
Trade Secret	LC 50 (Rabbit): 20.1 mg/l

**Repeated dose toxicity****Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Specified substance(s):**

Bisphenol A	Irritating.
Polyglycidyl Ether Resin	in vivo (Rabbit): Slightly irritating
4-Nonylphenol	in vivo (Rabbit): Category 1B
Magnesite	In vitro (Human, in vitro reconstituted epidermis model): Not irritant

**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Bisphenol A	Strongly irritating.
Polyglycidyl Ether Resin	Rabbit, 24 hrs: Slightly irritating
4-Nonylphenol	Rabbit, 24 - 72 hrs: Corrosive
Magnesite	Reconstituted Corneal Epithelium model, 10 min: Not irritating

**Respiratory or Skin Sensitization****Product:** No data available.**Carcinogenicity****Product:** No data available.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:****US. National Toxicology Program (NTP) Report on Carcinogens:****US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:****Germ Cell Mutagenicity****In vitro****Product:** No data available.**In vivo****Product:** No data available.

**Reproductive toxicity****Product:** Suspected of damaging fertility or the unborn child.**Specific Target Organ Toxicity - Single Exposure****Product:** No data available.**Specific Target Organ Toxicity - Repeated Exposure****Product:** No data available.**Aspiration Hazard****Product:** No data available.**Other effects:**

No data available.

**12. Ecological information****Ecotoxicity:****Acute hazards to the aquatic environment:****Fish****Product:** No data available.**Specified substance(s):**

Bisphenol A Polyglycidyl Ether Resin LC 50 (Oncorhynchus mykiss, 96 h): 2 mg/l Experimental result, Key study

4-Nonylphenol LC 50 (Fathead minnow (Pimephales promelas), 96 h): 0.13825 mg/l Mortality

**Aquatic Invertebrates****Product:** No data available.**Specified substance(s):**

Bisphenol A Polyglycidyl Ether Resin EC 50 (Daphnia magna, 48 h): 1.8 mg/l Experimental result, Key study

**Chronic hazards to the aquatic environment:****Fish****Product:** No data available.**Specified substance(s):**

4-Nonylphenol NOAEL (Oncorhynchus mykiss, 91 d): 0.006 mg/l Experimental result, Key study

**Aquatic Invertebrates****Product:** No data available.



**Specified substance(s):**  
Bisphenol A Polyglycidyl Ether Resin  
NOEC (Daphnia magna, 21 d): 0.3 mg/l Experimental result, Key study

**Toxicity to Aquatic Plants**  
**Product:** No data available.

#### Persistence and Degradability

**Biodegradation**  
**Product:** No data available.

**BOD/COD Ratio**  
**Product:** No data available.

#### Bioaccumulative potential

**Bioconcentration Factor (BCF)**  
**Product:** No data available.

**Specified substance(s):**  
Bisphenol A Polyglycidyl Ether Resin  
Bioconcentration Factor (BCF): 31 Aquatic sediment QSAR, Key study

4-Nonylphenol  
Fathead minnow (Pimephales promelas), Bioconcentration Factor (BCF): 988 (Flow through)

**Partition Coefficient n-octanol / water (log Kow)**  
**Product:** No data available.

**Specified substance(s):**  
Bisphenol A Polyglycidyl Ether Resin  
Log Kow: 2.64 - 3.78 25 °C Yes Experimental result, Key study

**Mobility in soil:** No data available.

**Other adverse effects:** Toxic to aquatic life with long lasting effects.

### 13. Disposal considerations

**Disposal methods:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Contaminated Packaging:** No data available.

### 14. Transport information

**TDG:**



UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A Epoxy Resin), 9, PG III

**CFR / DOT:**

UN3082, Environmentally hazardous substance, liquid, n.o.s. (Bisphenol A Epoxy Resin), 9, PG III

**IMDG:**

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A Epoxy Resin), 9, PG III, MARINE POLLUTANT

**Further Information:**

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

**15. Regulatory information**

**US Federal Regulations**

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

**Chemical Identity**

4-Nonylphenol

**Reportable quantity**

De minimis concentration: TSCA 5(a)(2)% One-Time Export Notification only.

**US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)**

None present or none present in regulated quantities.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended**

**Chemical Identity**

Crystalline Silica  
(Quartz)/ Silica Sand

**OSHA hazard(s)**

kidney effects  
lung effects  
immune system effects  
Cancer

**CERCLA Hazardous Substance List (40 CFR 302.4):**

**Chemical Identity**

Epichlorohydrin

**Reportable quantity**

100 lbs.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories**

- Immediate (Acute) Health Hazards
- Delayed (Chronic) Health Hazard
- Skin Corrosion or Irritation
- Serious eye damage or eye irritation
- Respiratory or Skin Sensitization
- Reproductive toxicity

**US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances**



**Chemical Identity**

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

<b><u>Chemical Identity</u></b>	<b><u>Reportable quantity</u></b>
Epichlorohydrin	lbs

**Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)**

None present or none present in regulated quantities.

**US State Regulations**

**US. California Proposition 65**



**WARNING**

Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**US. New Jersey Worker and Community Right-to-Know Act**

<b><u>Chemical Identity</u></b>
Calcium carbonate
Crystalline Silica (Quartz)/ Silica Sand
Talc

**US. Massachusetts RTK - Substance List**

<b><u>Chemical Identity</u></b>
Calcium carbonate
4-Nonylphenol
Crystalline Silica (Quartz)/ Silica Sand
Epichlorohydrin

**US. Pennsylvania RTK - Hazardous Substances**

<b><u>Chemical Identity</u></b>
Calcium carbonate
4-Nonylphenol
Crystalline Silica (Quartz)/ Silica Sand
Talc

**US. Rhode Island RTK**

<b><u>Chemical Identity</u></b>
Calcium carbonate

**International regulations**

**Montreal protocol**

Not applicable

**Stockholm convention**

Not applicable

**Rotterdam convention**

Not applicable

**Kyoto protocol**





Not applicable

**VOC:** When appropriately mixed with the other part, product has a VOC less water and exempt solvent of:  
1 g/l

Regulatory VOC (less water and exempt solvent) : 96 g/l

VOC Method 310 : 8.23 %

**Inventory Status:**

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	One or more components in this product are not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.



**16. Other information, including date of preparation or last revision**

**Revision Date:** 10/27/2020

**Version #:** 4.0

**Further Information:** No data available.

**Disclaimer:** For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.



# SAFETY DATA SHEET

## 1. Identification

**Product identifier:** DURAL 340 NS 1:1 PART B  
**Product Code:** TD5372104

### Recommended use and restriction on use

**Recommended use:** Curative  
**Restrictions on use:** Not known.

### Manufacturer/Importer/Supplier/Distributor Information

EUCLID CHEMICAL COMPANY  
19218 REDWOOD ROAD  
CLEVELAND OH 44110  
US

**Contact person:** EH&S Department  
**Telephone:** 216-531-9222  
**Emergency telephone number:** 1-800-424-9300 (US); 1-613-996-6666 (Canada)

## 2. Hazard(s) identification

### Hazard Classification

#### Health Hazards

Skin Corrosion/Irritation	Category 1B
Serious Eye Damage/Eye Irritation	Category 1
Toxic to reproduction	Category 2

#### Unknown toxicity - Health

Acute toxicity, oral	14.78 %
Acute toxicity, dermal	44.28 %
Acute toxicity, inhalation, vapor	73.77 %
Acute toxicity, inhalation, dust or mist	73.34 %

### Environmental Hazards

Acute hazards to the aquatic environment	Category 1
Chronic hazards to the aquatic environment	Category 1

#### Unknown toxicity - Environment

Acute hazards to the aquatic environment	46.51 %
Chronic hazards to the aquatic environment	46.51 %

**Label Elements****Hazard Symbol:****Signal Word:** Danger**Hazard Statement:** Causes severe skin burns and eye damage.  
Suspected of damaging fertility or the unborn child.  
Very toxic to aquatic life with long lasting effects.**Precautionary Statements****Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Avoid release to the environment. Use personal protective equipment as required. Wear protective gloves/protective clothing/eye protection/face protection.**Response:** IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Collect spillage.**Storage:** Store locked up.**Disposal:** Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.**Hazard(s) not otherwise classified (HNOC):** None.**3. Composition/information on ingredients****Mixtures**

Chemical Identity	Common name and synonyms	CAS number	Content in percent (%) <sup>*</sup>
4-Nonylphenol		84852-15-3	25 - <50%
Talc		14807-96-6	20 - <50%



Poly(oxypropylene) diamine		9046-10-0	20 - <50%
Tris(dimethylaminomethyl)phenol		90-72-2	1 - <5%
2-Methyl-1,5-pentanediamine		15520-10-2	1 - <5%
Wollastonite		13983-17-0	1 - <5%
Polyethylene		9002-88-4	1 - <5%
4-tert-Butylphenol		98-54-4	0.25 - <1%
m-Xylenediamine		1477-55-0	0.1 - <1%
Crystalline Silica (Quartz)/ Silica Sand		14808-60-7	0.1 - <1%

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures

##### Description of necessary first-aid measures

- Inhalation:** Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
- Skin Contact:** Call a physician or poison control center immediately. Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Destroy or thoroughly clean contaminated shoes.
- Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Call a physician or poison control center immediately.
- Ingestion:** Rinse mouth. Call a physician or poison control center immediately. Never give liquid to an unconscious person. Do not induce vomiting without advice from poison control center.
- Personal Protection for First-aid Responders:** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

##### Most important symptoms/effects, acute and delayed

- Symptoms:** Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping. Extreme irritation of eyes and mucous membranes, including burning and tearing.
- Hazards:** No data available.

##### Indication of immediate medical attention and special treatment needed

- Treatment:** Symptoms may be delayed.

#### 5. Fire-fighting measures

- General Fire Hazards:** No unusual fire or explosion hazards noted.

**Suitable (and unsuitable) extinguishing media**

**Suitable extinguishing media:** Use fire-extinguishing media appropriate for surrounding materials.

**Unsuitable extinguishing media:** Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical:** During fire, gases hazardous to health may be formed.

**Special protective equipment and precautions for firefighters**

**Special fire fighting procedures:** No data available.

**Special protective equipment for fire-fighters:** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

**6. Accidental release measures**

**Personal precautions, protective equipment and emergency procedures:** See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

**Accidental release measures:** In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

**Methods and material for containment and cleaning up:** Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

**Environmental Precautions:** Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

**7. Handling and storage****Handling**

**Technical measures (e.g. Local and general ventilation):** Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

**Safe handling advice:** Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Wash hands thoroughly after handling. Do not get in eyes. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not get in eyes, on skin, on clothing.

**Contact avoidance measures:** No data available.



**Hygiene measures:** Do not get in eyes. Observe good industrial hygiene practices. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated clothing before reuse. Do not get this material in contact with skin. Wash hands before breaks and immediately after handling the product.

**Storage**

**Safe storage conditions:** Store locked up.

**Safe packaging materials:** No data available.

**8. Exposure controls/personal protection****Control Parameters****Occupational Exposure Limits**

Chemical Identity	Type	Exposure Limit Values	Source
Talc - Respirable fraction.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values, as amended (2011)
Talc	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Talc - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Wollastonite - Inhalable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2019)
Polyethylene - Inhalable particles.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2015)
Polyethylene - Respirable particles.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2015)
Polyethylene - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Polyethylene - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Polyethylene - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
m-Xylenediamine	Ceiling	0.018 ppm	US. ACGIH Threshold Limit Values, as amended (01 2019)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	US. ACGIH Threshold Limit Values, as amended (2011)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.05 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (03 2016)
	OSHA_AC T	0.025 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (03





			2016)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	PEL	0.05 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (03 2016)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	TWA	0.1 mg/m <sup>3</sup>	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)

Chemical name	Type	Exposure Limit Values	Source
Talc - Respirable.	TWA	2 mg/m <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Talc - Respirable dust.	TWA	3 mg/m <sup>3</sup>	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Talc	TWA	2 Fibers/cc	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)
Talc - Respirable fraction.	TWA	2 mg/m <sup>3</sup>	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)
Polyethylene - Respirable fraction.	TWA	3 mg/m <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Polyethylene - Total dust.	TWA	10 mg/m <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Polyethylene - Inhalable fraction.	TWA	10 mg/m <sup>3</sup>	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Polyethylene - Respirable fraction.	TWA	3 mg/m <sup>3</sup>	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Polyethylene - Total dust.	TWA	10 mg/m <sup>3</sup>	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.10 mg/m <sup>3</sup>	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m <sup>3</sup>	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)



Chemical name	Type	Exposure Limit Values	Source
Talc - Respirable.	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Talc - Respirable dust.	TWA	3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Talc	TWA	2 Fibers/cc	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)
Talc - Respirable fraction.	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)
Wollastonite - fibers, total dust	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Wollastonite - Fiber.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Polyethylene - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Polyethylene - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Polyethylene - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Polyethylene - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Polyethylene - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
m-Xylenediamine	CEILING	0.1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
m-Xylenediamine	CEV	0.1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
m-Xylenediamine	CEILING	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)



Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)

**Appropriate Engineering Controls**

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection:** Wear a full-face respirator, if needed. Wear safety glasses with side shields (or goggles) and a face shield.

**Skin Protection**

**Hand Protection:** Additional Information: Use suitable protective gloves if risk of skin contact.

**Skin and Body Protection:** Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

**Respiratory Protection:** In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

**Hygiene measures:** Do not get in eyes. Observe good industrial hygiene practices. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated clothing before reuse. Do not get this material in contact with skin. Wash hands before breaks and immediately after handling the product.

**9. Physical and chemical properties****Appearance**

<b>Physical state:</b>	liquid
<b>Form:</b>	liquid
<b>Color:</b>	Off-white
<b>Odor:</b>	Mild pungent
<b>Odor threshold:</b>	No data available.
<b>pH:</b>	No data available.
<b>Melting point/freezing point:</b>	No data available.
<b>Initial boiling point and boiling range:</b>	No data available.
<b>Flash Point:</b>	> 93 °C > 200 °F (Setaflash Closed Cup)
<b>Evaporation rate:</b>	Slower than Ether
<b>Flammability (solid, gas):</b>	No
<b>Upper/lower limit on flammability or explosive limits</b>	
<b>Flammability limit - upper (%):</b>	No data available.
<b>Flammability limit - lower (%):</b>	No data available.



<b>Explosive limit - upper:</b>	No data available.
<b>Explosive limit - lower:</b>	No data available.
<b>Vapor pressure:</b>	No data available.
<b>Vapor density:</b>	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
<b>Relative density:</b>	1.21
<b>Solubility(ies)</b>	
<b>Solubility in water:</b>	Practically Insoluble
<b>Solubility (other):</b>	No data available.
<b>Partition coefficient (n-octanol/water):</b>	No data available.
<b>Auto-ignition temperature:</b>	No data available.
<b>Decomposition temperature:</b>	No data available.
<b>Viscosity:</b>	No data available.

## 10. Stability and reactivity

<b>Reactivity:</b>	No data available.
<b>Chemical Stability:</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions:</b>	No data available.
<b>Conditions to avoid:</b>	Avoid heat or contamination.
<b>Incompatible Materials:</b>	Avoid contact with acids.
<b>Hazardous Decomposition Products:</b>	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation:</b>	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
<b>Skin Contact:</b>	Causes severe skin burns.
<b>Eye contact:</b>	Causes serious eye damage.
<b>Ingestion:</b>	May be harmful if swallowed.

### Symptoms related to the physical, chemical and toxicological characteristics

<b>Inhalation:</b>	No data available.
<b>Skin Contact:</b>	No data available.
<b>Eye contact:</b>	No data available.
<b>Ingestion:</b>	No data available.

**Information on toxicological effects****Acute toxicity (list all possible routes of exposure)****Oral****Product:** ATEmix: 2,341.9 mg/kg**Dermal****Product:** ATEmix: 6,086.59 mg/kg**Inhalation****Product:****Specified substance(s):**

2-Methyl-1,5-pentanediamine	LC 50 (Rat): 4.9 mg/l
Wollastonite	LC 50 (Rabbit): 20.1 mg/l
Polyethylene	LC 50 (Rabbit): 20.1 mg/l
m-Xylenediamine	LC 50 (Rat): 1.16 mg/l

**Repeated dose toxicity****Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Specified substance(s):**

4-Nonylphenol	in vivo (Rabbit): Category 1B
Poly(oxypropylene) diamine	(Rabbit): Corrosive
Tris(dimethylaminomet hyl)phenol	in vivo (Rabbit): Corrosive
2-Methyl-1,5-pentanediamine	in vivo (Rabbit): Category 1A
4-tert-Butylphenol	in vivo (Rabbit): Highly irritating
m-Xylenediamine	in vivo (Rat): Corrosive

**Serious Eye Damage/Eye Irritation**

<b>Product:</b>	No data available.
<b>Specified substance(s):</b>	
4-Nonylphenol	Rabbit, 24 - 72 hrs: Corrosive
Poly(oxypropylene) diamine	Rabbit, 24 hrs: Corrosive
Tris(dimethylaminomet hyl)phenol	Rabbit, 3 d: Corrosive
4-tert-Butylphenol	Rabbit, 24 hrs: Category 1

**Respiratory or Skin Sensitization**

**Product:** No data available.

**Carcinogenicity**

**Product:** No data available.

**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:****US. National Toxicology Program (NTP) Report on Carcinogens:****US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:****Germ Cell Mutagenicity**

**In vitro**  
**Product:** No data available.

**In vivo**  
**Product:** No data available.

**Reproductive toxicity**

**Product:** Suspected of damaging fertility or the unborn child.

**Specific Target Organ Toxicity - Single Exposure**

**Product:** No data available.

**Specific Target Organ Toxicity - Repeated Exposure**

**Product:** No data available.

**Aspiration Hazard**

**Product:** No data available.

**Other effects:** No data available.

**12. Ecological information****Ecotoxicity:****Acute hazards to the aquatic environment:****Fish****Product:** No data available.**Specified substance(s):**4-Nonylphenol LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 0.13825 mg/l Mortality4-tert-Butylphenol LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 4.71 - 5.62 mg/l Mortality**Aquatic Invertebrates****Product:** No data available.**Chronic hazards to the aquatic environment:****Fish****Product:** No data available.**Specified substance(s):**4-Nonylphenol NOAEL (*Oncorhynchus mykiss*, 91 d): 0.006 mg/l Experimental result, Key study**Aquatic Invertebrates****Product:** No data available.**Toxicity to Aquatic Plants****Product:** No data available.**Persistence and Degradability****Biodegradation****Product:** No data available.**BOD/COD Ratio****Product:** No data available.**Bioaccumulative potential****Bioconcentration Factor (BCF)****Product:** No data available.**Specified substance(s):**



4-Nonylphenol Fathead minnow (Pimephales promelas), Bioconcentration Factor (BCF):  
988 (Flow through)

**Partition Coefficient n-octanol / water (log Kow)**  
**Product:** No data available.

**Mobility in soil:** No data available.

**Other adverse effects:** Very toxic to aquatic life with long lasting effects.

**13. Disposal considerations**

**Disposal methods:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Contaminated Packaging:** No data available.

**14. Transport information**

**TDG:**

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Nonylphenol), 9, PG III

**CFR / DOT:**

UN3082, Environmentally hazardous substance, liquid, n.o.s. (Nonylphenol), 9, PG III

**IMDG:**

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Nonylphenol), 9, PG III,  
MARINE POLLUTANT

**Further Information:**

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

**15. Regulatory information**

**US Federal Regulations**

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

**Chemical Identity**

4-Nonylphenol

Nonyl Phenol

**Reportable quantity**

De minimis concentration: TSCA 5(a)(2)% One-Time Export Notification only.

De minimis concentration: TSCA 5(a)(2)% One-Time Export Notification only.

**US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)**

None present or none present in regulated quantities.





**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended**

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Crystalline Silica (Quartz)/ Silica Sand	kidney effects lung effects immune system effects Cancer

**CERCLA Hazardous Substance List (40 CFR 302.4):**

None present or none present in regulated quantities.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories**

- Immediate (Acute) Health Hazards
- Delayed (Chronic) Health Hazard
- Skin Corrosion or Irritation
- Serious eye damage or eye irritation
- Reproductive toxicity

**US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances**

Chemical Identity

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

None present or none present in regulated quantities.

**Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)**

None present or none present in regulated quantities.

**US State Regulations**

**US. California Proposition 65**



**WARNING**

Cancer - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**US. New Jersey Worker and Community Right-to-Know Act**

Chemical Identity

Talc  
Crystalline Silica (Quartz)/ Silica Sand

**US. Massachusetts RTK - Substance List**

Chemical Identity

4-Nonylphenol  
Crystalline Silica (Quartz)/ Silica Sand



**US. Pennsylvania RTK - Hazardous Substances**

**Chemical Identity**

4-Nonylphenol  
Talc

**US. Rhode Island RTK**

**Chemical Identity**

Polyethylene

**International regulations**

**Montreal protocol**

Not applicable

**Stockholm convention**

Not applicable

**Rotterdam convention**

Not applicable

**Kyoto protocol**

Not applicable

**VOC:**

Regulatory VOC (less water and  
exempt solvent) : 390 g/l

VOC Method 310 : 32.19 %

**Inventory Status:**

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	One or more components in this product are not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical	All components in this product are



Substances: listed on or exempt from the Inventory.

Mexico INSQ: One or more components in this product are not listed on or exempt from the Inventory.

Taiwan Chemical Substance Inventory: One or more components in this product are not listed on or exempt from the Inventory.

**16. Other information, including date of preparation or last revision**

**Revision Date:** 10/27/2020

**Version #:** 4.0

**Further Information:** No data available.

**Disclaimer:** For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.