

This is a kit that contains the following components:

DURAL 452 MV 1:1 PART A

DURAL 452 MV 1:1 PT B



Version: 3.2 Revision Date: 11/17/2022

SAFETY DATA SHEET

1. Identification

Product identifier: DURAL 452 MV 1:1 PART A Product Code: 002DM 02

Recommended use and restriction on use

Recommended use: Sealant Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Euclid Admixture Canada Inc. 2835 Grand-Allee Saint Hubert QC J4T 2R4 CA

Contact person: Telephone: **Emergency telephone number:**

EH&S Department (450)465-2233 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards	
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2A
Skin sensitizer	Category 1
Germ Cell Mutagenicity	Category 2
Carcinogenicity	Category 1A

2.86 %

Unknown toxicity - Health				
Acute toxicity, oral				

Acute toxicity, dermal	3.15 %
Acute toxicity, inhalation, vapor	97 %
Acute toxicity, inhalation, dust or mist	91.11 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2
Chronic hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic 9.55 % environment



Chronic hazards to the aquatic 7.34 % environment

Label Elements

Hazard Symbol:	
Signal Word:	Danger
Hazard Statement:	Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of causing genetic defects. May cause cancer. Toxic to aquatic life with long lasting effects.
Precautionary Statements	
Prevention:	Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.
Response:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Wash contaminated clothing before reuse. Collect spillage.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	None.

3. Composition/information on ingredients

Mixtures



Chemical Identity	CAS number	Content in percent (%)*
Bisphenol A Polyglycidyl Ether Resin	25068-38-6	50 - <100%
o-Cresyl glycidyl ether	2210-79-9	5 - <10%
Titanium dioxide	13463-67-7	1 - <5%
Epichlorohydrin polymer	25085-99-8	1 - <2.5%
Aluminum hydroxide	21645-51-2	0.1 - <1%
Amorphous silica	7631-86-9	0.1 - <1%
Carbon Black	1333-86-4	0.1 - <1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Description of necessary first-aid measures				
Inhalation:	Move to fresh air.			
Skin Contact:	Get medical attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.			
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.			
Ingestion:	Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.			
Personal Protection for First- aid Responders:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.			
Most important symptoms/effe	ects, acute and delayed			
Symptoms:	Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping.			
Hazards:	No data available.			
Indication of immediate medica	al attention and special treatment needed			
Treatment:	Symptoms may be delayed.			
5. Fire-fighting measures				
General Fire Hazards:	No unusual fire or explosion hazards noted.			
Suitable (and unsuitable) extin	guishing media			
Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.			
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.			



Specific hazards arising from the chemical:	During fire, gases hazardous to health may be formed.			
Special protective equipment and precautions for fire-fighters				
Special fire-fighting procedures:	No data available.			
Special protective equipment for fire-fighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.			
6. Accidental release measures	6			
Personal precautions, protective equipment and emergency procedures:	See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.			
Accidental release measures:	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.			
Methods and material for containment and cleaning up:	Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.			
Environmental Precautions:	Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.			
7. Handling and storage				
Handling				
Technical measures (e.g. Local and general ventilation):	Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.			
Safe handling advice:	Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.Wash hands thoroughly after handling. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes. Avoid contact with skin. Avoid contact with eyes, skin, and clothing.			
Contact avoidance measures:	No data available.			
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Avoid contact with eyes. Wash contaminated clothing before reuse. Avoid contact with skin. Contaminated work clothing should not be allowed out of the workplace.			
Storage				
Safe storage conditions:	Store locked up.			
Safe packaging materials:	No data available.			



8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure Limit Values	Source
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (2008)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Titanium dioxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Titanium dioxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Titanium dioxide - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Titanium dioxide - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Aluminum hydroxide - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values, as amended (2011)
	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Aluminum hydroxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Aluminum hydroxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Aluminum hydroxide - Inhalable particles.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)
Aluminum hydroxide - Respirable particles.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)
Amorphous silica - Inhalable particles.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)
Amorphous silica - Respirable particles.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)
Amorphous silica - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Amorphous silica - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Amorphous silica - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Carbon Black	PEL	3.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as amended (12 2010)
Carbon Black - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
	TWA	15 millions of particles per	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)



		cubic foot of air	
Carbon Black - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)



Chemical name	Туре	Exposure Limit Values	Source
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Aluminum hydroxide - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Aluminum hydroxide - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Aluminum hydroxide - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Aluminum hydroxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Aluminum hydroxide - Respirable.	TWA	1.0 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Aluminum hydroxide - Respirable particles.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Aluminum hydroxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Aluminum hydroxide - Inhalable particles.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Aluminum hydroxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Amorphous silica - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Amorphous silica - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Amorphous silica - Respirable particles.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Amorphous silica - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Amorphous silica - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Amorphous silica - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)



Amorphous silica - Inhalable particles.	TWA		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Carbon Black - Inhalable	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction.	TWA		3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Carbon Black - Inhalable dust.	TWA		3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Stoddard solvent (Mineral Spirits)	STEL		580 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA		290 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm	525 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA		0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA		0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA		0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
1-Methoxy-2-propanol acetate	TWA	50 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	75 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1-Methoxy-2-propanol acetate	TWA	50 ppm	270 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (12 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm	123 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.



Individual protection measures, such as personal protective equipment

Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection Hand Protection:	Additional Information: Use suitable protective gloves if risk of skin contact.
Skin and Body Protection:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Avoid contact with eyes. Wash contaminated clothing before reuse. Avoid contact with skin. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance	
Physical state:	liquid
Form:	liquid
Color:	Gray
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	> 93 °C > 200 °F(Setaflash Closed Cup)
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive	ve limits
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper:	No data available.
Explosive limit - lower:	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.16
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.



Auto-ignition temperature: Decomposition temperature: Viscosity:	No data available. No data available. No data available.	
10. Stability and reactivity		
Reactivity:	No data available.	
Chemical Stability:	Material is stable under normal conditions.	
Possibility of hazardous reactions:	No data available.	
Conditions to avoid:	Avoid heat or contamination.	
Incompatible Materials:	No data available.	
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.	
11. Toxicological information		
Information on likely routes of e Inhalation:	exposure In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.	
Skin Contact:	May be harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.	
Eye contact:	Causes serious eye irritation.	
Ingestion:	May be harmful if swallowed.	
Symptoms related to the physical, chemical and toxicological characteristics		
Inhalation:	No data available.	
Skin Contact:	No data available.	
Eye contact:	No data available.	
Ingestion:	No data available.	
Information on toxicological eff	ects	
Acute toxicity (list all possibl	e routes of exposure)	
Oral Product:	Not classified for acute toxicity based on available data.	



Specified substance(s): Bisphenol A Polyglycidyl Ether Resin	LD 50 (Rat): > 2,000 mg/kg
o-Cresyl glycidyl ether	LD 50 (Rat): > 5,000 mg/kg
Aluminum hydroxide	LD 50 (Rat): > 2,000 mg/kg
Amorphous silica	LD 50 (Rat): > 5,000 mg/kg
Carbon Black	LD 50 (Rat): > 8,000 mg/kg
Dermal Product:	Not classified for acute toxicity based on available data.
Specified substance(s): Bisphenol A Polyglycidyl Ether Resin	LD 50 (Rat): > 2,000 mg/kg
o-Cresyl glycidyl ether	LD 50 (Rat): > 2,000 mg/kg
Amorphous silica	LD 50 (Rabbit): > 5,000 mg/kg
Inhalation Product:	Not classified for acute toxicity based on available data.
	Not classified for acute toxicity based on available data. LC 50: > 20 mg/l LC 50: > 5 mg/l
Product: Specified substance(s): Bisphenol A Polyglycidyl	LC 50: > 20 mg/l
Product: Specified substance(s): Bisphenol A Polyglycidyl Ether Resin	LC 50: > 20 mg/l LC 50: > 5 mg/l
Product: Specified substance(s): Bisphenol A Polyglycidyl Ether Resin o-Cresyl glycidyl ether	LC 50: > 20 mg/l LC 50: > 5 mg/l LC 50 (Rat): 6,090 mg/m3
Product: Specified substance(s): Bisphenol A Polyglycidyl Ether Resin o-Cresyl glycidyl ether Aluminum hydroxide	LC 50: > 20 mg/l LC 50: > 5 mg/l LC 50 (Rat): 6,090 mg/m3 LC 50 (Rat): 7.6 mg/l



Specified substance(s): Bisphenol A Polyglycidyl Ether Resin	in vivo (Rabbit): Moderately irritating , 24 h
o-Cresyl glycidyl ether	in vivo (Rabbit): Not irritant , 7 d
Aluminum hydroxide	in vivo (Rabbit): Not classified as an Irritant , 24 - 72 h
Amorphous silica	in vivo (Rabbit): Not irritant , 48 h
Carbon Black	in vivo (Rabbit): Not irritant , 120 h

Serious Eye Damage/Eye Irritation

Product: Specified substance(s):	No data available.
Aluminum hydroxide	Rabbit, 24 - 72 hrs: Not irritant
Amorphous silica	Rabbit, 24 - 72 hrs: Not irritant
Carbon Black	Rabbit, 24 - 72 hrs: Not irritant

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity	
Product:	

Suspected of causing cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Carbon Black Overall evaluation: Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens: Carbon Black Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended: No carcinogenic components identified

Germ Cell Mutagenicity

In vitro Product: No data available.

In vivo Product:

No data available.

Reproductive toxicity Product:

No data available.



Specific Target Organ Toxicity -	- Single Exposure
Product:	No data available.
Specific Target Organ Toxicity -	- Repeated Exposure
Product:	No data available.
Aspiration Hazard Product:	No data available.
Other effects:	Constituents of this product may include crystalline silica which, if in inhalable form, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimis exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish Product:	No data available.
Specified substance(s): Bisphenol A Polyglycidyl Ether Resin	LC 50 (Oncorhynchus mykiss, 96 h): 1.5 mg/l Experimental result, Key study
o-Cresyl glycidyl ether	LC 50 (Oncorhynchus mykiss, 96 h): 2.8 - 5.1 mg/l Experimental result, Key study
Aluminum hydroxide	LC 50 (Oncorhynchus mykiss, 96 h): 7.4 mg/l Experimental result, Weight of Evidence study
Aquatic Invertebrates Product:	No data available.
Specified substance(s): Bisphenol A Polyglycidyl Ether Resin	EC 50 (Daphnia magna, 48 h): 1.1 mg/l experimental result Experimental result, Key study
o-Cresyl glycidyl ether	EC 50 (Daphnia magna, 48 h): 3.3 mg/l experimental result Experimental result, Key study



Aluminum hydroxide	EC 50 (Ceriodaphnia dubia, 48 h): 1.5 mg/l experimental result Experimental result, Weight of Evidence study
Carbon Black	LC 50 (Daphnia sp., 48 h): 164 mg/I QSAR QSAR, Key study
Chronic hazards to the aquation	c environment:
Fish Product:	No data available.
Specified substance(s): Aluminum hydroxide	NOAEL (Pimephales promelas): 0.16 mg/l read-across based on grouping of substances (category approach) Read-across based on grouping of substances (category approach), Weight of Evidence study
Aquatic Invertebrates Product:	No data available.
Specified substance(s): Bisphenol A Polyglycidyl Ether Resin	NOAEL (Daphnia magna): 0.3 mg/l experimental result Experimental result, Key study
Aluminum hydroxide	NOAEL (Daphnia magna): 0.076 mg/l experimental result Experimental result, Weight of Evidence study
Carbon Black	EC 50 (Daphnia sp.): 4.9 mg/l QSAR QSAR, Key study
Toxicity to Aquatic Plants Product:	No data available.
Persistence and Degradability	
Biodegradation Product:	No data available.
Specified substance(s): Bisphenol A Polyglycidyl Ether Resin	82 % Detected in water. Experimental result, Key study
o-Cresyl glycidyl ether	11 - 17 % (28 d) Detected in water. Experimental result, Key study
BOD/COD Ratio Product:	No data available.
Bioaccumulative potential Bioconcentration Factor (BC Product:	F) No data available.

Specified substance(s):Bisphenol A PolyglycidylBioconcentration Factor (BCF): 31 Aquatic sediment QSAR, Key studyEther Resin

Partition Coefficient n-octanol / water (log Kow)



Product:	No data available.	
Specified substance(s): Bisphenol A Polyglycidyl Ether Resin	Log Kow: 2.64 - 3.78 25 °C Yes Experimental result, Key study	
Mobility in soil:	No data available.	
Other adverse effects:	Toxic to aquatic life with long lasting effects.	
13. Disposal considerations		
Disposal methods:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.	
Contaminated Packaging:	No data available.	

14. Transport information

TDG:

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A Epoxy Resin), 9, PG III

CFR / DOT:

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A Epoxy Resin), 9, PG III, MARINE POLLUTANT

IMDG:

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A Epoxy Resin), 9, PG III, MARINE POLLUTANT

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.



US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

<u>Chemical Identity</u> Crystalline Silica (Quartz)/ Silica Sand OSHA hazard(s)

kidney effects lung effects immune system effects Cancer

CERCLA Hazardous Substance List (40 CFR 302.4):

None present or none present in regulated quantities.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard Skin Corrosion or Irritation Serious eye damage or eye irritation Respiratory or Skin Sensitization Germ Cell Mutagenicity Carcinogenicity

US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

US. EPCRA (SARA Title III Section 313 Toxic Chemical Release Inventory (TRI) Reporting

Chemical Identity % by weight

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



WARNING

Cancer - www.P65Warnings.ca.gov

International regulations

Montreal protocol Not applicable

Stockholm convention Not applicable

Rotterdam convention Not applicable



Kyoto protocol Not applicable

VOC: When appropriately mixed with the other part, product has a VOC less water and exempt solvent of: 104 g/l

Regulatory VOC (less water and : 1 g/l exempt solvent) VOC Method 310 : 0.04 %



Inventory Status: Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	One or more components in this product are not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.



16.Other information, including date of preparation or last revision

Revision Date:	11/17/2022
Version #:	3.2
Further Information:	No data available.
Disclaimer:	For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.



Version: 3.2 Revision Date: 11/17/2022

SAFETY DATA SHEET

1. Identification

Product identifier: DURAL 452 MV 1:1 PT B Product Code: 002DM 02

Recommended use and restriction on use

Recommended use: Curative Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Euclid Admixture Canada Inc. 2835 Grand-Allee Saint Hubert QC J4T 2R4 CA

Contact person: Telephone: Emergency telephone number:

EH&S Department (450)465-2233 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards	
Acute toxicity (Oral)	Category 4
Acute toxicity (Inhalation - vapor)	Category 4
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 1
Toxic to reproduction	Category 2

Unknown toxicity - Health	
---------------------------	--

Acute toxicity, oral	9.75 %
Acute toxicity, dermal	35.33 %
Acute toxicity, inhalation, vapor	88.94 %
Acute toxicity, inhalation, dust	86.85 %
or mist	

Environmental Hazards

Acute hazards to the aquatic environment

Category 2


Unknown toxicity - Environment

Acute hazards to the aquatic	63.39 %
environment	
Chronic hazards to the aquatic	100 %
environment	



Label Elements

Hazard Symbol:



3. Composition/information on ingredients

Mixtures



Chemical Identity	CAS number	Content in percent (%)*
1,2-Cyclohexanediamine	694-83-7	25 - <50%
4-Nonylphenol	84852-15-3	10 - <25%
Benzyl alcohol	100-51-6	10 - <20%
4-tert-Butylphenol	98-54-4	3 - <5%
m-Xylenediamine	1477-55-0	1 - <3%
1,3-Cyclohexanedimethanamine	2579-20-6	1 - <3%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Description of necessary first-aid measures			
Inhalation:	Move to fresh air.		
Skin Contact:	Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.		
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Call a physician or poison control center immediately.		
Ingestion:	Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.		
Personal Protection for First- aid Responders:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.		
Most important symptoms/effects, acute and delayed			
Symptoms:	Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping. Extreme irritation of eyes and mucous membranes, including burning and tearing.		
Hazards:	No data available.		
Indication of immediate medica	al attention and special treatment needed		
Treatment:	Symptoms may be delayed.		
5. Fire-fighting measures			
General Fire Hazards:	No unusual fire or explosion hazards noted.		
Suitable (and unsuitable) extinguishing media			
Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.		
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.		



Specific hazards arising from the chemical:	During fire, gases hazardous to health may be formed.			
Special protective equipment and	d precautions for fire-fighters			
Special fire-fighting procedures:	No data available.			
Special protective equipment for fire-fighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.			
6. Accidental release measures	6			
Personal precautions, protective equipment and emergency procedures:	See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.			
Accidental release measures:	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.			
Methods and material for containment and cleaning up:	Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.			
Environmental Precautions:	Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.			
7. Handling and storage				
Handling				
Technical measures (e.g. Local and general ventilation):	Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.			
Safe handling advice:	Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.Do not taste or swallow. Wash hands thoroughly after handling. Do not get in eyes. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with skin.			
Contact avoidance measures:	No data available.			
Hygiene measures:	Observe good industrial hygiene practices. Do not eat, drink or smoke when using the product. Wash hands after handling. Do not get in eyes. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated clothing before reuse. Avoid contact with skin. Wash hands before breaks and immediately after handling the product.			
Storage				
Safe storage conditions:	Store locked up.			



Safe packaging materials: No data available.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure Limit Values	Source
m-Xylenediamine	Ceiling	0.018 ppm	US. ACGIH Threshold Limit Values, as amended (02 2020)

None of the components have assigned exposure limits.

Chemical name	Туре	Exposure Limit Values		Source
m-Xylenediamine	CEILING		0.1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
m-Xylenediamine	CEV		0.1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
m-Xylenediamine	CEILING		0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Hexamethylenediamine	TWA	0.5 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Hexamethylenediamine	TWA	0.5 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Hexamethylenediamine	TWA	0.5 ppm	2.3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Stoddard solvent (Mineral Spirits)	STEL		580 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA		290 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm	525 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
1-Methoxy-2-propanol acetate	TWA	50 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	75 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)



1-Methoxy-2-propanol acetate	TWA	50 ppm	270 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (12 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm	123 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)

Appropriate Engineering
ControlsObserve good industrial hygiene practices. Observe occupational exposure
limits and minimize the risk of inhalation of vapors and mist. Mechanical
ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

Eye/face protection:	Wear a full-face respirator, if needed. Wear safety glasses with side shields (or goggles) and a face shield.
Skin Protection Hand Protection:	Additional Information: Use suitable protective gloves if risk of skin contact.
Skin and Body Protection:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
Hygiene measures:	Observe good industrial hygiene practices. Do not eat, drink or smoke when using the product. Wash hands after handling. Do not get in eyes. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated clothing before reuse. Avoid contact with skin. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties

Appearance
Physical state:
Form:

Color: Odor: Odor threshold: pH: liquid liquid Amber Mild pungent No data available. No data available.



Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	> 93 °C > 200 °F(Setaflash Closed Cup)
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosi	ve limits
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper:	No data available.
Explosive limit - lower:	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.013 - 1.037
Solubility(ies)	
Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Avoid contact with acids.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure		
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.	
Skin Contact:	May be harmful in contact with skin. Causes skin irritation.	
Eye contact:	Causes serious eye damage.	
Ingestion:	Harmful if swallowed.	



Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.
Information on toxicological effe	cts
Acute toxicity (list all possible	routes of exposure)
Oral Product:	ATEmix: 1,925.44 mg/kg
Dermal Product:	ATEmix: 3,888.29 mg/kg
Inhalation Product:	ATEmix: 11.03 mg/l ATEmix : 7.21 mg/l
Repeated dose toxicity Product:	No data available.
Skin Corrosion/Irritation Product:	No data available.
Specified substance(s): 4-Nonylphenol	in vivo (Rabbit): Irritating , 1 - 8 d
Benzyl alcohol	in vivo (Rabbit): Slightly irritating
4-tert-Butylphenol	in vivo (Rabbit): Not Classified , 7 - 10 d
m-Xylenediamine	in vivo (Mouse): Corrosive , 4 h
1,3- Cyclohexanedimethana mine	in vivo (Rabbit): Corrosive , 1 h
Serious Eye Damage/Eye Irritatio Product: Specified substance(s):	on No data available.

4-Nonylphenol

Rabbit, 24 - 72 hrs: Corrosive



4-tert-Butylphenol	Rabbit, 24 hrs: Category 1	
Respiratory or Skin Sensitizatio Product:	n No data available.	
Carcinogenicity Product:	No data available.	
IARC Monographs on the Evaluation No carcinogenic component	ation of Carcinogenic Risks to Humans: is identified	
US. National Toxicology Progra No carcinogenic component	m (NTP) Report on Carcinogens: is identified	
US. OSHA Specifically Regulate No carcinogenic component	d Substances (29 CFR 1910.1001-1050), as amended: s identified	
Germ Cell Mutagenicity		
In vitro Product:	No data available.	
In vivo Product:	No data available.	
Reproductive toxicity Product:	Suspected of damaging fertility or the unborn child.	
Specific Target Organ Toxicity - Product:	Single Exposure No data available.	
Specific Target Organ Toxicity - Product:	Repeated Exposure No data available.	
Aspiration Hazard Product:	No data available.	
Other effects:	No data available.	

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:



Fish Product:	No data available.
Specified substance(s): 1,2-Cyclohexanediamine	LC 50 (Pimephales promelas, 96 h): 1,825 mg/l Read-across based on grouping of substances (category approach), Key study
4-Nonylphenol	EC 50 (Pimephales promelas, 96 h): 96 μ g/l Experimental result, Key study
Benzyl alcohol	LC 50 (Pimephales promelas, 96 h): 460 mg/l Experimental result, Key study
4-tert-Butylphenol	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 4.71 - 5.62 mg/l Mortality
m-Xylenediamine	LC 50 (Oryzias latipes, 96 h): 87.6 mg/l Experimental result, Key study
1,3- Cyclohexanedimethanam ine	LC 50 (Leuciscus idus, 96 h): 130 mg/l Experimental result, Key study
Aquatic Invertebrates Product:	No data available.
Specified substance(s): 1,2-Cyclohexanediamine	EC 50 (Daphnia magna, 48 h): 19.8 mg/l read-across based on grouping of substances (category approach) Read-across based on grouping of substances (category approach), Key study
4-Nonylphenol	EC 50 (Daphnia magna, 48 h): 84.4 µg/l experimental result Experimental result, Key study
Benzyl alcohol	EC 50 (Daphnia magna, 48 h): 230 mg/l experimental result Experimental result, Key study
4-tert-Butylphenol	EC 50 (Daphnia magna, 48 h): 4.8 mg/l experimental result Experimental result, Key study
m-Xylenediamine	EC 50 (Daphnia magna, 48 h): 15.2 mg/l experimental result Experimental result, Key study
1,3- Cyclohexanedimethanam ine	EC 50 (Daphnia magna, 48 h): 33.1 mg/l experimental result Experimental result, Key study

Chronic hazards to the aquatic environment:

Fish Product:	No data available.
Specified substance(s): 4-Nonylphenol	NOAEL (Oncorhynchus mykiss): 0.006 mg/l experimental result Experimental result, Key study
4-tert-Butylphenol	NOAEL (Pimephales promelas): 10 µg/l experimental result Experimental result, Key study



Aquatic Invertebrates Product:	No data available.	
Specified substance(s): 1,2-Cyclohexanediamine	NOAEL (Daphnia magna): 4.16 mg/l read-across based on grouping of substances (category approach) Read-across based on grouping of substances (category approach), Key study	
4-Nonylphenol	NOAEL (Daphnia magna): 0.024 mg/l experimental result Experimental result fresult (Daphnia magna): 0.024 mg/l experimental result, Key study	
Benzyl alcohol	NOAEL (Daphnia magna): 51 mg/l experimental result Experimental result, Key study	
4-tert-Butylphenol	NOAEL (Daphnia magna): 0.73 mg/l experimental result Experimental result, Key study	
m-Xylenediamine	NOAEL (Daphnia magna): 4.7 mg/l experimental result Experimental result, Key study	
Toxicity to Aquatic Plants Product:	No data available.	
Persistence and Degradability		
Biodegradation Product:	No data available.	
Specified substance(s): 1,2-Cyclohexanediamine	100 % Detected in water. Experimental result, Key study	
4-Nonylphenol	48.2 % (35 d) Detected in water. Experimental result, Key study	
Benzyl alcohol	97 % (21 d) Detected in water. Experimental result, Key study	
4-tert-Butylphenol	60 % (28 d) Detected in water. Experimental result, Key study	
m-Xylenediamine	49 % (28 d) Detected in water. Experimental result, Key study	
1,3- Cyclohexanedimethanami ne	29 % (28 d) Detected in water. Experimental result, Key study	
BOD/COD Ratio Product:	No data available.	
Bioaccumulative potential Bioconcentration Factor (BCF) Product: No data available.		

Specified substance(s):



4-Nonylphenol	Pimephales promelas, Bioconcentration Factor (BCF): 740 Aquatic sediment Experimental result, Key study
4-tert-Butylphenol	Cyprinus carpio, Bioconcentration Factor (BCF): 44 - 48 Aquatic sediment Experimental result, Key study
Partition Coefficient n-octanol / v	water (log Kow)
Product:	No data available.
Specified substance(s): Benzyl alcohol	Log Kow: 1.10
Mobility in soil:	No data available.
Other adverse effects:	Toxic to aquatic organisms.
13. Disposal considerations	
Disposal methods:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.

14. Transport information

TDG:

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Nonylphenol), 9, PG III

CFR / DOT:

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Nonylphenol), 9, PG III, MARINE POLLUTANT

IMDG:

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Nonylphenol), 9, PG III, MARINE POLLUTANT

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Chemical Identity

Reportable quantity

4-Nonylphenol

De minimis concentration: TSCA 5(a)(2)% One-Time Export Notification only.



Nonyl Phenol

De minimis concentration: TSCA 5(a)(2)% One-Time Export Notification only.

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

None present or none present in regulated quantities.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard Acute toxicity (any route or exposure) Skin Corrosion or Irritation Serious eye damage or eye irritation Reproductive toxicity

US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

US. EPCRA (SARA Title III Section 313 Toxic Chemical Release Inventory (TRI) Reporting

Chemical Identity	<u>% by weight</u>	
4-Nonylphenol	1.0%	
Nonyl Phenol		

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

No ingredient requiring a warning under CA Prop 65.

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable



Kyoto protocol Not applicable

VOC: When appropriately mixed with the other part, product has a VOC less water and exempt solvent of: 104 g/l

Regulatory VOC (less water and exempt solvent)	:	191 g/l
VOC Method 310	:	18.88 %



Inventory Status: Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	One or more components in this product are not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this



	product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	11/17/2022
Version #:	3.2
Further Information:	No data available.
Disclaimer:	For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.