

Revision Date: 11/17/2022

This is a kit that contains the following components: EUCOTHANE CLEAR PART A EUCOTHANE CLEAR PART A



Revision Date: 11/17/2022

SAFETY DATA SHEET

1. Identification

Product identifier: EUCOTHANE CLEAR PART A

Product Code: 154M 03

Recommended use and restriction on use

Recommended use: Coatings Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Euclid Admixture Canada Inc.

2835 Grand-Allee

Saint Hubert QC J4T 2R4

CA

Contact person: EH&S Department **Telephone:** (450)465-2233

Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids Category 3

Health Hazards

Acute toxicity (Inhalation - vapor) Category 4
Acute toxicity (Inhalation - dust and Category 4

mist)

Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2A
Carcinogenicity Category 2
Toxic to reproduction Category 1B
Specific Target Organ Toxicity - Category 2¹

Repeated Exposure

Target Organs

1. hearing

Unknown toxicity - Health

Acute toxicity, oral 4 %
Acute toxicity, dermal 9.5 %
Acute toxicity, inhalation, vapor 66 %
Acute toxicity, inhalation, dust 66 %

or mist

Environmental Hazards



Revision Date: 11/17/2022

Acute hazards to the aquatic Category 3

environment

Chronic hazards to the aquatic Category 3

environment

Unknown toxicity - Environment

Acute hazards to the aquatic 59.5 %

environment

Chronic hazards to the aquatic 59.5 %

environment

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Flammable liquid and vapor.

Harmful if inhaled.
Causes skin irritation.

Causes serious eye irritation. Suspected of causing cancer.

May damage fertility. May damage the unborn child.

May cause damage to organs through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects.

Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep

container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use non-sparking tools. Take action to prevent static

discharges. Do not breathe dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Use personal

protective equipment as required.

Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse

skin with water [or shower]. If skin irritation occurs: Get medical

advice/attention. Specific treatment (see supplemental first aid instructions

on this label). IF INHALED: Remove person to fresh air and keep

comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue



Revision Date: 11/17/2022

rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. In case of fire: Use dry sand, dry

chemical or alcohol-resistant foam for extinction.

Storage: Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents/ container to an approved facility in accordance with

local, regional, national and international regulations.

Hazard(s) not otherwise classified (HNOC):

Static accumulating flammable liquid can become electrostatically charged

even in bonded and grounded equipment.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Methyl n-amyl ketone	110-43-0	10 - <25%
Xylene	1330-20-7	10 - <20%
P-chlorobenzotrifluoride	98-56-6	5 - <10%
Ethylbenzene	100-41-4	1 - <2.5%
Dibutyl tin dilaurate	77-58-7	0.3 - <1%
Diisobutyl ketone	108-83-8	0.1 - <1%

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Description of necessary first-aid measures

Inhalation: Move to fresh air.

Skin Contact: Take off immediately all contaminated clothing. Immediately flush with

plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get

medical attention.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy

to do, remove contact lenses. Get medical attention.

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Personal Protection for First-

aid Responders:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

Most important symptoms/effects, acute and delayed

Symptoms: Respiratory tract irritation. Prolonged or repeated contact with skin

may cause redness, itching, irritation and eczema/chapping.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Revision Date: 11/17/2022

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Water may be

ineffective in fighting the fire. Fight fire from a protected location. Move

containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from

the chemical:

Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of

vapors or gases to explosive concentrations.

Special protective equipment and precautions for fire-fighters

Special fire-fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Accidental release measures:

In the event of a spill or accidental release, notify relevant authorities in

accordance with all applicable regulations.

Methods and material for containment and cleaning

up:

Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for

disposal according to local regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Handling



Revision Date: 11/17/2022

Technical measures (e.g. Local and general ventilation):

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical

ventilation or local exhaust ventilation may be required.

Safe handling advice: Provide adequate ventilation. Wear appropriate personal protective

equipment. Observe good industrial hygiene practices. Wash hands thoroughly after handling. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes. Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with

skin.

Contact avoidance measures: No data available.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. Avoid contact with eyes. When using do not smoke. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash

contaminated clothing before reuse. Avoid contact with skin.

Storage

Safe storage conditions: Store locked up. Store in a well-ventilated place. Store in a cool place.

Safe packaging materials: No data available.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure Lim	it Values	Source
Methyl n-amyl ketone	TWA	50 ppm		US. ACGIH Threshold Limit Values, as amended (2011)
	PEL	100 ppm	465 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Ethylbenzene	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Chemical Identity	Туре	Exposure Lim	it Values	Source
Methyl n-amyl ketone	TWA	50 ppm		US. ACGIH Threshold Limit Values, as amended (2011)
	PEL	100 ppm	465 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Xylene	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	STEL	150 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
	TWA	100 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
Ethylbenzene	TWA	20 ppm		US. ACGIH Threshold Limit Values, as





Revision Date: 11/17/2022

				amended (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air
				Contaminants (29 CFR 1910.1000), as
				amended (02 2006)
Diisobutyl ketone	PEL	50 ppm	290 mg/m3	US. OSHA Table Z-1 Limits for Air
				Contaminants (29 CFR 1910.1000), as
				amended (02 2006)
	TWA	25 ppm		US. ACGIH Threshold Limit Values, as
				amended (2008)
Dibutyl tin dilaurate - as Sn	STEL		0.2 mg/m3	US. ACGIH Threshold Limit Values, as
				amended (2011)
	TWA		0.1 mg/m3	US. ACGIH Threshold Limit Values, as
			_	amended (2011)
	PEL		0.1 mg/m3	US. OSHA Table Z-1 Limits for Air
			_	Contaminants (29 CFR 1910.1000), as
				amended (02 2006)

Chemical name	Туре	Exposure Lim	it Values	Source
Methyl n-amyl ketone	TWA	50 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methyl n-amyl ketone	TWA	25 ppm	115 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Methyl n-amyl ketone	TWA	50 ppm	233 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
1-Methoxy-2-propanol acetate	TWA	50 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	75 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1-Methoxy-2-propanol acetate	TWA	50 ppm	270 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (12 2007)
Ethyl 3-ethoxypropionate	TWA	50 ppm	300 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (12 2007)
Ethylbenzene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Ethylbenzene	TWA	20 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)





Revision Date: 11/17/2022

Chemical name	Туре	Exposure Lim	it Values	Source
Methyl n-amyl ketone	TWA	50 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methyl n-amyl ketone	TWA	25 ppm	115 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Methyl n-amyl ketone	TWA	50 ppm	233 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Xylene	STEL	150 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Xylene	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	STEL	150 ppm	651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Ethylbenzene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Ethylbenzene	TWA	20 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Diisobutyl ketone	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Diisobutyl ketone	TWA	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Diisobutyl ketone	TWA	25 ppm	145 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Dibutyl tin dilaurate - as Sn	STEL		0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA		0.1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)



Revision Date: 11/17/2022

Dibutyl tin dilaurate - as Sn	TWA	0.1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Additional Information: Use suitable protective gloves if risk of skin contact.

Skin and Body Protection: Wear suitable protective clothing. Wear chemical-resistant gloves,

footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific

information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. Avoid contact with eyes. When using do not smoke. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash

contaminated clothing before reuse. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state: liquid Form: liquid

Color: No data available.

Odor: Mild petroleum/solvent

Odor threshold: No data available.



Revision Date: 11/17/2022

pH: No data available.Melting point/freezing point: No data available.

Initial boiling point and boiling range: 137 - 191 °C 279 - 375 °F

Flash Point: 38 °C 100 °F
Evaporation rate: Slower than Ether

Flammability (solid, gas): No Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper:

Explosive limit - lower:

No data available.

No data available.

No data available.

No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and

in the bottom of containers.

Relative density: 1.0

Solubility(ies)

Solubility in water:
Solubility (other):
Partition coefficient (n-octanol/water):
No data available.
No data available.
No data available.
No data available.
Viscosity:
Practically Insoluble
No data available.
No data available.
No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

Conditions to avoid: Heat, sparks, flames.

Incompatible Materials: Alcohols. Amines. Strong acids. Strong bases. Water, moisture.

Hazardous Decomposition

Products:

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation: In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

Skin Contact: May be harmful in contact with skin. Causes skin irritation.

Eye contact: Causes serious eye irritation.

Ingestion: May be harmful if swallowed.



Revision Date: 11/17/2022

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 3,382.19 mg/kg

Dermal

Product: ATEmix: 4,782.61 mg/kg

Inhalation

Product: ATEmix: 13.76 mg/l

ATEmix: 1.5 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Methyl n-amyl ketone in vivo (Rabbit): Moderately irritating, 4 h

Xylene in vivo (Rat): Slightly irritating, 24 h

P-chlorobenzotrifluoride in vivo (Rabbit): Not irritant (unspecified classification), 24 - 72 h

Dibutyl tin dilaurate In vitro (Human, in vitro reconstituted epidermis model): Not irritant, 15 min

Diisobutyl ketone in vivo (Rabbit): Not irritant, 24 - 72 h

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Xylene Rabbit, 24 hrs: Moderately irritating

Rabbit, 1 hrs: Not irritant



Revision Date: 11/17/2022

P-chlorobenzotrifluoride Rabbit, 24 hrs: Not irritant

Dibutyl tin dilaurate Rabbit, 24 hrs: Highly irritating

Diisobutyl ketone Rabbit, 24 - 72 hrs: Not irritant

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: Suspected of causing cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

P- Overall evaluation: Possibly carcinogenic to humans.

chlorobenzotrifluori

de

Ethylbenzene Overall evaluation: Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: May damage fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Target Organs

Specific Target Organ Toxicity - Repeated Exposure: hearing

Aspiration Hazard

Product: No data available.



Revision Date: 11/17/2022

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Methyl n-amyl ketone LC 50 (Pimephales promelas, 96 h): 131 mg/l Experimental result, Key study

Xylene LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality

P-chlorobenzotrifluoride LC 50 (96 h): 3 mg/l Experimental result, Key study

Ethylbenzene LC 50 (Oncorhynchus mykiss, 96 h): 4.2 mg/l Experimental result, Key study

Diisobutyl ketone LC 50 (Oncorhynchus mykiss, 96 h): 30 mg/l Experimental result, Key study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Methyl n-amyl ketone EC 50 (Daphnia magna, 48 h): > 90.1 mg/l experimental result Experimental

result, Key study

P-chlorobenzotrifluoride EC 50 (Daphnia magna, 48 h): 18.84 mg/l experimental result Experimental

result, Key study

Ethylbenzene EC 50 (Daphnia magna, 48 h): 1.8 - 2.4 mg/l experimental result

Experimental result, Key study

Dibutyl tin dilaurate EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

EC 50 (Daphnia magna, 48 h): 1.7 - 3.4 mg/l experimental result

Experimental result, Key study

Diisobutyl ketone EC 50 (Daphnia magna, 48 h): 37.2 mg/l experimental result Experimental

result, Key study

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Specified substance(s):



Revision Date: 11/17/2022

Ethylbenzene NOAEL (Ceriodaphnia dubia): 1 mg/l secondary data Other, Key study

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

Methyl n-amyl ketone 69 % (28 d) Detected in water. Experimental result, Key study

P-chlorobenzotrifluoride 7 % (28 d) Detected in water. Experimental result, Key study

Ethylbenzene 70 - 80 % (28 d) Detected in water. Experimental result, Key study

Dibutyl tin dilaurate 23 % (39 d) Detected in water. Experimental result, Key study

Diisobutyl ketone 88 % Detected in water. Experimental result, Key study

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

Xylene

Oncorhynchus mykiss, Bioconcentration Factor (BCF): > 8.1 - < 25.9 Aquatic

sediment Experimental result, Key study

P-chlorobenzotrifluoride Bioconcentration Factor (BCF): 9 Aquatic sediment Estimated by calculation,

Key study

Ethylbenzene Oncorhynchus kisutch, Bioconcentration Factor (BCF): 1 Aquatic sediment

Other, Key study

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Methyl n-amyl ketone Log Kow: 1.98

Xylene Log Kow: 2.77 - 3.15 No Not specified, Not specified

P-chlorobenzotrifluoride Log Kow: 3.60 25 °C

Ethylbenzene Log Kow: 3.15

Log Kow: 3.13 - 3.14 No Other, Supporting study

Dibutyl tin dilaurate Log Kow: 3.12



Revision Date: 11/17/2022

Diisobutyl ketone Log Kow: 2.56

Mobility in soil: No data available.

Other adverse effects: Harmful to aquatic life with long lasting effects.

13. Disposal considerations

Disposal methods: Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

UN1993, FLAMMABLE LIQUID, N.O.S. (Xylene, Butyl Acetate), 3, PG III

CFR / DOT:

UN1993, Flammable liquids, n.o.s. (Xylene, Butyl Acetate), 3, PG III

IMDG:

UN1993, FLAMMABLE LIQUID, N.O.S. (Xylene, Butyl Acetate), 3, PG III

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

<u>Chemical Identity</u> <u>Reportable quantity</u>

P-chlorobenzotrifluoride De minimis concentration: TSCA 4% One-Time Export Notification only.

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

None present or none present in regulated quantities.



Revision Date: 11/17/2022

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity Reportable quantity

Xylene 100 lbs. Ethylbenzene 1000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route or exposure)

Skin Corrosion or Irritation

Serious eye damage or eye irritation

Carcinogenicity

Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

Hazards Not Otherwise Classified (HNOC)

US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

Not regulated.

US. EPCRA (SARA Title III Section 313 Toxic Chemical Release Inventory (TRI) Reporting

<u>Chemical Identity</u> <u>% by weight</u>

Xylene 1.0% Ethylbenzene 0.1%

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

Chemical Identity Reportable quantity

Xylene Reportable quantity: 100 lbs.

US State Regulations

US. California Proposition 65



WARNING

Cancer - www.P65Warnings.ca.gov

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable



Revision Date: 11/17/2022

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC: When appropriately mixed with the other part, product has a VOC less water and exempt solvent of: 253 g/l

Regulatory VOC (less water and : 311 g/l

exempt solvent)

VOC Method 310 : 25.90 %



Revision Date: 11/17/2022

Inventory Status:

Canada DSL Inventory List: One or more components in this

product are not listed on or exempt

from the Inventory.

Canada NDSL Inventory: One or more components in this

product are not listed on or exempt

from the Inventory.

Ontario Inventory: One or more components in this

product are not listed on or exempt

from the Inventory.

China Inv. Existing Chemical

Substances:

One or more components in this product are not listed on or exempt

from the Inventory.

Japan (ENCS) List: One or more components in this

product are not listed on or exempt

from the Inventory.

Japan ISHL Listing: One or more components in this

product are not listed on or exempt

from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this

product are not listed on or exempt

from the Inventory.

Korea Existing Chemicals Inv. (KECI): One or more components in this

product are not listed on or exempt

from the Inventory.

Mexico INSQ: One or more components in this

product are not listed on or exempt

from the Inventory.

New Zealand Inventory of Chemicals: One or more components in this

product are not listed on or exempt

from the Inventory.

Philippines PICCS: One or more components in this

product are not listed on or exempt

from the Inventory.

Taiwan Chemical Substance Inventory: One or more components in this

product are not listed on or exempt

from the Inventory.

US TSCA Inventory: One or more components in this



Revision Date: 11/17/2022

product are not listed on or exempt

from the Inventory.

EINECS, ELINCS or NLP: One or more components in this

product are not listed on or exempt

from the Inventory.

Australia Industrial Chem. Act (AIIC): One or more components in this

product are not listed on or exempt

from the Inventory.

Switzerland New Subs Notified/Registered:

One or more components in this product are not listed on or exempt

from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date: 11/17/2022

Version #: 3.1

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard

information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.



Revision Date: 11/17/2022

SAFETY DATA SHEET

1. Identification

Product identifier: EUCOTHANE CLEAR PART A

Product Code: 154M 03

Recommended use and restriction on use

Recommended use: Coatings Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Euclid Admixture Canada Inc.

2835 Grand-Allee

Saint Hubert QC J4T 2R4

CA

Contact person: EH&S Department **Telephone:** (450)465-2233

Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids Category 3

Health Hazards

Acute toxicity (Inhalation - dust and Category 4

mist)

Acute toxicity (Inhalation - vapor) Category 4
Acute toxicity (Inhalation - dust and Category 4

nist)

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Respiratory sensitizer

Skin sensitizer

Category 1

Category 1

Category 1

Category 2

Single Exposure

Specific Target Organ Toxicity - Category 2³

Repeated Exposure

- 2. Respiratory tract irritation.
- 3. hearing

Unknown toxicity - Health

Acute toxicity, inhalation, vapor 88 %



Revision Date: 11/17/2022

Acute toxicity, inhalation, dust or mist

11 %

Environmental Hazards

Acute hazards to the aquatic

Category 3

environment

Chronic hazards to the aquatic

Category 3

environment

Unknown toxicity - Environment

Acute hazards to the aquatic

78 %

environment

Chronic hazards to the aquatic

environment

78 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Flammable liquid and vapor.

Harmful if inhaled. Causes skin irritation.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction. Suspected of causing cancer. May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects.

Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep

container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use non-sparking tools. Take action to prevent static

discharges. Do not breathe dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective equipment as required. [In case of inadequate ventilation] wear



Revision Date: 11/17/2022

respiratory protection.

Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse

skin with water [or shower]. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention. Specific

treatment (see supplemental first aid instructions on this label). IF INHALED:

Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam for extinction.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked

up.

Disposal: Dispose of contents/ container to an approved facility in accordance with

local, regional, national and international regulations.

Hazard(s) not otherwise classified (HNOC):

Static accumulating flammable liquid can become electrostatically charged

even in bonded and grounded equipment.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Homopolymer of HDI	28182-81-2	50 - <100%
Xylene	1330-20-7	10 - <20%
Butyl acetate	123-86-4	10 - <20%
Hexamethylene diisocyanate (HDI)	822-06-0	1 - <5%
Ethylbenzene	100-41-4	1 - <2.5%

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Description of necessary first-aid measures

Inhalation: Call a physician or poison control center immediately. If breathing

stops, provide artificial respiration. Move to fresh air. If breathing is

difficult, give oxygen.

Skin Contact: Take off immediately all contaminated clothing. Get medical attention.

Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction

develops, get medical attention.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy

to do, remove contact lenses. Get medical attention.

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.



Revision Date: 11/17/2022

Personal Protection for First-

aid Responders:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

Most important symptoms/effects, acute and delayed

Symptoms: Respiratory tract irritation. Prolonged or repeated contact with skin

may cause redness, itching, irritation and eczema/chapping.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Water may be

ineffective in fighting the fire. Fight fire from a protected location. Move

containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from

the chemical:

Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of

vapors or gases to explosive concentrations.

Special protective equipment and precautions for fire-fighters

Special fire-fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.



Revision Date: 11/17/2022

Accidental release measures: In the event of a spill or accidental release, notify relevant authorities in

accordance with all applicable regulations.

Methods and material for containment and cleaning

up:

Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for

disposal according to local regulations.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe

to do so. Do not contaminate water sources or sewer.

7. Handling and storage

Handling

Technical measures (e.g. Local and general ventilation):

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical

ventilation or local exhaust ventilation may be required.

Safe handling advice: Provide adequate ventilation. Wear appropriate personal protective

equipment. Observe good industrial hygiene practices.Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin. Avoid contact

with eyes, skin, and clothing.

Contact avoidance measures: No data available.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. Avoid contact with eyes. When using do not smoke. Wash contaminated clothing before reuse. Avoid contact with skin. Contaminated work clothing should not be allowed out of

the workplace.

Storage

Safe storage conditions: Store locked up. Store in a well-ventilated place. Store in a cool place.

Safe packaging materials: No data available.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure Limit Values		Source
Xylene	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	STEL	150 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
	TWA	100 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
Butyl acetate	TWA	50 ppm	•	US. ACGIH Threshold Limit Values, as






Revision Date: 11/17/2022

	I			ded (02 004C)
	0.751	ļ		amended (03 2016)
	STEL	150 ppm		US. ACGIH Threshold Limit Values, as
				amended (03 2016)
	PEL	150 ppm	710 mg/m3	US. OSHA Table Z-1 Limits for Air
				Contaminants (29 CFR 1910.1000), as
				amended (02 2006)
Chemical Identity	Туре	Exposure Lim	it Values	Source
Xylene	PEL	100 ppm	435 mg/m3	US, OSHA Table Z-1 Limits for Air
Aylerie	FLL	тоо ррпп	433 mg/m3	Contaminants (29 CFR 1910.1000), as
				amended (02 2006)
	STEL	450		
	SIEL	150 ppm		US. ACGIH Threshold Limit Values, as
	T) 4 / 4	400		amended (2008)
	TWA	100 ppm		US. ACGIH Threshold Limit Values, as
				amended (2008)
Butyl acetate	TWA	50 ppm		US. ACGIH Threshold Limit Values, as
				amended (03 2016)
	STEL	150 ppm		US. ACGIH Threshold Limit Values, as
				amended (03 2016)
	PEL	150 ppm	710 mg/m3	US. OSHA Table Z-1 Limits for Air
			•	Contaminants (29 CFR 1910.1000), as
				amended (02 2006)
Hexamethylene diisocyanate	TWA	0.005 ppm		US. ACGIH Threshold Limit Values, as
(HDI)				amended (2008)
Ethylbenzene	TWA	20 ppm		US. ACGIH Threshold Limit Values, as
•				amended (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air
			Ü	Contaminants (29 CFR 1910.1000), as
				amended (02 2006)

Chemical name	Туре	Exposure Limit	t Values	Source
Xylene	STEL	150 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Xylene	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	STEL	150 ppm	651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Butyl acetate	TWA	50 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Butyl acetate	STEL	150 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Butyl acetate	STEL	150 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (01 2021)
	TWA	50 ppm		Canada. British Columbia OELs. (Occupational



EUCLID CHEMICAL

Version: 3.1

Revision Date: 11/17/2022

			Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (01 2021)
	TWA	50 ppm	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Hexamethylene diisocyanate (HDI)	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Hexamethylene diisocyanate (HDI)	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Hexamethylene diisocyanate (HDI)	TWA	0.005 ppm 0.034 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)

Chemical name	Туре	Exposure Limit Values		Source Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)	
Xylene	Viene STEL 150 ppm				
	TWA	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)	
Xylene	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)	
	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)	
Xylene	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)	
	STEL	150 ppm	651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)	
Butyl acetate	TWA	50 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)	
	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)	
Butyl acetate	STEL	150 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)	
Butyl acetate	STEL	150 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (01 2021)	
	TWA	50 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (01 2021)	
	TWA	50 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)	



Revision Date: 11/17/2022

Hexamethylene diisocyanate (HDI)	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)	
Hexamethylene diisocyanate (HDI)	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)	
Hexamethylene diisocyanate (HDI)	TWA	0.005 ppm 0.034 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)	
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)	
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)	
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)	
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)	
Ethylbenzene	TWA	20 ppm	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)	

Biological Limit Values

ogical Ellint Values						
Chemical Identity	Exposure Limit Values	Source				
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)				
Hexamethylene diisocyanate (HDI) (Hexamethylenediamine (with hydrolysis): Sampling time: End of shift.)	15 μg/g (Creatinine in urine)	ACGIH BEI (03 2015)				
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)				

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Additional Information: Use suitable protective gloves if risk of skin contact.

Skin and Body Protection: Wear chemical-resistant gloves, footwear, and protective clothing

appropriate for the risk of exposure. Contact health and safety professional

or manufacturer for specific information.



Revision Date: 11/17/2022

Respiratory Protection: If engineering controls do not maintain airborne concentrations below

recommended exposure limits (where applicable) or to an acceptable level

(in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter,

cartridge or canister. Contact health and safety professional or

manufacturer for specific information.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. Avoid contact with eyes. When using do not smoke. Wash contaminated clothing before reuse. Avoid contact with skin. Contaminated work clothing should not be allowed out of

the workplace.

9. Physical and chemical properties

Appearance

Physical state: liquid
Form: liquid

Color: No data available.

Odor: Mild petroleum/solvent

Odor threshold:

pH:

No data available.

137 °C 279 °F

137 °C 279 °F

Flash Point: 32.5 °C 90.5 °F
Evaporation rate: Slower than Ether

Flammability (solid, gas): No Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper:

Explosive limit - lower:

No data available.

No data available.

Vapor pressure:

No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and

in the bottom of containers.

Relative density: 1.100

Solubility(ies)

Solubility in water:
Solubility (other):
Partition coefficient (n-octanol/water):
No data available.
No data available.
No data available.
No data available.
Viscosity:
No data available.
No data available.



Revision Date: 11/17/2022

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

Conditions to avoid: Heat, sparks, flames.

Incompatible Materials: Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides

and chromates). Strong bases.

Hazardous Decomposition

Products:

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

Skin Contact: Causes skin irritation. May cause an allergic skin reaction.

Eye contact: Causes serious eye irritation.

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 21,059.12 mg/kg

Dermal

Product: ATEmix: 10,000 mg/kg

Inhalation

Product: ATEmix: 11 mg/l

ATEmix: 1.5 mg/l



Revision Date: 11/17/2022

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Homopolymer of HDI in vivo (Rabbit): Irritating, 24 - 72 h

Xylene in vivo (Rat): Slightly irritating, 24 h

Butyl acetate in vivo (Rabbit): Not irritant, 24 - 72 h

Hexamethylene

diisocyanate (HDI)

in vivo (Rabbit): Corrosive, 4 - 72 h

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Homopolymer of HDI Rabbit, 24 - 72 hrs: Not irritant

Xylene Rabbit, 24 hrs: Moderately irritating

Rabbit, 1 hrs: Not irritant

Butyl acetate Rabbit, 24 - 72 hrs: Not irritant

Respiratory or Skin Sensitization

Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause sensitization by inhalation.

Carcinogenicity

Product: Suspected of causing cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Ethylbenzene Overall evaluation: Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified



Revision Date: 11/17/2022

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure
Product:
No data available.

Specific Target Organ Toxicity - Single Exposure: Respiratory tract irritation.

Specific Target Organ Toxicity - Repeated Exposure: hearing

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality

Butyl acetate EC 50 (Pimephales promelas, 96 h): 18 mg/l Experimental result, Key study

Ethylbenzene LC 50 (Oncorhynchus mykiss, 96 h): 4.2 mg/l Experimental result, Key study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Homopolymer of HDI EC 50 (Daphnia sp., 24 h): >= 100 mg/l experimental result Experimental

result, Supporting study

31/37



Revision Date: 11/17/2022

Butyl acetate EC 50 (Daphnia sp., 48 h): 44 mg/l experimental result Experimental result,

Key study

Ethylbenzene EC 50 (Daphnia magna, 48 h): 1.8 - 2.4 mg/l experimental result

Experimental result, Key study

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Butyl acetate NOAEL (Daphnia magna): 23 mg/l read-across from supporting substance

(structural analogue or surrogate) Read-across from supporting substance

(structural analogue or surrogate), Key study

Ethylbenzene NOAEL (Ceriodaphnia dubia): 1 mg/l secondary data Other, Key study

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

Homopolymer of HDI 1 % (28 d) Detected in water. Experimental result, Key study

Butyl acetate 83 % Detected in water. Experimental result, Key study

Hexamethylene

diisocyanate (HDI)

42 % (28 d) Detected in water. Experimental result, Key study

Ethylbenzene 70 - 80 % (28 d) Detected in water. Experimental result, Key study

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

Xylene

Oncorhynchus mykiss, Bioconcentration Factor (BCF): > 8.1 - < 25.9 Aquatic

sediment Experimental result, Key study



Revision Date: 11/17/2022

Butyl acetate Bioconcentration Factor (BCF): 15.3 Aquatic sediment Estimated by

calculation, Supporting study

Hexamethylene Bioconcentration Factor (BCF): 57.63 Aquatic sediment Estimated by

diisocyanate (HDI) calculation, Key study

Ethylbenzene Oncorhynchus kisutch, Bioconcentration Factor (BCF): 1 Aquatic sediment

Other, Key study

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Xylene Log Kow: 2.77 - 3.15 No Not specified, Not specified

Butyl acetate Log Kow: 1.78

Hexamethylene

diisocyanate (HDI)

Log Kow: 3.20

Ethylbenzene Log Kow: 3.15

Log Kow: 3.13 - 3.14 No Other, Supporting study

Mobility in soil: No data available.

Other adverse effects: Harmful to aquatic life with long lasting effects.

13. Disposal considerations

Disposal methods: Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

UN1993, FLAMMABLE LIQUID, N.O.S. (Xylene, Butyl Acetate), 3, PG III

CFR / DOT:

UN1993, Flammable liquids, n.o.s. (Xylene, Butyl Acetate), 3, PG III

IMDG:

UN1993, FLAMMABLE LIQUID, N.O.S. (Xylene, Butyl Acetate), 3, PG III

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.



Revision Date: 11/17/2022

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity Reportable quantity

Xylene 100 lbs.
Butyl acetate 5000 lbs.
Hexamethylene 100 lbs.

diisocyanate (HDI)

Ethylbenzene 1000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route or exposure)

Skin Corrosion or Irritation

Serious eye damage or eye irritation Respiratory or Skin Sensitization

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

Hazards Not Otherwise Classified (HNOC)

US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

Not regulated.

US. EPCRA (SARA Title III Section 313 Toxic Chemical Release Inventory (TRI) Reporting

Chemical Identity% by weightXylene1.0%Hexamethylene1.0%

diisocyanate (HDI)

Ethylbenzene 0.1%

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

Chemical Identity Reportable quantity



Revision Date: 11/17/2022

Xylene Reportable quantity: 100 lbs.

US State Regulations

US. California Proposition 65



WARNING

Cancer - www.P65Warnings.ca.gov

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC: When appropriately mixed with the other part, product has a VOC less water and exempt solvent of: 253 g/l

Regulatory VOC (less water and : 135 g/l

exempt solvent)

VOC Method 310 : 12.30 %



Revision Date: 11/17/2022

Inventory Status:

Canada DSL Inventory List: All components in this product are

listed on or exempt from the

Inventory.

EINECS, ELINCS or NLP: All components in this product are

listed on or exempt from the

Inventory.

Japan (ENCS) List: One or more components in this

product are not listed on or exempt

from the Inventory.

China Inv. Existing Chemical

Substances:

All components in this product are

listed on or exempt from the

Inventory.

Korea Existing Chemicals Inv. (KECI): All components in this product are

listed on or exempt from the

Inventory.

Canada NDSL Inventory: One or more components in this

product are not listed on or exempt

from the Inventory.

Philippines PICCS: All components in this product are

listed on or exempt from the

Inventory.

US TSCA Inventory: All components in this product are

listed on or exempt from the

Inventory.

New Zealand Inventory of Chemicals: All components in this product are

listed on or exempt from the

Inventory.

Japan ISHL Listing: One or more components in this

product are not listed on or exempt

from the Inventory.

Japan Pharmacopoeia Listing: One or more components in this

product are not listed on or exempt

from the Inventory.

Ontario Inventory: One or more components in this

product are not listed on or exempt

from the Inventory.

Mexico INSQ: One or more components in this



Revision Date: 11/17/2022

product are not listed on or exempt

from the Inventory.

Taiwan Chemical Substance Inventory: One or more components in this

product are not listed on or exempt

from the Inventory.

Australia Industrial Chem. Act (AIIC): One or more components in this

product are not listed on or exempt

from the Inventory.

Switzerland New Subs Notified/Registered:

One or more components in this product are not listed on or exempt

from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date: 11/17/2022

Version #: 3.1

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard

information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.