

SAFETY DATA SHEET

1. Identification

Material name: FLEXDECK TIECOAT IND LT GRAY

Material: TD4324505502

Recommended use and restriction on use

Recommended use: Coatings

Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

EUCLID CHEMICAL COMPANY

19218 REDWOOD ROAD

CLEVELAND OH 44110

US

Contact person:

EH&S Department

Telephone:

216-531-9222

Emergency telephone number:

1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids	Category 3
-------------------	------------

Health Hazards

Acute toxicity (Inhalation - dust and mist)	Category 4
---	------------

Skin Corrosion/Irritation	Category 2
---------------------------	------------

Respiratory sensitizer	Category 1
------------------------	------------

Skin sensitizer	Category 1
-----------------	------------

Carcinogenicity	Category 1A
-----------------	-------------

Unknown toxicity - Health

Acute toxicity, inhalation, vapor	85.09 %
-----------------------------------	---------

Acute toxicity, inhalation, dust or mist	85.09 %
--	---------

Environmental Hazards

Acute hazards to the aquatic environment	Category 3
--	------------

Chronic hazards to the aquatic environment	Category 3
--	------------

Unknown toxicity - Environment

Acute hazards to the aquatic environment	71.4 %
Chronic hazards to the aquatic environment	70.9 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Flammable liquid and vapor.
Harmful if inhaled.
Causes skin irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause cancer.
Harmful to aquatic life with long lasting effects.

Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective equipment as required. [In case of inadequate ventilation] wear respiratory protection.

Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see supplemental first aid instructions on this label). IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician. IF exposed or concerned: Get medical advice/attention. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage: Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents/ container to an approved facility in accordance with

local, regional, national and international regulations.

Hazard(s) not otherwise classified (HNOC):

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Aromatic petroleum distillates	64742-95-6	10 - <20%
1,2,4-Trimethylbenzene	95-63-6	5 - <10%
Talc	14807-96-6	1 - <5%
Titanium dioxide	13463-67-7	1 - <5%
Xylene	1330-20-7	0.1 - <1%
Isophorone Diisocyanate	4098-71-9	0.5 - <1%
Cumene	98-82-8	0.1 - <1%
Carbon Black	1333-86-4	0.1 - <1%
Ethylbenzene	100-41-4	0.1 - <1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Description of necessary first-aid measures

Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	Take off immediately all contaminated clothing. Get medical attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.
Ingestion:	Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
Personal Protection for First-aid Responders:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Most important symptoms/effects, acute and delayed

Symptoms: Respiratory tract irritation. Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from the chemical: Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.

Special protective equipment and precautions for fire-fighters

Special fire-fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Accidental release measures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer.

7. Handling and storage

Handling

Technical measures (e.g. Local and general ventilation):

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Safe handling advice:

Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin. Wash hands thoroughly after handling. Avoid contact with eyes, skin, and clothing.

Contact avoidance measures:

No data available.

Hygiene measures:

Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. When using do not smoke. Wash contaminated clothing before reuse. Avoid contact with skin. Contaminated work clothing should not be allowed out of the workplace.

Storage
Safe storage conditions:

Store locked up. Store in a well-ventilated place. Store in a cool place.

Safe packaging materials:

No data available.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
1,2,4-Trimethylbenzene	REL	25 ppm 125 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	TWA	25 ppm 125 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	25 ppm	US. ACGIH Threshold Limit Values, as amended (2008)
Talc - Respirable fraction.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values, as amended (2011)
Talc	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Talc - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (2008)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Titanium dioxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)



Titanium dioxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Titanium dioxide - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Titanium dioxide - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Xylene	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	STEL	150 ppm	US. ACGIH Threshold Limit Values, as amended (2008)
	TWA	100 ppm	US. ACGIH Threshold Limit Values, as amended (2008)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values, as amended (2008)
Cumene	PEL	50 ppm 245 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	5 ppm	US. ACGIH Threshold Limit Values, as amended (01 2021)
Carbon Black	PEL	3.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as amended (12 2010)
Carbon Black - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Carbon Black - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values, as amended (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)



Chemical name	Type	Exposure Limit Values	Source
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Talc - Respirable.	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Talc	TWA	2 Fibers/cc	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)
Talc - Respirable fraction.	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)
Talc - Respirable dust.	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Xylene	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)



Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Cumene	STEL	75 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Cumene	TWA	50 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Cumene	TWA	50 ppm 246 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Carbon Black - Inhalable	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Carbon Black - Inhalable dust.	TWA	3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Ethylbenzene	TWA	20 ppm	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Additional Information: Use suitable protective gloves if risk of skin contact.
Skin and Body Protection:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. When using do not smoke. Wash contaminated clothing before reuse. Avoid contact with skin. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	Gray
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	43 °C 110 °F(Tag closed cup)
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper:	No data available.
Explosive limit - lower:	No data available.
Vapor pressure:	9.5 hPa (20 °C 68 °F)
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.



Relative density:	1.06
Solubility(ies)	
Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.
Incompatible Materials:	Alcohols. Amines. Strong acids. Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	Causes skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 46,590.91 mg/kg

Dermal

Product: ATEmix: 11,140.18 mg/kg

Inhalation

Product: ATEmix: 23.3 mg/l
ATEmix : 3.18 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Aromatic petroleum distillates	in vivo (Rabbit): Irritating , 7 d
1,2,4-Trimethylbenzene	in vivo (Rabbit): Irritating , 24 - 72 h
Xylene	in vivo (Rat): Slightly irritating , 24 h
Cumene	in vivo (Rabbit): Not irritant , 24 h
Carbon Black	in vivo (Rabbit): Not irritant , 120 h

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Aromatic petroleum distillates	Rabbit, 24 - 72 hrs: Minimal irritant
1,2,4-Trimethylbenzene	Rabbit, 30 min: Not irritant
Xylene	Rabbit, 24 hrs: Moderately irritating Rabbit, 1 hrs: Not irritant
Cumene	Rabbit, 24 - 72 hrs: Not irritant
Carbon Black	Rabbit, 24 - 72 hrs: Not irritant

Respiratory or Skin Sensitization

Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.

Carcinogenicity
Product: Suspected of causing cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Cumene	Overall evaluation: Possibly carcinogenic to humans.
Carbon Black	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Cumene	Reasonably Anticipated to be a Human Carcinogen.
Carbon Black	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity
Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.
Specified substance(s):
Cumene Inhalation - vapor: Category 3 with respiratory tract irritation.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects:

Constituents of this product may include crystalline silica which, if in inhalable form, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimis exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems.

12. Ecological information
Ecotoxicity:
Acute hazards to the aquatic environment:
Fish
Product:

No data available.

Specified substance(s):

1,2,4-Trimethylbenzene

LC 50 (Pimephales promelas, 96 h): 7.72 mg/l Experimental result, Key study

Xylene

LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality

Isophorone Diisocyanate

 LC 0 (Leuciscus idus, 48 h): 1 mg/l Experimental result, Not specified
 LC 0 (Danio rerio, 96 h): \geq 72 mg/l Experimental result, Key study
 LC 0 (Cyprinus carpio, 96 h): \geq 208 mg/l Experimental result, Key study
 LC 50 (Danio rerio, 96 h): $>$ 72 mg/l Experimental result, Key study
 LC 50 (Leuciscus idus, 48 h): 1.8 mg/l Experimental result, Not specified

Cumene

LC 50 (Cyprinodon variegatus, 96 h): 4.7 mg/l Experimental result, Key study

Ethylbenzene

LC 50 (Oncorhynchus mykiss, 96 h): 4.2 mg/l Experimental result, Key study

Aquatic Invertebrates
Product:

No data available.

Specified substance(s):

Aromatic petroleum distillates

EC 50 (Daphnia magna, 48 h): 4.5 mg/l experimental result Experimental result, Key study

1,2,4-Trimethylbenzene

LC 50 (Daphnia magna, 48 h): 3.6 mg/l experimental result Experimental result, Key study

Isophorone Diisocyanate

 EC 50 (Daphnia magna, 48 h): 35 mg/l experimental result Experimental result, Supporting study
 EC 50 (Daphnia magna, 24 h): 49 mg/l experimental result Experimental result, Key study
 LC 50 (Chaetogammarus marinus, 96 h): 4 mg/l experimental result Experimental result, Key study
 EC 100 (Daphnia magna, 48 h): 73 mg/l experimental result Experimental

	result, Supporting study ED 0 (Daphnia magna, 48 h): 18 mg/l experimental result Experimental result, Key study
Cumene	EC 50 (Daphnia magna, 48 h): 2.14 mg/l experimental result Experimental result, Key study
Carbon Black	LC 50 (Daphnia sp., 48 h): 164 mg/l QSAR QSAR, Key study
Ethylbenzene	EC 50 (Daphnia magna, 48 h): 1.8 - 2.4 mg/l experimental result Experimental result, Key study

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Aromatic petroleum distillates	EC 50 (Daphnia magna): 10 mg/l experimental result Experimental result, Key study
Isophorone Diisocyanate	NOAEL (Daphnia magna): 3 mg/l read-across from supporting substance (structural analogue or surrogate) Read-across from supporting substance (structural analogue or surrogate), Key study LOAEL (Daphnia magna): 10 mg/l read-across from supporting substance (structural analogue or surrogate) Read-across from supporting substance (structural analogue or surrogate), Key study
Cumene	NOAEL (Daphnia magna): 0.35 mg/l experimental result Experimental result, Key study
Carbon Black	EC 50 (Daphnia sp.): 4.9 mg/l QSAR QSAR, Key study
Ethylbenzene	NOAEL (Ceriodaphnia dubia): 1 mg/l secondary data Other, Key study

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

Isophorone Diisocyanate	62 % (28 d) Detected in water. Experimental result, Not specified > 0 % (28 d) Detected in water. Experimental result, Key study
Cumene	70 % (20 d) Detected in water. Experimental result, Key study
Ethylbenzene	70 - 80 % (28 d) Detected in water. Experimental result, Key study

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

Aromatic petroleum distillates	Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by calculation, Key study
1,2,4-Trimethylbenzene	Pimephales promelas, Bioconcentration Factor (BCF): 243 Aquatic sediment QSAR, Key study
Xylene	Oncorhynchus mykiss, Bioconcentration Factor (BCF): > 8.1 - < 25.9 Aquatic sediment Experimental result, Key study
Isophorone Diisocyanate	Bioconcentration Factor (BCF): 2,078 Aquatic sediment QSAR, Not specified Bioconcentration Factor (BCF): 910 Aquatic sediment QSAR, Not specified
Cumene	Bioconcentration Factor (BCF): 94.69 Aquatic sediment Estimated by calculation, Key study
Ethylbenzene	Oncorhynchus kisutch, Bioconcentration Factor (BCF): 1 Aquatic sediment Other, Key study

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

1,2,4-Trimethylbenzene	Log Kow: 3.78
Xylene	Log Kow: 2.77 - 3.15 No Not specified, Not specified
Isophorone Diisocyanate	Log Kow: 4.75
Cumene	Log Kow: 3.66
Ethylbenzene	Log Kow: 3.15 Log Kow: 3.13 - 3.14 No Other, Supporting study

Mobility in soil: No data available.

Other adverse effects: Harmful to aquatic life with long lasting effects.

13. Disposal considerations

Disposal methods: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

UN1139, COATING SOLUTION, 3, PG III

CFR / DOT:

UN1139, Coating solution, 3, PG III

IMDG:

UN1139, COATING SOLUTION, 3, PG III

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation.
Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Cumene	5000 lbs.
Ethylbenzene	1000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard
Immediate (Acute) Health Hazards
Delayed (Chronic) Health Hazard
Flammable (gases, aerosols, liquids, or solids)
Acute toxicity (any route or exposure)
Skin Corrosion or Irritation
Respiratory or Skin Sensitization
Carcinogenicity
Hazards Not Otherwise Classified (HNOC)

US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

Not regulated.

US. EPCRA (SARA Title III Section 313 Toxic Chemical Release Inventory (TRI) Reporting

<u>Chemical Identity</u>	<u>% by weight</u>
1,2,4-Trimethylbenzene	1.0%
Cumene	0.1%
Ethylbenzene	0.1%

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	Reportable quantity: 100 lbs.

US State Regulations

US. California Proposition 65



WARNING

Cancer - www.P65Warnings.ca.gov

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC:

Regulatory VOC (less water and exempt solvent) : 233 g/l

VOC Method 310 : 22.00 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision
--

Revision Date: 11/12/2022

Version #: 5.1

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.