

Revision Date: 11/11/2022

SAFETY DATA SHEET

1. Identification

Material name: FLEXDECK MEMBRANE PART A

Material: TA4323105M

Recommended use and restriction on use

Recommended use: Coatings Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

EUCLID CHEMICAL COMPANY 19218 REDWOOD ROAD CLEVELAND OH 44110

US

Contact person: EH&S Department **Telephone:** 216-531-9222

Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids Category 4

Health Hazards

Acute toxicity (Inhalation - dust and Category 2

mist)

Respiratory sensitizer Category 1
Skin sensitizer Category 1
Carcinogenicity Category 1B

Unknown toxicity - Health

Acute toxicity, oral 13 %
Acute toxicity, dermal 13 %
Acute toxicity, inhalation, vapor 100 %
Acute toxicity, inhalation, dust 99 %

or mist

Environmental Hazards

Acute hazards to the aquatic Category 3

environment

Unknown toxicity - Environment

Acute hazards to the aquatic 94.78 %

environment



Revision Date: 11/11/2022

Chronic hazards to the aquatic 100 % environment

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Combustible liquid.

Fatal if inhaled.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May cause cancer. Harmful to aquatic life.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Use personal protective equipment as required. Avoid release to the

environment.

Response: IF INHALED: Remove person to fresh air and keep comfortable for

breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/ physician. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Immediately call a POISON CENTER/doctor. Specific treatment is urgent (see on this label).

Wash contaminated clothing before reuse. In case of fire: Use... to

extinguish.

Storage: Store in a well-ventilated place. Keep cool. Keep container tightly closed.

Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

Static accumulating flammable liquid can become electrostatically charged

even in bonded and grounded equipment.



Revision Date: 11/11/2022

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Talc	14807-96-6	10 - <20%
Aromatic petroleum distillates	64742-95-6	1 - <5%
1,2,4-Trimethylbenzene	95-63-6	1 - <5%
Xylene	1330-20-7	1 - <5%
Toluene diisocyanate	26471-62-5	1 - <5%
Ethylbenzene	100-41-4	0.1 - <1%
Cumene	98-82-8	0.1 - <1%

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Description of necessary first-aid measures

Inhalation: Call a physician or poison control center immediately. If breathing

stops, provide artificial respiration. Move to fresh air. If breathing is

difficult, give oxygen.

Skin Contact: If skin irritation occurs: Get medical advice/attention. Destroy or

thoroughly clean contaminated shoes. Immediately remove

contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get

medical attention.

Eye contact: Any material that contacts the eye should be washed out immediately

with water. If easy to do, remove contact lenses. If eye irritation

persists: Get medical advice/attention.

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Personal Protection for First-

aid Responders:

Firefighters must use standard protective equipment including flame

retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

Most important symptoms/effects, acute and delayed

Symptoms: Respiratory tract irritation.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Move containers from fire area if you can do so without risk.



Revision Date: 11/11/2022

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from

the chemical:

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for fire-fighters

Special fire-fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Accidental release measures:

In the event of a spill or accidental release, notify relevant authorities in

accordance with all applicable regulations.

Methods and material for containment and cleaning

up:

Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for

disposal according to local regulations.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe

to do so.

7. Handling and storage

Handling

Technical measures (e.g. Local and general ventilation):

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.



Revision Date: 11/11/2022

Safe handling advice: Provide adequate ventilation. Wear appropriate personal protective

equipment. Observe good industrial hygiene practices. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after

handling.

Contact avoidance measures: No data available.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. When using do not smoke.

Contaminated work clothing should not be allowed out of the workplace.

Avoid contact with skin.

Storage

Safe storage conditions: Store locked up. Store in a well-ventilated place. Store in a cool place.

Safe packaging materials: No data available.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure Lim	it Values	Source
Talc - Respirable fraction.	TWA		2 mg/m3	US. ACGIH Threshold Limit Values, as amended (2011)
Talc	TWA	20 millions of particles per cubic foot of air		US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Talc - Respirable.	TWA	2.4 millions of particles per cubic foot of air		US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	TWA		0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
1,2,4-Trimethylbenzene	REL	25 ppm	125 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	TWA	25 ppm	125 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	25 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
Xylene	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	STEL	150 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
	TWA	100 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
Toluene diisocyanate - Inhalable fraction and vapor.	TWA	0.001 ppm		US. ACGIH Threshold Limit Values, as amended (03 2016)
·	STEL	0.005 ppm		US. ACGIH Threshold Limit Values, as amended (03 2016)
Ethylbenzene	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as



Revision Date: 11/11/2022

		amended (02 2006)		
Cumene	PEL	50 ppm	245 mg/m3	US. OSHA Table Z-1 Limits for Air
			_	Contaminants (29 CFR 1910.1000), as
				amended (02 2006)
	TWA	5 ppm		US. ACGIH Threshold Limit Values, as
				amended (01 2021)

Chemical name	Туре	Exposure Lir	nit Values	Source	
Talc - Respirable.	TWA	2 mg/m3		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)	
Talc	TWA		2 Fibers/cc	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)	
Talc - Respirable fraction.	TWA		2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)	
Talc - Respirable dust.	TWA		2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)	
1,2,4-Trimethylbenzene	TWA	25 ppm	123 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)	
1,2,4-Trimethylbenzene	TWA	25 ppm Canada. British Columbia OELs. (Occupa Exposure Limits for Chemical Biological Substances, Occupational Health and Sat		Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)	
1,2,4-Trimethylbenzene	TWA			Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)	
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)	
Xylene	STEL	150 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)	
	TWA	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)	
Xylene	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)	
	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)	
Xylene	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)	
	STEL	150 ppm	651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)	
Toluene diisocyanate	TWA	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)	
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)	
Toluene diisocyanate	STEL	0.02 ppm	0.14 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)	
	TWA	0.005 ppm	0.036 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and	

EUCLID CHEMICAL



Revision Date: 11/11/2022

				safety), as amended (09 2017)
Ethylbenzene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm		
Ethylbenzene	TWA	20 ppm Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)		
Cumene	STEL	75 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Cumene	TWA	50 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Cumene	TWA	50 ppm	246 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
p-Dioxane	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
p-Dioxane	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
p-Dioxane	TWA	20 ppm	72 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (12 2008)
Benzene	STEL	2.5 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.5 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Benzene	TWA	0.5 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
	STEL	2.5 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Benzene	TWA	1 ppm	3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	STEL	5 ppm	15.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Propylene oxide	TWA	2 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Propylene oxide	TWA	2 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Propylene oxide	TWA	2 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)



Revision Date: 11/11/2022

Chemical Identity	Exposure Limit Values	Source
Toluene diisocyanate (Toluene diamine (sum of 2,4- and 2,6-isomers), with hydrolysis: Sampling time: End of shift.)	5 μg/g (Creatinine in urine)	ACGIH BEI (03 2018)
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering

Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical

ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

Eye/face protection: Wear goggles/face shield.

Skin Protection

Hand Protection: Additional Information: Use suitable protective gloves if risk of skin contact.

Skin and Body Protection: Wear chemical-resistant gloves, footwear, and protective clothing

appropriate for the risk of exposure. Contact health and safety professional

or manufacturer for specific information.

Respiratory Protection: If engineering controls do not maintain airborne concentrations below

recommended exposure limits (where applicable) or to an acceptable level

(in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an

appropriate, government approved (where applicable), air-purifying filter,

cartridge or canister. Contact health and safety professional or

manufacturer for specific information.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. When using do not smoke. Contaminated work clothing should not be allowed out of the workplace.

Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state: liquid Form: liquid Color: Gray

Odor: Mild petroleum/solvent
Odor threshold: No data available.
pH: No data available.

Melting point/freezing point: No data available.



Revision Date: 11/11/2022

Initial boiling point and boiling range:No data available.

Flash Point: 76 °C 169 °F(Tag closed cup)

Evaporation rate: Slower than Ether

Flammability (solid, gas): No Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper:

Explosive limit - lower:

No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and

in the bottom of containers.

Relative density: 1.139

Solubility(ies)

Solubility in water: Practically Insoluble
Solubility (other): No data available.

Partition coefficient (n-octanol/water): No data available.

Auto-ignition temperature:No data available.Decomposition temperature:No data available.Viscosity:No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

Conditions to avoid: Heat, sparks, flames.

Incompatible Materials: Alcohols. Amines. Strong acids. Strong bases. Water, moisture.

Hazardous Decomposition

Thermal decomposition or combustion may liberate carbon oxides and

Products: other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation: In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

Skin Contact: Causes mild skin irritation. May cause an allergic skin reaction.

Eye contact: Eye contact is possible and should be avoided.

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.



Revision Date: 11/11/2022

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Aromatic petroleum

distillates

LD 50 (Rat): > 5,000 mg/kg

1,2,4-Trimethylbenzene LD 50 (Rat): 3,280 mg/kg

Xylene LD 50 (Rat): 3,523 mg/kg

Toluene diisocyanate LD 50 (Rat): 4,130 mg/kg

Ethylbenzene LD 50 (Rat): 3,500 mg/kg

Cumene LD 50 (Rat): 1,400 mg/kg

Dermal

Product: Not classified for acute toxicity based on available data.



Revision Date: 11/11/2022

Specified substance(s):

Aromatic petroleum

distillates

LD 50 (Rabbit): > 2,000 mg/kg

1,2,4-Trimethylbenzene LD 50 (Rat): 3,440 mg/kg

Xylene LD 50 (Rabbit): 12,126 mg/kg

Toluene diisocyanate LD 50 (Rabbit): > 9,400 mg/kg

Ethylbenzene LD 50 (Rabbit): 17,800 mg/kg

LD 50 (Rabbit): > 20,000 mg/kg

Cumene LD 50 (Rabbit): 10,600 mg/kg

Inhalation

Product: ATEmix: 0.35 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Aromatic petroleum

distillates

in vivo (Rabbit): Irritating, 7 d

1,2,4-Trimethylbenzene in vivo (Rabbit): Irritating, 24 - 72 h

Xylene in vivo (Rat): Slightly irritating, 24 h

Toluene diisocyanate in vivo (Rabbit): Moderately irritating, 72 h

Cumene in vivo (Rabbit): Not irritant, 24 h

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Aromatic petroleum

distillates

Rabbit, 24 - 72 hrs: Minimal irritant

1,2,4-Trimethylbenzene Rabbit, 30 min: Not irritant



Revision Date: 11/11/2022

Xylene Rabbit, 24 hrs: Moderately irritating

Rabbit, 1 hrs: Not irritant

Toluene diisocyanate Rabbit, 24 - 72 hrs: Category 2

Cumene Rabbit, 24 - 72 hrs: Not irritant

Respiratory or Skin Sensitization

Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause sensitization by inhalation.

Carcinogenicity

Product: May cause cancer. Suspected of causing cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Talc Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall

evaluation: Possibly carcinogenic to humans.

Toluene Over

diisocyanate

Overall evaluation: Possibly carcinogenic to humans.

Ethylbenzene Overall evaluation: Possibly carcinogenic to humans.

Cumene Overall evaluation: Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Toluene Reasonably Anticipated to be a Human Carcinogen.

diisocyanate

Cumene Reasonably Anticipated to be a Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specified substance(s):

Cumene Inhalation - vapor: Category 3 with respiratory tract irritation.



Revision Date: 11/11/2022

Specific Target Organ Toxicity - Repeated Exposure
Product:
No data available.

Aspiration Hazard

Product: No data available.

Other effects: Constituents of this product may include crystalline silica which, if in

inhalable form, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimis exposure to these impurities in inhalable form may be carcinogenic

or cause other serious lung problems.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

1,2,4-Trimethylbenzene LC 50 (Pimephales promelas, 96 h): 7.72 mg/l Experimental result, Key

study

Xylene LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality

Toluene diisocyanate LC 50 (Oncorhynchus mykiss, 96 h): 133 mg/l Experimental result, Key

study

Ethylbenzene LC 50 (Oncorhynchus mykiss, 96 h): 4.2 mg/l Experimental result, Key study

Cumene LC 50 (Cyprinodon variegatus, 96 h): 4.7 mg/l Experimental result, Key

study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Aromatic petroleum

distillates

EC 50 (Daphnia magna, 48 h): 4.5 mg/l experimental result Experimental

result, Key study

1,2,4-Trimethylbenzene LC 50 (Daphnia magna, 48 h): 3.6 mg/l experimental result Experimental

result, Key study

Toluene diisocyanate EC 50 (Daphnia magna, 48 h): 12.5 mg/l experimental result Experimental

13/19



Revision Date: 11/11/2022

result, Key study

Ethylbenzene EC 50 (Daphnia magna, 48 h): 1.8 - 2.4 mg/l experimental result

Experimental result, Key study

Cumene EC 50 (Daphnia magna, 48 h): 2.14 mg/l experimental result Experimental

result, Key study

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Aromatic petroleum

distillates

EC 50 (Daphnia magna): 10 mg/l experimental result Experimental result,

Key study

Toluene diisocyanate NOAEL (Daphnia magna): 1.1 mg/l experimental result Experimental result,

Key study

Ethylbenzene NOAEL (Ceriodaphnia dubia): 1 mg/l secondary data Other, Key study

Cumene NOAEL (Daphnia magna): 0.35 mg/l experimental result Experimental result,

Key study

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

Ethylbenzene 70 - 80 % (28 d) Detected in water. Experimental result, Key study

Cumene 70 % (20 d) Detected in water. Experimental result, Key study

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

Aromatic petroleum

Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by

distillates calculation, Key study

Revision Date: 11/11/2022

1,2,4-Trimethylbenzene Pimephales promelas, Bioconcentration Factor (BCF): 243 Aquatic sediment

QSAR, Key study

Xylene

Oncorhynchus mykiss, Bioconcentration Factor (BCF): > 8.1 - < 25.9 Aquatic

sediment Experimental result, Key study

Ethylbenzene Oncorhynchus kisutch, Bioconcentration Factor (BCF): 1 Aquatic sediment

Other, Key study

Cumene Bioconcentration Factor (BCF): 94.69 Aquatic sediment Estimated by

calculation, Key study

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

1,2,4-Trimethylbenzene Log Kow: 3.78

Xylene Log Kow: 2.77 - 3.15 No Not specified, Not specified

Ethylbenzene Log Kow: 3.15

Log Kow: 3.13 - 3.14 No Other, Supporting study

Cumene Log Kow: 3.66

Mobility in soil: No data available.

Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal methods: Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:



Revision Date: 11/11/2022

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Chemical Identity Reportable quantity

Toluene diisocyanate De minimis concentration: TSCA 5(a)(2)% One-Time Export Notification

only.

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

Chemical Identity OSHA hazard(s)

Benzene Blood

respiratory tract irritation Central nervous system

Flammability Cancer Skin Aspiration Eye

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity Reportable quantity Xylene 100 lbs. Toluene diisocyanate 100 lbs. Ethylbenzene 1000 lbs. Cumene 5000 lbs. 100 lbs. **Furan** 100 lbs. p-Dioxane 10 lbs. Benzene

Superfund Amendments and Reauthorization Act of 1986 (SARA)

100 lbs.

Hazard categories

Propylene oxide

Fire Hazard

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route or exposure)
Respiratory or Skin Sensitization

Carcinogenicity

Hazards Not Otherwise Classified (HNOC)

US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances



Revision Date: 11/11/2022

US. EPCRA (SARA Title III Section 313 Toxic Chemical Release Inventory (TRI) Reporting

Chemical Identity% by weight1,2,4-Trimethylbenzene1.0%Xylene1.0%Toluene diisocyanate0.1%Ethylbenzene0.1%

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Chemical Identity Reportable quantity

Toluene diisocyanate lbs Furan lbs Propylene oxide lbs

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

Chemical IdentityReportable quantityXyleneReportable quantity: 100 lbs.

US State Regulations

US. California Proposition 65



WARNING

Cancer and Reproductive Harm - www.P65Warnings.ca.gov

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC: When appropriately mixed with the other part, product has a VOC less water and exempt solvent of: 98 g/l

Regulatory VOC (less water and

exempt solvent)

113 g/l

VOC Method 310 : 9.89 %



Revision Date: 11/11/2022

Inventory Status:

Australia AICS: One or more components in this

product are not listed on or exempt

from the Inventory.

Canada DSL Inventory List: All components in this product are

listed on or exempt from the

Inventory.

EINECS, ELINCS or NLP: One or more components in this

product are not listed on or exempt

from the Inventory.

Japan (ENCS) List: One or more components in this

product are not listed on or exempt

from the Inventory.

China Inv. Existing Chemical

Substances:

One or more components in this product are not listed on or exempt

from the Inventory.

Korea Existing Chemicals Inv. (KECI): One or more components in this

product are not listed on or exempt

from the Inventory.

Canada NDSL Inventory: One or more components in this

product are not listed on or exempt

from the Inventory.

Philippines PICCS: One or more components in this

product are not listed on or exempt

from the Inventory.

US TSCA Inventory: All components in this product are

listed on or exempt from the

Inventory.

New Zealand Inventory of Chemicals: One or more components in this

product are not listed on or exempt

from the Inventory.

Japan ISHL Listing: One or more components in this

product are not listed on or exempt

from the Inventory.

Japan Pharmacopoeia Listing: One or more components in this

product are not listed on or exempt

from the Inventory.



Revision Date: 11/11/2022

16.Other information, including date of preparation or last revision

Revision Date: 11/11/2022

Version #: 2.1

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard

information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.