

Revision Date: 11/11/2022

# SAFETY DATA SHEET

## 1. Identification

Material name: HI - FLOW METALLIC GROUT

Material: 088M 50

Recommended use and restriction on use

Recommended use: Cement, Portland, chemicals

Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

EUCLID CHEMICAL COMPANY 19218 REDWOOD ROAD CLEVELAND OH 44110 US

Cantaat n

**Contact person:** EH&S Department **Telephone:** 216-531-9222

**Emergency telephone number:** 1-800-424-9300 (US); 1-613-996-6666 (Canada)

## 2. Hazard(s) identification

#### **Hazard Classification**

#### **Health Hazards**

Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 1
Skin sensitizer Category 1
Carcinogenicity Category 1A
Specific Target Organ Toxicity - Category 3<sup>1</sup>

Single Exposure

Specific Target Organ Toxicity - Category 1<sup>2</sup>

Repeated Exposure

## **Target Organs**

1. Respiratory tract irritation.

2. Lung

## **Unknown toxicity - Health**

Acute toxicity, oral 73.75 %
Acute toxicity, dermal 94.7 %
Acute toxicity, inhalation, vapor 99.96 %
Acute toxicity, inhalation, dust 70.06 %
or mist

**Label Elements** 

## **Hazard Symbol:**



Revision Date: 11/11/2022



Signal Word: Danger

Hazard Statement: Causes skin irritation.

Causes serious eye damage.

May cause an allergic skin reaction.

May cause cancer.

May cause respiratory irritation.

Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements

**Prevention:** Wash thoroughly after handling. Wear protective gloves/protective

clothing/eye protection/face protection. Contaminated work clothing should not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapors/spray. Do

not eat, drink or smoke when using this product.

**Response:** IF INHALED: Remove person to fresh air and keep comfortable for

breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Immediately call a POISON CENTER/doctor. Specific treatment (see on this label). Wash contaminated clothing before

reuse.

Storage: Store locked up. Store in a well-ventilated place. Keep container tightly

closed.

**Disposal:** Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

None.

#### 3. Composition/information on ingredients

#### **Mixtures**

Chemical Identity	CAS number	Content in percent (%)*
Portland cement	65997-15-1	20 - <50%
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	20 - <50%
Iron oxide	1309-37-1	10 - <20%



Revision Date: 11/11/2022

Silica, fused	60676-86-0	10 - <20%
Fumed silica	69012-64-2	1 - <5%
Calcium oxide	1305-78-8	1 - <3%
Aluminum oxide	1344-28-1	0.1 - <1%
Carbon	7440-44-0	0.1 - <1%
Silicon	7440-21-3	0.1 - <1%

<sup>\*</sup> All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures

#### Description of necessary first-aid measures

**Inhalation:** Move to fresh air.

**Skin Contact:** Get medical attention. Destroy or thoroughly clean contaminated

shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic

skin reaction develops, get medical attention.

**Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy

to do, remove contact lenses. Call a physician or poison control

center immediately.

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

**Personal Protection for First-**

aid Responders:

Self-contained breathing apparatus and full protective clothing must

be worn in case of fire.

Most important symptoms/effects, acute and delayed

**Symptoms:** Prolonged or repeated contact with skin may cause redness, itching,

irritation and eczema/chapping. Extreme irritation of eyes and mucous membranes, including burning and tearing. Respiratory tract irritation.

**Hazards:** No data available.

Indication of immediate medical attention and special treatment needed

**Treatment:** Symptoms may be delayed.

#### 5. Fire-fighting measures

**General Fire Hazards:** No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

During fire, gases hazardous to health may be formed.



Revision Date: 11/11/2022

#### Special protective equipment and precautions for fire-fighters

Special fire-fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be

worn in case of fire.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate

protective clothing. Keep unauthorized personnel away.

Accidental release measures: In the event of a spill or accidental release, notify relevant authorities in

accordance with all applicable regulations.

Methods and material for containment and cleaning

up:

Collect spillage in containers, seal securely and deliver for disposal

according to local regulations.

**Environmental Precautions:** Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so.

## 7. Handling and storage

#### Handling

Technical measures (e.g. Local and general ventilation):

Mechanical ventilation or local exhaust ventilation may be required.

Observe good industrial hygiene practices. Observe occupational exposure

limits and minimize the risk of inhalation of dust.

Safe handling advice: Ventilate well, avoid breathing vapors. Use approved respirator if air

contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust.Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not get in eyes. Wash hands thoroughly after handling. Avoid contact with skin. Avoid

contact with eyes, skin, and clothing.

Contact avoidance measures: No data available.

**Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. Do not get in eyes. Wash

contaminated clothing before reuse. Avoid contact with skin. Contaminated

work clothing should not be allowed out of the workplace.

**Storage** 

Safe storage conditions: Store locked up.

Safe packaging materials: No data available.



Revision Date: 11/11/2022

## 8. Exposure controls/personal protection

## **Control Parameters**

**Occupational Exposure Limits** 

Chemical Identity	Туре	<b>Exposure Limit Values</b>	Source
Portland cement - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values, as amended (2011)
Portland cement - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Portland cement - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Portland cement	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.05 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (03 2016)
	OSHA_AC T	0.025 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (03 2016)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	PEL	0.05 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (03 2016)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	US. ACGIH Threshold Limit Values, as amended (02 2020)
Iron oxide - Respirable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values, as amended (2011)
Iron oxide - Fume.	PEL	10 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Iron oxide - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Iron oxide - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Iron oxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Silica, fused	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	TWA	0.8 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Fumed silica	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	TWA	0.8 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Fumed silica - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as





	T) A / 2		amended (09 2016)
Fumed silica - Inhalable particles.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)
Fumed silica - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Fumed silica - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Fumed silica - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Fumed silica - Respirable particles.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values, as amended (2008)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Aluminum oxide - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values, as amended (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Aluminum oxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Aluminum oxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Aluminum oxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Aluminum oxide - Inhalable particles.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)
Aluminum oxide - Respirable particles.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)
Carbon - Respirable fraction.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values, as amended (2011)
Carbon - Respirable particles.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2014)
Carbon - Inhalable particles.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2014)
Carbon - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Carbon - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Carbon - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Carbon - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Carbon	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Carbon - Total dust.	TWA	50 millions of particles per cubic foot of	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)





		air	
Carbon - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Carbon - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Carbon - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Silicon - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Silicon - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Silicon - Respirable particles.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)
Silicon - Inhalable particles.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)
Silicon - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Silicon - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)





Chemical name	Туре	Exposure Limit Values	Source
Portland cement - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Portland cement - Respirable dust.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Portland cement - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2017)
Portland cement - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Iron oxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Dust as Fe	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Fume as Fe	STEL	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Fume as Fe	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Dust and fume as Fe	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Iron oxide - Respirable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Silica, fused - Respirable fraction.	TWA	0.1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Silica, fused - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Fumed silica - Respirable fume.	TWA	1.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Fumed silica - Respirable fraction.	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Fumed silica - Respirable dust and/or fume.	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)





Fumed silica - Total fume.	TWA	4 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2021)
Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (12 2007)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Aluminum oxide - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Aluminum oxide - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Aluminum oxide - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Aluminum oxide - Total dust. - as Al	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Aluminum oxide - Respirable.	TWA	1.0 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Aluminum oxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Aluminum oxide - Inhalable particles.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Aluminum oxide - Respirable particles.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Aluminum oxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Carbon - Respirable.	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Carbon - Respirable fraction.	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)



**EUCLID CHEMICAL** 

Version: 2.1

Carbon - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Carbon - Respirable dust.	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Carbon - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Carbon - Inhalable particles.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Carbon - Respirable particles.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Carbon - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Carbon - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Silicon - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Silicon - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Silicon - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Silicon - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Silicon - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Silicon - Inhalable particles.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Silicon - Respirable particles.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Manganese - as Mn	TWA	0.2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Manganese - Fume, total dust as Mn	TWA	0.2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Manganese - Respirable as Mn	TWA	0.02 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2018)
Manganese - Total - as Mn	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2018)
Chromium - as Cr	TWA	0.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Chromium	TWA	0.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Chromium - Total	TWA	0.5 mg/m3	Canada. British Columbia OELs. (Occupational



Revision Date: 11/11/2022

			Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2018)
Aluminum - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Aluminum	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Aluminum - as Al	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Aluminum - Welding fume as Al	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Aluminum - Respirable.	TWA	1.0 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Stearic acid - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Stearic acid - Respirable.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (01 2021)
Stearic acid - Inhalable	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (01 2021)
Stearic acid	TWA	10 ppm	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

**Eye/face protection:** Wear a full-face respirator, if needed. Wear safety glasses with side shields

(or goggles) and a face shield.

Skin Protection

**Hand Protection:** Additional Information: Use suitable protective gloves if risk of skin contact.

**Skin and Body Protection:** Wear chemical-resistant gloves, footwear, and protective clothing

appropriate for the risk of exposure. Contact health and safety professional

or manufacturer for specific information.

**Respiratory Protection:** In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

**Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. Do not get in eyes. Wash

contaminated clothing before reuse. Avoid contact with skin. Contaminated

work clothing should not be allowed out of the workplace.



Revision Date: 11/11/2022

## 9. Physical and chemical properties

**Appearance** 

Physical state: solid
Form: Powder
Color: Gray
Odor: Odorless

Odor threshold:

pH:

No data available.

Flash Point:

No data available.

No data available.

No data available.

Flammability (solid, gas): No Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper:

Explosive limit - lower:

Vapor pressure:

No data available.

Relative density: 3.45

Solubility(ies)

Solubility in water: Miscible with water.
Solubility (other): No data available.
Partition coefficient (n-octanol/water): No data available.

Auto-ignition temperature:No data available.Decomposition temperature:No data available.Viscosity:No data available.

#### 10. Stability and reactivity

**Reactivity:** No data available.

**Chemical Stability:** Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

**Conditions to avoid:** Avoid heat or contamination.

**Incompatible Materials:** No data available.

**Hazardous Decomposition** 

**Products:** 

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.



Revision Date: 11/11/2022

## 11. Toxicological information

#### Information on likely routes of exposure

**Inhalation:** In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

**Skin Contact:** Causes skin irritation. May cause an allergic skin reaction.

**Eye contact:** Causes serious eye damage.

**Ingestion:** May be ingested by accident. Ingestion may cause irritation and malaise.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation:** No data available.

**Skin Contact:** No data available.

**Eye contact:** No data available.

**Ingestion:** No data available.

## Information on toxicological effects

#### Acute toxicity (list all possible routes of exposure)

Oral

**Product:** ATEmix: 19,593.55 mg/kg

**Dermal** 

**Product:** Not classified for acute toxicity based on available data.

Specified substance(s):

Fumed silica LD 50 (Rabbit): > 5,000 mg/kg

Calcium oxide LD 50 (Rabbit): > 2,500 mg/kg

Silicon LD 50 (Rabbit): > 5,000 mg/kg

Inhalation

**Product:** Not classified for acute toxicity based on available data.



Revision Date: 11/11/2022

Specified substance(s):

Crystalline Silica LC 50: > 5.0 mg/l

(Quartz)/ Silica Sand

Fumed silica LC 50 (Rat): > 2.08 mg/l

Calcium oxide LC 50 (Rat): 40 mg/m3

Aluminum oxide LC 50 (Rat): 7.6 mg/l

Silicon LC 50 (Rat): > 2.08 mg/l

Repeated dose toxicity

**Product:** No data available.

Skin Corrosion/Irritation

**Product:** No data available.

Specified substance(s):

Iron oxide in vivo (Rabbit): Not irritant, 24 - 72 h

Fumed silica in vivo (Rabbit): Not irritant, 24 h

Calcium oxide in vivo (Rabbit): Irritating, 24 - 72 h

Aluminum oxide in vivo (Rabbit): Not irritant, 24 - 72 h

Carbon in vivo (Rabbit): Not irritant, > 0 - 72 h

Silicon in vivo (Rabbit): Not irritant

Serious Eye Damage/Eye Irritation

**Product:** No data available.

Specified substance(s):

Fumed silica Rabbit, 1 hrs: Not irritant

Calcium oxide Rabbit, 1 hrs: Irritating

Aluminum oxide Rabbit, 24 hrs: Not irritant

Silicon Rabbit, 1 hrs: Not irritant

Respiratory or Skin Sensitization

**Product:** No data available.



Revision Date: 11/11/2022

Carcinogenicity

**Product:** No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Crystalline Silica

(Quartz)/ Silica

Sand

**US. National Toxicology Program (NTP) Report on Carcinogens:** 

Silica Known To Be Human Carcinogen. Crystalline

(Quartz)/

Sand

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

Overall evaluation: Carcinogenic to humans.

Crystalline Silica

(Quartz)/ Silica Cancer

Sand

**Germ Cell Mutagenicity** 

In vitro

No data available. Product:

In vivo

No data available. **Product:** 

Reproductive toxicity

**Product:** No data available.

**Specific Target Organ Toxicity - Single Exposure** 

Product: No data available.

**Specific Target Organ Toxicity - Repeated Exposure** 

**Product:** No data available.

**Target Organs** 

Specific Target Organ Toxicity - Single Exposure: Respiratory tract irritation.

Specific Target Organ Toxicity - Repeated Exposure: Lung

**Aspiration Hazard** 

Product: No data available.



Revision Date: 11/11/2022

Other effects: Constituents of this product may include crystalline silica which, if in

inhalable form, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or

non-asbestiform tremolite or other silicates as impurities, and above de minimis exposure to these impurities in inhalable form may be carcinogenic

or cause other serious lung problems.

## 12. Ecological information

#### **Ecotoxicity:**

#### Acute hazards to the aquatic environment:

Fish

**Product:** No data available.

Specified substance(s):

Iron oxide LC 50 (Pimephales promelas, 96 h): 3.66 mg/l Experimental result,

Supporting study

LC 90 (Danio rerio, 96 h): 100,000 mg/l Experimental result, Key study

Fumed silica LC 50 (Danio rerio, 96 h): > 100 mg/l Experimental result, Supporting study

Calcium oxide LC 100 (Poecilia reticulata, 96 h): 560 mg/l Experimental result, Key study

Aluminum oxide LC 50 (Pimephales promelas, 96 h): 1.16 mg/l Experimental result, Weight

of Evidence study

Carbon LL 50 (Danio rerio, 96 h): > 100 mg/l Experimental result, Key study

**Aquatic Invertebrates** 

**Product:** No data available.

Specified substance(s):

Iron oxide EC 50 (Daphnia magna, 48 h): > 100 mg/l Experimental result, Key study

Fumed silica EC 50 (Daphnia magna, 24 h): > 1,003 mg/l experimental result

Experimental result, Key study

Calcium oxide EC 50 (Daphnia magna, 48 h): > 100 mg/l read-across based on grouping of

substances (category approach) Read-across based on grouping of

substances (category approach), Key study

Aluminum oxide EC 50 (Ceriodaphnia dubia, 48 h): 1.5 mg/l experimental result Experimental

result, Weight of Evidence study

Carbon EC 50 (Daphnia magna, 48 h): > 100 mg/l experimental result Experimental

result, Key study

#### Chronic hazards to the aquatic environment:



Revision Date: 11/11/2022

**Fish** 

**Product:** No data available.

Specified substance(s):

Calcium oxide NOAEL (Oncorhynchus mykiss): 307 mg/l read-across based on grouping of

substances (category approach) Read-across based on grouping of

substances (category approach), Key study

**Aquatic Invertebrates** 

**Product:** No data available.

Specified substance(s):

Iron oxide LC 50 (Daphnia magna): 5.9 mg/l Experimental result, Supporting study

Aluminum oxide NOAEL (Daphnia magna): 1.89 mg/l experimental result Experimental result,

Weight of Evidence study

**Toxicity to Aquatic Plants** 

**Product:** No data available.

Persistence and Degradability

Biodegradation

**Product:** No data available.

Specified substance(s):

Silicon 77 - 99 % (67 min) Detected in water. Experimental result, Key study

**BOD/COD Ratio** 

**Product:** No data available.

**Bioaccumulative potential** 

**Bioconcentration Factor (BCF)** 

**Product:** No data available.

Partition Coefficient n-octanol / water (log Kow)

**Product:** No data available.

Specified substance(s):

Silicon Log Kow: 57 - 77 25 °C Estimated by calculation, Key study

Mobility in soil: No data available.

Other adverse effects: No data available.

13. Disposal considerations

**Disposal methods:** Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.



Revision Date: 11/11/2022

Contaminated Packaging: No data available.

## 14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

## 15. Regulatory information

#### **US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.

## US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

Chemical IdentityOSHA hazard(s)Crystalline Silicakidney effects(Quartz)/ Silica Sandlung effects

immune system effects

Cancer

## CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u> <u>Reportable quantity</u>

Chromium 5000 lbs.

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### **Hazard categories**

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

Skin Corrosion or Irritation

Serious eye damage or eye irritation

Respiratory or Skin Sensitization

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)



Revision Date: 11/11/2022

US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

US. EPCRA (SARA Title III Section 313 Toxic Chemical Release Inventory (TRI) Reporting Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

#### **US State Regulations**

**US.** California Proposition 65



#### **WARNING**

: 0 g/l

Cancer - www.P65Warnings.ca.gov

#### International regulations

#### **Montreal protocol**

Not applicable

## Stockholm convention

Not applicable

#### **Rotterdam convention**

Not applicable

## **Kyoto protocol**

Not applicable

#### VOC:

Regulatory VOC (less water and

exempt solvent)

VOC Method 310 : 0.00 %



Revision Date: 11/11/2022

**Inventory Status:** 

Australia AICS: All components in this product are

listed on or exempt from the

Inventory.

Canada DSL Inventory List: All components in this product are

listed on or exempt from the

Inventory.

EINECS, ELINCS or NLP: One or more components in this

product are not listed on or exempt

from the Inventory.

Japan (ENCS) List: One or more components in this

product are not listed on or exempt

from the Inventory.

China Inv. Existing Chemical

Substances:

All components in this product are

listed on or exempt from the

Inventory.

Korea Existing Chemicals Inv. (KECI): All components in this product are

listed on or exempt from the

Inventory.

Canada NDSL Inventory: One or more components in this

product are not listed on or exempt

from the Inventory.

Philippines PICCS: One or more components in this

product are not listed on or exempt

from the Inventory.

US TSCA Inventory: All components in this product are

listed on or exempt from the

Inventory.

New Zealand Inventory of Chemicals: All components in this product are

listed on or exempt from the

Inventory.

Japan ISHL Listing: One or more components in this

product are not listed on or exempt

from the Inventory.

Japan Pharmacopoeia Listing: One or more components in this

product are not listed on or exempt

from the Inventory.

Ontario Inventory: One or more components in this



Revision Date: 11/11/2022

product are not listed on or exempt

from the Inventory.

Mexico INSQ: One or more components in this

product are not listed on or exempt

from the Inventory.

Taiwan Chemical Substance Inventory: One or more components in this

product are not listed on or exempt

from the Inventory.

## 16.Other information, including date of preparation or last revision

**Revision Date:** 11/11/2022

Version #: 2.1

Further Information: No data available.

**Disclaimer:** For Industrial Use Only. Keep out of Reach of Children. The hazard

information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.