

Revision Date: 10/06/2020

# SAFETY DATA SHEET

# 1. Identification

Material name: SUPER DIAMOND CLEAR 350 - 5 GAL PAIL

Material: 359ADC 05

Recommended use and restriction on use

Recommended use: Coatings Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Euclid Admixture Canada Inc.

2835 Grand-Allee

Saint Hubert QC J4T 2R4

CA

**Contact person:** EH&S Department **Telephone:** (450)465-2233

**Emergency telephone number:** 1-800-424-9300 (US); 1-613-996-6666 (Canada)

# 2. Hazard(s) identification

#### **Hazard Classification**

# **Physical Hazards**

Flammable liquids Category 2

#### **Health Hazards**

Acute toxicity (Inhalation - vapor) Category 4
Acute toxicity (Inhalation - dust and Category 4

mist)

Skin Corrosion/Irritation Category 2
Germ Cell Mutagenicity Category 1B
Carcinogenicity Category 1B

# **Unknown toxicity - Health**

Acute toxicity, oral 0.22 %
Acute toxicity, dermal 0.22 %
Acute toxicity, inhalation, vapor 95.3 %
Acute toxicity, inhalation, dust 95.68 %

or mist

#### **Environmental Hazards**

Acute hazards to the aquatic Category 3

environment

Chronic hazards to the aquatic Category 3

environment



Revision Date: 10/06/2020

# **Unknown toxicity - Environment**

Acute hazards to the aquatic

environment

Chronic hazards to the aquatic 95.76 %

environment

#### **Label Elements**

# **Hazard Symbol:**



Signal Word: Danger

**Hazard Statement:** Highly flammable liquid and vapor.

Harmful if inhaled. Causes skin irritation. May cause genetic defects.

92.87 %

May cause cancer.

Harmful to aquatic life with long lasting effects.

Precautionary Statements

**Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Keep container tightly closed. Ground and bond

container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective

equipment as required. Avoid release to the environment.

**Response:** IF INHALED: Remove person to fresh air and keep comfortable for

breathing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation occurs: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see on this label). Take off contaminated clothing. In

case of fire: Use... to extinguish.

**Storage:** Store in a well-ventilated place. Keep cool. Store locked up.

**Disposal:** Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.



Revision Date: 10/06/2020

Hazard(s) not otherwise classified (HNOC):

Static accumulating flammable liquid can become electrostatically charged

even in bonded and grounded equipment.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical Identity	Common name and synonyms	CAS number	Content in percent (%)*
Aromatic petroleum distillates		64742-95-6	5 - <10%
1,2,4-Trimethylbenzene		95-63-6	2.5 - <5%
Diisodecyl phthalate		26761-40-0	1 - <5%
Cumene		98-82-8	0.1 - <1%
Xylene		1330-20-7	0.1 - <1%
Tert-Butyl Acetate		540-88-5	0.1 - <1%
Acetone		67-64-1	0.1 - <1%

<sup>\*</sup> All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

# 4. First-aid measures

Description of necessary first-aid measures

**Inhalation:** Move to fresh air.

Skin Contact: Take off immediately all contaminated clothing. Immediately flush with

plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get

medical attention.

**Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy

to do, remove contact lenses. Get medical attention.

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

**Personal Protection for First-**

aid Responders:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

Most important symptoms/effects, acute and delayed

**Symptoms:** Respiratory tract irritation. Prolonged or repeated contact with skin

may cause redness, itching, irritation and eczema/chapping.

**Hazards:** No data available.

Indication of immediate medical attention and special treatment needed

**Treatment:** Symptoms may be delayed.

# 5. Fire-fighting measures



Revision Date: 10/06/2020

**General Fire Hazards:** Use water spray to keep fire-exposed containers cool. Water may be

ineffective in fighting the fire. Fight fire from a protected location. Move

containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from

the chemical:

Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of

vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

# 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Accidental release measures:

In the event of a spill or accidental release, notify relevant authorities in

accordance with all applicable regulations.

Methods and material for containment and cleaning

up:

Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for

disposal according to local regulations.

**Environmental Precautions:** Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so. Avoid release to the environment.

# 7. Handling and storage

#### Handling

Technical measures (e.g. Local and general ventilation):

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.



Revision Date: 10/06/2020

Safe handling advice: Provide adequate ventilation. Wear appropriate personal protective

equipment. Observe good industrial hygiene practices.Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with

skin. Wash hands thoroughly after handling.

Contact avoidance measures: No data available.

**Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. When using do not smoke. Wash

contaminated clothing before reuse. Avoid contact with skin.

Storage

Safe storage conditions: Store locked up. Store in a well-ventilated place. Store in a cool place.

Safe packaging materials: No data available.

# 8. Exposure controls/personal protection

#### **Control Parameters**

**Occupational Exposure Limits** 

Chemical Identity	Туре	Exposure Lim	it Values	Source
1,2,4-Trimethylbenzene	REL	25 ppm	125 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	TWA	25 ppm	125 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	25 ppm	125 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
	AN ESL		25 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (07 2011)
	ST ESL		140 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (02 2013)
	ST ESL		700 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (02 2013)
	AN ESL		125 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (07 2011)
	TWA PEL	25 ppm	125 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (08 2010)
	TWA	25 ppm		US. ACGIH Threshold Limit Values, as amended (2011)
Xylene	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical



				Hazards, as amended (2010)
	STEL	150 ppm	655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000),
	"	тоо ррпп	ooo mg/mo	as amended (1989)
	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000),
	''''	100 ppiii	.55 mg/m6	as amended (1989)
	TWA	100 ppm	435 mg/m3	US. Tennessee. OELs. Occupational Exposure
			· ·	Limits, Table Z1A, as amended (06 2008)
	STEL	150 ppm	655 mg/m3	US. Tennessee. OELs. Occupational Exposure
				Limits, Table Z1A, as amended (06 2008)
	ST ESL		350 µg/m3	US. Texas. Effects Screening Levels (Texas
				Commission on Environmental Quality), as
				amended (07 2011)
	ST ESL		80 ppb	US. Texas. Effects Screening Levels (Texas
				Commission on Environmental Quality), as
				amended (07 2011)
	AN ESL		42 ppb	US. Texas. Effects Screening Levels (Texas
				Commission on Environmental Quality), as
	ANIFOL		100/0	amended (07 2011)
	AN ESL		180 μg/m3	US. Texas. Effects Screening Levels (Texas
				Commission on Environmental Quality), as amended (07 2011)
	STEL	150 ppm	655 mg/m3	US. California Code of Regulations, Title 8,
	SILL	130 ppm	000 mg/m3	Section 5155. Airborne Contaminants, as
				amended (08 2010)
	Ceiling	300 ppm		US. California Code of Regulations, Title 8,
	Coming	ооо ррпп		Section 5155. Airborne Contaminants, as
				amended (08 2010)
	TWA PEL	100 ppm	435 mg/m3	US. California Code of Regulations, Title 8,
				Section 5155. Airborne Contaminants, as
				amended (08 2010)
	TWA	100 ppm		US. ACGIH Threshold Limit Values, as
		• •		amended (2011)
	STEL	150 ppm		US. ACGIH Threshold Limit Values, as
				amended (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air
				Contaminants (29 CFR 1910.1000), as
	77.44			amended (02 2006)
Cumene	TWA	50 ppm		US. ACGIH Threshold Limit Values, as
	551		0.45 / -	amended (2011)
	PEL	50 ppm	245 mg/m3	US. OSHA Table Z-1 Limits for Air
				Contaminants (29 CFR 1910.1000), as
Tort Butyl Acctoto	TWA	E∩ nn∞		amended (02 2006) US. ACGIH Threshold Limit Values, as
Tert-Butyl Acetate	IVVA	50 ppm		amended (03 2016)
	STEL	150 nnm		US. ACGIH Threshold Limit Values, as
	SIEL	150 ppm		amended (03 2016)
	PEL	200 ppm	950 mg/m3	US. OSHA Table Z-1 Limits for Air
	'	200 ρριτι	JJU HIG/HIJ	Contaminants (29 CFR 1910.1000), as
				amended (02 2006)
Acetone	TWA	250 ppm		US. ACGIH Threshold Limit Values, as
	[,	-00 PP		amended (03 2015)
	STEL	500 ppm		US. ACGIH Threshold Limit Values, as
		2 FF		amended (03 2015)
	1			
	PEL	1,000 ppm	2,400 mg/m3	US. OSHA Table Z-1 Limits for Air
	PEL	1,000 ppm	2,400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as





Chemical name	Туре	Exposure Lim	it Values	Source
1,2,4-Trimethylbenzene	TWA	25 ppm	123 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm	123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Diisodecyl phthalate	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Xylene	TWA	100 ppm	434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	STEL	150 ppm	651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Xylene	TWA	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Xylene	STEL	150 ppm	651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Cumene	STEL	75 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Cumene	TWA	50 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Cumene	TWA	50 ppm	246 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)





Chemical name	Туре	Exposure Lim	it Values	Source
1,2,4-Trimethylbenzene	TWA	25 ppm	123 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm	123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Diisodecyl phthalate	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Xylene	TWA	100 ppm	434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	STEL	150 ppm	651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Xylene	TWA	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Xylene	STEL	150 ppm	651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Cumene	STEL	75 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)



Cumene	TWA	50 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Cumene	TWA	50 ppm	246 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Tert-Butyl Acetate	TWA	200 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Tert-Butyl Acetate	TWA	200 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Tert-Butyl Acetate	TWA	200 ppm	950 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Acetone	STEL	500 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	250 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Acetone	TWA	500 ppm	1,190 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	STEL	1,000 ppm	2,380 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Acetone	TWA	250 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)
	STEL	500 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)
Methanol	STEL	250 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	200 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methanol	STEL	250 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	TWA	200 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Methanol	STEL	250 ppm	328 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	TWA	200 ppm	262 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Tert-Butyl Alcohol	TWA	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Tert-Butyl Alcohol	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Tert-Butyl Alcohol	TWA	100 ppm	303 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)



Revision Date: 10/06/2020

**Biological Limit Values** 

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids:	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Sampling time: End of shift.)		
Acetone (acetone: Sampling	25 mg/l (Urine)	ACGIH BEI (03 2015)
time: End of shift.)		

**Appropriate Engineering** 

**Controls** 

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical

ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

**Eye/face protection:** Wear safety glasses with side shields (or goggles).

**Skin Protection** 

**Hand Protection:** Additional Information: Use suitable protective gloves if risk of skin contact.

**Skin and Body Protection:** Wear suitable protective clothing. Wear chemical-resistant gloves,

footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific

information.

**Respiratory Protection:** In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

**Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. When using do not smoke. Wash

contaminated clothing before reuse. Avoid contact with skin.

# 9. Physical and chemical properties

# **Appearance**

Physical state:liquidForm:liquidColor:Colorless

Odor: Mild petroleum/solvent
Odor threshold: No data available.

pH: No data available.

Melting point/freezing point: No data available.

Initial boiling point and boiling range: > 35 °C > 95 °F

**Flash Point:** 17 °C 63 °F(Closed Cup) **Evaporation rate:** Slower than Ether

Flammability (solid, gas): No Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper:

No data available.

No data available.



Revision Date: 10/06/2020

**Explosive limit - lower:**No data available. **Vapor pressure:**No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and

in the bottom of containers.

Relative density: 1.034

Solubility(ies)

Solubility in water: Practically Insoluble
Solubility (other): No data available.
Partition coefficient (n-octanol/water): No data available.

Auto-ignition temperature:No data available.Decomposition temperature:No data available.Viscosity:No data available.

# 10. Stability and reactivity

**Reactivity:** No data available.

**Chemical Stability:** Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

Conditions to avoid: Heat, sparks, flames.

Incompatible Materials: Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides

and chromates). Strong bases.

**Hazardous Decomposition** 

Products:

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

# 11. Toxicological information

# Information on likely routes of exposure

**Inhalation:** In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

**Skin Contact:** May be harmful in contact with skin. Causes skin irritation.

**Eye contact:** Eye contact is possible and should be avoided.

**Ingestion:** May be ingested by accident. Ingestion may cause irritation and malaise.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation:** No data available.

**Skin Contact:** No data available.

**Eye contact:** No data available.

**Ingestion:** No data available.



Revision Date: 10/06/2020

# Information on toxicological effects

# Acute toxicity (list all possible routes of exposure)

Oral

**Product:** ATEmix: 86,942.69 mg/kg

**Dermal** 

**Product:** ATEmix: 2,768.87 mg/kg

Inhalation

**Product:** ATEmix: 13.71 mg/l

ATEmix: 1.72 mg/l

Repeated dose toxicity

**Product:** No data available.

Skin Corrosion/Irritation

**Product:** No data available.

Specified substance(s):

Aromatic petroleum

distillates

in vivo (Rabbit): Irritating

1,2,4-Trimethylbenzene in vivo (Rabbit): Irritating

Cumene in vivo (Rabbit): Not irritant

Xylene in vivo (Rabbit): Moderate irritant

Tert-Butyl Acetate in vivo (Rabbit): Not irritant

Acetone in vivo (Rabbit): Not irritant

Serious Eye Damage/Eye Irritation

**Product:** No data available.

Specified substance(s):

Aromatic petroleum

distillates

Rabbit, 24 - 72 hrs: Not irritating

1,2,4-Trimethylbenzene Rabbit, 30 min: Not irritating

Cumene Rabbit, 24 hrs: Not irritating

Xylene Rabbit, 24 hrs: Moderately irritating



Revision Date: 10/06/2020

Tert-Butyl Acetate Rabbit, 24 hrs: Not irritating

Acetone Irritating

Respiratory or Skin Sensitization

**Product:** No data available.

Carcinogenicity

**Product:** May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Cumene Overall evaluation: Possibly carcinogenic to humans.

**US. National Toxicology Program (NTP) Report on Carcinogens:** 

Cumene Reasonably Anticipated to be a Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

**Germ Cell Mutagenicity** 

In vitro

**Product:** No data available.

In vivo

**Product:** No data available.

Reproductive toxicity

**Product:** No data available.

Specific Target Organ Toxicity - Single Exposure
Product:
No data available.

Specified substance(s):

Cumene Inhalation - vapor: Category 3 with respiratory tract irritation.

**Specific Target Organ Toxicity - Repeated Exposure** 

**Product:** No data available.

**Aspiration Hazard** 

**Product:** No data available.

Other effects: No data available.



Revision Date: 10/06/2020

# 12. Ecological information

# **Ecotoxicity:**

# Acute hazards to the aquatic environment:

Fish

**Product:** No data available.

Specified substance(s):

1,2,4-Trimethylbenzene LC 50 (Fathead minnow (Pimephales promelas), 96 h): 7.19 - 8.28 mg/l

Mortality

Diisodecyl phthalate LC 50 (Fathead minnow (Pimephales promelas), 96 h): > 0.47 mg/l Mortality

Cumene LC 50 (Fathead minnow (Pimephales promelas), 96 h): 6.04 - 6.61 mg/l

Mortality

Xylene LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality

Tert-Butyl Acetate LC 50 (Fathead minnow (Pimephales promelas), 96 h): 296 - 362 mg/l

Mortality

Acetone LC 50 (Fathead minnow (Pimephales promelas), 96 h): 5,490 - 7,030 mg/l

Mortality

**Aquatic Invertebrates** 

**Product:** No data available.

Specified substance(s):

Diisodecyl phthalate EC 50 (Opossum shrimp (Americamysis bahia), 96 h): > 0.08 mg/l Mortality

Cumene LC 50 (Water flea (Daphnia magna), 48 h): 7.9 - 45.1 mg/l Mortality

Acetone EC 50 (Water flea (Daphnia magna), 48 h): 10,294 - 17,704 mg/l Intoxication

# Chronic hazards to the aquatic environment:

**Fish** 

**Product:** No data available.

**Aquatic Invertebrates** 

**Product:** No data available.

**Toxicity to Aquatic Plants** 

**Product:** No data available.

# Persistence and Degradability

**Biodegradation** 

**Product:** No data available.



Revision Date: 10/06/2020

**BOD/COD Ratio** 

**Product:** No data available.

**Bioaccumulative potential** 

**Bioconcentration Factor (BCF)** 

**Product:** No data available.

Partition Coefficient n-octanol / water (log Kow)

**Product:** No data available.

Specified substance(s):

Cumene Log Kow: 3.66

Xylene Log Kow: 3.12 - 3.20

Tert-Butyl Acetate Log Kow: 1.76

Acetone Log Kow: -0.24

Mobility in soil: No data available.

Other adverse effects: Harmful to aquatic life with long lasting effects.

# 13. Disposal considerations

**Disposal methods:** Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Contaminated Packaging: No data available.

# 14. Transport information

#### TDG:

UN1866, RESIN SOLUTION, 3, PG II

# CFR / DOT:

UN1866, Resin solution, 3, PG II

#### IMDG:

UN1866, RESIN SOLUTION, 3, PG II

# **Further Information:**

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.



Revision Date: 10/06/2020

# 15. Regulatory information

# **US Federal Regulations**

# TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

# US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.

# US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

None present or none present in regulated quantities.

#### **CERCLA Hazardous Substance List (40 CFR 302.4):**

Chemical Identity	Reportable quan
Dimethyl carbonate	100 lbs.
Xylene	100 lbs.
Cumene	5000 lbs.
Tert-Butyl Acetate	5000 lbs.
Acetone	5000 lbs.
Methanol	5000 lbs.
Tert-Butyl Alcohol	100 lbs.

# Superfund Amendments and Reauthorization Act of 1986 (SARA)

# **Hazard categories**

Fire Hazard

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route or exposure)

Skin Corrosion or Irritation Germ Cell Mutagenicity

Carcinogenicity

Hazards Not Otherwise Classified (HNOC)

# US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

# Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

Chemical IdentityReportable quantityXyleneReportable quantity: lbs.

# **US State Regulations**

#### **US. California Proposition 65**



Revision Date: 10/06/2020



#### **WARNING**

Cancer and Reproductive Harm - www.P65Warnings.ca.gov

# US. New Jersey Worker and Community Right-to-Know Act

# **Chemical Identity**

Dimethyl carbonate 1,2,4-Trimethylbenzene

#### US. Massachusetts RTK - Substance List

# **Chemical Identity**

Dimethyl carbonate 1,2,4-Trimethylbenzene

# US. Pennsylvania RTK - Hazardous Substances

# **Chemical Identity**

Dimethyl carbonate 1,2,4-Trimethylbenzene Diisodecyl phthalate

# **US. Rhode Island RTK**

# **Chemical Identity**

1,2,4-Trimethylbenzene

# International regulations

# **Montreal protocol**

Not applicable

# Stockholm convention

Not applicable

#### **Rotterdam convention**

Not applicable

# **Kyoto protocol**

Not applicable

# VOC:

Regulatory VOC (less water and : 350 g/l

exempt solvent)

VOC Method 310 : 15.00 %



Revision Date: 10/06/2020

**Inventory Status:** 

Australia AICS: All components in this product are

listed on or exempt from the

Inventory.

Canada DSL Inventory List: All components in this product are

listed on or exempt from the

Inventory.

EINECS, ELINCS or NLP: One or more components in this

product are not listed on or exempt

from the Inventory.

Japan (ENCS) List: One or more components in this

product are not listed on or exempt

from the Inventory.

China Inv. Existing Chemical

Substances:

All components in this product are

listed on or exempt from the

Inventory.

Korea Existing Chemicals Inv. (KECI): All components in this product are

listed on or exempt from the

Inventory.

Canada NDSL Inventory: One or more components in this

product are not listed on or exempt

from the Inventory.

Philippines PICCS: All components in this product are

listed on or exempt from the

Inventory.

US TSCA Inventory: All components in this product are

listed on or exempt from the

Inventory.

New Zealand Inventory of Chemicals: All components in this product are

listed on or exempt from the

Inventory.

Japan ISHL Listing: One or more components in this

product are not listed on or exempt

from the Inventory.

Japan Pharmacopoeia Listing: One or more components in this

product are not listed on or exempt

from the Inventory.



Revision Date: 10/06/2020

# 16.Other information, including date of preparation or last revision

**Revision Date:** 10/06/2020

Version #: 9.0

Further Information: No data available.

**Disclaimer:** For Industrial Use Only. Keep out of Reach of Children. The hazard

information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.