

Version: 1.1 Revision Date: 11/11/2022

SAFETY DATA SHEET

1. Identification

Material name: TAMMSDECK MEMBRANE 5 GL PL Material: TD4304505M

Recommended use and restriction on use

Recommended use: Coatings Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

EUCLID CHEMICAL COMPANY 19218 REDWOOD ROAD CLEVELAND OH 44110 US

Contact person: Telephone: Emergency telephone number: EH&S Department 216-531-9222 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids	Category 3	
Health Hazards		
Respiratory sensitizer	Category 1	
Skin sensitizer	Category 1	
Germ Cell Mutagenicity	Category 1B	
Carcinogenicity	Category 1B	

Unknown toxicity - Health	
Acute toxicity, oral	85.59 %
Acute toxicity, dermal	85.59 %
Acute toxicity, inhalation, vapor	100 %
Acute toxicity, inhalation, dust or mist	99.9 %
Environmental Hazards	
Acute hazards to the aquatic environment	Category 3
Unknown toxisity Environment	

Unknown toxicity - Environment

Acute hazards to the aquatic 93.88 % environment



Chronic hazards to the aquatic 100 % environment

Label Elements

Hazard Symbol: Signal Word: Danger Hazard Statement: Flammable liquid and vapor. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause genetic defects. May cause cancer. Harmful to aquatic life. Precautionary **Statements** Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. **Response:** If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Wash contaminated clothing before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction. Storage: Store in a well-ventilated place. Keep cool. Store locked up. **Disposal:** Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. Hazard(s) not otherwise Static accumulating flammable liquid can become electrostatically charged classified (HNOC): even in bonded and grounded equipment.



3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Talc	14807-96-6	10 - 30%
Aromatic petroleum distillates	64742-95-6	7 - 13%
1,2,4-Trimethylbenzene	95-63-6	3 - 7%
Cumene	98-82-8	1 - 5%
Xylene	1330-20-7	0.1 - 1%
Toluene diisocyanate	26471-62-5	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures				
Description of necessary first-aid measures				
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.			
Skin Contact:	Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.			
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.			
Ingestion:	Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.			
Personal Protection for First- aid Responders:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.			
Most important symptoms/effe	cts, acute and delayed			
Symptoms:	Respiratory tract irritation.			
Hazards:	No data available.			
Indication of immediate medical attention and special treatment needed				
Treatment:	Symptoms may be delayed.			
5. Fire-fighting measures				
General Fire Hazards:	Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.			



Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.			
Unsuitable extinguishing media:	Avoid water in straight hose stream; will scatter and spread fire.			
Specific hazards arising from the chemical:	Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.			
Special protective equipment and precautions for fire-fighters				
Special fire-fighting procedures:	No data available.			
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.			

6. Accidental release measures	
V. ACCINEIIIai I Elease IIIeasules	

7. Handling and storage	
Environmental Precautions:	Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.
Methods and material for containment and cleaning up:	Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.
Accidental release measures:	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.
Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Technical measures (e.g. Local	Observe good industrial hygiene practices. Observe occupational exposure
and general ventilation):	limits and minimize the risk of inhalation of vapors and mist. Mechanical
	ventilation or local exhaust ventilation may be required.



Safe handling advice:	Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Contact avoidance measures:	No data available.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. When using do not smoke. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.
Storage	
Safe storage conditions:	Store locked up. Store in a well-ventilated place. Store in a cool place.
Safe packaging materials:	No data available.

8. Exposure controls/personal protection

Control Parameters

Chemical Identity	Туре	Exposure Limit Values 2 mg/m3		Source
Talc - Respirable fraction.	TWA			US. ACGIH Threshold Limit Values, as amended (2011)
Talc	TWA		20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Talc - Respirable.	TWA		2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	TWA		0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
1,2,4-Trimethylbenzene	REL	25 ppm	125 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	TWA	25 ppm	125 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	25 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
Cumene	PEL	50 ppm	245 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	5 ppm		US. ACGIH Threshold Limit Values, as amended (01 2021)
Xylene	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	STEL	150 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
	TWA	100 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
Toluene diisocyanate - Inhalable fraction and vapor.	TWA	0.001 ppm		US. ACGIH Threshold Limit Values, as amended (03 2016)



	STEL	0.005 ppm		US. ACGIH Threshold Limit Values, as amended (03 2016)
Chemical name	Туре	Exposure Lim	it Values	Source
Talc - Respirable.	TWA	2 mg/m3		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Talc	TWA		2 Fibers/cc	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)
Talc - Respirable fraction.	TWA		2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)
Talc - Respirable dust.	TWA		2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
1,2,4-Trimethylbenzene	TWA	25 ppm	123 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Cumene	STEL	75 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Cumene	TWA	50 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Cumene	TWA	50 ppm	246 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Xylene	STEL	150 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Xylene	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	STEL	150 ppm	651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)



Т

Toluene diisocyanate	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Toluene diisocyanate	STEL	0.02 ppm 0.14 mg	y/m3 Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	TWA	0.005 ppm 0.036 mg	J/m3 Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)

Biological Limit Values

	Chemical Identity	Exposure Limit Values	Source
	ropriate Engineering ontrols	Observe good industrial hygiene practices. Ol limits and minimize the risk of inhalation of va ventilation or local exhaust ventilation may be	pors and mist. Mechanical
Indiv	vidual protection measure	es, such as personal protective equipment	
Eye/	face protection:	Wear safety glasses with side shields (or gog	gles).
-	Protection d Protection:	Additional Information: Use suitable protective	e gloves if risk of skin contact.
Skin	and Body Protection:	Wear suitable protective clothing. Wear chem footwear, and protective clothing appropriate Contact health and safety professional or maninformation.	for the risk of exposure.
Res	biratory Protection:	If engineering controls do not maintain airborr recommended exposure limits (where applica (in countries where exposure limits have not b approved respirator must be worn. Air-purifyir appropriate, government approved (where ap cartridge or canister. Contact health and safet manufacturer for specific information.	ble) or to an acceptable level been established), an ng respirator with an plicable), air-purifying filter,
Hygi	ene measures:	Observe good industrial hygiene practices. W immediately after handling the product. When Contaminated work clothing should not be all Avoid contact with skin.	i using do not smoke.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	Various



Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	43 °C 110 °F(Tag closed cup)
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explo	sive limits
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper:	No data available.
Explosive limit - lower:	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.15
Solubility(ies)	
Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.
Incompatible Materials:	Alcohols. Amines. Strong acids. Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:

In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.



Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Symptoms related to the physica	al, chemical and toxicological characteristics
Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.
Information on toxicological effe	ects
Acute toxicity (list all possible	e routes of exposure)
Oral Product:	ATEmix: 10,385.17 mg/kg
Dermal Product:	ATEmix: 4,116.61 mg/kg
Inhalation Product:	Not classified for acute toxicity based on available data.
Specified substance(s): 1,2,4-Trimethylbenzene	LC 50 (Rat): 10,200 mg/m3
Toluene diisocyanate	LC 50 (Rat): 350 mg/m3
Repeated dose toxicity Product:	No data available.
Skin Corrosion/Irritation Product: Specified substance(s):	No data available.



Aromatic petroleum distillates	in vivo (Rabbit): Irritating , 7 d
1,2,4-Trimethylbenzene	in vivo (Rabbit): Irritating , 24 - 72 h
Cumene	in vivo (Rabbit): Not irritant , 24 h
Xylene	in vivo (Rat): Slightly irritating , 24 h
Toluene diisocyanate	in vivo (Rabbit): Moderately irritating, 72 h

Prod	Eye Damage/Eye Irritation luct: ecified substance(s):	on No data available.
	Aromatic petroleum distillates	Rabbit, 24 - 72 hrs: Minimal irritant
	1,2,4-Trimethylbenzene	Rabbit, 30 min: Not irritant
	Cumene	Rabbit, 24 - 72 hrs: Not irritant
	Xylene	Rabbit, 24 hrs: Moderately irritating Rabbit, 1 hrs: Not irritant
	Toluene diisocyanate	Rabbit, 24 - 72 hrs: Category 2
	ory or Skin Sensitization duct:	n May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause sensitization by inhalation.
Carcino Prod		May cause cancer.
IARC Mo	onographs on the Evalua	ation of Carcinogenic Risks to Humans:
	Talc	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Possibly carcinogenic to humans.
	Cumene	Overall evaluation: Possibly carcinogenic to humans.
	Toluene diisocyanate	Overall evaluation: Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Cumene	Reasonably Anticipated to be a Human Carcinogen.
Toluene	Reasonably Anticipated to be a Human Carcinogen.
diisocyanate	

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended: No carcinogenic components identified



Germ Cell Mutagenicity

In vitro Product:	No data available.
In vivo Product:	No data available.
Reproductive toxicity Product:	No data available.
Specific Target Organ Toxicity - Product: Specified substance(s): Cumene	Single Exposure No data available. Inhalation - vapor: Category 3 with respiratory tract irritation.
Specific Target Organ Toxicity - Product:	Repeated Exposure No data available.
Aspiration Hazard Product:	No data available.
Other effects:	Constituents of this product may include crystalline silica which, if in inhalable form, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimis exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish Product:	No data available.
Specified substance(s): 1,2,4-Trimethylbenzene	LC 50 (Pimephales promelas, 96 h): 7.72 mg/l Experimental result, Key study
Cumene	LC 50 (Cyprinodon variegatus, 96 h): 4.7 mg/l Experimental result, Key 11/17



	study
Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality
Toluene diisocyanate	LC 50 (Oncorhynchus mykiss, 96 h): 133 mg/l Experimental result, Key study
Aquatic Invertebrates Product:	No data available.
Specified substance(s): Aromatic petroleum distillates	EC 50 (Daphnia magna, 48 h): 4.5 mg/l experimental result Experimental result, Key study
1,2,4-Trimethylbenzene	LC 50 (Daphnia magna, 48 h): 3.6 mg/l experimental result Experimental result, Key study
Cumene	EC 50 (Daphnia magna, 48 h): 2.14 mg/l experimental result Experimental result, Key study
Toluene diisocyanate	EC 50 (Daphnia magna, 48 h): 12.5 mg/l experimental result Experimental result, Key study
Chronic hazards to the aquati	c environment:
Fish Product:	No data available.
Aquatic Invertebrates Product:	No data available.
	No data available. EC 50 (Daphnia magna): 10 mg/l experimental result Experimental result, Key study
Product: Specified substance(s): Aromatic petroleum	EC 50 (Daphnia magna): 10 mg/l experimental result Experimental result,
Product: Specified substance(s): Aromatic petroleum distillates	EC 50 (Daphnia magna): 10 mg/l experimental result Experimental result, Key study NOAEL (Daphnia magna): 0.35 mg/l experimental result Experimental result,
Product: Specified substance(s): Aromatic petroleum distillates Cumene	EC 50 (Daphnia magna): 10 mg/l experimental result Experimental result, Key study NOAEL (Daphnia magna): 0.35 mg/l experimental result Experimental result, Key study NOAEL (Daphnia magna): 1.1 mg/l experimental result Experimental result,
Product: Specified substance(s): Aromatic petroleum distillates Cumene Toluene diisocyanate Toxicity to Aquatic Plants	EC 50 (Daphnia magna): 10 mg/l experimental result Experimental result, Key study NOAEL (Daphnia magna): 0.35 mg/l experimental result Experimental result, Key study NOAEL (Daphnia magna): 1.1 mg/l experimental result Experimental result, Key study
Product: Specified substance(s): Aromatic petroleum distillates Cumene Toluene diisocyanate Toxicity to Aquatic Plants Product:	EC 50 (Daphnia magna): 10 mg/l experimental result Experimental result, Key study NOAEL (Daphnia magna): 0.35 mg/l experimental result Experimental result, Key study NOAEL (Daphnia magna): 1.1 mg/l experimental result Experimental result, Key study
Product: Specified substance(s): Aromatic petroleum distillates Cumene Toluene diisocyanate Toxicity to Aquatic Plants Product: Persistence and Degradability Biodegradation	EC 50 (Daphnia magna): 10 mg/l experimental result Experimental result, Key study NOAEL (Daphnia magna): 0.35 mg/l experimental result Experimental result, Key study NOAEL (Daphnia magna): 1.1 mg/l experimental result Experimental result, Key study No data available.



Bioaccumulative potential Bioconcentration Factor (B	
Product:	No data available.
Specified substance(s): Aromatic petroleum distillates	Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by calculation, Key study
1,2,4-Trimethylbenzene	Pimephales promelas, Bioconcentration Factor (BCF): 243 Aquatic sediment QSAR, Key study
Cumene	Bioconcentration Factor (BCF): 94.69 Aquatic sediment Estimated by calculation, Key study
Xylene	Oncorhynchus mykiss, Bioconcentration Factor (BCF): > 8.1 - < 25.9 Aquatic sediment Experimental result, Key study
Partition Coefficient n-octanol / Product:	water (log Kow) No data available.
Specified substance(s): 1,2,4-Trimethylbenzene	Log Kow: 3.78
Cumene	Log Kow: 3.66
Xylene	Log Kow: 2.77 - 3.15 No Not specified, Not specified
Mobility in soil:	No data available.
Other adverse effects:	Harmful to aquatic organisms.
13. Disposal considerations	
Disposal methods:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.

14. Transport information

TDG:

UN1139, COATING SOLUTION, 3, PG III

CFR / DOT:

UN1139, Coating solution, 3, PG III



IMDG:

UN1139, COATING SOLUTION, 3, PG III

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Chemical Identity

Toluene diisocyanate

Reportable quantity

De minimis concentration: TSCA 5(a)(2)% One-Time Export Notification only.

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended None present or none present in regulated guantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Cumene	5000 lbs.
Xylene	100 lbs.
Toluene diisocyanate	100 lbs.
Ethylbenzene	1000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard Delayed (Chronic) Health Hazard Immediate (Acute) Health Hazards

US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

US. EPCRA (SARA Title III Section 313 Toxic Chemical Release Inventory (TRI) Reporting

Chemical Identity	<u>% by weight</u>
1,2,4-Trimethylbenzene	1.0%
Cumene	0.1%
Toluene diisocyanate	0.1%

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Chemical Identity	
Toluene diisocyanate	Э

Repo	rtable	quantity	
lbs			

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.



US State Regulations

US. California Proposition 65

For more information go to www.P65Warnings.ca.gov.

International regulations

Montreal protocol Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC:

Regulatory VOC (less water and exempt solvent)	:	166 g/l
VOC Method 310	:	14.41 %



Inventory Status: Australia AICS:	All components in this product are listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	All components in this product are listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	All components in this product are listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	All components in this product are listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	All components in this product are listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.



16.Other information, including date of preparation or last revision

Revision Date:	11/11/2022
Version #:	1.1
Further Information:	No data available.
Disclaimer:	For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.