



EUCLID CHEMICAL

WEATHER-GUARD

SOLVENT-BASED, PENETRATING SILOXANE WATER REPELLENT

PACKAGING

5 gal (18.9 L) pail
Code: 052A 05
55 gal (208 L) drum
Code: 052A 55
1 gal (3.8 L) pail, case of 4
Code: 052A 93

APPROXIMATE COVERAGE

See coverage rate section below for application rates.

CLEAN UP

Use mineral spirits or acetone to clean tools and equipment.

SHELF LIFE

2 years in original, unopened package

SPECIFICATIONS AND COMPLIANCES

- Complies with Federal AIM Rule VOC regulations

DESCRIPTION

WEATHER-GUARD is a siloxane penetrating sealer designed specifically for the treatment of masonry materials and concrete surfaces. WEATHER-GUARD protects concrete and masonry surfaces from the effects of exterior exposure and weathering. WEATHER-GUARD penetrates deep into the surface pores and reacts chemically to provide a durable, long lasting barrier against water and salt intrusion. This level of protection can substantially reduce the damaging effects of freeze/thaw cycling, precipitation, acid rain, efflorescence, and dust/dirt degradation.

PRODUCT CHARACTERISTICS

FEATURES/BENEFITS

- Deep penetrating pore action for long lasting protection
- Preserves a natural appearance without membrane build-up
- Provides a highly efficient barrier to water and salt ingress
- Allows concrete and masonry surfaces to maintain breathability while providing high water repellency characteristics
- Easy to use requiring only low pressure spraying equipment
- Economical due its durability over many years

PRIMARY APPLICATIONS

- Concrete and masonry block
- Natural stone
- Brick facings
- Precast concrete
- Clay brick
- Exposed aggregate
- Stucco
- Architectural concrete

APPEARANCE

WEATHER-GUARD is a clear liquid that does not change the color or appearance of the substrate. After application of WEATHER-GUARD, the color of the substrate may initially appear darker but will lighten upon drying.

COVERAGE

Required coverage rates will vary depending on surface density and porosity. In some cases, test sections may be necessary to develop a feel for adequate coverage. In general, coverage rates of 100 to 150 ft²/gal (2.4 to 3.7 m²/L) are recommended.

TECHNICAL INFORMATION

The following are typical values obtained under laboratory conditions. Expect reasonable variation under field conditions.

Flash point	104 °F (40 °C)
Active Content (by weight)	5%
VOC Content	749 g/L
Water absorption, ASTM C67 (multi-celled brick raked face, 24 hr immersion)	0.259%
Drying time at 70 °F (21 °C)1 to 2 hours
Foot Traffic4 to 6 hours
Wheel Traffic	10 to 12 hours

DIRECTIONS FOR USE

Surface Preparation: All surfaces to be treated should be clean and free from all dirt, dust, and other forms of contamination that could prevent WEATHER-GUARD penetration. Any membranes present on the surface must be completely removed. Protect adjacent glass and metal surfaces from overspray or accidental contamination. All joint materials should be installed before WEATHER-GUARD application. Surfaces should be in a dry or damp condition without being saturated.

Mixing: WEATHER-GUARD is ready to use and requires no pre-mixing.

Placement: The preferred method of application is with a low pressure, non-atomizing, airless sprayer. Brushes or rollers may also be used if enough material can be applied to assure uniform coverage. Use WEATHER-GUARD directly from the container. No dilution is necessary or permissible. Apply in a uniform manner working back and forth lapping the previous pass. On vertical surfaces, apply from the bottom up. Avoid extra heavy build-up in isolated areas. One application in two passes is recommended to assure complete, uniform coverage. After the first pass has been completed, apply the second pass so that a wet-on-wet process is assured.

PRECAUTIONS/LIMITATIONS

- Do not use over previously applied membrane-forming curing compounds or sealers.
- Masonry temperature at the time of application should be above 40 °F (4 °C). Drying time in cool weather will be extended.
- New concrete and masonry surfaces should be a minimum of 3 days old and have undergone some drying before WEATHER-GUARD application.
- Confined or inside areas must be properly ventilated.
- Protect adjacent areas from overspray.
- COMBUSTIBLE - Keep material away from open flames, sparks, or other sources of ignition.
- WEATHER-GUARD is a solvent-based product with a distinct odor. When used in enclosed areas, or on extremely porous substrates, the solvent odor may dissipate slowly. Where solvent odors are not acceptable, use a water-based product such as BARCADE WB 244 or CHEMSTOP WB.
- All joint sealant materials should be installed before WEATHER-GUARD application.
- Do not apply if rain is expected within 8 hours.
- Do not allow to puddle. All product should penetrate the substrate with no surface build-up.
- This product does not prevent oil stains or discoloration from fallen tree leaves.
- A small (6' x 6') test area is strongly recommended prior to starting full application, in order to ensure desired performance results, aesthetics, and coverage rates. Allow 5 to 7 days for product to fully react before evaluating.
- In all cases, consult the Safety Data Sheet before use.

Rev. 05.22

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.