

# Technical Information Sheet



## 18" QuickSeam™ SA Flashing

Item Description	Item Number
50' (15.25 mm) Roll	W56RAC1620

### Description

QuickSeam SA Flashing is 18" wide .060" (60 mil) non-reinforced RubberGard™ membrane fully laminated to Elevate QuickSeam Tape. SA Flashing is a labor saving and environmentally friendly alternative to conventional methods which use contact adhesive for attachment. A Flashing can be used for curbs or parapets where flashing heights allow.

Because the QuickSeam Tape Technology is used as the adhesive it is considered self-seaming. Simply prime the membrane with Elevate QuickPrime to which the SA Flashing will be installed.

### Method of Application

1. Using Elevate QuickScrubber™ or QuickScrubber Plus pad and handle, apply QuickPrime Plus to the roof membrane and substrate to receive the SA Flashing.
2. Refer to Elevate's instruction sheet for Elevate 18" QuickSeam SA Flashing which is included in each carton for more specific information.
3. Contact a Regional Technical Coordinator at 1-800-428-4511 for specific application information.

### Packaging

- 50' (15.25 mm) roll, 1 roll per carton
- 24 cartons per pallet

**NOTE:** QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product

### Storage

- Store in original unopened cartons indoors at temperatures between 60 °F (16 °C) and 80 °F (27 °C).
- Do not store on the roof in direct sunlight or at temperatures above 100 °F (38 °C).
- When exposed to lower temperatures, restore to 60 °F (16 °C) and 80 °F (27 °C) prior to use.

## Shelf Life

Shelf life of 24 months can be expected if stored in original container at temperatures between 60 °F (16 °C) and 80 °F (27 °C). Shelf life will be shortened if exposed to elevated temperatures.

## Precautions

Refer to Safety Data Sheets (SDS) for additional safety information.

## LEED® Information

Post-Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: Michigan Center, MI

NOTE: LEED® is a registered trademark of the U.S. Green Building Council

Typical Properties	
Properties – QuickSeam Tape	Value
Base	Rubber Polymers
Color	Black
Solvents	None
Solids	100%
Cured State	Cured
Thickness	0.020" ± 0.005" (0.51 mm ± 0.13 mm)
Width	18" (457 mm)
Properties – Membrane	Value
Base	EPDM
Color	Black
Solvents	None
Cure State	Cured
Thickness	0.060" ± 0.005" (1.5 mm ± 0.13 mm)
Width	18" (457 mm)
Type	Non-Reinforced
Properties – Release Liner	Value
Base	Polyester

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.

Firestone, the brand of premier roofing, wall, and lining systems you know and trust, will be coming to you under a new name: Elevate. During our transition, products carrying the brand name **Firestone** will change to **Elevate** on product labels and packaging, Technical Information Sheets, and elsewhere. Only the brand name is changing. Our products remain the same.

For further information on our brand transition to Elevate, scan the code below with your smartphone, or visit our website: [www.holcimelevate.com](http://www.holcimelevate.com)

