

Technical Information Sheet



AP ACCUTRAC* KITS

Size	Item Number	Size	Item Number
1 5/8"	W56RACFB16	4"	W56RACFB40
2 1/2"	W56RACFB22	5"	W56RACFB50
3"	W56RACFB30	6"	W56RACFB60

DESCRIPTION

The AP AccuTrac Kits are specifically designed to be used in roofing applications for the attachment of insulation into steel and wood roof decks with OMG AccuTrac installation equipment. A kit consists of both #12 fasteners and insulation plates for the AccuTrac tool. The AccuTrac system provides consistent vertical and depth setting of fasteners.

METHOD OF APPLICATION

1. Remove the stacked AccuTrac plates from the bucket and align the notch in the plates with the projection on the back side of the AccuTrac tool plate holder and set the plates into position.
2. Lock the screw gun trigger in the ON position. Using the lock will keep the screw gun running cooler.
3. Drop one screw, point down, into the feeder tube, fully compress the AccuTrac tool to allow a plate to be ejected from the stack and moved into position to drive the screw through the AccuTrac plate until it contacts the deck. Continue to hold down on the tool until the plate is fully seated.
4. Allow the tool to retract to its original position.
5. Pull the tool back on its wheels, push it to the next plate position on the roof and repeat.

NOTE: These fasteners may not work as expected through existing roof systems or unusual substrates. Consideration should be given to using Elevate HD fasteners in these instances.

Steel Decks: Select fastener length to penetrate through the deck a minimum of 3/4" (19.1 mm).

Wood Decks: Select fastener length to penetrate through deck a minimum of 1" (25.4 mm).

STORAGE

Store in original, unopened packaging protected from the weather.

PRECAUTIONS

- Eye protection must be worn during the installation of fasteners.
- The AccuTrac fasteners and plates are designed exclusively for use in the OMG AccuTrac tool. Using other fasteners or plates in the AccuTrac tool will not work and may damage the tool.

TIS 1007

September 8, 2025

Sales: (800) 428-4442

Technical: (800) 428-4511

Page 1

LEED® INFORMATION

Post-Consumer Content: 0%
 Pre-Consumer Content: 25%
 Manufacturing Location: Addison, IL

NOTE: LEED® is a registered trademark of the U.S. Green Building Council



PRODUCT PACKAGING			
Screw Length	Thread Length	Pieces per Carton	Cartons per Pallet
1 5/8" (70 mm)	Full	1000	40
2 1/4" (57.15 mm)	Full	1000	40
3" (76.2 mm)	Full	1000	40
4" (101.6 mm)	3" (76.2 mm)	1000	40
5" (127 mm)	4" (101.6 mm)	1000	40
6" (152.4 mm)	4" (101.6 mm)	1000	40

PRODUCT DATA	
Property: Metal Plate	Value
Material	SAE 1010 CR, AZ-55 Galvalume®
Thickness	0.018" (.46 mm)
Shape	3" (76.2 mm) square
Corrosion Resistance	Meets FM No. 4470 criteria
Pull Through Resistance	400 lbf (181.4 kgf) minimum
Property: Fastener	
Material	SAE 1022 heat treated steel
Thread Size	.220" (5.58 mm)
Thread Type	Modified Buttruss thread
Head Type	#3 Phillips
Point Type	Drill Point
Pullout	
Pullout in New 22 ga. (0.76 mm) Steel Deck	
Grade C (Grade 33)	240 lb (108.9 kg) minimum
Grade E (Grade 80)	300 lb (136.1 kg) minimum
Pullout in New 1/2" (12.7 mm) Plywood	280 lb (127 kg) minimum
Corrosion Resistance Coating	Electrocoating Elevates Red fasteners exceed requirements of FM 4470
Color	Red (PMS 485)

*Galvalume® is a registered trademark of BIEC International, Inc.

**AccuTrac™ is a trademark of OMG. Inc

Please contact Elevate Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Amrize takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Amrize nor its representatives practice architecture. Amrize offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Amrize accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Amrize representative is authorized to vary this disclaimer.