


## 1. Identification

<b>Product identifier</b>	<b>AcryliTop PC-100 - Tan</b>
<b>Other means of identification</b>	
<b>Product code</b>	W56RACTOPT
<b>Recommended use</b>	Architectural coating and waterproofing
<b>Recommended restrictions</b>	None known.
<b>Manufacturer/Importer/Supplier/Distributor information</b>	
<b>Distributed by</b>	Holcim Solutions and Products US, LLC
<b>Address</b>	26 Century Boulevard, Suite 205 Nashville, TN 37214 Elevate™ is a Holcim Solutions and Products US, LLC brand.
<b>Website</b>	holcimelevate.com
<b>Telephone Number</b>	1-800-428-4442
<b>Emergency Telephone Number</b>	For Chemical Emergency, Spill, Leak, Fire, Exposure, or Incident:  CHEMTREC within USA and Canada: 1-800-424-9300 CHEMTREC outside USA and Canada: +1 703-527-3887 (collect calls accepted)

## 2. Hazard(s) identification

<b>Physical hazards</b>	Not classified.	
<b>Health hazards</b>	Sensitization, skin	Category 1A
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
<b>OSHA defined hazards</b>	Not classified.	
<b>Label elements</b>		
<b>Signal word</b>	Warning	
<b>Hazard statement</b>	May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.	
<b>Precautionary statement</b>		
<b>Prevention</b>	Avoid breathing mist/vapors. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves.	
<b>Response</b>	If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.	
<b>Storage</b>	Store away from incompatible materials.	
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.	
<b>Hazard(s) not otherwise classified (HNOC)</b>	None known.	
<b>Supplemental information</b>	None.	

## 3. Composition/information on ingredients

### Mixtures

Chemical name	CAS number	%
Titanium Dioxide	13463-67-7	3 - 7
Propane -1,2 -diol	57-55-6	1 - 5
Quartz (SiO <sub>2</sub> )	14808-60-7	0.1 - < 1
Diuron	330-54-1	0.1
2-octyl-2H-isothiazol-3-one	26530-20-1	0.07
2-Methyl-2H-isothiazol-3-one	2682-20-4	0.006

**Composition comments** All concentrations are in percent by weight unless otherwise indicated. Components not listed are either non-hazardous or are below reportable limits. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

#### 4. First-aid measures

**Inhalation** Move to fresh air. Call a physician if symptoms develop or persist.

**Skin contact** Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

**Eye contact** Rinse with water. Get medical attention if irritation develops and persists.

**Ingestion** Rinse mouth. Get medical attention if symptoms occur.

**Most important symptoms/effects, acute and delayed** May cause an allergic skin reaction. Dermatitis. Rash.

**Indication of immediate medical attention and special treatment needed** Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

#### 5. Fire-fighting measures

**Suitable extinguishing media** Water fog. Foam. Dry chemical powder. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical** During fire, gases hazardous to health may be formed such as: Carbon oxides (CO<sub>x</sub>).

**Special protective equipment and precautions for firefighters** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

**Fire fighting equipment/instructions** Move containers from fire area if you can do so without risk.

**Specific methods** Use standard firefighting procedures and consider the hazards of other involved materials.

**General fire hazards** No unusual fire or explosion hazards noted.

#### 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures** Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

**Methods and materials for containment and cleaning up** This product is miscible in water. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

**Environmental precautions** Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

### Precautions for safe handling

Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

### Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Components	Type	Value
Quartz (SiO <sub>2</sub> ) (CAS 14808-60-7)	TWA	0.05 mg/m <sup>3</sup>

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Ammonium hydroxide (CAS 1336-21-6)	PEL	35 mg/m <sup>3</sup>	
		50 ppm	
Limestone (CAS 1317-65-3)	PEL	5 mg/m <sup>3</sup>	Respirable fraction.
		15 mg/m <sup>3</sup>	Total dust.
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m <sup>3</sup>	Total dust.

#### US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Limestone (CAS 1317-65-3)	TWA	5 mg/m <sup>3</sup>	Respirable fraction.
		15 mg/m <sup>3</sup>	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Quartz (SiO <sub>2</sub> ) (CAS 14808-60-7)	TWA	0.1 mg/m <sup>3</sup>	Respirable.
		2.4 mppcf	Respirable.

#### US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Ammonium hydroxide (CAS 1336-21-6)	STEL	35 ppm	
	TWA	25 ppm	
Diuron (CAS 330-54-1)	TWA	10 mg/m <sup>3</sup>	
Quartz (SiO <sub>2</sub> ) (CAS 14808-60-7)	TWA	0.025 mg/m <sup>3</sup>	Respirable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	2.5 mg/m <sup>3</sup>	Respirable finescale particles
		0.2 mg/m <sup>3</sup>	Respirable nanoscale particles

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Ammonium hydroxide (CAS 1336-21-6)	STEL	27 mg/m <sup>3</sup>	
		35 ppm	
		18 mg/m <sup>3</sup>	
Diuron (CAS 330-54-1)	TWA	25 ppm	
		10 mg/m <sup>3</sup>	
Limestone (CAS 1317-65-3)	TWA	5 mg/m <sup>3</sup>	Respirable.
		10 mg/m <sup>3</sup>	Total

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
Quartz (SiO <sub>2</sub> ) (CAS 14808-60-7)	TWA	0.05 mg/m <sup>3</sup>	Respirable dust.

**US. Workplace Environmental Exposure Level (WEEL) Guides**

Components	Type	Value	Form
Propane -1,2 -diol (CAS 57-55-6)	TWA	10 mg/m <sup>3</sup>	Aerosol.

<b>Biological limit values</b>	No biological exposure limits noted for the ingredient(s).
<b>Appropriate engineering controls</b>	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
<b>Individual protection measures, such as personal protective equipment</b>	
<b>Eye/face protection</b>	Wear safety glasses with side shields (or goggles). Face shield is recommended.
<b>Skin protection</b>	
<b>Hand protection</b>	Wear appropriate chemical resistant gloves. Examples of preferred glove barrier materials include: Nitrile. Suitable gloves can be recommended by the glove supplier.
<b>Skin protection</b>	
<b>Other</b>	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
<b>Respiratory protection</b>	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.
<b>General hygiene considerations</b>	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

**9. Physical and chemical properties****Appearance**

**Physical state** Liquid.

**Form** Viscous liquid.

**Color** Tan.

**Odor** Mild ammonia.

**Odor threshold** Not available.

**pH** 8.8 (68 °F (20 °C))

**Melting point/freezing point** Not determined.

**Initial boiling point and boiling range** Not determined.

**Flash point** > 199.4 °F (> 93 °C) Closed Cup

**Evaporation rate** Not determined.

**Flammability (solid, gas)** Not applicable.

**Upper/lower flammability or explosive limits**

**Explosive limit - lower (%)** Not determined.

**Explosive limit - upper (%)** Not determined.

**Vapor pressure** Not determined.

**Vapor density** Not determined.

**Relative density** 1.4 (77 °F (25 °C))

**Solubility(ies)**

**Solubility (water)** Soluble.

**Partition coefficient (n-octanol/water)** Not applicable, product is a mixture.

<b>Auto-ignition temperature</b>	Not determined.
<b>Decomposition temperature</b>	Not determined.
<b>Viscosity</b>	115 ku (77 °F (25 °C))
<b>Other information</b>	Solids content: 65%
<b>Density</b>	Not determined.
<b>Explosive properties</b>	Not explosive.
<b>Kinematic viscosity</b>	Not determined.
<b>Oxidizing properties</b>	Not oxidizing.
<b>VOC</b>	44.5 g/l 0.37 lb/gal

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents. Fluorine.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	No adverse effects due to inhalation are expected. Inhalation of titanium dioxide dust may cause cancer, however due to the physical form of the product, inhalation of dust is not likely. Crystalline silica poses a health hazard when it is inhaled as a dust. Normal use of product does not generate silica or other dust.
<b>Skin contact</b>	May cause an allergic skin reaction.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Ingestion</b>	Expected to be a low ingestion hazard.
<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	May cause an allergic skin reaction. Dermatitis. Rash.

### Information on toxicological effects

**Acute toxicity** Not expected to be acutely toxic.

Components	Species	Test Results
2-octyl-2H-isothiazol-3-one (CAS 26530-20-1)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
ATE		311 mg/kg
<b>Inhalation</b>		
<i>Mist</i>		
ATE		0.27 mg/l
<b>Oral</b>		
ATE		125 mg/kg
3-Iodo-2-propynyl butylcarbamate (CAS 55406-53-6)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Oral</b>		
LD50	Rat	1.1 g/kg

Components	Species	Test Results
Ammonium hydroxide (CAS 1336-21-6)		
<b>Acute</b>		
<b>Oral</b>		
LD50	Rat	350 mg/kg
Propane -1,2 -diol (CAS 57-55-6)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	20800 mg/kg
<b>Oral</b>		
LD50	Rat	22000 mg/kg
Quartz (SiO <sub>2</sub> ) (CAS 14808-60-7)		
<b>Chronic</b>		
<b>Inhalation</b>		
LOEC	Human	0.0563 mg/m <sup>3</sup>
Titanium Dioxide (CAS 13463-67-7)		
<b>Acute</b>		
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
<b>Skin corrosion/irritation</b>	Prolonged skin contact may cause temporary irritation.	
<b>Serious eye damage/eye irritation</b>	Direct contact with eyes may cause temporary irritation.	
<b>Respiratory or skin sensitization</b>		
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.	
<b>Skin sensitization</b>	May cause an allergic skin reaction.	
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
<b>Carcinogenicity</b>	Due to the form of the product, exposure to the potentially carcinogenic components is not expected. Titanium dioxide is considered carcinogenic only when in an inhalable powdered form. Crystalline silica poses a health hazard when it is inhaled as a dust. Normal use of product does not generate silica or other dust.	
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>		
Quartz (SiO <sub>2</sub> ) (CAS 14808-60-7)	1 Carcinogenic to humans.	
Titanium Dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.	
<b>NTP Report on Carcinogens</b>		
Quartz (SiO <sub>2</sub> ) (CAS 14808-60-7)	Known To Be Human Carcinogen.	
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)</b>		
Quartz (SiO <sub>2</sub> ) (CAS 14808-60-7)	Cancer	
<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.	
<b>Specific target organ toxicity - single exposure</b>	Not classified.	
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.	
<b>Aspiration hazard</b>	Not an aspiration hazard.	

## 12. Ecological information

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Components	Species	Test Results
2-octyl-2H-isothiazol-3-one (CAS 26530-20-1)		
<b>Aquatic</b>		
<i>Acute</i>		
Algae	EC50	Algae
Crustacea	EC50	Crustacea
		0.15 mg/l, 72 Hours
		0.181 mg/l, 48 Hours

Components		Species	Test Results
Fish	LC50	Fish	0.122 mg/l, 96 Hours
<i>Chronic</i>			
Algae	NOEC	Algae	0.068 mg/l, 72 Hours
Crustacea	NOEC	Crustacea	0.035 mg/l, 21 days
Fish	NOEC	Fish	0.022 mg/l, 21 days

3-Iodo-2-propynyl butylcarbamate (CAS 55406-53-6)

**Aquatic**

Fish LC50 Oncorhynchus mykiss 67 µg/l, 96 hours

Titanium Dioxide (CAS 13463-67-7)

**Aquatic**

*Acute*

Crustacea EC50 Daphnia magna > 100 mg/l, 48 Hours

Fish LL50 Oryzias latipes > 100 mg/l, 96 Hours

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** No data available for this product.

**Partition coefficient n-octanol / water (log Kow)**

Ammonium hydroxide (CAS 1336-21-6) -2.66

Diuron (CAS 330-54-1) 2.68

Propane -1,2 -diol (CAS 57-55-6) -0.92

**Mobility in soil** No data available.

**Other adverse effects** No data available.

### 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. Transport information

**DOT**

**UN number** UN3082

**UN proper shipping name** Environmentally hazardous substance, liquid, n.o.s. (Diuron RQ = 100000 LBS, 2-octyl-2H-isothiazol-3-one)

**Transport hazard class(es)**

**Class** 9

**Subsidiary risk** -

**Label(s)** 9

**Packing group** III

**Environmental hazards**

**Marine pollutant** Yes.

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**Special provisions** 8, 146, 173, 335, IB3, T4, TP1, TP29

**Packaging exceptions** 155

**Packaging non bulk** 203

**Packaging bulk** 241

Non-bulk shipments may not be subject to DOT provisions as per 49CFR 171.4(c). Refer to regulation for specific requirements for this exception.

#### IATA

**UN number** UN3082  
**UN proper shipping name** Environmentally hazardous substance, liquid, n.o.s. (Diuron, 2-octyl-2H-isothiazol-3-one)  
**Transport hazard class(es)**  
**Class** 9  
**Subsidiary risk** -  
**Packing group** III  
**Environmental hazards** Yes.  
**ERG Code** 9L  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

Non-bulk shipments may not be subject to IATA provisions as per special provision A147. Refer to IATA regulations for specific requirements for this exception.

#### IMDG

**UN number** UN3082  
**UN proper shipping name** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Diuron, 2-octyl-2H-isothiazol-3-one)  
**Transport hazard class(es)**  
**Class** 9  
**Subsidiary risk** -  
**Packing group** III  
**Environmental hazards**  
**Marine pollutant** Yes.  
**EmS** F-A, S-F  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

Non-bulk shipments may not be subject to IMDG provisions as per special provision 375. Refer to IMDG regulations for specific requirements for this exception.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not established.

### 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

2-Methyl-2H-isothiazol-3-one (CAS 2682-20-4) 1.0 % One-Time Export Notification only.

#### CERCLA Hazardous Substance List (40 CFR 302.4)

Ammonium hydroxide (CAS 1336-21-6) Listed.  
Diuron (CAS 330-54-1) Listed.

#### SARA 304 Emergency release notification

Ammonia; Ammonia (anhydrous) (CAS 1336-21-6) 100 LBS

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz (SiO<sub>2</sub>) (CAS 14808-60-7) Cancer  
lung effects  
immune system effects  
kidney effects

**Toxic Substances Control Act (TSCA)** All components of the mixture on the TSCA 8(b) inventory are designated "active".



## Superfund Amendments and Reauthorization Act of 1986 (SARA)

### SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)
Ammonium hydroxide	1336-21-6	100	500		

### SARA 311/312 Hazardous chemical

**Classified hazard categories** Respiratory or skin sensitization

### SARA 313 (TRI reporting)

Not regulated.

## Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Ammonium hydroxide (CAS 1336-21-6)

**Safe Drinking Water Act (SDWA)** Contains component(s) regulated under the Safe Drinking Water Act.

## US state regulations

### US. Massachusetts RTK - Substance List

Ammonium hydroxide (CAS 1336-21-6)  
Diuron (CAS 330-54-1)  
Limestone (CAS 1317-65-3)  
Quartz (SiO<sub>2</sub>) (CAS 14808-60-7)  
Titanium Dioxide (CAS 13463-67-7)

### US. New Jersey Worker and Community Right-to-Know Act

3-Iodo-2-propynyl butylcarbamate (CAS 55406-53-6)  
Ammonium hydroxide (CAS 1336-21-6)  
Diuron (CAS 330-54-1)  
Limestone (CAS 1317-65-3)  
Propane -1,2 -diol (CAS 57-55-6)  
Quartz (SiO<sub>2</sub>) (CAS 14808-60-7)  
Titanium Dioxide (CAS 13463-67-7)

### US. Pennsylvania Worker and Community Right-to-Know Law

Ammonium hydroxide (CAS 1336-21-6)  
Diuron (CAS 330-54-1)  
Limestone (CAS 1317-65-3)  
Propane -1,2 -diol (CAS 57-55-6)  
Quartz (SiO<sub>2</sub>) (CAS 14808-60-7)  
Titanium Dioxide (CAS 13463-67-7)

### US. Rhode Island RTK

Ammonium hydroxide (CAS 1336-21-6)  
Diuron (CAS 330-54-1)  
Limestone (CAS 1317-65-3)  
Propane -1,2 -diol (CAS 57-55-6)  
Quartz (SiO<sub>2</sub>) (CAS 14808-60-7)  
Titanium Dioxide (CAS 13463-67-7)

## California Proposition 65



**WARNING:** This product can expose you to chemicals including 1,4-Dioxane, Diuron, Ethylene oxide, Methyloxirane, which are known to the State of California to cause cancer, and Ethylene oxide, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,4-Dioxane (CAS 123-91-1)	Listed: January 1, 1988
Diuron (CAS 330-54-1)	Listed: May 31, 2002
Ethylene oxide (CAS 75-21-8)	Listed: July 1, 1987
Methyloxirane (CAS 75-56-9)	Listed: October 1, 1988

**California Proposition 65 - CRT: Listed date/Developmental toxin**

Ethylene oxide (CAS 75-21-8) Listed: August 7, 2009

**California Proposition 65 - CRT: Listed date/Female reproductive toxin**

Ethylene oxide (CAS 75-21-8) Listed: February 27, 1987

**California Proposition 65 - CRT: Listed date/Male reproductive toxin**

Ethylene oxide (CAS 75-21-8) Listed: August 7, 2009

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

Ammonium hydroxide (CAS 1336-21-6)

Quartz (SiO<sub>2</sub>) (CAS 14808-60-7)

Titanium Dioxide (CAS 13463-67-7)

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**16. Other information, including date of preparation or last revision****Issue date** 15-December-2022**Revision date** -**Version #** 01**HMIS® ratings**  
Health: 2  
Flammability: 0  
Physical hazard: 0**Disclaimer**  
Holcim Solutions and Products US, LLC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.