ELEVATE

SAFETY DATA SHEET

1. Identification

Product identifier AcryliTop PC-100 - Gray

Other means of identification

Product code W56RACTOPG

Recommended use Architectural coating and waterproofing

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Distributed by Holcim Solutions and Products US, LLC

Address 26 Century Boulevard, Suite 205

Nashville, TN 37214

Elevate™ is a Holcim Solutions and Products US, LLC brand.

Website holcimelevate.com
Telephone Number 1-800-428-4442

Emergency Telephone

Number

For Chemical Emergency, Spill, Leak, Fire, Exposure, or Incident:

CHEMTREC within USA and Canada: 1-800-424-9300

CHEMTREC outside USA and Canada: +1 703-527-3887 (collect calls accepted)

Category 2

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Sensitization, skin Category 1A

Environmental hazards Hazardous to the aquatic environment, acute Category 2

hazard

Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention Avoid breathing mist/vapors. Contaminated work clothing must not be allowed out of the

workplace. Avoid release to the environment. Wear protective gloves.

Response If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

AcryliTop PC-100 - Gray SDS US

959153 Version #: 01 Revision date: - Issue date: 14-December-2022

Chemical name	CAS number	%
Titanium Dioxide	13463-67-7	3 - 7
Propane -1,2 -diol	57-55-6	1 - 5
Quartz (SiO2)	14808-60-7	0.1 - < 1
Diuron	330-54-1	0.1
2-octyl-2H-isothiazol-3-one	26530-20-1	0.07
2-Methyl-2H-isothiazol-3-one	2682-20-4	0.006

Composition comments

All concentrations are in percent by weight unless otherwise indicated.

Components not listed are either non-hazardous or are below reportable limits.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions.

Rinse with water. Get medical attention if irritation develops and persists. Eye contact

Rinse mouth. Get medical attention if symptoms occur. Ingestion Most important May cause an allergic skin reaction. Dermatitis. Rash.

symptoms/effects, acute and delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

During fire, gases hazardous to health may be formed such as: Carbon oxides (COx).

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

General information

Specific hazards arising from

the chemical Special protective equipment

and precautions for firefighters

Move containers from fire area if you can do so without risk.

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Fire fighting equipment/instructions

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up This product is miscible in water. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

AcryliTop PC-100 - Gray SDS US

7. Handling and storage

Precautions for safe handling Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged

exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid

release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated S Components	Type	-1053) Value	
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.05 mg/m3	
US. OSHA Table Z-1 Limits for Air (Contaminants (29 CFR 1910.10	000)	
Components	Туре	Value	Form
Ammonium hydroxide (CAS 1336-21-6)	PEL	35 mg/m3	
		50 ppm	
Limestone (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFR 1910.			_
Components	Туре	Value	Form
Limestone (CAS 1317-65-3)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
,		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit Values	Typo	Value	Form
Components	Туре		10111
Ammonium hydroxide (CAS 1336-21-6)	STEL	35 ppm	
	TWA	25 ppm	
Diuron (CAS 330-54-1)	TWA	10 mg/m3	
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	2.5 mg/m3	Respirable finescale particles
		0.2 mg/m3	Respirable nanoscale particles
US. NIOSH: Pocket Guide to Chemi	ical Hazards		
Components	Туре	Value	Form
Ammonium hydroxide (CAS 1336-21-6)	STEL	27 mg/m3	
-,		35 ppm	
	TWA	18 mg/m3	
		25 ppm	
Diuron (CAS 330-54-1)	TWA	10 mg/m3	
Limestone (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
•		10 mg/m3	Total

AcryliTop PC-100 - Gray SDS US

US. NIOSH: Pocket Guide to Chemical Hazards
Components Type Value Form

Quartz (SiO2) (CAS TWA 0.05 mg/m3 Respirable dust.

14808-60-7)

US. Workplace Environmental Exposure Level (WEEL) Guides

ComponentsTypeValueFormPropane -1,2 -diol (CASTWA10 mg/m3Aerosol.57-55-6)

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Examples of preferred glove barrier materials include:

Nitrile. Suitable gloves can be recommended by the glove supplier.

Skin protection

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Liquid.

Form Viscous liquid.
Color Light gray.

Odor Mild ammonia.

Odor threshold Not available.
pH 8.8 (68 °F (20 °C))

Melting point/freezing point Not determined.

Initial boiling point and boiling Not determined.

range

Flash point > 199.4 °F (> 93 °C) Closed Cup

Evaporation rate Not determined.
Flammability (solid, gas) Not applicable.
Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not determined.

Explosive limit - upper (%) Not determined.

Vapor pressure Not determined.

Vapor density Not determined.

Relative density 1.4 (77 °F (25 °C))

Solubility(ies)

Solubility (water) Soluble.

Partition coefficient Not applicable, product is a mixture.

(n-octanol/water)

AcryliTop PC-100 - Gray SDS US

Not determined. **Auto-ignition temperature Decomposition temperature** Not determined.

Viscosity 115 ku (77 °F (25 °C)) Other information Solids content: 65%

Not determined. Density Not explosive. **Explosive properties** Kinematic viscosity Not determined. **Oxidizing properties** Not oxidizing. VOC

44.5 g/l 0.37 lb/gal

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

Conditions to avoid

reactions

No dangerous reaction known under conditions of normal use.

Incompatible materials Strong oxidizing agents. Fluorine.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation No adverse effects due to inhalation are expected. Inhalation of titanium dioxide dust may cause

cancer, however due to the physical form of the product, inhalation of dust is not likely. Crystalline

silica poses a health hazard when it is inhaled as a dust. Normal use of product does not

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

generate silica or other dust.

Skin contact May cause an allergic skin reaction.

Eye contact Direct contact with eyes may cause temporary irritation.

Expected to be a low ingestion hazard. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Test Results Components **Species**

2-octyl-2H-isothiazol-3-one (CAS 26530-20-1)

Acute

Dermal

ATE 311 mg/kg

Inhalation

Mist

ATE 0.27 mg/l

Oral

ATE 125 mg/kg

3-lodo-2-propynyl butylcarbamate (CAS 55406-53-6)

Acute

Dermal

Rabbit LD50 > 2000 mg/kg

Oral

LD50 Rat 1.1 g/kg

SDS US AcryliTop PC-100 - Gray

5/10

959153 Version #: 01 Issue date: 14-December-2022 Revision date: -

Components Species Test Results

Ammonium hydroxide (CAS 1336-21-6)

Acute Oral

LD50 Rat 350 mg/kg

Propane -1,2 -diol (CAS 57-55-6)

Acute Dermal

LD50 Rabbit 20800 mg/kg

Oral

LD50 Rat 22000 mg/kg

Quartz (SiO2) (CAS 14808-60-7)

Chronic Inhalation

LOEC Human 0.0563 mg/m3

Titanium Dioxide (CAS 13463-67-7)

Acute Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Due to the form of the product, exposure to the potentially carcinogenic components is not

expected. Titanium dioxide is considered carcinogenic only when in an inhalable powdered form. Crystalline silica poses a health hazard when it is inhaled as a dust. Normal use of product does

not generate silica or other dust.

IARC Monographs. Overall Evaluation of Carcinogenicity

Quartz (SiO2) (CAS 14808-60-7) 1 Carcinogenic to humans.

Titanium Dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

NTP Report on Carcinogens

Quartz (SiO2) (CAS 14808-60-7) Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz (SiO2) (CAS 14808-60-7)

Cancer

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components Species Test Results

2-octyl-2H-isothiazol-3-one (CAS 26530-20-1)

Aquatic

Acute

 Algae
 EC50
 Algae
 0.15 mg/l, 72 Hours

 Crustacea
 EC50
 Crustacea
 0.181 mg/l, 48 Hours

AcryliTop PC-100 - Gray SDS US

959153 Version #: 01 Revision date: - Issue date: 14-December-2022

Components		Species	Test Results		
Fish	LC50	Fish	0.122 mg/l, 96 Hours	_	
Chronic					
Algae	NOEC	Algae	0.068 mg/l, 72 Hours		
Crustacea	NOEC	Crustacea	0.035 mg/l, 21 days		
Fish	NOEC	Fish	0.022 mg/l, 21 days		
3-lodo-2-propynyl buty	3-lodo-2-propynyl butylcarbamate (CAS 55406-53-6)				
Aquatic					
Fish	LC50	Oncorhynchus mykiss	67 μg/l, 96 hours		
Titanium Dioxide (CAS 13463-67-7)					
Aquatic					
Acute					
Crustacea	EC50	Daphnia magna	> 100 mg/l, 48 Hours		

Persistence and degradability

Fish

No data is available on the degradability of this product.

Oryzias latipes

No data available for this product. Bioaccumulative potential

LL50

Partition coefficient n-octanol / water (log Kow)

Ammonium hydroxide (CAS 1336-21-6) -2.66 Diuron (CAS 330-54-1) 2.68 Propane -1,2 -diol (CAS 57-55-6) -0.92

Mobility in soil No data available. Other adverse effects No data available.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

> 100 mg/l, 96 Hours

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN3082

UN proper shipping name Environmentally hazardous substance, liquid, n.o.s. (Diuron RQ = 100000 LBS,

2-octyl-2H-isothiazol-3-one)

Transport hazard class(es)

Class 9 Subsidiary risk Label(s) 9 Packing group Ш **Environmental hazards**

> Yes. Marine pollutant

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions 8, 146, 173, 335, IB3, T4, TP1, TP29

Packaging exceptions 155 Packaging non bulk 203 Packaging bulk 241

AcryliTop PC-100 - Gray SDS US Non-bulk shipments may not be subject to DOT provisions as per 49CFR 171.4(c). Refer to regulation for specific requirements for this exception.

IATA

UN number UN3082

UN proper shipping name Environmentally hazardous substance, liquid, n.o.s. (Diuron, 2-octyl-2H-isothiazol-3-one)

Transport hazard class(es)

Class 9
Subsidiary risk Packing group III
Environmental hazards Yes.
ERG Code 9L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Non-bulk shipments may not be subject to IATA provisions as per special provision A147. Refer to IATA regulations for specific requirements for this exception.

IMDG

UN number UN3082

UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Diuron,

2-octyl-2H-isothiazol-3-one)

Transport hazard class(es)

Class 9
Subsidiary risk Packing group III
Environmental hazards

Marine pollutant Yes. EmS F-A, S-F

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Non-bulk shipments may not be subject to IMDG provisions as per special provision 375. Refer to IMDG regulations for specific requirements for this exception.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

2-Methyl-2H-isothiazol-3-one (CAS 2682-20-4) 1.0 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

Ammonium hydroxide (CAS 1336-21-6) Listed. Diuron (CAS 330-54-1) Listed.

SARA 304 Emergency release notification

Revision date: -

Ammonia; Ammonia (anhydrous) (CAS 1336-21-6) 100 LBS OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz (SiO2) (CAS 14808-60-7) Cancer lung effects

immune system effects

kidney effects

Toxic Substances Control Act (TSCA)

All components of the mixture on the TSCA 8(b) inventory are designated

"active".

AcryliTop PC-100 - Gray SDS US

Issue date: 14-December-2022

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)	
Ammonium hydroxide	1336-21-6	100	500			

Ammonium hydroxide

Yes

chemical

Classified hazard

SARA 311/312 Hazardous

Respiratory or skin sensitization

categories

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Ammonium hydroxide (CAS 1336-21-6)

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Ammonium hydroxide (CAS 1336-21-6)

Diuron (CAS 330-54-1)

Limestone (CAS 1317-65-3)

Quartz (SiO2) (CAS 14808-60-7)

Titanium Dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

3-lodo-2-propynyl butylcarbamate (CAS 55406-53-6)

Ammonium hydroxide (CAS 1336-21-6)

Diuron (CAS 330-54-1)

Limestone (CAS 1317-65-3)

Propane -1,2 -diol (CAS 57-55-6)

Quartz (SiO2) (CAS 14808-60-7)

Titanium Dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Ammonium hydroxide (CAS 1336-21-6)

Diuron (CAS 330-54-1)

Limestone (CAS 1317-65-3)

Propane -1,2 -diol (CAS 57-55-6)

Quartz (SiO2) (CAS 14808-60-7)

Titanium Dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Ammonium hydroxide (CAS 1336-21-6)

Diuron (CAS 330-54-1)

Limestone (CAS 1317-65-3)

Propane -1,2 -diol (CAS 57-55-6)

Quartz (SiO2) (CAS 14808-60-7)

Titanium Dioxide (CAS 13463-67-7)

California Proposition 65



WARNING: This product can expose you to chemicals including 1,4-Dioxane, Diuron, Ethylene oxide, Methyloxirane, which are known to the State of California to cause cancer, and Ethylene oxide, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,4-Dioxane (CAS 123-91-1) Diuron (CAS 330-54-1) Ethylene oxide (CAS 75-21-8) Methyloxirane (CAS 75-56-9)

Listed: January 1, 1988 Listed: May 31, 2002 Listed: July 1, 1987 Listed: October 1, 1988

AcryliTop PC-100 - Gray SDS US 9/10

959153 Version #: 01 Revision date: - Issue date: 14-December-2022

California Proposition 65 - CRT: Listed date/Developmental toxin

Ethylene oxide (CAS 75-21-8) Listed: August 7, 2009

California Proposition 65 - CRT: Listed date/Female reproductive toxin

Ethylene oxide (CAS 75-21-8) Listed: February 27, 1987

California Proposition 65 - CRT: Listed date/Male reproductive toxin

Ethylene oxide (CAS 75-21-8) Listed: August 7, 2009

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Ammonium hydroxide (CAS 1336-21-6) Quartz (SiO2) (CAS 14808-60-7) Titanium Dioxide (CAS 13463-67-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances	Yes

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI) No United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

16. Other information, including date of preparation or last revision

14-December-2022 Issue date

Revision date Version # 01

Health: 2 **HMIS®** ratings

Flammability: 0 Physical hazard: 0

Disclaimer Holcim Solutions and Products US, LLC cannot anticipate all conditions under which this

information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience

currently available.

SDS US

Issue date: 14-December-2022

Revision date: -

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).