

**1. Identification**

<b>Product identifier</b>	<b>Elevate Ceramic Coated Roofing Granules - Black</b>
<b>Other means of identification</b> Product code	W70RACGGBK
<b>Recommended use</b>	Only for professional use. Roofing.
<b>Recommended restrictions</b>	Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations. Uses other than the recommended use.

**Manufacturer/Importer/Supplier/Distributor information****Manufacturer**

<b>Distributed by</b>	Amrize Building Envelope LLC
<b>Address</b>	26 Century Boulevard, Suite 205 Nashville, TN 37214 Elevate is part of the Amrize family of brands. amrize.com Website: Elevatecommercialbp.com
<b>Telephone Number</b>	Sales: 1-800-428-4442 • Technical: 1-800-428-4511 • Français: 1-888-292-6265

**Emergency Telephone Number**

For Chemical Emergency, Spill, Leak, Fire, Exposure, or Incident:  
CHEMTREC within USA and Canada: 1-800-424-9300  
CHEMTREC outside USA and Canada: +1 703-527-3887 (collect calls accepted)

**2. Hazard(s) identification****Hazards for the product as sold**

**Physical hazards** Not classified.

**Hazards for the product as sold**

<b>Health hazards</b>	Carcinogenicity (inhalation)	Category 1A
	Specific target organ toxicity, repeated exposure (inhalation)	Category 2 (Lungs)

**Hazards for the product as sold**

**OSHA defined hazards** Not classified.

**Label elements**

<b>Signal word</b>	Danger
<b>Hazard statement</b>	May cause cancer by inhalation. May cause damage to organs (Lungs) through prolonged or repeated exposure by inhalation.
<b>Precautionary statement</b>	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Wear protective gloves/protective clothing/eye protection/face protection.
Response	IF exposed or concerned: Get medical advice/attention.
Storage	Store locked up.

<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Hazard(s) not otherwise classified (HNOC)</b>	No additional hazards are known to be associated with the expected conditions of use at the time of publication. This document does not address hazards that may arise from uses not reasonably anticipated by the manufacturer.
<b>Supplemental information</b>	None.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	CAS number	%
Quartz	14808-60-7	15 - 40
Mica	12001-26-2	10 - 30
Ceramic materials and wares, chemicals	66402-68-4	1 - 5
Dolomite	16389-88-1	1 - 5
Ilmenite	12168-52-4	1 - 5
Magnetite	1309-38-2	1 - 5
Carbon black	1333-86-4	0.1 - 1
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	0.1 - 1

**Composition comments** All concentrations are in percent by weight. Components not listed are either non-hazardous or are below reportable limits. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

### 4. First-aid measures

<b>Inhalation</b>	Move to fresh air. If not breathing, give artificial respiration. Call a physician if symptoms develop or persist.
<b>Skin contact</b>	Wash off with soap and water. Get medical attention if irritation develops and persists.
<b>Eye contact</b>	Rinse with water. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Rinse mouth. Get medical attention if symptoms occur.
<b>Most important symptoms/effects, acute and delayed</b>	Coughing. Prolonged exposure may cause chronic effects.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

**General information** IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	During fire, gases hazardous to health may be formed. Combustion products may include: Silicon oxides. Aluminum oxides. Potassium oxides.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Use water spray to cool unopened containers.
<b>General fire hazards</b>	No unusual fire or explosion hazards noted.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Do not breathe dust. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

### Methods and materials for containment and cleaning up

The product is immiscible with water and will spread on the water surface. Stop the flow of material, if this is without risk. Following product recovery, flush area with water. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS. The product is insoluble in water.

### Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

### Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

### Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### U.S. - OSHA

##### Components

Components	Type	Value	Form
Ilmenite (CAS 12168-52-4)	TWA	5 mg/m <sup>3</sup>	Respirable
		15 mg/m <sup>3</sup>	Total dust
Magnetite (CAS 1309-38-2)	TWA	5 mg/m <sup>3</sup>	Respirable
		15 mg/m <sup>3</sup>	Total dust

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

##### Components

Components	Type	Value
Quartz (CAS 14808-60-7)	TWA	0.05 mg/m <sup>3</sup>

#### US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

##### Components

Components	Type	Value	Form
Carbon black (CAS 1333-86-4)	PEL	3.5 mg/m <sup>3</sup>	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	PEL	5 mg/m <sup>3</sup>	Mist.
		2000 mg/m <sup>3</sup>	
		500 ppm	

#### US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)

##### Components

Components	Type	Value	Form
Dolomite (CAS 16389-88-1)	TWA	5 mg/m <sup>3</sup>	Respirable fraction.
		15 mg/m <sup>3</sup>	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Mica (CAS 12001-26-2)	TWA	20 mppcf	
Quartz (CAS 14808-60-7)	TWA	0.1 mg/m <sup>3</sup>	Respirable.
		2.4 mppcf	Respirable.

#### ACGIH

##### Components

Components	Type	Value	Form
Ilmenite (CAS 12168-52-4)	TWA	3 mg/m <sup>3</sup>	Respirable

**ACGIH**

Components	Type	Value	Form
Magnetite (CAS 1309-38-2)	TWA	10 mg/m <sup>3</sup>	Inhalable
		3 mg/m <sup>3</sup>	Respirable
		10 mg/m <sup>3</sup>	Inhalable

**US. ACGIH Threshold Limit Values (TLV)**

Components	Type	Value	Form
Carbon black (CAS 1333-86-4)	TWA	3 mg/m <sup>3</sup>	Inhalable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m <sup>3</sup>	Inhalable fraction.
Mica (CAS 12001-26-2)	TWA	0.1 mg/m <sup>3</sup>	Respirable fraction.
Quartz (CAS 14808-60-7)	TWA	0.025 mg/m <sup>3</sup>	Respirable fraction.

**NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended**

Components	Type	Value
Carbon black (CAS 1333-86-4)	IDLH	1750 mg/m <sup>3</sup>
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	IDLH	2500 mg/m <sup>3</sup>
Mica (CAS 12001-26-2)	IDLH	1500 mg/m <sup>3</sup>
Quartz (CAS 14808-60-7)	IDLH	50 mg/m <sup>3</sup>

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m <sup>3</sup>	
Mica (CAS 12001-26-2)	TWA	3 mg/m <sup>3</sup>	Respirable.
Quartz (CAS 14808-60-7)	TWA	0.05 mg/m <sup>3</sup>	Respirable dust.

**Biological limit values**

No biological exposure limits noted for the ingredient(s).

**Exposure guidelines**

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

**Appropriate engineering controls**

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

If contact is likely, safety glasses with side shields are recommended.

**Skin protection****Hand protection**

Wear appropriate chemical resistant gloves. Glove material: Nitrile. Use gloves with breakthrough time of 480 minutes. Minimum glove thickness 0.06 mm. Glove material: Polyvinyl acetate. Use gloves with breakthrough time of 240 minutes. Minimum glove thickness 0.07 mm. Glove material: Neoprene. Use gloves with breakthrough time of 240 minutes. Minimum glove thickness 0.12 mm. Glove material: Polyvinyl chloride. Use gloves with breakthrough time of 240 minutes. Minimum glove thickness 0.1 mm. Suitable gloves can be recommended by the glove supplier.

**Skin protection****Other**

Use of an impervious apron is recommended.

**Respiratory protection** If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Appropriate respirator selection should be made by a qualified professional. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations** Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

**Physical state** Solid.

**Form** Granules.

**Color** Black.

**Odor** Oily.

**Odor threshold** Property has not been measured.

**Melting point/freezing point** Technically not possible to determine.

**Boiling point or initial boiling point and boiling range** Technically not possible to determine.

**Flammability** Not flammable.

**Upper/lower flammability or explosive limits**

**Explosive limit - lower (%)** Not applicable, material is a solid.

**Explosive limit - upper (%)** Not applicable, material is a solid.

**Flash point** Not applicable, material is a solid.

**Auto-ignition temperature** Not applicable, material is a solid.

**Decomposition temperature** Property has not been measured.

**pH** Material is non soluble in water.

**pH concentration** Material is non-polar/aprotic.

**Kinematic viscosity** Not applicable, material is a solid.

**Solubility**

**Solubility (water)** Insoluble

**Partition coefficient (n-octanol/water)** Not applicable, product is a mixture.

**Vapor pressure** Property has not been measured.

**Vapor pressure temp.** Property has not been measured.

**Density and/or relative density**

**Density** 10 lb/gal (68 °F (20 °C))

**Relative density** 2.6 <2.9

**Relative density temperature** 68 °F (20 °C)

**Vapor density** Not applicable, material is a solid.

**Particle characteristics** Property has not been measured.

**Other information**

**Evaporation rate** Not applicable, material is a solid.

**Explosive properties** Not explosive.

**Oxidizing properties** Not oxidizing.

**Viscosity** Not applicable, material is a solid.

## 10. Stability and reactivity

**Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Contact with incompatible materials.
<b>Incompatible materials</b>	Powerful oxidizers. Chlorine.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known. In the event of fire: See Section 5.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause cancer by inhalation.
<b>Skin contact</b>	Prolonged skin contact may cause temporary irritation.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Ingestion</b>	May cause discomfort if swallowed.

**Symptoms related to the physical, chemical and toxicological characteristics** Coughing. Prolonged exposure may cause chronic effects.

### Information on toxicological effects

**Acute toxicity** Not expected to be acutely toxic.

Product	Species	Test Results
Elevate Ceramic Coated Roofing Granules - Black (CAS Mixture)		
<b>Acute</b>		
<b>Dermal</b>		
ATEmix		200000 mg/kg bw
<b>Components</b>		
<b>Species</b>		
<b>Test Results</b>		
Carbon black (CAS 1333-86-4)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 3000 mg/kg
<b>Oral</b>		
LD50	Rat	> 8000 mg/kg
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Inhalation</b>		
<i>Aerosol</i>		
LC50	Rat	> 5.53 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
Dolomite (CAS 16389-88-1)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rat	> 2000 mg/kg
<b>Inhalation</b>		
<i>dust/mist</i>		
LC50	Rat	> 3 mg/l, 4 hours
<b>Oral</b>		
LD50	Rat	> 2000 mg/kg

Components	Species	Test Results												
Quartz (CAS 14808-60-7)														
<b>Chronic Inhalation</b>														
LOEC	Human	0.0563 mg/m3												
<b>Skin corrosion/irritation</b>	Prolonged skin contact may cause temporary irritation.													
<b>Serious eye damage/eye irritation</b>	Direct contact with eyes may cause temporary irritation.													
<b>Respiratory or skin sensitization</b>														
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.													
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.													
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.													
<b>Carcinogenicity</b>	<p>In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer by inhalation. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled. Crystalline silica poses a health hazard when it is inhaled as a dust. Normal use of product does not generate silica or other dust. Inhalation of carbon black dust may cause cancer, however due to the physical form of the product, inhalation of dust is not likely.</p> <p><b>IARC Monographs. Overall Evaluation of Carcinogenicity</b></p> <table border="0"> <tr> <td>Carbon black (CAS 1333-86-4)</td> <td>2B Possibly carcinogenic to humans.</td> </tr> <tr> <td>Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)</td> <td>3 Not classifiable as to carcinogenicity to humans.</td> </tr> <tr> <td>Quartz (CAS 14808-60-7)</td> <td>1 Carcinogenic to humans.</td> </tr> </table> <p><b>NTP Report on Carcinogens</b></p> <table border="0"> <tr> <td>Carbon black (CAS 1333-86-4)</td> <td>Known To Be Human Carcinogen.</td> </tr> <tr> <td>Quartz (CAS 14808-60-7)</td> <td>Known To Be Human Carcinogen.</td> </tr> </table> <p><b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)</b></p> <table border="0"> <tr> <td>Quartz (CAS 14808-60-7)</td> <td>Cancer</td> </tr> </table>		Carbon black (CAS 1333-86-4)	2B Possibly carcinogenic to humans.	Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	3 Not classifiable as to carcinogenicity to humans.	Quartz (CAS 14808-60-7)	1 Carcinogenic to humans.	Carbon black (CAS 1333-86-4)	Known To Be Human Carcinogen.	Quartz (CAS 14808-60-7)	Known To Be Human Carcinogen.	Quartz (CAS 14808-60-7)	Cancer
Carbon black (CAS 1333-86-4)	2B Possibly carcinogenic to humans.													
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	3 Not classifiable as to carcinogenicity to humans.													
Quartz (CAS 14808-60-7)	1 Carcinogenic to humans.													
Carbon black (CAS 1333-86-4)	Known To Be Human Carcinogen.													
Quartz (CAS 14808-60-7)	Known To Be Human Carcinogen.													
Quartz (CAS 14808-60-7)	Cancer													
<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.													
<b>Specific target organ toxicity - single exposure</b>	Not classified.													
<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to organs (Lungs) through prolonged or repeated exposure by inhalation.													
<b>Aspiration hazard</b>	Not an aspiration hazard.													
<b>Chronic effects</b>	Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.													

## 12. Ecological information

<b>Ecotoxicity</b>	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
--------------------	--

Components	Species	Test Results
Carbon black (CAS 1333-86-4)		
<b>Aquatic</b>		
<i>Acute</i>		
Fish	LC50	Leuciscus idus
		>= 1000 mg/l, 96 Hours
Dolomite (CAS 16389-88-1)		
<b>Aquatic</b>		
<i>Acute</i>		
Crustacea	EC50	Daphnia magna
		> 16.6 mg/l, 48 hours
Fish	LC50	Oncorhynchus mykiss
		> 16.6 mg/l, 96 hours

<b>Persistence and degradability</b>	No data is available on the degradability of this product.
<b>Bioaccumulative potential</b>	No data available.
<b>Mobility in soil</b>	The product is insoluble in water. Not expected to be mobile in soil.
<b>Other adverse effects</b>	No data available.

### 13. Disposal considerations

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. Transport information

<b>DOT</b>	Not regulated as dangerous goods.
<b>IATA</b>	Not regulated as dangerous goods.
<b>IMDG</b>	Not regulated as dangerous goods.
<b>Transport in bulk according to IMO instruments</b>	Not applicable.

### 15. Regulatory information

<b>US federal regulations</b>	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
<b>TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)</b>	Not regulated.
<b>CERCLA Hazardous Substance List (40 CFR 302.4)</b>	Not listed.
<b>SARA 304 Emergency release notification</b>	Not regulated.
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)</b>	Quartz (CAS 14808-60-7)
	Cancer lung effects immune system effects kidney effects
<b>Toxic Substances Control Act (TSCA)</b>	One or more components of the mixture are not on the TSCA 8(b) inventory or are designated "inactive".

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

### SARA 302 Extremely hazardous substance

Not listed.

**SARA 311/312 Hazardous chemical** Yes

**Classified hazard categories** Carcinogenicity  
Specific target organ toxicity (single or repeated exposure)

### SARA 313 (TRI reporting)

Not regulated.

## Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

## US state regulations

### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Carbon black (CAS 1333-86-4)  
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  
Quartz (CAS 14808-60-7)

### US. Massachusetts RTK - Substance List

Carbon black (CAS 1333-86-4)  
Mica (CAS 12001-26-2)  
Quartz (CAS 14808-60-7)

### US. New Jersey Worker and Community Right-to-Know Act

Carbon black (CAS 1333-86-4)  
Mica (CAS 12001-26-2)  
Quartz (CAS 14808-60-7)

### US. Pennsylvania Worker and Community Right-to-Know Law

Carbon black (CAS 1333-86-4)  
Mica (CAS 12001-26-2)  
Quartz (CAS 14808-60-7)

### US. Rhode Island RTK

Carbon black (CAS 1333-86-4)  
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  
Dolomite (CAS 16389-88-1)  
Mica (CAS 12001-26-2)  
Quartz (CAS 14808-60-7)

### California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)  
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

**Issue date** 18-August-2025

**Revision date** -

**Version #** 01

**HMIS® ratings**  
Health: 2\*  
Flammability: 0  
Physical hazard: 0

**Disclaimer** Amrize Building Envelope LLC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.