

TECHNICAL INFORMATION SHEET

EcoWhite™ QuickSeam™ Joint Cover

Item Description

White: 5.75" ± 0.125" diameter (146 mm ± 3.17 mm)

Item Number

W56RACEWJC



Product Information

Description:

Firestone EcoWhite QuickSeam Joint Cover is an uncured, white EPDM flashing laminated to white QuickSeam Tape. A second 3" (76 mm) diameter layer of uncured, flowing tape is applied at the center. The EcoWhite EPDM QuickSeam Joint Cover conforms to irregular surfaces such as encountered at single-ply membrane "T" joints, readily providing an excellent seal.

EcoWhite QuickSeam Joint Covers are designed to cover and seal:

- T- Joints formed by field seam intersections.
- T- Joints formed by the installation of pre-fabricated pipe flashings over field or factory seams.
- As a protection pad under sheet metal joints for EdgeGard™ or snap-on metals.

Method of Application:

1. Clean the EcoWhite EPDM membrane to receive EcoWhite QuickSeam Joint Covers using Single-Ply QuickPrime™ Primer or Single-Ply QuickPrime™ LVOC Primer with a QuickScrubber™ or QuickScrubber Plus pad and handle to remove all dust, dirt and other contaminants that will affect the finished seam.
2. Allow to dry according to the touch-push test.
3. Additional cleaning may be required to ensure that the membrane is completely cleaned. (Caution: more cleaning is needed at factory seams.)
4. Remove the release paper from the joint cover, taking care not to touch the outside edges of the joint cover.
5. Fold the joint cover in half. Position the center of the joint cover over the target point and mate the joint cover to the prepared surface.
6. Roll the mated surface of the joint cover with a 2" (51 mm) silicone roller from the center outward working the joint cover into the step-off or irregularity.
7. Install Seam Edge Treatment per Firestone Specifications and Details.
8. Refer to application instructions for specifics: www.firestonebpco.com

Storage:

- Store in original unopened containers indoors at temperatures between 60 °F (16 °C) and 80 °F (27 °C).
- Do not store on roof in direct sunlight or at temperatures above 100 °F (38 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.

Shelf Life:

- Shelf life of six months can be expected when stored in original container at temperatures between 60 °F (16 °C) and 80 °F (27 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

TECHNICAL INFORMATION SHEET

EcoWhite™ QuickSeam™ Joint Cover

Precautions:

Refer to Safety Data Sheet (SDS) for additional information.

LEED® Information:

Post-Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: Prescott, AR

*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

Typical Properties

Property	Value
QuickSeam Tape:	
Base	Rubber Polymers
Color	White
Solvents	None
Solids	100%
Cured State:	
Splice Tape	Cured
Center Tape	Uncured and flowable
Thickness:	
Splice Tape	0.030" (0.77 mm) ± 0.005" (0.13 m)
Center Layer	0.037" (0.94 mm) ± 0.005" (0.13 mm)
EPDM Flashing:	
Material	Semi-cured flashing, conforming to ASTM 4811 minimum specifications
Color	White
Size	5.75" ± 0.125" diameter (146 mm ± 3.17 mm)
Thickness	0.060" ± 0.005" (1.5 mm ± .13 mm)

Packaging:

100 per carton, 60 cartons per pallet

Please contact Firestone Technical Services at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.