

# Technical Information Sheet



## ECOWHITE™ QUICKSEAM™ SPLICE TAPE

Item Description	Item Number
3" x 100' (76.2 mm x 30.48 m)	W56RAC160B
6" x 100' (152.4 mm 30.48 m)	W56RAC160E
<i>NOTE: 6" Shown in photo</i>	

### DESCRIPTION

Elevate EcoWhite EPDM 3" (76.2 mm) and 6" (152.4 mm) QuickSeam Splice Tape is designed for field splicing of EcoWhite EPDM membrane panels and flashing.

### METHOD OF APPLICATION

1. Use Single-Ply QuickPrime™ Primer or Single-Ply LVOC Primer with a QuickScrubber™ or QuickScrubber Plus pad and handle to clean and prime mating surfaces.
2. Refer to application instructions for specifics: Technical Database, [www.HolcimElevate.com](http://www.HolcimElevate.com)

### STORAGE

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 100 °F (37.7 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.

### SHELF LIFE

A shelf life of 24 months can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C). Shelf life will be shortened if exposed to elevated temperatures.

### PRECAUTIONS

Refer to Safety Data Sheets (SDS) for additional safety information.

### PACKAGING

Roll: 3" x 100' (76.2 mm x 30.48 m) roll, 4 rolls per carton; 6" x 100' (152.4 mm 30.48 m) roll, 2 rolls per carton

**NOTE:** QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.

## LEED® INFORMATION

Post-Consumer Recycled Content: 0%  
 Post Industrial Recycled Content: 0%  
 Manufacturing Location: Michigan Center, MI  
 NOTE: LEED® is a registered trademark of the U.S. Green Building Council



TYPICAL PROPERTIES	
Properties	Value
Base	Rubber Polymers
Color	White
Solvents	None
Solids	100%
Cured State	Cured
Thickness	0.030" (0.77 mm) ± 0.005" (0.127 mm)

Please contact Elevate Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Amrize takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Amrize nor its representatives practice architecture. Amrize offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Amrize accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Amrize representative is authorized to vary this disclaimer.