



The Sample Assembly Shown is generic. Consult the information in this Specification and refer to the Firestone on-line database for specific warranty requirements. Contact your Technical Coordinator at 800-428-4511 for additional information.

Refer to the Firestone Technical Database at www.firestonebpc.com for additional information

Deck Requirement

- Min. 22 gage Steel
- Min. 3000 psi Concrete

Slope Requirement

A minimum slope of 1/4":12" must be provided to ensure positive drainage.

Insulation (Optional)

Firestone ISO 95+GL

Insulation Attachment

- Firestone concrete drive fasteners & plates
- Approved hot asphalt
- Firestone ISO TwinPack™
- Firestone ISO Spray™
- Firestone ISO FIX™
- Firestone ISO Stick™

A pull test required on deck if the following are used to attach Insulation to deck:

- I.S.O. FIX™ Adhesive
- I.S.O.Spray™ S
- I.S.O. Twin Pack™
- I.S.O. Stick™

Cover Board (Optional)

- Firestone IsoGard HD⁽¹⁾
- Firestone Dens-Deck Prime⁽³⁾

Surfacing

- SBS Granule Surfaced Cap Sheet
- SBS Granule Surfaced Cap Sheet coated with Acrylic Base Coat for Asphalt and AcryliTop PC-100

Mopping asphalt temperature must not exceed 450 °F when mopping to DensDeck Prime. Use only ASTM D 312 Type III asphalt.

20 YEAR WARRANTY REQUIREMENTS		
ONE FULLY Adhered SBS GRANULE SURFACED CAP SHEET	PLUS ONE MECHANICALLY ATTACHED SBS BASE	FLASHING REQUIREMENTS
<input type="checkbox"/> SBS Premium FR <input type="checkbox"/> SBS Premium <input type="checkbox"/> SBS Torch FR	<input type="checkbox"/> SBS Poly Base <input type="checkbox"/> SBS Premium Base	20 year Red Shield warranties require a minimum of one fully adhered layer of SBS Base Sheet and one fully adhered layer of SBS cap sheet equal to or better than the field sheet in use to be used for flashing.

Notes:

1. Do not use hot asphalt to install or adhere to ISOGARD HD.
2. A pull test required on deck if the following are used to attach Insulation to deck: I.S.O. FIX™ Adhesive, I.S.O.Spray™ S, I.S.O. Twin Pack™ or I.S.O. Stick™
3. **Mopping asphalt temperature must not exceed 450 °F when mopping to DensDeck Prime. Use only ASTM D 312 Type III asphalt.**

Products not supplied by Firestone are not covered under the Firestone Warranty