

Polyiso Insulation				
All Firestone Polyiso insulations have a polyisocyanurate foam core. The standard compressive strength is 20 psi, but 25 psi is also available, upon request. Different facers are used to make specific products, as described below:				
Product Name	Top Side		Bottom Side	
ISO 95+	Black Glass Reinforced Mat		Black Glass Reinforced Mat	
HailGard	7/16" Oriented Strand Board		Black Glass Reinforced Mat	
ISO 95+ Woodfiber Composite	1/2" Wood Fiber		Black Glass Reinforced Mat	
Insulation Thickness	Pieces Per Bundle	Square Feet Per Bundle 4x8	Square Feet Per Bundle 4x4	Square Feet Per Truckload
1.00	48	1,536	768	36,864
1.25	38	1,216	608	29,184
1.50	32	1,024	512	24,576
1.75	27	864	432	20,376
2.00	24	768	384	18,432
2.30	20	640	320	15,360
2.50	19	608	304	14,592
2.80	17	544	272	13,056
3.00	16	512	256	12,288
3.25	14	448	224	10,752
3.50	13	416	208	9,984
3.75	12	384	192	9,216
4.00	12	384	192	9,216
Tapered Polyiso Insulation				
Panel Code	Pieces Per Bundle	Square Feet Per Bundle 4x4	Slope	Min - Max Thickness
AA	64	1,024	1/8" Slope	0.5"-1.0"
A	38	608	1/8" Slope	1.0"-1.5"
B	26	416	1/8" Slope	1.5"-2.0"
C	20	320	1/8" Slope	2.0"-2.5"
G	32	512	1/4" Slope	1.0"-2.0"
H	18	288	1/4" Slope	2.0"-3.0"
X	48	768	1/4" Slope	0.5"-1.5"
Y	24	384	1/4" Slope	1.5"-2.5"
Q	32	512	1/2" Slope	0.5"-2.5"

Note: The most commonly used tapered panels are listed here. Firestone Tapered ISO 95+ is available in 1/2", 1/4", 1/8" 1/16" and 3/16" slopes per foot and in 4'x 8' panels. For more information, tapered system quotes or design assistance, please contact your Firestone sales representative or the Firestone Tapered Department.

Firestone Plant Locations: Colorado, Connecticut, Florida, Kentucky, Pennsylvania, Texas, Wisconsin, and Utah.

ISOGARD HD				
Thickness	Item Code	Pieces Per Bundle	Bundles Per Truckload	Square Feet Per Truckload
1/2" - 4' x 4'	W8H-3GG-0504	96	48	73,728
1/2" - 4' x 8'	W8H-3GG-0508	96	24	73,728
1/2" - 4' x 4' Double Bundle	W8H-3GG-050D	96	24	73,728

Note: Stopover fee of \$100.00 charged for a second delivery destination located within 50 miles of the first delivery point.

RESISTA™ POLYISO INSULATION

Resista is a closed cell polyisocyanurate foam core, bonded chemically to a heavy duty, dimensionally stable, inorganic glass facer. The standard compressive strength is 20 psi.

Product Name	Top Side		Bottom Side	
RESISTA	Inorganic Double Coated Glass Mat		Inorganic Double Coated Glass Mat	
Insulation Thickness	Pieces Per Bundle	Square Feet Per Bundle 4x8	Square Feet Per Bundle 4x4	Square Feet Per Truckload
1.00*	48	1,536	768	36,864
1.25	38	1,216	608	29,184
1.50*	32	1,024	512	24,576
1.75	27	864	432	20,376
2.00*	24	768	384	18,432
2.30	20	640	320	15,360
2.50*	19	608	304	14,592
2.80	17	544	272	13,056
3.00*	16	512	256	12,288
3.25	14	448	224	10,752
3.50	13	416	208	9,984
3.75	12	384	192	9,216
4.00	12	384	192	9,216

*Note: 1.0", 1.5", 2.0", 2.5", and 3.0" do not have a minimum bundle requirement.
 For all other thicknesses a minimum 20 bundle order is required.

RESISTA Tapered Polyiso Insulation

Panel Code	Pieces Per Bundle	Square Feet Per Bundle 4x4	Slope	Min - Max Thickness
AA*	64	1,024	1/8" Slope	0.5"-1.0"
A*	38	608	1/8" Slope	1.0"-1.5"
B	26	416	1/8" Slope	1.5"-2.0"
C	20	320	1/8" Slope	2.0"-2.5"
G	32	512	1/4" Slope	1.0"-2.0"
H	18	288	1/4" Slope	2.0"-3.0"
X*	48	768	1/4" Slope	0.5"-1.5"
Y*	24	384	1/4" Slope	1.5"-2.5"
Q*	32	512	1/2" Slope	0.5"-2.5"

*Note: The Tapered AA, A, X, Y, and Q panels do not have a minimum bundle requirement.
 For all other thicknesses a minimum 20 bundle order is required.

Note: For more information, tapered system quotes or design assistance, please contact your Firestone sales representative or the Firestone Tapered Department.

Firestone Plant Locations: Kentucky, Pennsylvania, and Utah.

Lead Time: A 7-10 lead time can be expected

Dens-Deck				
Thickness	Item Code	Pieces Per Bundle	Bundles Per Truckload	Square Feet Per Truckload
	W56RAC...			
1/4" - 4' x 8'	8625	42	28 - 29	37,632 - 38,976
1/2" - 4' x 8'	8650	30	24 - 25	23,040 - 24,000
5/8" - 4' x 8'	8662	30	18 - 19	17,280 - 18,240
Dens-Deck Prime				
Panel Code	Item Code	Pieces Per Bundle	Bundles Per Truckload	Square Feet Per Truckload
	W56RAC...			
1/4" - 4' x 4'	8724	60	40	38,400
1/4" - 4' x 8'	8725	42	28 - 29	37,632 - 38,976
1/2" - 4' x 4'	8754	50	28	22,400
1/2" - 4' x 8'	8750	30	24 - 25	23,040 - 24,000
5/8" - 4' x 4'	8764	40	28	17,920
5/8" - 4' x 8'	8762	30	18 - 19	17,280 - 18,240
Dens-Deck DuraGuard				
Panel Code	Item Code	Pieces Per Bundle	Bundles Per Truckload	Square Feet Per Truckload
	W56RAC...			
1/4" - 4' x 4'	8824	60	40	38,400
1/4" - 4' x 8'	8825	42	28 - 29	37,632 - 38,976
1/2" - 4' x 4'	8854	50	28	22,400
1/2" - 4' x 8'	8850	30	24 - 25	23,040 - 24,000
5/8" - 4' x 4'	8864	40	28	17,920
5/8" - 4' x 8'	8862	30	18 - 19	17,280 - 18,240

*1/4" Dens-Deck is available in select ISO plants and may be combined with ISO 95+ orders.

Note: Stopover fee of \$100.00 charged for a second delivery destination located within 50 miles of the first delivery point.

Firestone Wood Fiber Roof Insulation							
Product	Item Code	Size	Pieces Per Bundle	Square Feet Per Bundle	Weight Per Bundle	Bundles Per Truck	Square Feet Per Truckload
	W56358...						
1/2" FiberTop "E" (Jarret, VA)	8501	4' x 4'	95	1,520	973	44	66,880
	8502	4' x 8'	95	3,040	1,946	22	66,880
1" FiberTop "E" (Jarret, VA)	8504	4' x 4'	48	768	907	44	33,792
	8505	4' x 8'	48	1,536	1,813	22	33,792
1/2" FiberTop "B" (Intl' Falls, MN)	8501	4' x 4'	90	1,440	1,140	44	63,360
	8502	4' x 8'	90	2,880	2,300	22	63,360
1" FiberTop "B" (Intl' Falls, MN)	8504	4' x 4'	45	720	1,120	44	45,760
	8505	4' x 8'	45	1,440	2,080	22	45,760
<p>Availability: Firestone FiberTop is manufactured in a number of strategically located facilities in order to provide prompt and efficient delivery throughout the United States.</p> <p>Poly Bagging: All truckloads of FiberTop are shipped without poly bagging. Poly bags are available upon request for an additional charge.</p>							
Wood Fiber Freight Terms							
<ul style="list-style-type: none"> - Freight allowed on truckload shipments of 1/2" and 1" wood fiber roof insulation for full truckloads only. - For an additional charge, 1/2" 4' x 8' wood fiber roof insulation is inventoried in some Firestone insulation plants and may be combined with ISO 95+ for prepaid shipments. - 1" wood fiber roof insulation is not inventoried at any Firestone location and is only shipped in full truckload quantities. 							