



1. Firestone RubberGard™ EPDM Membrane
2. Fully Adhered with Bonding Adhesive
3. Mechanically Attached or Adhered Cover Board (Optional)
4. Mechanically Attached or Adhered Insulation
5. Wood Deck

Consult Firestone Technical Specifications, Guides and Details at [www.firestonebpco.com](http://www.firestonebpco.com)

**Slope Requirement**

Positive slope required for warranty.<sup>5</sup>

**Construction Type**

New construction, complete tear-off, or recover with any wet or damaged materials removed prior to installation.

**Building Height Limitation**

Firestone RubberGard™ EPDM Adhered Systems are limited to buildings 250' (76.2 m) or less.

**Use of Air Barrier**

An air barrier is recommended for projects with large wall openings greater than 10% of the total wall area.

**Base Tie-Ins**

Must be attached to substrates which provide a minimum of 200 lbf (1 kN) in any direction.

**Increased Wind Speed and Codes**

Any wind speed coverage exceeding 55 mph (88 km/h) or projects with codes requirements must be reviewed by a Firestone Roof Systems Advisor.

**Deck Requirement**

- Minimum ½" Plywood
- Minimum 7/16" OSB

**Fastener Type**

- Firestone All Purpose Fastener
- Firestone Heavy Duty Fastener
- Firestone HailGard™ Fastener (with HailGard Composite Board or OSB only)

**Insulation Adhesive\***

- Firestone I.S.O. Twin Pack™ Insulation Adhesive
- Firestone I.S.O. Spray™ S Insulation Adhesive
- Firestone I.S.O. Fix™ II Insulation Adhesive
- Firestone I.S.O. Stick™ Insulation Adhesive

\*Note: Max. 4' x 4' boards must be used when attaching insulation with adhesives.

**Adhesive Attachment**

**Max. 15 Year Warranty:**

- Bead Spacing: F: 12", P: 12", C: 12"

**20 Year Warranty:**

- Bead Spacing: F: 12", P: 6", C: 4"
- Full Application (I.S.O. Spray S Insulation Adhesive)

**Membrane Requirement**

**Max. 15 Year Warranty:**

- RubberGard EPDM, Any Thickness
- RubberGard MAX EPDM, Any Thickness

**20 Year Warranty:**

- RubberGard EPDM, Minimum 0.060"
- RubberGard MAX EPDM, Any Thickness

**Seaming Requirement**

QuickSeam™ Splice Tape in side and end laps. QuickSeam Joint Covers are required at all joints and at angle changes 1:12 or greater.

**Firestone Membrane Adhesive**

- EPDM Bonding Adhesive BA-2004 (T)
- Single-Ply LVOC Bonding Adhesive
- Single-Ply LVOC Bonding Adhesive 1168
- Water Based Bonding Adhesive (P) (Max. 15 Year Warranty)
- Solvent Free Bonding Adhesive (Max. 20 Year Warranty on .060 and .090 mil)

**Edge Metal System**

- Firestone EdgeGard™ System
- Firestone AnchorGard™ System
- Firestone Coping System
- Firestone Termination Bar
- Firestone Aluminum Drain Bar

**Insulation Fastener and Insulation Plate Attachment Rates – Field Rates for Standard 55 mph Wind Speed**

Insulation (Top Layer)	4' x 8'	Coverboard (Optional)	4' x 8'
1.0" to 1.4" Firestone ISO 95+™ GL or RESISTA™ Insulation	16	½" or 1.0" FiberTop Wood Fiber Board (Max. 15 Year Warranty)	16
1.5" to 1.9" Firestone ISO 95+ GL or RESISTA Insulation	12	Firestone ISOGARD™ HD Cover Board	12
2.0" to 4.0" Firestone ISO 95+ GL or RESISTA Insulation	8	¼" SECUROCK® Gypsum-Fiber or DensDeck® / (Prime)	16 16/(12)
Firestone HailGard™ Composite Board	16	½" SECUROCK Gypsum-Fiber or DensDeck / (Prime)	12 12/(10)
Firestone ISOGARD™ HD Composite Board	8	5/8" SECUROCK Gypsum-Fiber or DensDeck / (Prime)	8 8/(8)

**Detail Description**

<b>Wall Terminations:</b>	Firestone Termination Bar with AP Sealant applied along the caulk lip. Surface mounted or inserted counter flashing may also be used in accordance with current Firestone details.
<b>Curb &amp; Wall Flashings:</b>	Curbs, walls, and expansion joints must be anchored with appropriate base tie-in detail, using QuickSeam Reinforced Perimeter Fastening Strip (RPF) and Batten Strip or 2" Metal Seam Plates. Curbs and walls must be flashed using one ply minimum 0.045" RubberGard EPDM, QuickSeam Curb Flashing, or 18" QuickSeam SA Flashing.
<b>Corners:</b>	QuickSeam Corner Flashing or 9" QuickSeam FormFlash™ Flashing may be used.
<b>Roof Edges/Parapets:</b>	Firestone AnchorGard™ or EdgeGard™ Fascia or Drain Bar systems. ANSI/SPRI ES-1 rated edge metal may also be used.
<b>Penetrations:</b>	Flash with QuickSeam Pipe Flashing, QuickSeam EPDM Penetration Pocket, or field fabricate with EPDM flashing.

**Notes:**

1. Only Firestone brand products are covered in a Red Shield warranty.
2. Refer to the Firestone Technical Database at [www.firestonebpco.com](http://www.firestonebpco.com) for additional information regarding RubberGard EPDM Roof Systems.
3. Refer to the Firestone RoofGenuity™ tool to create roof assemblies with high-performance Firestone products at [www.RoofGenuity.com](http://www.RoofGenuity.com).
4. DensDeck is a registered trademark of Georgia-Pacific Gypsum LLC.
5. It is the installing contractor's responsibility to follow applicable building codes.
6. SECUROCK is a registered trademark of USG Corporation.