

# Firestone Metal Products Company

## Material Safety Data Sheet

March 16, 2009

Page: 1

### SECTION 1: PRODUCT IDENTIFICATION

Product Name: Metal Roofing Products: UC-1, 2, 3, 4, 5, 6, 7, 8, 9, 11, 14, 600, 601, 700; UR, HR, VR, 5VC, Flat Lock, ES-1, 2, 3, 4; sheet and coil stock, UNA-Edge DE, GS, CO; Brake metal

Chemical Name / Synonym: Wrought Aluminum Products, 3xxx series alloys

Chemical Family: None

24-Hour Emergency Phone: (800) 424-9300 CHEMTREC

Manufacturer's Name: Firestone Metal Products Company

Manufacturer's Address: 250 West 96<sup>th</sup> Street, Indianapolis, IN 46260

NFPA Hazard Rating: Health 1, Flammability 0, Reactivity 0

HMIS Hazard Rating: Health 0, Flammability 0, Reactivity 0

### SECTION 2: CHEMICAL COMPOSITION

| Chemical Name: | Common Name:    | CAS #:    | % (by wt) | Exposure Limits:   |
|----------------|-----------------|-----------|-----------|--|
| Aluminum       | Aluminum Metal  | 7429-90-5 | >92       | 10 mg/m <sup>3</sup> (total) TLV<br>5 mg/m <sup>3</sup> (respirable) PEL<br>15 mg/m <sup>3</sup> (total) PEL   |
| Magnesium      | Magnesium Metal | 7439-95-4 | <2.8      | 10 mg/m <sup>3</sup> (inhalable) TLV – (MgO)<br>15 mg/m <sup>3</sup> (total) PEL (MgO)   |
| Manganese      | Manganese       | 7439-96-5 | <2        | 0.2 mg/m <sup>3</sup> TLV<br>5 mg/m <sup>3</sup> PEL - Ceiling   |
| Silicon        | Silicon         | 7440-21-3 | <1.9      | 5 mg/m <sup>3</sup> (respirable) PEL<br>15 mg/m <sup>3</sup> (total) PEL   |
| Zinc           | Zinc            | 7440-66-6 | <2.3      | 2 mg/m <sup>3</sup> (respirable) TLV (ZnO)<br>10 mg/m <sup>3</sup> (respirable) TLV – STEL (ZnO)<br>5 mg/m <sup>3</sup> (respirable) PEL (ZnO)<br>15 mg/m <sup>3</sup> (total) PEL (ZnO) |
| Chromium       | None            | 7440-47-3 | <0.6      | 0.5 mg/m <sup>3</sup> TLV  |

**Note: The following weight percentage applies only to a Regal Red paint finish on coated portion of a finished product:**

|                                 |      |            |       |   |
|---------------------------------|------|------------|-------|---|
| Lead Chromate Molybdate Pigment | None | 12656-85-8 | 10-15 | 0.05 mg/m <sup>3</sup> (as Pb) TLV<br>0.012 mg/m <sup>3</sup> (as Cr) TLV |
|---------------------------------|------|------------|-------|---|

# Firestone Metal Products Company

## Material Safety Data Sheet

March 16, 2009

Page: 2

---

### SECTION 3: HAZARD IDENTIFICATION

---

|  |  |
|--|--|
| Primary Route of Exposure:                 | Skin; inhalation if cutting, grinding or welding occurs.   |
| Signs and Symptoms of Exposure:            | <p>General handling of metal products typically do not present a health hazard. Sharp metal edges may cause skin cuts.</p> <p>Upon welding, cutting, or welding on materials the following signs and symptoms of exposure:</p> <p>Dusts and fumes generated during welding, cutting or welding activities can cause irritation to the eyes, respiratory tract and mucous membranes. Accumulation of zinc oxide dust can cause skin eruptions, typically in warm and moist areas of the body. Inhalation of the zinc oxide fume and magnesium oxide fume (and some other metals found in this compound in very low concentrations) can cause metal fume fever, symptoms including muscular pain, chills, nausea and vomiting. Symptoms typically last for 24-48 hours, and are not life-threatening nor cause any permanent damage.</p> <p>Upon welding, cutting, or welding on materials that have been painted regal red, in addition to effects noted in above paragraph, the following are signs and symptoms of exposure to lead chromate:</p> <p>Dizziness, headache, nausea and/or respiratory irritation may be associated with inhalation of lead chromate fume.</p> |
| Medical Conditions Aggravated by Exposure: | <p>As a fume or dust, chronic respiratory disorders, including (but not limited to) asthma, chronic bronchitis and emphysema. Among people with chronic kidney disease; neurological, neuromuscular and cardiovascular ailments can be enhanced/aggravated due to retained magnesium.</p>  |
| Chronic Effects:                           | <p>No chronic effects are expected due to general handling of metal products.</p> <p>Upon heating of this material (e.g., welding, cutting, or welding), the following chronic effects may occur:</p> <p>The repeated inhalation of large amounts of manganese dust and fume can cause fibrotic changes in the lung, including some resembling those of silicosis. Additionally, repeated exposures to large amounts of manganese can lead to central nervous system (CNS) effects.</p> <p>If painted regal red, may cause central nervous system depression.</p>  |
| Carcinogenicity:                           | <p>Applies to metal painted regal red only: contains lead chromate, which is an IARC class 1 carcinogen, <i>carcinogenic to humans</i>, and an NTP <i>known to be a human carcinogen</i>.</p>  |

---

### SECTION 4: FIRST AID MEASURES

---

|                       |  |
|-----------------------|--|
| First Aid Procedures: | Treat skin cuts via washing wound with soap and clean water, and apply antibiotic. |
|-----------------------|--|

# Firestone Metal Products Company

## Material Safety Data Sheet

March 16, 2009

Page: 3

If particles from this material contact the eyes, hold eyelids open and flush immediately with a gentle stream of water for at least 15 minutes, preferably at an eyewash fountain. If particles become imbedded, or irritation continues, get medical attention. Following skin contact, clean immediately by washing affected area with soap and water. In case of inhalation of fumes or dusts, remove to fresh uncontaminated air. Administer oxygen if breathing is labored. Give artificial respiration if breathing has stopped. Get medical attention immediately if oxygen or artificial respiration are administered. While an unlikely means of exposure, in case of accidental ingestion, do not induce vomiting. Get medical attention and advise the physician of the nature of the material.

---

### SECTION 5: FIRE FIGHTING PROCEDURES

---

|                                       |  |
|---------------------------------------|--|
| Suitable Extinguishing Media:         | Not applicable. Material will not burn unless involved in an intense fire supported by surrounding materials. In this case, extinguish using suitable media for surrounding materials. |
| Hazardous Combustion Products:        | Various metal oxides and carbon oxides.  |
| Recommended Fire Fighting Procedures: | No special procedures recommended for solid material. Do not permit water to come in contact with molten metal.  |
| Unusual Fire and Explosion Hazards:   | None for solid material. Small chips, dust or other fines may be readily ignitable, generating considerable heat. Molten metal will splatter when it comes in contact with water.      |

---

### SECTION 6: PRECAUTIONS FOR SAFE HANDLING AND USE

---

|  |  |
|--|--|
| Steps to Be Taken in Case Material is Released or Spilled: | Not Applicable for solid material. When cleaning up fine dusts, avoid creating airborne dust. Use non-sparking tools, and avoid water. |
| Precautions to Be Taken in Handling and Storing:           | Keep dry.  |

---

### SECTION 7: EXPOSURE CONTROLS / PERSONAL PROTECTION

---

|                         |  |
|-------------------------|--|
| Ventilation:            | Activities involving the generation of high amounts of fine dusts and/or fumes should be evaluated to determine if additional local exhaust is necessary. If a local exhaust system is used, explosion-proof equipment may be warranted.   |
| Respiratory Protection: | Activities involving the generation of high amounts of fine dusts and/or fumes should be evaluated to determine if a NIOSH approved air purifying respirator may be appropriate based on employer-determined exposure levels. Air supplied or SCBA respirators may be required when the measured chemical concentration exceeds the capacity of the air purifying respirator or when personal exposure levels are unknown. |
| Eye Protection:         | Safety glasses with side shields may be warranted when cutting or grinding on this product. Employer-determined protective eye ware for welding, torching or other hot-work activities is  |

# Firestone Metal Products Company

## Material Safety Data Sheet

March 16, 2009

Page: 4

required.

Skin Protection: Cut-resistant gloves may be warranted while handling solid material. Welding or other hot-work gloves may be warranted when carrying out welding, cutting or other hot-work activities involving this material.

Other: Other protective clothing may be warranted depending upon the activities involving this material. The employer must make this determination.

Work / Hygienic Practices: Wash exposed skin prior to eating, drinking or smoking and at the end of each shift.

### SECTION 8: PHYSICAL AND CHEMICAL PROPERTIES

|                         |  |                        |                |
|-------------------------|--|------------------------|----------------|
| Appearance and Odor:    | Solid metallic gray or red-painted metal with no odor. |                        |                |
| Flash Point:            | Not Applicable   | Lower Explosive Limit: | Not Applicable |
| Method Used:            | Not Applicable   | Upper Explosive Limit: | Not Applicable |
| Evaporation Rate:       | Not Applicable   | Boiling Point:         | Not Applicable |
| pH (undiluted product): | Not Applicable   | Melting Point:         | 1150-1220 °F   |
| Solubility in Water:    | Insoluble  | Specific Gravity:      | Unknown        |
| Vapor Density:          | Not Applicable   | Percent Volatile:      | Not Applicable |
| Vapor Pressure:         | Not Applicable   |                        |                |

### SECTION 9: STABILITY AND REACTIVITY

|                           |  |
|---------------------------|--|
| Thermal Stability:        | Stable   |
| Hazardous Polymerization: | Will not occur   |
| Conditions to Avoid:      | None when material is in solid form. When dusts, chips or other fines are present, avoid water, strong oxidizers, acids, alkalis, and halogenated compounds. |

### SECTION 10: TRANSPORTATION

|                        |                |
|------------------------|----------------|
| Regulatory Agency:     | Not Regulated  |
| Proper Shipping Name:  | Not Applicable |
| Hazard Classification: | Not Applicable |
| Identification Number: | Not Applicable |
| Labels Required:       | Not Applicable |
| Other Requirements:    | Not Applicable |

Firestone Metal Products Company  
Material Safety Data Sheet

March 16, 2009

Page: 5

---

SECTION 11: MISCELLANEOUS INFORMATION

---

|  |                     |
|--|---------------------|
| Additional Comments:                         | None.               |
| Date of Previous MSDS:                       | February 20, 2008   |
| Changes Since Previous MSDS:                 | Company name change |
| Telephone Number for Additional Information: | (317) 575-7190      |

---

DISCLAIMER

---

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information, is accurate, complete or representative. Firestone Metal Products Company, a subsidiary of Firestone Diversified Products, LLC, assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons, if reasonable safety procedures are not followed. Additionally, Firestone Metal Products Company assumes no responsibility for injury to buyer, the buyer's employees, or any third persons caused by abnormal use of this material, even if reasonable safety procedures are followed.