

# **Technical Information Sheet**



# **HD Plus Seam Plate**

Item Description Pail: 500 Pieces Item Number W56TPOPL02

# Description

The HD Plus Seam Plate is specifically designed to be used for the attachment of Firestone thermoplastic membranes to approved substrates. Elevate HD Plus Seam Plates are suitable for use with Elevate HD Plus Fasteners into 22-gauge steel decking.

# Method of Application

- 1. HD Plus Seam Plates are positioned within the seam area as specified by current Elevate specifications with the Elevate logo facing up and the Eyehooks™ against the membrane.
- 2. Attach the plate through the roof membrane and into the deck substrate with Elevate HD Plus Fasteners.

### Storage

Store in unopened original containers protected for the weather.

#### Precautions

- Do not overdrive or underdrive fastener.
- For use with Heavy Duty Plus Fasteners only.
- Avoid installing HD Seam Plates / field seams directly over insulation plates.

## **LEED®** Information

| Post-Consumer Recycled Content:   | 0%         |
|-----------------------------------|------------|
| Post Industrial Recycled Content: | 21%        |
| Manufacturing Location:           | ltasca, IL |

APPROVED

#### NOTE: LEED® is a registered trademark of the U.S. Green Building Council

September 29, 2022





| Product Packaging      |                   |  |
|------------------------|-------------------|--|
| Weather Resistant Pail | 500 pieces        |  |
| Weight of Pail         | 33 lb (14 kg) per |  |
|                        |                   |  |

| Typical Properties      |  |  |
|-------------------------|--|--|
| Properties              | Typical Performance                              |  |
| Material                | Galvalume® Sheet Steel AZ50 or AZ55              |  |
| Material Thickness      | 0.037" (0.94 mm)                                 |  |
| Size                    | 2 3/4″ (69.8 mm) diameter                        |  |
| Hole Diameter           | 0.335" ±.005" (8.5 mm ± 0.127 mm)                |  |
| Pull-Through Resistance | 900 lb (408.2 kg) from center hole               |  |
| Corrosion Resistance    | Meets FM requirement – less than 15% red rust in |  |
|                         | 15 cycles of Kesternich testing (DIN 50018)      |  |

 $^{*}\mbox{Galvalume}\mbox{$\mathbb{R}$}$  is a registered trademark of BIEC International, Inc.

\*\*Eyehook™ is a trademark of OMG.

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.

September 29, 2022

