

Technical Information Sheet



LWC Base-Ply Fastener (Lightweight Concrete)

Size	Item Number
1.2"	W56RAC4256
1.7"	W56RAC4257

Description

The LWC Base-Ply Fastener is specifically designed to be used in all Elevate asphalt roof systems to attach base sheets to lightweight insulating or cellular concrete decks or gypsum roof decks. It is suitable for use with all Elevate base sheets.

Method of Application

1. Lightweight concrete must be a minimum of 2" (51 mm) thick, dry, and have reached full compressive strength.
2. This fastener is not suitable for applications where the hardness of the deck causes the fastener's leg to distort.
3. Do not overdrive.
4. The LWC Base-Ply Fastener should be installed using a stand-up magnetic driver or standard 2 lb (0.9 kg) mallet.

Storage

Store in original, unopened packaging protected from the weather.

Precautions

Eye protection must be worn during the installation of the fasteners.

LEED® Information

Post-Consumer Recycled Content: 0%
 Pre-Consumer Recycled Content: 30%
 Manufacturing Location: Bristol, RI



NOTE: LEED® is a registered trademark of the U.S. Green Building Council

Product Packaging

Screw Length	Pieces Per Carton	Carton Per Pallet
1.2" (30.5 mm)	1,000	35
1.7" (43.2 mm)	1,000	39

Typical Properties

Property: Metal Plate	Value
Material	Galvalume® Sheet Steel
Thickness	0.013" (.33 mm)
Corrosion Resistance	Meets FM No. 4470 Criteria
Property: Fastener	Value
Material	G-90 Steel Black Urethane Coated
Fastener Head	1.2" (30.48 mm) Diameter
Fastener Lengths	1.2" (30.48 mm); 1.7" (43.18 mm)
Corrosion Resistance	Meets FM NO. 4470 Criteria

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.