


Technical Information Sheet



Metal Batten Strip

Item Description	Item Number
6" (152 mm) o.c. Pre-Punched Strips	W56RAC3053

Description

Metal Batten Strip is specifically designed to be used for anchoring Elevate membrane and flashing details as specified in Elevate Specifications and Details.

Method of Application

Attach batten strips to the roof substrate or penetration using the appropriate Elevate fastener. Do not overdrive or underdrive fasteners. Start at one end of the batten strip and fasten towards the other to reduce bowing between fasteners.

Storage

Store in original unopened containers protected from the weather.

Packaging

50 – 10' (3 m) pieces per cardboard tube

Precautions

- When cutting battens, round ends and remove burrs and sharp edges with a file.
- Do not overdrive or underdrive fastener.

LEED® Information

Post-Consumer Recycled Content: 8%

Post Industrial Recycled Content: 17%

Manufacturing Location: Cleveland, OH

NOTE: LEED® is a registered trademark of the U.S. Green Building Council



Typical Properties

Properties	Test Method
Material	Galvalume® AZ 55
Corrosion Resistance	Meets FM No. 4470 criteria
Length	10' (3 m)
Width	1" (25.4 mm)
Thickness	0.04"/0.05" (1.13 mm/1.29 mm)
Holes	.343" (8.71 mm) diameter, at 6" (152 mm) o.c. (Accommodates Elevate All-Purpose, Heavy-Duty, and Concrete Drive Fasteners)
<i>Galvalume® is a registered trademark of BIEC International, Inc.</i>	

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.