

# Technical Information Sheet

Image Coming Soon

## Polymer Fastener Metal Batten Strip

Item Description	Item Number
6" (152 mm) o.c. pre-punched strips	W56RAC3059

### Description

Polymer Fastener Metal Batten Strip is specifically designed to be used with the Elevate Polymer Fastener for anchoring Elevate membranes as specified in Elevate Specifications and Details.

### Method of Application

Polymer Fastener Metal Batten Strips are to be installed with "UP" side showing and as specified by Elevate Specifications and Details. Attach batten strips to roof substrate using the appropriate length Polymer Fastener.

### Storage

Store in original unopened containers protected from the weather.

### Packaging

50 – 10' (3 m) pieces per tube

### Precautions

- When cutting battens, round ends and remove burrs and sharp edges with a file.
- Do not overdrive or underdrive fastener.

### LEED® Information

Post-Consumer Recycled Content: 8%

Post Industrial Recycled Content: 17%

Manufacturing Location: Cleveland, OH

NOTE: LEED® is a registered trademark of the U.S. Green Building Council



## Typical Properties

Properties	Value
Material	Galvalume® Sheet Steel
Corrosion Resistance	Meets FM No. 4470 criteria
Length	10' (3 m)
Width	1¼" (31.6 mm)
Thickness	0.045"/0.051" (1.13 mm/1.29 mm)
Holes	0.625" (15.9 mm) diameter, at 6" (152 mm) o.c. with 12 teeth equally spaced around the hole to provide back-out resistance when used with the Elevate Polymer Fastener.
<i>Galvalume® is a registered trademark of BIEC International, Inc.</i>	

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.

Firestone, the brand of premier roofing, wall, and lining systems you know and trust, will be coming to you under a new name: Elevate. During our transition, products carrying the brand name **Firestone** will change to **Elevate** on product labels and packaging, Technical Information Sheets, and elsewhere. Only the brand name is changing. Our products remain the same.

For further information on our brand transition to Elevate, scan the code below with your smartphone, or visit our website: [www.holcimelevate.com](http://www.holcimelevate.com)

