

1. Identification

Product identifier W563587065 - Firestone Pourable Sealer S-10 (Part B)
Other means of identification W563587065
Recommended use Construction. Sealant.
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name Firestone Building Products Company, LLC
200 4th Avenue South
Nashville, TN 37201 USA
Email firestonemsds@bfdp.com
Telephone Number 1-800-428-4442
Contact Person SDS request
Emergency Telephone Number CHEMTREC: 1-800-424-9300

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards
Acute toxicity, inhalation Category 4
Skin corrosion/irritation Category 2
Serious eye damage/eye irritation Category 2A
Sensitization, respiratory Category 1
Sensitization, skin Category 1
Specific target organ toxicity, single exposure Category 3 respiratory tract irritation
Specific target organ toxicity, repeated exposure (inhalation) Category 2 (Respiratory system)
OSHA defined hazards Not classified.

Label elements



Signal word Danger
Hazard statement Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause damage to organs (Respiratory system) through prolonged or repeated exposure by inhalation.
Precautionary statement
Prevention Do not breathe mist/vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection.
Response If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. If experiencing respiratory symptoms: Call a poison center/doctor. Take off contaminated clothing and wash it before reuse.
Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Methylene diphenyl diisocyanate	101-68-8	25 - 50
Polymethylene polyphenylene isocyanate	9016-87-9	25 - 50
o-(p-Isocyanatobenzyl)phenyl isocyanate	5873-54-1	2.5 - 10
Carbon Black	1333-86-4	< 2.5
2,2'-Methylenediphenyl diisocyanate	2536-05-2	< 1
Other components below reportable levels		< 20

Composition comments All concentrations are in percent by weight.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If experiencing respiratory symptoms: Call a poison center or doctor/physician.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Coughing. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Powder. Carbon dioxide (CO₂). Water spray may be used if no other available and then in copious quantities. Reaction between water and hot isocyanate may be vigorous.

Unsuitable extinguishing media

Do not use water unless flooding amounts are available. Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Containers may rupture or explode if exposed to heat. During fire, gases hazardous to health may be formed such as: Carbon oxides (CO_x). Nitrogen Oxides (NO_x). Isocyanates. Hydrogen cyanide.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Cool containers with flooding quantities of water until well after fire is out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

Will burn if involved in a fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

The product is immiscible with water and will spread on the water surface.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Persons already sensitized to diisocyanates may develop allergic reactions when using this product. Do not breathe mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Carbon Black (CAS 1333-86-4)	PEL	3.5 mg/m ³
Methylene diphenyl diisocyanate (CAS 101-68-8)	Ceiling	0.2 mg/m ³
		0.02 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Carbon Black (CAS 1333-86-4)	TWA	3 mg/m ³	Inhalable fraction.
Methylene diphenyl diisocyanate (CAS 101-68-8)	TWA	0.005 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Carbon Black (CAS 1333-86-4)	TWA	0.1 mg/m ³
Methylene diphenyl diisocyanate (CAS 101-68-8)	Ceiling	0.2 mg/m ³
		0.02 ppm
	TWA	0.05 mg/m ³
		0.005 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. General ventilation normally adequate. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear approved chemical safety goggles.
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves. Examples of preferred glove barrier materials include: Nitrile rubber. Butyl rubber. Chloroprene rubber. Suitable gloves can be recommended by the glove supplier.
Skin protection	
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Organic vapor cartridge with a particulate pre-filter.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Liquid.
Color	Black.
Odor	Slightly musty.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	> 572 °F (> 300 °C)
Flash point	231.8 °F (111.0 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.

Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.

Solubility(ies)

Solubility (water)	Not miscible or difficult to mix.
---------------------------	-----------------------------------

Partition coefficient (n-octanol/water)	Not available.
--	----------------

Auto-ignition temperature	> 1112 °F (> 600 °C)
----------------------------------	----------------------

Decomposition temperature	Not available.
----------------------------------	----------------

Viscosity	Not available.
------------------	----------------

Other information

Density	1.67 g/cm ³ (68 °F (20 °C)) 9.74 lb/gal (68 °F (20 °C))
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.

VOC 0 g/l

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Diisocyanates react with many materials and the rate of reaction increases with temperature as well as increased contact; these reactions can become violent. Contact is increased with stirring or if the other material mixes with the diisocyanate. Diisocyanates are not soluble in water and sink to the bottom, but react slowly at the interface. The reaction forms carbon dioxide gas and a layer of solid polyurea. Reaction with water will generate carbon dioxide and heat.
Conditions to avoid	Avoid high temperatures. Moisture. Humidity. Contact with incompatible materials.
Incompatible materials	Water. Strong oxidizing agents. Acids. Alkaline metals. Alcohols. Amines. Ammonia. Phenols.
Hazardous decomposition products	Fire or excessive heat may produce hazardous decomposition products. For hazardous combustion products, see section 5.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Harmful if inhaled. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Coughing. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

Information on toxicological effects

Acute toxicity Harmful if inhaled.

Components	Species	Test Results
Carbon Black (CAS 1333-86-4)		
Acute		
Inhalation		
LC0	Rat	4.6 mg/m ³ , 4 h
Oral		
LD50	Rat	> 10000 mg/kg
Methylene diphenyl diisocyanate (CAS 101-68-8)		
Acute		
Inhalation		
LC50	Rat	> 2.24 mg/l, 1 Hours
Polymethylene polyphenylene isocyanate (CAS 9016-87-9)		
Acute		
Dermal		
LD50	Rabbit	> 10000 mg/kg
Inhalation		
<i>Mist</i>		
LC50	Rat	> 490 mg/m ³ , 4 Hours
Oral		
LD50	Rat	> 10000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Not classifiable as to carcinogenicity to humans. Inhalation of carbon black dust may cause cancer, however due to the physical form of the product, inhalation of dust is not likely.

IARC Monographs. Overall Evaluation of Carcinogenicity

2,2'-Methylenediphenyl diisocyanate (CAS 2536-05-2)	3 Not classifiable as to carcinogenicity to humans.
Carbon Black (CAS 1333-86-4)	2B Possibly carcinogenic to humans.
Methylene diphenyl diisocyanate (CAS 101-68-8)	3 Not classifiable as to carcinogenicity to humans.
o-(p-Isocyanatobenzyl)phenyl isocyanate (CAS 5873-54-1)	3 Not classifiable as to carcinogenicity to humans.
Polymethylene polyphenylene isocyanate (CAS 9016-87-9)	3 Not classifiable as to carcinogenicity to humans.

NTP Report on Carcinogens

Carbon Black (CAS 1333-86-4)	Known To Be Human Carcinogen.
------------------------------	-------------------------------

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	May cause respiratory irritation.
Specific target organ toxicity - repeated exposure	May cause damage to organs (Respiratory system) through prolonged or repeated exposure by inhalation.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	The product is immiscible with water and will sediment in water systems.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not incinerate sealed containers. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT	Not regulated as dangerous goods.
IATA	Not regulated as dangerous goods.
IMDG	Not regulated as dangerous goods.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

TSCA Chemical Action Plans, Chemicals of Concern

2,2'-Methylenediphenyl diisocyanate

(CAS 2536-05-2)

Diisodecyl phthalate (CAS 26761-40-0)

Methylene diphenyl diisocyanate (CAS 101-68-8)

o-(p-Isocyanatobenzyl)phenyl isocyanate

(CAS 5873-54-1)

Polymethylene polyphenylene isocyanate

(CAS 9016-87-9)

Methylene Diphenyl Diisocyanate (MDI) And Related Compounds
Action Plan [RIN 2070-ZA15]

Phthalates Action Plan

Methylene Diphenyl Diisocyanate (MDI) And Related Compounds
Action Plan [RIN 2070-ZA15]

Methylene Diphenyl Diisocyanate (MDI) And Related Compounds
Action Plan [RIN 2070-ZA15]

Methylene Diphenyl Diisocyanate (MDI) And Related Compounds
Action Plan [RIN 2070-ZA15]

CERCLA Hazardous Substance List (40 CFR 302.4)

Diisodecyl phthalate (CAS 26761-40-0)

Listed.

Methylene diphenyl diisocyanate (CAS 101-68-8)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA)

All components of the mixture on the TSCA 8(b) inventory are designated "active".

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

Yes

Classified hazard categories

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation

Respiratory or skin sensitization

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Methylene diphenyl diisocyanate	101-68-8	25 - 50
Polymethylene polyphenylene isocyanate	9016-87-9	25 - 50

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Methylene diphenyl diisocyanate (CAS 101-68-8)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

Carbon Black (CAS 1333-86-4)

Methylene diphenyl diisocyanate (CAS 101-68-8)

US. New Jersey Worker and Community Right-to-Know Act

2,2'-Methylenediphenyl diisocyanate (CAS 2536-05-2)

Carbon Black (CAS 1333-86-4)

Methylene diphenyl diisocyanate (CAS 101-68-8)

o-(p-Isocyanatobenzyl)phenyl isocyanate (CAS 5873-54-1)

Polymethylene polyphenylene isocyanate (CAS 9016-87-9)

US. Pennsylvania Worker and Community Right-to-Know Law

Carbon Black (CAS 1333-86-4)

Diisodecyl phthalate (CAS 26761-40-0)

Methylene diphenyl diisocyanate (CAS 101-68-8)

US. Rhode Island RTK

Carbon Black (CAS 1333-86-4)

Methylene diphenyl diisocyanate (CAS 101-68-8)

California Proposition 65



WARNING: This product can expose you to Carbon Black, which is known to the State of California to cause cancer, and Diisodecyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Carbon Black (CAS 1333-86-4)

Listed: February 21, 2003

California Proposition 65 - CRT: Listed date/Developmental toxin

Diisodecyl phthalate (CAS 26761-40-0)

Listed: April 20, 2007

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

2,2'-Methylenediphenyl diisocyanate (CAS 2536-05-2)

Carbon Black (CAS 1333-86-4)

Diisodecyl phthalate (CAS 26761-40-0)

Methylene diphenyl diisocyanate (CAS 101-68-8)

o-(p-Isocyanatobenzyl)phenyl isocyanate (CAS 5873-54-1)

Polymethylene polyphenylene isocyanate (CAS 9016-87-9)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 14-February-2020

Revision date -

Version # 01

HMIS® ratings Health: 2*
Flammability: 1
Physical hazard: 1

Disclaimer Firestone Building Products cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.