

# Technical Information Sheet



## QUICKSEAM™ CONDUIT FLASHING

Item Description	Item Number
Various sizes from ½" to 2 ½"	W563581070

### DESCRIPTION

Elevate QuickSeam Conduit Flashing is specifically designed to be used in roofing applications for flashing of rigid round penetrations and conduit. Conduit Flashing will fit various size penetrations from ½" to 2 ½" (12.7 mm to 63.5 mm) and can be cut to desired diameter before installation.

QuickSeam Conduit Flashing may be used to flash small diameter penetrations and conduit for RubberGard™ EPDM.

### METHOD OF APPLICATION

1. Penetration must be clean of prior flashing and foreign materials.
2. Cut along the top edge of the ring on the QuickSeam Conduit Flashing corresponding to the size of pipe or conduit.
3. Clean the RubberGard membrane using QuickPrime™ Plus and a QuickScrubber™ or QuickScrubber Plus pad and handle to remove all dusting agent, dirt and other contaminants that will affect the finished bond.
4. Allow to dry according to the touch-push test.
5. Remove the release paper.
6. Install the pipe flashing and roll the flange with a silicone hand roller.
7. Install the clamping ring and Lap Sealant per Elevate Specifications and Details.

### SHELF LIFE

24 Months

### PRECAUTIONS

- Refer to Safety Data Sheets (SDS) for additional safety information.
- Do not install on uneven substrates.

## LEED® INFORMATION

Post-Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: Bensenville, IL

NOTE: LEED® is a registered trademark of the U.S. Green Building Council

TYPICAL PROPERTIES	
Properties	Value
<b>Molded Pipe Flashing</b>	
Base	Molded EPDM
Color	Black
Clamp	Stainless Steel – worm gear type (clamps are included)
Pipe Flange	9" (229 mm) outside diameter
Thickness	0.055" – 0.075" (1.4 mm -1.9 mm)
<b>QuickSeam Tape</b>	
Base	Rubber Polymer
Color	Black
Solvents	None
Percent Solids	100%
Cured State	Cured
Thickness	0.030" (0.762 mm) + 0.005" (0.13 mm)

FIT GUIDE		
½" (12.7 mm)	1 ¼" (32.0 mm)	2" (51.0 mm)
¾" (19.0 mm)	1 ½" (37.0 mm)	2 ¼" (57.15 mm)
1" (25.4 mm)	1 ¾" (45.0 mm)	2 ½" (64.0 mm)

Please contact Elevate Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Amrize takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Amrize nor its representatives practice architecture. Amrize offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Amrize accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Amrize representative is authorized to vary this disclaimer.