

Technical Information Sheet



QuickSeam™ Corner Flashing

Item Description	Item Number
8.5" (216 mm) Diameter	W56RAC1646

DESCRIPTION

Elevate QuickSeam Corner Flashing consists of Elevate FormFlash™ factory laminated to QuickSeam Tape. It is designed to flash inside and outside corners of RubberGard™ EPDM roofing installations.

METHOD OF APPLICATION

1. Clean and prepare the RubberGard EPDM membrane using QuickPrime™ Plus, QuickPrime Plus LVOC, Single-Ply QuickPrime or Single-Ply LVOC Primer and a QuickScrubber™ or QuickScrubber Plus pad and handle to remove all dusting agents, dirt and other contaminants that will affect the finished seam.
2. When cloudy conditions below 60 °F (16 °C) occur, use heat guns (without ignition sources) to heat QuickSeam Corner Flashing. This will ensure good formability of the QuickSeam Corner Flashing to the primed substrate.
3. On sunny days less than 70 °F (21 °C), place QuickSeam Corner Flashing on roof (prior to application) with flashing side up to allow QuickSeam Corner Flashing to warm to ensure good formability.
4. On sunny days greater than 70 °F (21 °C), place QuickSeam Corner Flashing on roof (prior to application) with release paper side up to prevent QuickSeam Corner Flashing from gaining too much heat and to ensure good formability.
5. Refer to application instructions for specifics: www.elevatecommercialbp.com

STORAGE

- Store in original unopened containers indoors at temperatures between 60 °F (16 °C) and 80 °F (27 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (27 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.

Shelf Life

Shelf life of one year can be expected when stored in original container at temperatures between 60 °F (16 °C) and 80 °F (27 °C). Shelf life will be shortened if exposed to elevated temperatures.

PRECAUTIONS

- Refer to Safety Data Sheets (SDS) for additional safety information.
- FormFlash will cure when exposed to heat and over time.

PACKAGING

20 per carton, 100 cartons per pallet

NOTE: QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.

LEED® INFORMATION

Post-Consumer Recycled Content: 0%
 Post Industrial Recycled Content: 0%
 Manufacturing Location: Prescott, AR

NOTE: LEED® is a registered trademark of the U.S. Green Building Council

TYPICAL PROPERTIES		
Properties	QuickSeam Tape	Flashing Material
Base	Rubber Polymers	EPDM
Color	Black	Black
Solvents	None	None
Solids	100%	100%
Cured State	Cured	Uncured
Thickness	0.025" (0.64 mm) ± 0.005" (0.13 mm)	0.065" (1.59 mm) ± 0.005" (0.13 mm)
Size	---	8.5" (216 mm)

Please contact Elevate Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Amrize takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Amrize nor its representatives practice architecture. Amrize offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Amrize accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Amrize representative is authorized to vary this disclaimer.