


Technical Information Sheet



QuickSeam™ Curb Flashing

Item Description	Item Number
QuickSeam Curb Flashing	W56RAC1622

DESCRIPTION

QuickSeam Curb Flashing is 18" (457.2 mm) wide 60 mil non-reinforced RubberGard™ EPDM membrane with 3" (76.2 mm) wide tape factory laminated along one edge. The 3" (76.2 mm) tape portion is used to splice the QuickSeam Curb Flashing to the roof membrane. The balance of the QuickSeam Curb Flashing is applied to the vertical surface with Elevate EPDM Bonding Adhesive BA-2004 (T), Water-Based Bonding Adhesive P, or Single-Ply LVOC Bonding Adhesive to hold the membrane in place, then terminated using an approved termination detail.

METHOD OF APPLICATION

1. Use Elevate QuickPrime™ Plus, QuickPrime Plus LVOC, Single-Ply QuickPrime Primer or Single-Ply LVOC Primer applied with QuickScrubber™ or QuickScrubber Plus pad and handle clean and prime membrane area to receive tape.
2. Refer to Elevate Specification and Details.
3. Application temperature range is between -10 °F (-23 °C) and 120 °F (49 °C).
4. Refer to the Elevate website (HolcimElevate.com) for application instructions.

STORAGE

- Store in original unopened containers indoors at temperatures between 60 °F (16 °C) and 80 °F (27 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (27 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.

SHELF LIFE

Shelf life of 24 months can be expected when stored in original container at temperatures between 60 °F (16 °C) and 80 °F (27 °C). Shelf life will be shortened if exposed to elevated temperatures.

PRECAUTIONS

Refer to Safety Data Sheets (SDS) for additional safety information.

LEED® INFORMATION

Post-Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: Prescott, AR

NOTE: LEED® is a registered trademark of the U.S. Green Building Council

TYPICAL PROPERTIES		
Properties	QuickSeam Tape	EPDM Membrane
Base	Rubber Polymers	EPDM, Non-reinforced
Color	Black	Black
Solvents	None	None
Solids	100%	100%
Cured State	Cured	Cured
Thickness	0.030" (0.635 mm) ± 0.005" (0.127 mm)	0.060" (1.52 mm) ± 0.005" (0.127 mm)
Width	3.0" (77 mm)	18.0" (457.2 mm)

PRODUCT PACKAGING		
Length	Quantity Per Carton	Pallet
50' (15.25 m)	1	24
NOTE: QuickScrubber Kits (pads and handles) are included in each carton.		

Please contact Elevate Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Amrize takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Amrize nor its representatives practice architecture. Amrize offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Amrize accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Amrize representative is authorized to vary this disclaimer.