

Technical Information Sheet



QUICKSEAM™ REINFORCED PERIMETER FASTENING (RPF) STRIP

Item Description	Item Number
6" (152 mm) x 100' (30.5 m)	W56RAC1632

DESCRIPTION

QuickSeam Reinforced Perimeter Fastening (RPF) Strip is a 6" (152 mm) wide RubberGard™ MAX membrane with 3" (76 mm) wide QuickSeam Tape factory laminated to it along one edge. It is used for non-penetrating membrane securement as specified in Elevate Specifications and Details.

METHOD OF APPLICATION

1. Unroll the QuickSeam RPF Strip with the release paper up and the tape portion farthest away from the wall or penetration.
2. Anchor QuickSeam RPF Strip using Elevate 2" seam plates and fasteners 12" (305 mm) o.c. max. per current base tie-in details.
3. Attachment option: QuickSeam RPF Strip may be fastened with metal or polymer batten strips to the deck (in the mechanically attached and fully adhered systems only) or fastened into the wall (metal battens only). Polymer batten may be used to fasten into wood sheathed parapet walls. Refer to appropriate Elevate details for specifics.
4. Position EPDM membrane over QuickSeam RPF Strip with release paper in place and allow membrane to relax.
5. Fold back EPDM membrane to expose the tape.
6. Prime the EPDM to be spliced to the tape using QuickPrime™ Plus, QuickPrime Plus LVOC, Single-Ply QuickPrime Primer or Single-Ply LVOC Primer and QuickScrubber™ or QuickScrubber Plus pad and handle per current procedures.
7. Allow the primer to dry or to flash-off according to the specification for each priming product.
8. Remove the release paper.
9. Roll the primed EPDM membrane into the tape.
10. Bond the portion of the QuickSeam RPF Strip without tape to the membrane using an approved Elevate bonding adhesive or Splice Adhesive SA-1065.
11. Roll the EPDM membrane over the QuickSeam RPF Strip with a 1½" (38 mm) wide silicone hand roller to ensure proper adhesion.

PACKAGING

- 2 – 6" (152.4 mm) x 100' (30.5 m) rolls per carton
- 21 cartons per pallet

NOTE: QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.

STORAGE

- Store in original unopened containers indoors at temperatures between 60 °F (16 °C) and 80 °F (27 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (27 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.

SHELF LIFE

Shelf life of 24 months can be expected when stored in original container at temperatures between 60 °F (16 °C) and 80 °F (27 °C). Shelf life will be shortened if exposed to elevated temperatures.

PRECAUTIONS

Refer to Safety Data Sheets (SDS) for additional safety information.

LEED® INFORMATION

Post-Consumer Recycled Content: 0%
 Post Industrial Recycled Content: 0%
 Manufacturing Location: Prescott, AR

NOTE: LEED® is a registered trademark of the U.S. Green Building Council



TYPICAL PROPERTIES – QUICKSEAM TAPE	
Properties	Value
Base	Rubber Polymers
Color	Black
Solvents	None
Solids	100%
Specific Gravity	98± 0.02 (H2O = 1)
Cured State	Cured
Thickness	0.030" (0.77 mm) ± 0.007" (0.18 mm)
Width	3" (133.3 mm) + 0, - 1/16"
Length	100' (30.48 m) +1'-0

TYPICAL PROPERTIES – RUBBERGARD MAX	
Properties	Value
Base	EPDM
Color	Black
Solvents	None
Solids	100%
Cured State	Cured
Thickness	0.060" (1.52 mm) ± 10%
Width	6" + 0, - 0.125"
Breaking Strength	80 lb/ft (355.9 N)

Please contact Elevate Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Amrize takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Amrize nor its representatives practice architecture. Amrize offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Amrize accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Amrize representative is authorized to vary this disclaimer.