


Technical Information Sheet



QUICKSEAM™ YELLOW SAFETY STRIP

Item Description	Item Number
1 Roll: 5½" x 100' (139.7 mm x 30.5 m)	W56RAC1870

DESCRIPTION

QuickSeam Yellow Safety Strip is a nominal 30 mil (0.76 mm) yellow unsupported TPO membrane laminated to a 35 mil (0.89 mm), white cured seaming tape. The QuickSeam Yellow Safety Strip is acceptable to be used on UltraPly™ TPO Membrane, RubberGard™ EPDM Membrane and RubberGard EcoWhite™ EPDM Membrane. The QuickSeam Yellow Safety Strip is used for designating a safety perimeter around the roof edge, equipment, and any other rooftop hazards.

METHOD OF APPLICATION

1. Use Single Ply Quick Prime Primer or Single Ply LVOC Primer and QuickScrubber™ Pad or QuickScrubber Plus Pad to clean and prime the membrane and mating surface(s).
2. Once the primer has dried completely, apply the QuickSeam Yellow Safety Strip to the membrane. Hand roll with a silicone roller to ensure adequate adhesion.
3. TPO QuickSeam products must be heat-formed to conform to any step-offs or angle changes.

STORAGE

- Store indoors in original, unopened containers at temperatures between 60 and 80 °F (16 and 27 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (26.7 °C).
- When exposed to lower temperatures, restore to room temperature prior to use.

SHELF LIFE

A shelf life of 18 months can be expected when stored in original container at temperatures between 60 and 80 °F (16 and 27 °C). Shelf life will be shortened if exposed to elevated temperatures.

PRECAUTIONS

Refer to Safety Data Sheets (SDS) for additional safety information.

PRODUCT PACKAGING

Roll: 5½" x 100' (139.7 mm x 30.5 m)

Carton: 1 Roll per Carton

LEED® INFORMATION

Post-Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: Michigan Center, MI

NOTE: LEED® is a registered trademark of the U.S. Green Building Council

TYPICAL PROPERTIES		
Properties	QuickSeam Tape Typical Performance	TPO Flashing Typical Performance
Base	Rubber Polymers	TPO
Color	White	Yellow
Solvents	None	None
Solids	100%	100%
Specified Gravity	98 ± 0.02 (H2O = 1)	1.15 ± 0.05
Cured State	Cured	N/A
Thickness	0.035" + 0.002", - 0.005" (0.889 mm + 0.051 mm, - 0.13 mm)	0.030" (0.76 mm) ± 10%
Width	5¾" - 0, + 1/16" (146 mm - 0, + 1.6 mm)	5½" (139.7 mm) + 0, - 1/8"
Length	100' (30.5 m)	100' (30.5 m)

Please contact Elevate Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Amrize takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Amrize nor its representatives practice architecture. Amrize offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Amrize accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Amrize representative is authorized to vary this disclaimer.