

Technical Information Sheet

Image Coming Soon

RubberGard™ EcoWhite™ EPDM QuickSeam™ Flashing

Item Description	Item Number
50' (15.2 m) Roll	W56RAC160G

Description

RubberGard EcoWhite EPDM QuickSeam SA Flashing (“EW QS SA Flashing”) consists of 18" (457 mm) wide EcoWhite membrane fully and completely factory laminated to EcoWhite seam tape. It can be used to flash curbs and walls in conjunction with EcoWhite roofing systems where allowed by Elevate specifications.

EcoWhite tape is used as the tape adhesive to field splice EW QS SA Flashing to primed RubberGard membrane, as well as the adhesive to bond EW QS SA Flashing to primed vertical substrates. The polymeric release liner (protects the tape until field application) is perforated 6" (152 mm) from the tape selvage edge to delineate the lap portion of the EW QS SA Flashing. The perforated release liner allows removal of the liner in separate vertical and horizontal sections.

Method of Application

1. Prime all surfaces (membrane and substrates) to receive EW QS SA Flashing using Single-Ply QuickPrime™ Primer or Single-Ply QuickPrime LVOC Primer scrub applied with QuickScrubber™ Pad and Handle.
2. Allow primer to flash off. Use Touch-Push test to verify primer readiness.
3. Fold the 6" (152 mm) horizontal lap portion of EW QS SA Flashing (delineated by the liner perforation) back and apply the vertical portion of EW QS SA Flashing to the primed vertical substrate using the top of the curb/wall as a guide.
4. Cut/trim the EW QS SA Flashing at corner areas to allow the tape lap portion to lie flat on the primed membrane.
5. Remove release liner in sections and only when EW QS SA Flashing is properly positioned over primed substrate.
6. Roll the freshly mated EW QS SA Flashing with silicone coated rubber hand roller to ensure proper mating.
7. Refer to Application Instructions included in each carton for specifics.

Packaging

1 - 50' (15.2 m) Roll, 1 roll per carton, 24 cartons per pallet

NOTE: QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.

Storage

- Store in original unopened containers indoors at temperatures between 60 °F (16 °C) and 80 °F (27 °C).
- Do not store on roof in direct sunlight or at temperatures above 100 °F (38 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.

Shelf Life

Shelf life of 24 months can be expected when stored in original container at temperatures between 60 °F (16 °C) and 80 °F (27 °C). Shelf life will be shortened if exposed to elevated temperatures.

Precautions

Refer to Safety Data Sheets (SDS) for additional safety information.

LEED® Information

Post-Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: Michigan Center, MI

NOTE: LEED® is a registered trademark of the U.S. Green Building Council

Typical Properties			
Properties – QuickSeam Tape		Properties – Membrane	
	Value		Value
Base	Rubber Polymers	Base	EPDM, Non-reinforced
Color	White	Color	White op ply over black ply
Solvents	None	Solvents	None
Solids	100%	Cured State	Cured
Cured State	Cured	Thickness	0.060" (1.52 mm) ± .005" (.13 mm)
Thickness	0.030" (.76 mm) ± .005" (.13 mm)	Width	18" (457 mm)
Width	18" (457 mm)	Release Liner	Polymeric, perforated

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.