

Technical Information Sheet



RUBBERGARD™ ECOWHITE™ EPDM QUICKSEAM™ SA PATCH FOR CONDUIT FLASHING

Item Description	Item Number
18" x 18" (457 mm x 457 mm) White	W56RAC160H

DESCRIPTION

RubberGard EcoWhite EPDM QuickSeam SA Patch for Conduit Flashing (EW QS SA Patch for Conduit Flashing) consists of 18" X 18" (457 mm x 457 mm) EcoWhite membrane fully and completely factory laminated to EcoWhite seam tape with a 3¼" (83 mm) diameter hole die-cut in the center. It can be used to flash the flange of QuickSeam Conduit Flashings in conjunction with EcoWhite roofing systems where allowed by Elevate specifications.

EcoWhite tape is used as the tape adhesive to field splice EW QS SA Patch for Conduit Flashing to primed flanges of QuickSeam Conduit flashings and EcoWhite membrane. The polymeric release liner (protects the tape until field application) is perforated to allow removal of the liner in separate sections.

METHOD OF APPLICATION

1. Prime all surfaces (membrane and flanges) to receive EW QS SA Patch for Conduit Flashing using Single-Ply QuickPrime™ Primer or Single-Ply LVOC Primer scrub applied with QuickScrubber™ Pad and Handle.
2. Allow primer to flash off. Use Touch-Push test to verify primer readiness.
3. Remove release liner in sections to mate EW QS SA Patch for Conduit flashing to primed substrates only when EW QS SA Patch for Conduit Flashing is properly positioned over primed substrate.
4. Roll the freshly mated EW QS SA Patch for Conduit Flashing with silicone coated rubber hand roller to ensure proper mating.
5. Apply seam edge treatment at all lap edges of the EW QS SA Patch for Conduit Flashing: the perimeter and the die-cut center hole.

STORAGE

- Store in original unopened containers indoors at temperatures between 60 °F (16 °C) and 80 °F (27 °C).
- Do not store on roof in direct sunlight or at temperatures above 100 °F (38 °C).
- When exposed to lower temperatures, restore to room temperature prior to use.

SHELF LIFE

- Shelf life of 24 months can be expected when stored in original container at temperatures between 60 °F (16 °C) and 80 °F (27 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

PACKAGING:

- 25 pieces per carton
- 20 cartons per pallet

NOTE: QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.

LEED® INFORMATION

Post Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: Michigan Center, MI

NOTE: LEED® is a registered trademark of the U.S. Green Building Council

TYPICAL PROPERTIES			
QuickSeam Tape	Value	EPDM Flashing	Value
Base	Rubber Polymer	Base	EPDM, Non-reinforced
Color	White	Color	White top ply over black ply
Solvents	None	Solvents	None
Solids	100%	Solids	100%
Cured State	Cured	Cured State	Cured
Thickness	0.020" (0.51 mm) ± 0.005" (0.13 mm)	Thickness	0.060" (1.6 mm) ± 0.005" (0.13 mm)
Dimensions	18" X 18" (457 mm X 457 mm) with 3 1/4" (83 mm) diameter center hole	Dimensions	18" X 18" (457 mm X 457 mm) with 3 1/4" (83 mm) diameter center hole
Release Liner:	The tape portion of EW QS SA Patch for Conduit Flashing is protected by polymeric release liner, perforated to allow removal in separate sections to facilitate application.		

Please contact Elevate Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Amrize takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Amrize nor its representatives practice architecture. Amrize offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Amrize accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Amrize representative is authorized to vary this disclaimer.