

Technical Information Sheet

Image Coming Soon

SA PRIMER

Item Description	Item Number
SA Primer (5-gal pail)	W70RACSAP5

DESCRIPTION

SA Primer is designed to prime substrates prior to the application of BASEGARD™ SA membrane where required by Elevate Technical Specifications and Details. SA Primer must be applied with a solvent-resistant roller. **NOT FOR USE** with self-adhered single-ply membranes and QuickSeam accessories.

METHOD OF APPLICATION

1. Surfaces must be clean, dry, and free of foreign materials. Stir SA Primer thoroughly before and during use.
2. Apply SA Primer with a solvent-resistant roller at the rate of 100-125 ft² per gallon (2.45 – 3.07 m² per liter) depending upon the porosity of the substrate.
3. Apply SA Primer until the substrate surface becomes dark in color with no streaking or puddling.
4. Apply SA Primer to all side and end laps.
5. Allow primed surfaces to dry according to the touch-push test (usually less than 10 minutes) before applying BASEGARD SA membrane.
6. Prime all laps and complete seaming procedures per Elevate Technical Specifications and Details.

STORAGE

- Store SA Primer in its original unopened container at temperatures between 60 °F (16 °C) and 80 °F (27 °C).
- Do not store SA Primer on the roof in direct sunlight or at temperatures above 80 °F (27 °C).
- When exposed to lower temperatures, restore SA Primer to room temperature prior to use.

SHELF LIFE

- Shelf life of one year can be expected when SA Primer is stored in its original container at recommended temperatures.
- The shelf life of SA Primer will be shortened if it is exposed to temperatures in excess of 80 °F (27 °C).

COVERAGE RATE

100-125 ft² per gallon (2.45 – 3.07 m² per liter) depending upon the porosity of the substrate.

PRECAUTIONS

- SA Primer is Flammable. Keep it away from open flame and other possible ignition sources during storage and use.
- Do not thin SA Primer.
- Mix SA Primer thoroughly before and during use.
- SA Primer is for professional use only.
- Use SA Primer only in well-ventilated areas.
- Use neoprene or nitrile gloves and eye protection with side shields when using SA Primer.
- Do not apply SA Primer with brushes or rags.
- Not for use with V-Force™ Vapor Barrier Membrane.
- Refer to Safety Data Sheets (SDS) for additional safety information.
- NOT FOR USE** with self-adhered single-ply membranes and QuickSeam accessories.

LEED® INFORMATION

Post-Consumer Recycled Content: 0%
 Post Industrial Recycled Content: 0%
 Manufacturing Location: South Bend, IN

NOTE: LEED® is a registered trademark of the U.S. Green Building Council



PRODUCT DATA	
Property	Value
Base	Synthetic Rubber Polymers
Color	Translucent Grey
Solvents	Heptane, Toluene
Percent Solids	16-18%
Viscosity	Very thin, free flowing
Weight (Nominal)	6.62 lb/gal (0.79 kg/L)
Specific Gravity	0.793 nominal (H ₂ O=1)
Flash Point	0.0 °F (-17.8 °C)
V.O.C. Content	Not to exceed 5.55 lb/Gal (664 g/L)

Please contact Elevate Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Amrize takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Amrize nor its representatives practice architecture. Amrize offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Amrize accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Amrize representative is authorized to vary this disclaimer.