

# Technical Information Sheet

Image Coming Soon

## Single-Ply LVOC Splice Wash

Item Description	Item Number
3 Gallon (11.4 L)	W563587113

### Description

Elevate Single-Ply LVOC Splice Wash is designed to clean and prepare Elevate single-ply membranes to be welded, or to receive Elevate Primers, Adhesives or Sealants, as noted in Elevate Specifications and Details. This product is not intended for use with PVC or PVC KEE membranes.

### Method of Application

1. Surfaces to be welded, or to receive primer, adhesive or sealant shall be clean, dry, and free of foreign materials and excess dusting agent. Remove loose contaminates using brooms or rags.
2. Clean/prepare dirty surfaces using clean cotton rags wetted with Single-Ply LVOC Splice Wash, moving in circular motions with heavy pressure over affected areas. Membrane with caked dirt, including in-service thermoplastic membranes, should be scrubbed using QuickScrubber™ Handle & Pad wetted with Single-Ply Splice Wash LVOC, followed by wiping with clean rags to remove contaminates. On thermoplastic surfaces, the wipe with Single-Ply LVOC Splice Wash should be in one direction, flipping the rag often to avoid transferring contaminates.
3. Allow surfaces cleaned with Single-Ply Splice Wash LVOC to dry completely (usually within 10 to 30 minutes) before welding or applying primer, adhesive or sealant per current Elevate specifications and details.

### Storage

- Store in original unopened container, at temperatures between 60 °F (16 °C) and 80 °F (27 °C), away from all sources of direct heat and ignition, until ready for use. This is a flammable liquid.
- When exposed to lower temperatures, restore to room temperature prior to use.
- Keep the material out of direct sunlight until ready for immediate use.

## Shelf Life

Shelf life of two (2) years can be expected when stored in original unopened container at temperatures between 60 °F (16 °C) and 80 °F (27 °C).

## Coverage Rate

200-250 ft<sup>2</sup>/gallon (4.9 - 6.1 m<sup>2</sup>/L) on one side

## Precautions

- Refer to Safety Data Sheets (SDS) for additional safety information.
- Flammable liquid. Store and use away from all sources of direct heat and ignition.
- Cover tightly when not in use.
- Thinning is not allowed.
- Use solvent-resistant Neoprene gloves is required when applying Splice Wash. Avoid contact with eyes and skin.
- Avoid breathing vapors. Use only in well ventilated areas. Do not take internally.
- Do not directly wash QuickSeam™ Tape with Single-Ply LVOC Splice Wash.

## LEED® Information

Post-Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: South Bend, IN

**NOTE: LEED® is a registered trademark of the U.S. Green Building Council**

Typical Properties	
Properties	Value
Solvents	Solvent Blend of Acetone and Mineral Spirits
Viscosity	Very Thin, Free Flowing
Weight / Gallon	6.593 ± 0.329 lb/gal (790 ± 39.42 g/l)
VOC Content	Less than 250 g/l

Packaging Data	
Properties	Value
Pail	3 gal (11.4 L)
Weight	Appx 20 lb (9 kg)

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.

Firestone, the brand of premier roofing, wall, and lining systems you know and trust, will be coming to you under a new name: Elevate. During our transition, products carrying the brand name **Firestone** will change to **Elevate** on product labels and packaging, Technical Information Sheets, and elsewhere. Only the brand name is changing. Our products remain the same.

For further information on our brand transition to Elevate, scan the code below with your smartphone, or visit our website: [www.holcimelevate.com](http://www.holcimelevate.com)

