# **SAFETY DATA SHEET**



#### 1. Identification

Product identifier Elevate Single Ply LVOC Splice Wash

Other means of identification

Product code W563587113
Recommended use Construction.
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

**Distributed by**Holcim Solutions and Products US, LLC

Address 26 Century Boulevard, Suite 205

Nashville, TN 37214

Elevate™ is a Holcim Solutions and Products US, LLC brand.

Website holcimelevate.com
Telephone Number 1-800-428-4442

**Emergency Telephone** 

Number

For Chemical Emergency, Spill, Leak, Fire, Exposure, or Incident:

CHEMTREC within USA and Canada: 1-800-424-9300

CHEMTREC outside USA and Canada: +1 703-527-3887 (collect calls accepted)

# 2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 2Health hazardsSkin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2

Serious eye damage/eye imalion Calegory 2

Specific target organ toxicity, single exposure Category 3 narcotic effects
Aspiration hazard Category 1

Environmental hazards Hazardous to the aquatic environment, acute

hazard

Hazardous to the aquatic environment,

long-term hazard

Category 2

Category 2

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin

irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Toxic to aquatic life

with long lasting effects.

Precautionary statement

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist/vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective

gloves/eye protection/face protection.

Elevate Single Ply LVOC Splice Wash
955258 Version #: 01 Revision date: - Issue date: 28-February-2023

#### Response

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use alcohol resistant foam, carbon dioxide, dry powder or water fog to extinguish. Collect spillage.

**Storage** 

Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	CAS number	%
Acetone	67-64-1	60 - 80
Distillates (petroleum), hydrotreated light	64742-47-8	15 - 40

#### **Composition comments**

All concentrations are in percent by weight unless otherwise indicated.

Components not listed are either non-hazardous or are below reportable limits.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

#### 4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation

occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

**General information** 

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

# 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed such as: Carbon oxides (COx).

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved.

Specific methods General fire hazards Use standard firefighting procedures and consider the hazards of other involved materials.

Highly flammable liquid and vapor.

Elevate Single Ply LVOC Splice Wash 955258 Version #: 01 Revision date: -Issue date: 28-February-2023

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

# Methods and materials for containment and cleaning up

Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. The product is immiscible with water and will spread on the water surface. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

### **Environmental precautions**

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

#### Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

# Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat and sources of ignition. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

#### Occupational exposure limits

US. OSHA Table Z-1 Limits for A Components	Туре `	Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
US. ACGIH Threshold Limit Valu	ies		
Components	Туре	Value	
Acetone (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
US. NIOSH: Pocket Guide to Che	emical Hazards		
Components	Туре	Value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	
		250 ppm	

#### **Biological limit values**

ACGIH Biological Exposure Indices				
Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*

<sup>\* -</sup> For sampling details, please see the source document.

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an

acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear chemical goggles.

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves. Examples of preferred glove barrier materials include:

Polyvinyl alcohol (PVA). Neoprene. Suitable gloves can be recommended by the glove supplier.

Skin protection

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

**Respiratory protection** In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with

organic vapor cartridge and full facepiece. Appropriate respirator selection should be made by a

qualified professional.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

**Appearance** 

Physical stateLiquid.FormLiquid.ColorClear.

Odor Characteristic.
Odor threshold Not available.

**pH** Not determined; product is not soluble in water.

Melting point/freezing point Not determined.

Initial boiling point and boiling 131 °F (55 °C)

range

Flash point -2.2 °F (-19 °C)

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) 0.5
Explosive limit - upper (%) 13

Vapor pressure 233 hPa (68 °F (20 °C))

174.8 mm Hg (68 °F (20 °C))

Vapor density Not determined.
Relative density Not determined.

Solubility(ies)

Solubility (water) Insoluble.

**Partition coefficient** Not applicable, product is a mixture.

(n-octanol/water)

Auto-ignition temperature Not self-igniting.

**Decomposition temperature** Not applicable as the product is not unstable.

Viscosity Not available.

Other information

**Density** > 750.58 - < 829.42 g/l

> 6.26 - < 6.92 lb/gal

Explosive properties Not explosive.

Kinematic viscosity Not determined.

Oxidizing properties Not oxidizing.

VOC 244 g/l (SCAQMD)

224 g/l 2 lb/gal

## 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous

Conditions to avoid

reactions

No dangerous reaction known under conditions of normal use.

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

**Incompatible materials** Acids. Strong oxidizing agents.

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

**Inhalation** May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful

**Skin contact** Causes skin irritation.

**Eye contact** Causes serious eye irritation.

**Ingestion** Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing,

redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

#### Information on toxicological effects

**Acute toxicity** 

Components	Species	Test Results
------------	---------	--------------

Acetone (CAS 67-64-1)

**Acute** 

**Dermal** 

LD50 Rabbit > 15700 mg/kg, 24 Hours

Inhalation

Vapor

LC50 Rat 76 mg/l, 4 Hours

Oral

LD50 Rat 5800 mg/kg

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

**Acute** 

**Dermal** 

LD50 Rabbit > 2000 mg/kg bw

Inhalation

LC50 Rat > 5.28 mg/l, 4 hours

Oral

LD50 Rat > 5000 mg/kg bw

**Skin corrosion/irritation** Causes skin irritation.

Serious eye damage/eye

irritation

955258

Causes serious eye irritation.

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Issue date: 28-February-2023

Elevate Single Ply LVOC Splice Wash

Version #: 01 Revision date: -

SDS US

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

**NTP Report on Carcinogens** 

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** May be fatal if swallowed and enters airways.

**Chronic effects** Prolonged inhalation may be harmful.

12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

**Test Results** Components Species Acetone (CAS 67-64-1) Aquatic Acute Crustacea LC50 Daphnia pulex 8800 mg/l, 48 Hours Fish LC50 Pimephales promelas 7163 mg/l, 96 Hours Chronic Crustacea NOEC > 79 mg/l, 21 days Daphnia magna Distillates (petroleum), hydrotreated light (CAS 64742-47-8) Aquatic

Acute

LL50 > 2 - < 5 mg/l, 96 hours Fish Oncorhynchus mykiss

> **NOEC** Oncorhynchus mykiss 2 mg/l, 96 hours

> > -0.24

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available. Partition coefficient n-octanol / water (log Kow)

Acetone (CAS 67-64-1)

No data available. Mobility in soil

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the **Disposal instructions** 

material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in

accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

Elevate Single Ply LVOC Splice Wash

## 14. Transport information

DOT

UN number UN1993

**UN proper shipping name** Flammable liquids, n.o.s. (Acetone RQ = 7143 LBS)

Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Packing group II
Environmental hazards

Marine pollutant No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions IB2, T7, TP1, TP8, TP28

Packaging exceptions 150
Packaging non bulk 202
Packaging bulk 242

**IATA** 

UN number UN1993

**UN proper shipping name** Flammable liquid, n.o.s. (Acetone)

Transport hazard class(es)

Class 3
Subsidiary risk Packing group II
Environmental hazards Yes.
ERG Code 3H

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

**IMDG** 

UN number UN1993

UN proper shipping name FLAMMABLE LIQUID, N.O.S. (Acetone)

Transport hazard class(es)

Class 3
Subsidiary risk Packing group II
Environmental hazards

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

Not established.

## 15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Acetone (CAS 67-64-1) Listed. Distillates (petroleum), hydrotreated light Listed.

(CAS 64742-47-8)

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA)

All components of the mixture on the TSCA 8(b) inventory are designated

"active".

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

Elevate Single Ply LVOC Splice Wash

SARA 311/312 Hazardous

chemical

Yes

Classified hazard

categories

Flammable (gases, aerosols, liquids, or solids)

Skin corrosion or irritation

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

## SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

6532

(SDWA)

#### Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and **Chemical Code Number**

Acetone (CAS 67-64-1)

#### Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

**DEA Exempt Chemical Mixtures Code Number** 

Acetone (CAS 67-64-1) 6532

## FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Acetone (CAS 67-64-1) Low priority

#### **US** state regulations

#### **US. Massachusetts RTK - Substance List**

Acetone (CAS 67-64-1)

## US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

#### US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)

#### **US. Rhode Island RTK**

Acetone (CAS 67-64-1)

#### **California Proposition 65**



WARNING: This product can expose you to chemicals including Benzene, which is known to the State of

California to cause cancer and birth defects or other reproductive harm. For more information go

to www.P65Warnings.ca.gov.

#### California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene (CAS 71-43-2) Listed: February 27, 1987 Cumene (CAS 98-82-8) Listed: April 6, 2010 Ethylbenzene (CAS 100-41-4) Listed: June 11, 2004 Naphthalene (CAS 91-20-3) Listed: April 19, 2002

### California Proposition 65 - CRT: Listed date/Developmental toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997 Toluene (CAS 108-88-3) Listed: January 1, 1991

#### California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997

## US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Acetone (CAS 67-64-1)

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No

Elevate Single Ply LVOC Splice Wash 955258 Version #: 01 Revision date: -Issue date: 28-February-2023

On inventory (yes/no)\* Country(s) or region Inventory name China Inventory of Existing Chemical Substances in China (IECSC) Inventory of Existing and New Chemical Substances (ENCS) Japan No Korea Existing Chemicals List (ECL) Yes New Zealand New Zealand Inventory Yes **Philippines** Philippine Inventory of Chemicals and Chemical Substances Yes (PICCS)

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

# 16. Other information, including date of preparation or last revision

Issue date 28-February-2023

Revision date - Version # 01

HMIS® ratings Health: 3

Flammability: 3 Physical hazard: 0

Disclaimer Holcim Solutions and Products US, LLC cannot anticipate all conditions under which this

information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience

currently available.

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).