

Technical Information Sheet



SKYSCAPE™ CAPILLARY MAT

Item Description	Item Number
28 oz Capillary Mat	Custom
36 oz Capillary Mat	Custom

DESCRIPTION

SkyScape Capillary Mat is a thick geotextile mat made from mechanically consolidated, needle punched, fine-denier, polyester fibers. It offers exceptional water storage capacity, superior to that of many dimpled plastic drainage sheets, and it wicks water vertically. Typically used with sloped systems to aid in water retention.

METHOD OF APPLICATION

- Starting at one corner of the highest part of the roof, unroll SkyScape Capillary Mat. Ends and sides should overlap approximately 2" (51 mm).
- Cut to remove any leftover material.

STORAGE

- Deliver and store products in original packaging with Manufacturer's labels and materials list intact and signed off.
- Store Products in designated weather protected areas, elevated from ground, and protected from environmental damage.

CLEAN-UP

- Gather and dispose all debris upon completion of work.
- Clean all surfaces and inspect final assembly for approval.

LEED® INFORMATION

Post-consumer recycled content: 100%

Post-industrial recycled content: 0%

Manufacturing location: Murfreesboro, TN

NOTE: LEED® is a registered trademark of the U.S. Green Building Council

TYPICAL PROPERTIES			
Property	SkyScape Drainage Panel		Test Method
	28 oz	36 oz	
Roll Dimensions	6' x 555' (1.8 m x 15.2 m)	6' x 33' (1.8 m x 10.1 m)	---
Roll Area	300 ft ² (227.9 m ²)	200 ft ² (18.6 m ²)	---
Roll Weight	60 lb (27 kg)	45 lb (20 kg)	---
Dry Weight	28 oz/yd ² (949 g/m ²)	36 oz/yd ² (1,221 g/m ²)	ASTM D5261
Thickness	3/16" (4.8 mm)	5/16" (7.9 mm)	ASTM D5729
Water Retention	0.1 gal/ft ² (4 L/m ²)	1.8 gal/ft ² (79 L/m ²)	ASTM D2398
Saturated Density	1.1 lb/ft ² (5.4 kg/m ²)	1.7 lb/ft ² (8.3 kg/m ²)	ASTM D2398
Capillary Rise (after 24 hours)	6.5" (64 mm)	2.5" (64 mm)	--
Static Puncture	1120 lb (508 kg)	1530 lb (694 kg)	ASTM D6241
Pin Puncture	280 lb (127 kg)	310 lb (141 kg)	ASTM D4833
Elongation	50%	50%	ASTM D4632
Grab Tensile	560 lb (254 kg)	450 lb (204 kg)	ASTM D4632
Trapezoidal Tear	200 lb (91 kg)	210 lb (95 kg)	ASTM D533

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Amrize takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Amrize nor its representatives practice architecture. Amrize offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Amrize accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Amrize representative is authorized to vary this disclaimer.