

Technical Information Sheet



SkyScape™ Sedum Cuttings

Item Description
Sedum Cuttings

Description

Bulk Sedum Cuttings may be used for overplanting plug installations, filling in sparse areas, enhancing SkyScape Sedum Mat plant production, and for certain projects as the primary green roof planting. Cuttings are cultivated from the wide variety of SkyScape Sedum species (see next page for list) and can easily be installed by one crew member.

Method of Application

- Hand cast cuttings directly over a minimum 2" (51 mm) depth freshly-wetted growing media, at the required rate for the intended application. Use of a temporary hydro mulch, a lightweight erosion control blanket, or sand/topsoil or sand/compost mix can help hold the cuttings in place in windy conditions. Once broadcast, daily thorough watering of SkyScape Sedum Cuttings for the first several weeks will help encourage root establishment.
- Cuttings are provided in bulk bags [typically 20 lb (9 kg) or 50 lb (23 kg)].

Storage

- Deliver and store products in original packaging with manufacturer's labels and materials list intact and signed off.
- Store products in designated weather protected areas, elevated from ground and protected from environmental damage.

Shelf Life

- Sedum Cuttings should be installed immediately upon delivery.
- If inclement weather forces overnight storage, product must be placed in a cool, shaded (or air-conditioned indoor) location.

Coverage Rate

Standard distribution rate is 10 lb per 100 ft² (5 kg per 10 m²). Rates may vary with need [fill-in or overplanting rate could be as low as 5 lb per 100 ft² (2.4 kg per 10 m²)].

Clean-Up

- Gather and dispose all debris upon completion of work.
- Clean all surfaces and inspect final assembly for approval.

LEED® Information

Post-Consumer Recycled Content: 0%
 Post Industrial Recycled Content: 0%
 Manufacturing Location: Murfreesboro, TN

NOTE: LEED® is a registered trademark of the U.S. Green Building Council

Typical Properties	
Property	Value
Length	0.5" to 3.0" (13 to 76 mm)
Number of cuttings (depending on variety)	200 to 600 per pound (90 to 272 per kilogram)
Sedum Varieties Included (typical)	<i>Delosperma cooperi</i> , <i>Sedum</i> 'Autumn Joy', <i>Sedum</i> 'Bertram Anderson', <i>Sedum</i> 'Weihestephaner Gold', <i>Sedum album</i> 'Coral Carpet', <i>Sedum album</i> 'France', <i>Sedum album</i> 'Murale', <i>Sedum hispanicum</i> , <i>Sedum hybridum</i> 'Immergrunchen', <i>Sedum k.</i> 'Golden Carpet', <i>Sedum kamtschaticum</i> , <i>Sedum reflexum</i> 'Blue Spruce', <i>Sedum rupestra</i> 'Angelina', <i>Sedum sexangulare</i> , <i>Sedum spurium</i> 'Dragon's Blood', <i>Sedum spurium</i> 'Fuldaglut', <i>Sedum spurium</i> 'John Creech', <i>Sedum spurium</i> 'Roseum', <i>Sedum spurium</i> 'Superbum'

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.

Firestone, the brand of premier roofing, wall, and lining systems you know and trust, will be coming to you under a new name: Elevate. During our transition, products carrying the brand name **Firestone** will change to **Elevate** on product labels and packaging, Technical Information Sheets, and elsewhere. Only the brand name is changing. Our products remain the same.

For further information on our brand transition to Elevate, scan the code below with your smartphone, or visit our website: www.holcimelevate.com

