

Technical Information Sheet



SKYSCAPE™ SLOPE CLEATS

Item Description	Item Number
Slope Cleats	Custom

DESCRIPTION

The SkyScape Slope Cleat helps stabilize SkyScape Growing Media at slopes greater than 2:12 or 10°. Each Slope Cleat features preformed hooks at both ends which easily clip into the SkyScape Geogrid.

METHOD OF APPLICATION

1. Starting at the highest point of the roof, set a row of cleats at the distance shown on the spacing guide located below. Clip each hook at the end of the cleat into the SkyScape Geogrid.
2. To help with growing media stabilization, offset the next row by starting the first cleat with its outside end directly underneath the midpoint of the row above.
3. Repeat the row spacing and offset to the lowest point in the roof.

STORAGE

- Deliver and store products in original packaging with Manufacturer's labels and materials list intact and signed off.
- Store products in designated weather protected areas, elevated from ground, and protected from environmental damage.

COVERAGE RATE

Slope	Cleat Spacing
2:12 to 3:12 (10° to 14°)	50" (1.27 mm)
3:12 to 4:12 (14° to 18°)	40" (1.02 mm)
4:12 to 5:12 (18° to 23°)	30" (762 mm)
5:12 to 6:12 (23° to 26°)	20" (508 mm)
6:12 to 7:12 (26° to 30°)	10" (254 mm)

SHELF LIFE

Indefinite

TIS 1919

September 9, 2025

Sales: (800) 428-4442

Technical: (800) 428-4511

Page 1

CLEAN-UP

- Gather and dispose all debris upon completion of work.
- Clean all surfaces and inspect final assembly for approval.

LEED® INFORMATION

Post-consumer recycled content: 0%
Post-industrial recycled content: 100%
Manufacturing location: Murfreesboro, TN
NOTE: LEED® is a registered trademark of the U.S. Green Building Council

Typical Properties	
Property	Value
Dimension	28½" x 3⅛" x 2⅜" (724 mm x 79 mm x 60 mm)
Material	Recycled ABS Plastic

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Amrize takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Amrize nor its representatives practice architecture. Amrize offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Amrize accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Amrize representative is authorized to vary this disclaimer.

TIS 1919

September 9, 2025

Sales: (800) 428-4442

Technical: (800) 428-4511

Page 2