

Technical Information Sheet



SKYSCAPE™ STORMWATER MAX GROWING MEDIA

Item Description	Item Number
Stormwater Growing Medium	Custom

DESCRIPTION

SkyScape Stormwater Max Growing Media is an engineered, lightweight, soil-less mix of organic and inorganic components specifically designed to maximize the benefits of retaining and remediating storm water run-off. This medium has also been designed to support a wide variety of vegetation while maximizing the functionality of the vegetative roof system to offset the storm water footprint of the building.

METHOD OF APPLICATION

1. SkyScape Stormwater Max Growing Media is typically delivered in 2 cubic yard (1.5 m³) super sacks. The medium may also be delivered in bulk and blown to the roof by blower trucks; application by blower truck may be requested through Amrize Estimating Services at the time of project quotation.
2. Install all SkyScape Drainage, Edging, and all other related components according to the design and to their application instructions.
3. Hoist super sacks to the roof and bring them to a hover within 3-5 vertical feet over the installation zone.
4. Cut the bottom of the sack using a box cutter and allow the media to deposit on the drainage materials.
5. Evenly spread the medium to the desired depth by lightly raking the media across vegetative roof area.
6. Dampen the media with a fine mist of water.
7. Install vegetation according to the design.

STORAGE

- Deliver and store products in original packaging with Manufacturer's labels and materials list intact and signed off.
- Store Products in designated weather protected areas and protected from environmental damage.

CLEAN-UP

- Gather and dispose all debris upon completion of work.
- Clean all surfaces and inspect final assembly for approval.

PRECAUTIONS

Wash hands, arms, and any exposed skin thoroughly after installation.

LEED® INFORMATION

Post-consumer recycled content: 0%

Post-industrial recycled content: 0%

Manufacturing location: Varies with regional location of project

NOTE: LEED® is a registered trademark of the U.S. Green Building Council

TYPICAL PROPERTIES		
Property	Value	ASTM
Pore Volume	>60%	---
Air Filled Porosity	>10%	---
Saturated Hydraulic Conductivity	>15" per hour (381 mm/hr)	---
Water Holding Capacity	>60%	E2399
Dry Weight	30 – 38 lb/ft ³ (481 – 609 kg/m ³)	E2399
Maximum Media Density at Saturation	68 – 71 lb/ft ³ (1,089 – 1,137 kg/m ³)	---
Medium Retention Value	0.49	---
pH	6.0 – 7.5	---
EC	<1.75	---

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Amrize takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Amrize nor its representatives practice architecture. Amrize offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Amrize accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Amrize representative is authorized to vary this disclaimer.