#### **Safety Data Sheet**

## Firestone Building Products Company

### Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

#### 1.1 Product identifier

**Product Name** 

Splice Adhesive SA-1065

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified use(s)

· Roof Application - Adhesive

Use(s) advised against

· Anything other than roof application.

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer

Firestone Building Products Company

200 4th Avenue S

Nashville, TN 37201-2208

**United States** 

firestonemsds@bfdp.com

**Telephone (General)** • 800-428-4442

#### 1.4 Emergency telephone number

Manufacturer

• (800) 424-9300 - CHEMTREC

Manufacturer

• (703) 527-3887 - CHEMTREC - International

#### Section 2: Hazards Identification

#### **EU/EEC**

According to: Regulation (EC) No 1272/2008 (CLP)/REACH 1907/2006 [amended by 2015/830]

According to: EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

#### 2.1 Classification of the substance or mixture

CLP

Flammable Liquids 2 - H225

Skin Irritation 2 - H315

Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects - H336

Reproductive Toxicity 2 - H361fd

Specific Target Organ Toxicity Repeated Exposure 2 - H373 Hazardous to the aquatic environment Chronic 3 - H412

DSD/DPD Highly Flammable (F)

Irritant (Xi)

Harmful (Xn)

Substances Toxic To Reproduction - Category 3 R11, R38, R48/20, R62, R63, R67, R52, R53

### 2.2 Label Elements

**CLP** 

#### **DANGER**







#### Hazard statements •

H225 - Highly flammable liquid and vapour

H315 - Causes skin irritation

H336 - May cause drowsiness or dizziness

H361fd - Suspected of damaging fertility. Suspected of damaging the unborn child. H373 - May cause damage to organs Central Nervous System and Nervous System

through prolonged or repeated exposure

H412 - Harmful to aquatic life with long lasting effects

#### **Precautionary statements**

**Prevention •** P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground and/or bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting/equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P260 - Do not breathe mist/vapours/spray.

P264 - Wash thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

#### Response •

P370+P378 - In case of fire: Use appropriate media to extinguish.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 - Call a POISON CENTER/doctor if you feel unwell.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P321 - Specific treatment, see supplemental first aid information.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention. P308+P313 - IF exposed or concerned: Get medical advice/attention.

P314 - Get medical advice/attention if you feel unwell.

#### Storage/Disposal •

P235 - Keep cool.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P501 - Dispose of content and/or container in accordance with local, regional,

national, and/or international regulations.

# DSD/DPD

**Supplemental information** • 25-35 percent of this product consists of an ingredient of unknown toxicity.







**Risk phrases** • R11 - Highly flammable.

R38 - Irritating to skin.

R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R62 - Possible risk of impaired fertility.

R63 - Possible risk of harm to the unborn child.

R67 - Vapours may cause drowsiness and dizziness.

R52 - Harmful to aquatic organisms.

R53 - May cause long-term adverse effects in the aquatic environment.

#### Safety phrases •

S9 - Keep container in a well ventilated place

S16 - Keep away from sources of ignition - No Smoking.

S37 - Wear suitable gloves.

#### 2.3 Other Hazards

• According to Regulation (EC) No. 1272/2008 (CLP) this material is considered

hazardous.

• According to European Directive 1999/45/EC this preparation is considered

dangerous.

### **United States (US)**

According to: OSHA 29 CFR 1910.1200 HCS

#### 2.1 Classification of the substance or mixture

OSHA HCS 2012 • Flammable Liquids 2

Acute Toxicity Oral 4 Skin Irritation 2 Eye Irritation 2A

Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects

Reproductive Toxicity 2

Specific Target Organ Toxicity Repeated Exposure 2

# 2.2 Label elements OSHA HCS 2012

#### **DANGER**







#### Hazard statements • 1

Highly flammable liquid and vapour

Harmful if swallowed Causes skin irritation

Causes serious eye irritation May cause drowsiness or dizziness

Suspected of damaging fertility or the unborn child.

May cause damage to organs Central Nervous System and Nervous System through

prolonged or repeated exposure

#### **Precautionary statements**

**Prevention** • Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.

Keep container tightly closed.

Ground and/or bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe mist/vapours/spray. Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

**Response** • In case of fire: Use appropriate media for extinction.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

IF ON SKIN (or hair):

Rinse skin with water/shower.

If skin irritation occurs: Get medical advice/attention. Specific treatment, see supplemental first aid information. Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician if you feel

unwell.

Rinse mouth.

IF exposed or concerned: Get medical advice/attention.

Storage/Disposal • Keep cool.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of content and/or container in accordance with local, regional, national, and/or

international regulations.

**Supplemental information** • 25-35 percent of this product consists of an ingredient of unknown toxicity.

2.3 Other hazards

**OSHA HCS 2012** 

 Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

#### Canada

According to: WHMIS

#### 2.1 Classification of the substance or mixture

**WHMIS** • Flammable Liquids - B2

Other Toxic Effects - D2A Other Toxic Effects - D2B

2.2 Label elements

WHMIS .





WHMIS
 Flammable Liquids - B2

Other Toxic Effects - D2A Other Toxic Effects - D2B

2.3 Other hazards

WHMIS
 In Canada, the product mentioned above is considered hazardous under the

Workplace Hazardous Materials Information System (WHMIS).

#### 2.4 Other information

20-25 percent of this product consists of an ingredient of unknown toxicity.

See Section 12 for Ecological Information.

## Section 3 - Composition/Information on Ingredients

#### 3.1 Substances

 Material does not meet the criteria of a substance in accordance with Regulation (EC) No 1272/2008.

#### 3.2 Mixtures

Composition						
Chemical Name	Identifiers	%	1 D50/I G50	Classifications According to Regulation/Directive	Comments	
				EU DSD/DPD: Annex I - F; R11 Repr. Cat. 3; R63		

Toluene	CAS:108-88-3 EC Number:203- 625-9 UN:UN1294	20% TO 50%		Xn; R48/20-65 R67 Xi; R38 <b>EU CLP:</b> Annex VI - Flam. Liq. 2, H226; Repr. 2, H361d; Asp. Tox. 1, H304; STOT RE 2 * H373; Skin Irrit. 2, H315; STOT SE 3, H336 <b>OSHA HCS 2012:</b> Flam. Liq. 2; Eye Irrit. 2A; Skin Irrit. 2; Repr. 2; Acute Tox. 4 (oral); STOT SE 3: Narc.; Asp. Tox. 1	NDA
Xylene	CAS:1330-20- 7 EC Number:215- 535-7 UN:UN1307	2.5% TO 10%		EU DSD/DPD: Annex I - R10 Xn; R20/21 Xi; R38 EU CLP: Annex VI - Flam. Liq. 3, H226; Acute Tox. 4 * H312; Acute Tox. 4 * H332; Skin Irrit. 2 , H315 OSHA HCS 2012: Flam. Liq. 3; Acute Tox. 4 (skin); Eye Irrit. 2A; Skin Irrit; 2, Repr. 2 (inhalation)	NDA
Hexane	CAS:110-54-3 EC Number:203- 777-6	5% TO 20%		EU DSD/DPD: Annex I - F; R11; Repr. 3; R62; Xn; R65-48/20; Xi; R38; R67; N; R51-53 EU CLP: Annex VI - Flam. Liq. 2, H225; Repr. 2, H361f; Asp. Tox. 1, H304; STOT RE 2*, H373; Skin Irrit. 2, H315; STOT SE 3: Narc., H336; Aquatic Chronic 2, H411 OSHA HCS 2012: Flam. Liq. 2; Repr. 2; STOT RE 2 - CNS & Nervous System; Skin Irrit. 2; Eye Irrit. 2B; STOT SE 3: Narc. & Resp. Irrit.; Asp. Tox. 1	NDA
1,6- Diisocyanatohexane homopolymer	CAS:28182-81 -2 EC Number:500- 060-2	< 2.5%	Inhalation-Rat LC50 • 18500 mg/m³ 1 Hour(s)	EU DSD/DPD: Self Classified - Xi, R36/38 EU CLP: Self Classified - Eye Irrit. 2A, Skin Irrit 2 OSHA HCS 2012: Eye Irrit. 2A, Skin Irrit 2	NDA
Isobutylene-Isoprene polymer	<b>CAS</b> :9010-85-9	20% TO 30%	NDA	EU DSD/DPD: Data Lacking EU CLP: Data Lacking OSHA HCS 2012: Data Lacking	NDA

See Section 11 for Toxicological Information.

#### Section 4 - First Aid Measures

### 4.1 Description of first aid measures

Inhalation

• IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. Get medical attention immediately if symptoms occur.

Skin

 Rinse skin with rubbing alcohol first, followed immediately by washing affected area with soap and water. Remove and isolate contaminated clothing and shoes. If skin irritation occurs: Get medical advice/attention.

Eye

• In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.

Ingestion

 If swallowed, rinse mouth with water (only if the person is conscious) Do NOT induce vomiting. Do not give anything by mouth to an unconscious person. Get medical attention immediately if symptoms occur.

### 4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 - Toxicological Information.

#### 4.3 Indication of any immediate medical attention and special treatment needed

**Notes to Physician** 

All treatments should be based on observed signs and symptoms of distress in the
patient. Consideration should be given to the possibility that overexposure to materials
other than this product may have occurred.

### Section 5 - Firefighting Measures

### 5.1 Extinguishing media

Suitable Extinguishing Media •

LARGE FIRE: Water spray, fog or regular foam. SMALL FIRES: Dry chemical, CO2, water spray or regular foam.

Unsuitable Extinguishing Media

· No data available.

#### 5.2 Special hazards arising from the substance or mixture

**Unusual Fire and Explosion Hazards** 

 Heat builds up pressure in closed containers. Cool with water stream. Toxic fumes and vapors may be produced.

**Hazardous Combustion Products** 

Carbon dioxide, carbon monoxide, acrid smoke, irritating fumes.

### 5.3 Advice for firefighters

 Structural firefighters' protective clothing provides limited protection in fire situations ONLY: it is not effective in spill situations where direct contact with the substance is possible.

Wear positive pressure self-contained breathing apparatus (SCBA). Wear chemical protective clothing that is specifically recommended by the

manufacturer. It may provide little or no thermal protection.

Runoff from fire control may cause pollution.

LARGE FIRES: Dike fire-control water for later disposal.

#### Section 6 - Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### **Personal Precautions**

 CAUTION: Victim may be a source of contamination. Do not touch or walk through spilled material.

#### **Emergency Procedures**

As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions. LARGE SPILL: Consider initial downwind evacuation for at least 300 meters (1000 feet) ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.

### 6.2 Environmental precautions

Prevent entry into waterways, sewers, basements or confined areas.

### 6.3 Methods and material for containment and cleaning up

#### Containment/Clean-up Measures

Stop leak if you can do it without risk.

Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Use clean non-sparking tools to collect absorbed material. A vapor suppressing foam may be used to reduce vapors.

All equipment used when handling the product must be grounded. LARGE SPILLS: Dike far ahead of liquid spill for later disposal.

LARGE SPILLS: Water spray may reduce vapor; but may not prevent ignition in closed spaces.

#### 6.4 Reference to other sections

 Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

## Section 7 - Handling and Storage

## 7.1 Precautions for safe handling

Format: EU CLP/REACH Language: English (US) EU DSD/DPD, EU CLP, OSHA HCS 2012, WHMIS

#### Handling

• Do not use in areas without adequate ventilation. Handle and open container with care. Use good safety and industrial hygiene practices.

## 7.2 Conditions for safe storage, including any incompatibilities

**Storage** 

• Keep away from fire. Store in a well-ventilated place. Keep container tightly closed.

### 7.3 Specific end use(s)

· Refer to Section 1.2 - Relevant identified uses.

## **Section 8 - Exposure Controls/Personal Protection**

### 8.1 Control parameters

				Expos	sure Limits	/Guideline	s			
	Res	ult	ACGIH	Canad	da Ontario	Canada Q	uebec	China	Europe	
Xylene STE		Ls 150	150 ppm STEL		150 ppm STEL		150 ppm STEV; 651 mg/m3 STEV		Not established	
(1330-20-7)	TWA	As 100	ppm TWA	100 ppm	TWA	100 ppm TW/ mg/m3 TWAE		50 mg/m3 TWA	Not established	
Hexane	TWA	As 50 p	pm TWA	50 ppm 1	ΓWA	50 ppm TWA mg/m3 TWAE		100 mg/m3 TWA	20 ppm TWA; 72 mg/m3 TWA	
(110-54-3)	STE	Ls Not	established	Not estat	olished	Not establish	ed	180 mg/m3 STEL	Not established	
Toluene	STE	Ls Not	established	Not estat	olished	Not establishe	ed	100 mg/m3 STEL	100 ppm STEL; 384 mg/m3 STEL	
(108-88-3)	TWA	As 20 p	pm TWA	20 ppm 1	ΓWA	50 ppm TWA mg/m3 TWAE		50 mg/m3 TWA	50 ppm TWA; 192 mg/m3 TWA	
			E	xposure	Limits/Gu	idelines (Co	on't.)			
		Result	Germany I	DFG	Germai	ny TRGS		NIOSH	OSHA	
Xylene		TWAs Not established			100 ppm TWA AGW (all isomers, exposure factor 2); 440 mg/m3 TWA AGW (all isomers, exposure factor 2)		Not esta	blished	100 ppm TWA; 435 mg/m3 TWA	
(1330-20-7)	-	Ceilings	200 ppm Peak (all isomers); 880 mg/m3 Peak (all isomers)		Not established Not e		Not esta	blished	Not established	
		MAKs	100 ppm TWA M mg/m3 TWA MAR			ned	Not esta	blished	Not established	
Hexane		TWAs	As Not established		50 ppm TWA AGW (exposure factor 8); 180 mg/m3 TWA AGW (exposure factor 8)		50 ppm <sup>·</sup> TWA	TWA; 180 mg/m3	500 ppm TWA; 1800 mg/m3 TWA	
(110-54-3)		Ceilings	400 ppm Peak; 1- mg/m3 Peak	440	Not established		Not established		Not established	
		MAKs	50 ppm TWA MA mg/m3 TWA MAk		Not established		Not established		Not established	
		Ceilings	200 ppm Peak; 76 Peak	60 mg/m3	Not establish	ned	Not esta	blished	300 ppm Ceiling	
					50 ppm TWA risk of dama embryo or fe excluded wh BGW values	ge to the etus can be en AGW and				

Toluene (108-88-3)	TWAs	Not established	observed, exposure factor 4); 190 mg/m3 TWA AGW (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed, exposure factor 4)	100 ppm TWA; 375 mg/m3 TWA	200 ppm TWA
	STELs	Not established	Not established	150 ppm STEL; 560 mg/m3 STEL	Not established
	MAKs	50 ppm TWA MAK; 190 mg/m3 TWA MAK	Not established	Not established	Not established

#### **Exposure Control Notations**

#### China

Toluene (108-88-3): Skin: (Skin notation)Hexane (110-54-3): Skin: (Skin notation)

#### Canada Ontario

•Hexane (110-54-3): **Skin:** (Absorption through skin, eyes, or mucous membranes)

#### Canada Quebec

Toluene (108-88-3): Skin: (Skin designation)
Hexane (110-54-3): Skin: (Skin designation)

#### **ACGIH**

- •Toluene (108-88-3): **Carcinogens:** (A4 Not Classifiable as a Human Carcinogen) •Xylene (1330-20-7): **Carcinogens:** (A4 Not Classifiable as a Human Carcinogen)
- •Hexane (110-54-3): Skin: (Skin potential significant contribution to overall exposure by the cutaneous route)

#### **Germany TRGS**

- •Toluene (108-88-3): Skin: (skin notation)
- •Xylene (1330-20-7): Skin: (skin notation (all isomers))

#### **Germany DFG**

- •Toluene (108-88-3): **Pregnancy:** (no risk to embryo/fetus if exposure limits adhered to) | **Skin:** (skin notation) •Xylene (1330-20-7): **Pregnancy:** (classification not yet possible (all isomers)) | **Skin:** (skin notation (all isomers))
- •Hexane (110-54-3): Pregnancy: (no risk to embryo/fetus if exposure limits adhered to)

# **Exposure Limits Supplemental** ACGIH

- •Toluene (108-88-3): **BEIs:** (0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene; 0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene; 0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)) | **TLV Basis Critical Effects:** (female reproductive; pregnancy loss; visual impairment)
- •Xylene (1330-20-7): **BEIs**: (1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids) | **TLV Basis Critical Effects**: (CNS impairment; eye and upper respiratory tract irritation)
- •Hexane (110-54-3): **BEIs:** (0.4 mg/L Medium: urine Time: end of shift at end of workweek Parameter: 2,5-Hexanedione without hydrolysis) | **TLV Basis Critical Effects:** (CNS impairment; eye irritation; peripheral neuropathy)

### 8.2 Exposure controls

# **Engineering Measures/Controls**

This material is designed to be used outdoors, in roofing applications. Good general
ventilation should be used. Ventilation rates should be matched to conditions. If
applicable, use process enclosures, local exhaust ventilation, or other engineering
controls to maintain airborne levels below recommended exposure limits. If exposure
limits have not been established, maintain airborne levels to an acceptable level.

#### **Personal Protective Equipment**

Respiratory

• Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.

Eye/Face Skin/Body

- Wear protective eyewear (goggles, face shield, or safety glasses).
- Wear appropriate gloves.

# **Environmental Exposure Controls**

 In case of spills, keep product clear of sewers, waterways or land areas. Dispose of waste product in accordance with national and local laws and regulations.

### **Section 9 - Physical and Chemical Properties**

### 9.1 Information on Basic Physical and Chemical Properties

Material Description			
Physical Form	Liquid	Appearance/Description	Black viscous liquid with aromatic odor.
Color	Black	Odor	Aromatic
Odor Threshold	Data lacking		
General Properties	-		-
Boiling Point	217 °F(102.7778 °C)	Melting Point/Freezing Point	Data lacking
Decomposition Temperature	Data lacking	Heat of Decomposition	Data lacking
рН	Data lacking	Specific Gravity/Relative Density	= 0.86 Water=1
Water Solubility	Negligible < 0.1 %	Viscosity	Not relevant
Explosive Properties	Explosion hazard.	Oxidizing Properties:	Static hazard.
Volatility	-		-
Vapor Pressure	120 mmHg (torr) @ 20 °C(68 °F)	Vapor Density	> 3.7 Air=1
Evaporation Rate	1.9 to 9.5 n-Butyl Acetate = 1	Volatiles (Wt.)	71.4 %
Flammability	-	•	
Flash Point	1 °F(-17.2222 °C) TCC (Tagliabue Closed Cup)	UEL	7.4 %
LEL	1.2 %	Autoignition	Product is not self-igniting.
Flammability (solid, gas)	Not relevant.		
Environmental			
Octanol/Water Partition coefficient	Data lacking		

#### 9.2 Other Information

No additional physical and chemical parameters noted.

## Section 10: Stability and Reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

Stable under normal temperatures and pressures.

### 10.3 Possibility of hazardous reactions

· Hazardous polymerization will not occur.

#### 10.4 Conditions to avoid

 Avoid flames, sparks, and other sources of ignition. Avoid contact with combustible materials. Avoid contact with incompatible materials.

### 10.5 Incompatible materials

· Acids, bases, combustible materials, oxidizing materials.

### 10.6 Hazardous decomposition products

• Thermal decomposition could produce CO, CO2, and Oxides of Nitrogen.

## **Section 11 - Toxicological Information**

## 11.1 Information on toxicological effects

	Components							
Toluene (20% TO 50%)	108- 88-3	Acute Toxicity: Ingestion/Oral-Rat LD50 • 636 mg/kg; Inhalation-Rat LC50 • 49 g/m³ 4 Hour(s); Skin-Rabbit LD50 • 14100 µL/kg; Irritation: Eye-Rabbit • 2 mg 24 Hour(s) • Severe irritation; Skin-Rabbit • 20 mg 24 Hour(s) • Moderate irritation; Reproductive: Inhalation-Rat TCLo • 800 mg/m³ 6 Hour(s)(14-20D preg); Reproductive Effects:Effects on Embryo or Fetus:Fetotoxicity (except death, e.g., stunted fetus); Reproductive Effects:Effects on Newborn:Behavioral						
Xylene (2.5% TO 10%)	1330- 20-7	Acute Toxicity: Ingestion/Oral-Rat LD50 • 4300 mg/kg; Liver:Other changes; Kidney, Ureter, and Bladder:Other changes; Inhalation-Rat LC50 • 5000 ppm 4 Hour(s); Skin-Rabbit LD50 • >1700 mg/kg; Irritation: Eye-Rabbit • 5 mg 24 Hour(s) • Severe irritation; Skin-Rabbit • 500 mg 24 Hour(s) • Moderate irritation; Reproductive: Inhalation-Rat TCLo • 50 mg/m³ 6 Hour(s)(1-21D preg); Reproductive Effects:Specific Developmental Abnormalities:Musculoskeletal system; Reproductive Effects:Specific Developmental Abnormalities:Other developmental abnormalities; Reproductive Effects:Effects on Newborn:Growth statistics (e.g., reduced weight gain)						
Hexane (5% TO 20%)	110- 54-3	Acute Toxicity: Ingestion/Oral-Rat LD50 • 25 g/kg; Inhalation-Rat LC50 • 48000 ppm 4 Hour(s); Irritation: Eye-Rabbit • 10 mg • Mild irritation; Reproductive: Inhalation-Rat TCLo • 5000 ppm (6-19D preg); Reproductive Effects:Specific Developmental Abnormalities:Musculoskeletal system; Reproductive Effects:Specific Developmental Abnormalities:Urogenital system						

GHS Properties	Classification
Acute toxicity	EU/CLP • Classification criteria not met OSHA HCS 2012 • Acute Toxicity - Oral 4
Skin corrosion/Irritation	EU/CLP • Skin Irritation 2 OSHA HCS 2012 • Skin Irritation 2
Serious eye damage/Irritation	EU/CLP • Classification criteria not met OSHA HCS 2012 • Eye Irritation 2A
Skin sensitization	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Respiratory sensitization	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Aspiration Hazard	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Carcinogenicity	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Germ Cell Mutagenicity	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Toxicity for Reproduction	EU/CLP • Toxic to Reproduction 2 OSHA HCS 2012 • Toxic to Reproduction 2
STOT-SE	EU/CLP • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects OSHA HCS 2012 • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects
STOT-RE	EU/CLP • Specific Target Organ Toxicity Repeated Exposure 2 OSHA HCS 2012 • Specific Target Organ Toxicity Repeated Exposure 2

# Route(s) of entry/exposure Potential Health Effects

• Skin, Eye

#### Inhalation

Acute (Immediate)

 May be harmful. May affect the central nervous system. Symptoms may include dizziness, drowsiness, lethargy, coma and death.

Chronic (Delayed)

Repeated and prolonged expousre may cause Central Nervous System (CNS) effects.

Skin

Acute (Immediate)

· Causes skin irritation.

**Chronic (Delayed)** 

· No data available.

Eye

Acute (Immediate)

· Causes serious eye irritation.

**Chronic (Delayed)** 

· No data available.

Ingestion

Acute (Immediate)

May be harmful.

**Chronic (Delayed)** 

· No data available.

**Reproductive Effects** 

Repeated and prolonged exposure may cause reproductive effects.

### Section 12 - Ecological Information

### 12.1 Toxicity

 This material may be toxic to aquatic organisms and cause long-term adverse effects in the aquatic environment.

### 12.2 Persistence and degradability

No information available for the product.

## 12.3 Bioaccumulative potential

No information available for the product.

## 12.4 Mobility in Soil

No information available for the product.

#### 12.5 Results of PBT and vPvB assessment

PBT and vPvB assessment has not been carried out.

#### 12.6 Other adverse effects

· No studies have been found.

## Section 13 - Disposal Considerations

#### 13.1 Waste treatment methods

**Product waste** 

 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

## Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	UN1133	Adhesives	3		NDA

TDG	UN1133	ADHESIVES	3	II	NDA
IMO/IMDG	UN1133	ADHESIVES	3	II	NDA
ADN	UN1133	ADHESIVES	3	II	NDA
ADR/RID	UN1133	Adhesives	3	II	NDA
IATA/ICAO	UN1133	Adhesives	3	II	NDA

- 14.6 Special precautions for user
- None known.
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code
- · Not relevant.
- 14.8 Other information
- **DOT** Toluene has a reportable quantity of 1000 lbs (454 kg) as listed in Appendix A to 49 CFR 172.101. Xylene has a reportable quantity of 1000 lbs (454 kg) as listed in Appendix A to 49 CFR 172.101. Hexane has a reportable quantity of 5000 lbs (2270 kg) as listed in Appendix A to 49 CFR 172.101.

## **Section 15 - Regulatory Information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications • Acute, Chronic, Fire

State Right To Know							
Component	CAS	MA	NJ	PA			
1,6- Diisocyanatohexane homopolymer	28182-81-2	No	No	No			
Hexane	110-54-3	Yes	Yes	Yes			
Isobutylene- Isoprene polymer	9010-85-9	No	No	No			
Toluene	108-88-3	Yes	Yes	Yes			
Xylene	1330-20-7	Yes	Yes	Yes			

CAS 28182-81-2	Canada DS	SL Canada NDSL	China	EU EIN	EC9	EU ELNICS
8182-81-2					LUJ	EU ELNICS
	Yes	No	Yes	No		No
10-54-3	Yes	No	Yes	Yes	S	No
010-85-9	Yes	No	Yes	No		No
08-88-3	Yes	No	Yes	Yes	s	No
330-20-7	Yes	No	Yes	Yes	S	No
		Inventory (Con	n't.)			
	CAS	Japan ENCS	Korea KE	CL		TSCA
1,6-Diisocyanatohexane homopolymer 28182-81-2		Yes	Yes		Yes	
110-5	4-3	Yes	Yes			Yes
	10-54-3 010-85-9 08-88-3 330-20-7	10-54-3 Yes 010-85-9 Yes 08-88-3 Yes 330-20-7 Yes	10-54-3 Yes No 10-54-3 Yes No 010-85-9 Yes No 08-88-3 Yes No 330-20-7 Yes No Inventory (Cor CAS Japan ENCS 28182-81-2 Yes	10-54-3   Yes	10-54-3   Yes	10-54-3   Yes

Isobutylene-Isoprene polymer	9010-85-9	Yes	Yes	Yes
Toluene	108-88-3	Yes	Yes	Yes
Xylene	1330-20-7	Yes	Yes	Yes

## Australia

Australia		
Labor		
Australia - Work Health and Safety Regulations - Hazardous Su		-
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
• Toluene	108-88-3	Not Listed
• Xylene	1330-20-7	Not Listed
Hexane	110-54-3	Not Listed
1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed
Australia - High Volume Industrial Chemicals List		
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
Toluene	108-88-3	
Xylene	1330-20-7	
Hexane	110-54-3	
• 1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed
Australia - List of Designated Hazardous Substances - Classifi	cation	
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
• Toluene	108-88-3	F, Xn, Xi Repr.Cat.3 R11, R63 R48/20, R65, R38, R67
Xylene	1330-20-7	Xn, Xi R10, R20/21, R38
• Hexane	110-54-3	F, Xn, Xi, N Repr.Cat.3 R11, R62, R48/20, R65, R38, R67, R51, R53
1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed
Environment		
Australia - National Pollutant Inventory (NPI) Substance List  • Isobutylene-Isoprene polymer	9010-85-9	Not Listed
ioobatyione toopiene polymor	3010-03-3	10 tonne/yr Threshold
Toluene	108-88-3	ro torine/yr rifleshold

Environment		
Australia - National Pollutant Inventory (NPI) Substance List		
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
Toluene	108-88-3	10 tonne/yr Threshold category 1
• Xylene	1330-20-7	10 tonne/yr Threshold category 1 (including individual or mixed isomers)
Hexane	110-54-3	10 tonne/yr Threshold category 1
1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed
Australia - Ozone Protection Act - Scheduled Substances		
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
• Toluene	108-88-3	Not Listed
• Xylene	1330-20-7	Not Listed
• Hexane	110-54-3	Not Listed
1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed
Australia - Priority Existing Chemical Program		
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
Toluene	108-88-3	Candidate chemical
Xylene	1330-20-7	Candidate chemical
Hexane	110-54-3	Not Listed

1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed
Bulgaria		
Environment		
Bulgaria - Air Quality - Maximum Admissible Hazardous Contaminant Le	vels - 24 Hour	
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
• Toluene	108-88-3	0.25 mg/m3 MAHCL
Xylene	1330-20-7	0.1 mg/m3 MAHCL
Hexane	110-54-3	Not Listed
1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed
Canada		
Labor		
Canada - WHMIS - Classifications of Substances		
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
Toluene	108-88-3	B2, D2A, D2B
Xylene	1330-20-7	B2, D2A, D2B
Hexane	110-54-3	B2, D2A, D2B
1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed
Canada - WHMIS - Ingredient Disclosure List		
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
• Toluene	108-88-3	1 %
Xylene	1330-20-7	Not Listed
Hexane	110-54-3	1 %
1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed
Environment		
Canada - CEPA - Priority Substances List		
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
• Toluene	108-88-3	Priority Substance List 1 (substance not considered toxic)
• Xylene	1330-20-7	Priority Substance List 1 (substance not considered toxic)
Hexane	110-54-3	Not Listed
1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed
Europe		
Other		
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Classification		
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
• Toluene	108-88-3	F; R11 Xi; R38 Xn; R48/20-65 Repr.Cat.3; R63 R67
• Xylene	1330-20-7	R10 Xn; R20/21 Xi; R38
Hexane	110-54-3	F; R11 Xi; R38 N; R51-53 Repr.Cat.3; R62 Xn; R65-48/20 R67
1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Concentration Limits		
Isobutylene-Isoprene polymer	9010-85-9	Not Listed

• Toluene	108-88-3	Not Listed
• Xylene	1330-20-7	12.5%<=C: Xn; R20/21
• Hexane	110-54-3	5%<=C: Xn; R48/20
1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Labelling		
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
• Toluene	108-88-3	F Xn R:11-38-48/20-63-65-67 S:(2)-36/37-46-62
• Xylene	1330-20-7	Xn R:10-20/21-38 S:(2)-25
		F Xn N R:11-38-48/20-62-65-
• Hexane	110-54-3	67-51/53 S:(2)-9-16-29-33-
		36/37-61-62
1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Notes - Substances and Preparations		
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
• Toluene	108-88-3	Not Listed
• Xylene	1330-20-7	С
• Hexane	110-54-3	Not Listed
1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Safety Phrases		
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
• Toluene	108-88-3	S:(2)-36/37-46-62
• Xylene	1330-20-7	S:(2)-25
• Hexane	110-54-3	S:(2)-9-16-29-33-36/37-61-62
• 1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed

### **Mexico**

Other Mexico - Hazard Classifications		
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
• Toluene	108-88-3	Hazard Class = 3 PG = II UN1294
		Hazard Class = 3 PG = II
• Xylene	1330-20-7	UN1307; Hazard Class = 3 PG = III UN1307
Hexane	110-54-3	Not Listed
• 1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed
Mexico - Regulated Substances		
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
• Toluene	108-88-3	UN1294
• Xylene	1330-20-7	UN1307; UN1307
Hexane	110-54-3	Not Listed
• 1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed

### **United States**

Labor U.S OSHA - Process Safety Management - Highly Hazardo	us Chemicals	
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
• Toluene	108-88-3	Not Listed
• Xylene	1330-20-7	Not Listed
Hexane	110-54-3	Not Listed

1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed
U.S OSHA - Specifically Regulated Chemicals		
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
• Toluene	108-88-3	Not Listed
• Xylene	1330-20-7	Not Listed
• Hexane	110-54-3	Not Listed
1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed
Environment		
U.S CAA (Clean Air Act) - 1990 Hazardous Air Pollutants		
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
• Toluene	108-88-3	
• Xylene	1330-20-7	(isomers and mixtures)
Hexane	110-54-3	
1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed
U.S CERCLA/SARA - Hazardous Substances and their Reportable Quantities		
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
• Toluene	108-88-3	1000 lb final RQ; 454 kg final RQ
• Xylene	1330-20-7	100 lb final RQ; 45.4 kg final RQ
• Hexane	110-54-3	5000 lb final RQ; 2270 kg final RQ
1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed
U.S CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs		
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
• Toluene	108-88-3	Not Listed
• Xylene	1330-20-7	Not Listed
• Hexane	110-54-3	Not Listed
1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed
U.S CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs		
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
• Toluene	108-88-3	Not Listed
• Xylene	1330-20-7	Not Listed
• Hexane	110-54-3	Not Listed
1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed
U.S CERCLA/SARA - Section 313 - Emission Reporting		
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
• Toluene	108-88-3	1.0 % de minimis concentration
• Xylene	1330-20-7	1.0 % de minimis concentration
• Hexane	110-54-3	1.0 % de minimis concentration
1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed
U.S CERCLA/SARA - Section 313 - PBT Chemical Listing		
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
• Toluene	108-88-3	Not Listed
• Xylene	1330-20-7	Not Listed

• Hexane	110-54-3	Not Listed
1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed
U.S RCRA (Resource Conservation & Recovery Act) - Hazardous Constituents - Ap	pendix VIII to 40	CFR 261
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
• Toluene	108-88-3	waste number U220
• Xylene	1330-20-7	Not Listed
Hexane	110-54-3	Not Listed
1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed
U.S RCRA (Resource Conservation & Recovery Act) - List for Hazardous Constitu	ents	
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
• Toluene	108-88-3	
• Xylene	1330-20-7	
• Hexane	110-54-3	Not Listed
1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed

### **United States - California**

Environment		
U.S California - Proposition 65 - Carcinogens List		
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
• Toluene	108-88-3	Not Listed
Xylene	1330-20-7	Not Listed
Hexane	110-54-3	Not Listed
1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed
U.S California - Proposition 65 - Developmental Toxicity		
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
Toluene	108-88-3	developmental toxicity, initial date 1/1/91
• Xylene	1330-20-7	Not Listed
Hexane	110-54-3	Not Listed
1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed
U.S California - Proposition 65 - Reproductive Toxicity - Female		
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
Toluene	108-88-3	female reproductive toxicity, initial date 8/7/09
• Xylene	1330-20-7	Not Listed
Hexane	110-54-3	Not Listed
1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed
U.S California - Proposition 65 - Reproductive Toxicity - Male		
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
• Toluene	108-88-3	Not Listed
Xylene	1330-20-7	Not Listed
Hexane	110-54-3	Not Listed
1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed

## **United States - Pennsylvania**

Labor U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List		
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
• Toluene	108-88-3	

Xylene     Hexane     1,6-Diisocyanatohexane homopolymer	1330-20-7 110-54-3 28182-81-2	Not Listed Not Listed
U.S Pennsylvania - RTK (Right to Know) - Special Hazardous Substances		
Isobutylene-Isoprene polymer	9010-85-9	Not Listed
• Toluene	108-88-3	Not Listed
• Xylene	1330-20-7	Not Listed
Hexane	110-54-3	Not Listed
1,6-Diisocyanatohexane homopolymer	28182-81-2	Not Listed

#### **United States - Rhode Island**

9010-85-9	Not Listed
108-88-3	Toxic (skin); Flammable (skin)
1330-20-7	Toxic (skin); Flammable (skin)
110-54-3	Toxic; Flammable
28182-81-2	Not Listed
	108-88-3 1330-20-7 110-54-3

### 15.2 Chemical Safety Assessment

· No Chemical Safety Assessment has been carried out.

#### **Section 16 - Other Information**

**Revision Date** 

**Preparation Date** 

**Other Information** 

Disclaimer/Statement of Liability

- 28/February/2018
- 11/January/2012
- · Changes to this revision: Updated mailing address.
- The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information, is accurate, complete or representative. Firestone Building Products Company, LLC assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons, if reasonable safety procedures are not followed. Additionally, Firestone Building Products Company assumes no responsibility for injury to buyer, the buyer's employees, or any third persons caused by abnormal use of this material, even if reasonable safety procedures are followed.

**Key to abbreviations**NDA = No data available