

# Technical Information Sheet

Image Coming Soon

## UltraPly™ TPO Clear Cut Edge Sealant

Item Description	Item Number
Clear	W56TPOC002

### Description

Elevate UltraPly TPO Clear Cut Edge Sealant is a polymer-based sealant used to seal all cut edges of UltraPly TPO Membrane where the polyester reinforcement is exposed. It is approved for use with all Elevate TPO membranes.

### Method of Application

1. Surfaces to receive UltraPly TPO Clear Cut Edge Sealant must be clean, dry, and free of loose and foreign materials, oil and grease.
2. Allow the welded seam to cool prior to application of UltraPly TPO Cut Edge Sealant. Seam should be cool to the touch.
3. Clean seam area with Elevate Splice Wash SW-100 prior to treating the cut edge with sealant.
4. Trim the tip of the nozzle to provide approximately a 1/8" (3.175 mm) opening.
5. Apply an approximate 1/8" (3.175 mm) to 1/4" (6.35 mm) diameter bead of sealant to all exposed cut edges of UltraPly TPO Membrane with exposed reinforcement. The UltraPly TPO Clear Cut Edge Sealant can be used at 20 °F (-6.67 °C) and rising if blushing is not present.

### Clean-Up

Recommended cleaner is rubbing alcohol followed by soap and water.

### Coverage Rate

- 1/8" (3.175 mm) diameter bead: 188 lf/pt (57 m/0.47L)
- 1/4" (6.35 mm) diameter bead: 50 lf/pt (15.2 m/0.47L)

### Storage

- Store in original unopened containers at temperatures between 60 °F and 80 °F (15.6 °C and 26.7 °C) until ready for use.
- When exposed to lower temperatures, restore to room temperature prior to use.
- For option results, rotate stock to ensure stored material has not exceeded the shelf life of one (1) year.

## Shelf Life

Shelf life of one (1) year can be expected when stored in original, sealed container at temperatures between 60 °F and 80 °F (15.6 °C and 26.7 °C). Shelf life will be shortened if exposed to elevated temperatures for a prolonged period of time.

## Precautions

- Refer to Safety Data Sheets (SDS) for additional safety information.
- Flammable. Keep away from fire and open flames during storage and use. Do not smoke when using.
- Use only in well ventilated areas.
- Cover tightly when not in use.
- Do not contaminate with foreign materials.
- Do not thin.
- UltraPly TPO Clear Cut Edge Sealant is not to be used for splicing or as a general-purpose caulking.

## LEED® Information

Post-Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: Akron, OH

**NOTE: LEED® is a registered trademark of the U.S. Green Building Council**

Typical Properties	
Properties	Value
Base	Synthetic Rubber
Color	Clear
Solids	28 - 32%
Viscosity	3,000 – 4,000 cps
Weight/Gallon	7.4 lb/gal (3.4 kg/L)
V.O.C. Content	611 g/L
Cure Time	24 hours
Tack Free Time	4 hours

<b>Product Packaging</b>	
Bottle	1 Pint (0.47 L)
Carton	12 Squeeze Bottle with Applicator Nozzles
Carton Weight	13 lb (5.9 kg)

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.

Firestone, the brand of premier roofing, wall, and lining systems you know and trust, will be coming to you under a new name: Elevate. During our transition, products carrying the brand name **Firestone** will change to **Elevate** on product labels and packaging, Technical Information Sheets, and elsewhere. Only the brand name is changing. Our products remain the same.

For further information on our brand transition to Elevate, scan the code below with your smartphone, or visit our website: [www.holcimelevate.com](http://www.holcimelevate.com)

