

# Technical Information Sheet



## UltraPly™ TPO Large Pipe Flashing

Item Description	Item Number
White	W56TPO3013
Tan	W56TPOT013
Gray	W56TPOG013

### Description

Elevate UltraPly TPO Large Pipe Flashings are specifically designed for flashing of large round penetrations between 6" (150 mm) and 8" (200 mm) outside diameter. The pipe flashing fits various penetration sizes and can be cut as necessary to ensure a tight fit before installation.

### Method of Application

1. Penetration shall be clean of prior flashings or foreign material.
2. Cut out a circle above the level ring of the pipe flashing that is just smaller than the penetration.
3. Cut the extra material from the pipe flashing base around the indented circle.
4. Weld the flashing into place and install the clamp and sealant per current UltraPly TPO specifications.

### Storage

Store material in its original unopened packaging away from sources of physical damage or chemical contamination.

### Precautions

- Refer to Safety Data Sheet (SDS) for TPO systems for safety information.
- Contact a Regional Technical Coordinator at 1-800-428-4511 for specific recommendations regarding chemical or waste product compatibility with Elevate UltraPly TPO Large Pipe Flashing.

### LEED® Information

Post-Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: Wellford, SC

NOTE: LEED® is a registered trademark of the U.S. Green Building Council

**Product Data**

Material	Thermoplastic Polyolefin (TPO)
Colors	White, Tan, Gray
Size	Outside diameters of 6" (152 mm) to 8" (203 mm)
Clamp	All stainless steel, quick release, worm gear type

**Product Packaging**

Units per Carton	10 with 10 stainless steel clamps
Carton Weight	16 lb (7 kg)

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.