

Date Revised: 08/24/2022

Supersedes: 02/18/2019

### **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

Product Name(s): Five Star® Fluid Epoxy Grout/Component B

Synonyms: N/A

Product Use: Epoxy grouting of equipment

Restrictions on Use: To be used with Fluid Epoxy Grout/Component A

Manufacturer/Supplier Five Star Products, Inc.

2 Enterprise Drive, Suite 303 Shelton, CT 06484 USA

Phone #: 203-336-7900

Emergency Phone #: VelocityEHS 1-800-255-3924

(Outside the U.S. 1-813-248-0585)

### **SECTION 2: HAZARD(S) IDENTIFICATION-GHS INFORMATION**

**Classification:** Acute Toxicity – Oral Category 4

Acute Toxicity - Dermal, Category 3

Skin Corrosion, Category 1B Eye Damage, Category 1

Specific Target Organ Toxicity - Single Exposure, Category 3

Sensitization - Skin, Category 1

Label Elements/Hazard

**Pictograms:** 





Signal Word: Danger

**Hazard Statements:** H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

**Precautionary** P260 Do not breathe dust, fume, gas, mist, vapors, or spray.

**Statements/Prevention:** P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing should not be allowed out of the

workplace.

P280 Wear protective gloves, protective clothing, eye protection and

face protection.

P284 Wear respiratory protection.



Date Revised: 08/24/2022

Supersedes: 02/18/2019

**Response:** P330, P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P361, P353 If on skin (or hair): Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P340 If inhaled: Remove person to fresh air and keep comfortable for

breathing.

P351 If in eyes: Rinse cautiously with water for several minutes.

P338 Remove contact lenses, if present and easy to do. Continue

rinsing.

P310 Immediately call a poison center or doctor.

P333 If skin irritation or rash occurs: P313 Get medical advice /

attention.

P342 If experiencing respiratory symptoms: P310 Call a poison center

or doctor. P363 Wash contaminated clothing before reuse.

**Storage:** Store locked up.

**Disposal:** Dispose of contents/container in accordance with applicable regional,

national, and local laws and regulations.

**Hazards Not Otherwise** 

Classified:

Not Applicable

Ingredients with Unknown

**Toxicity:** 

Not Applicable

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS						
Hazardous Ingredient(s)	Common Name/Synonyms	CAS No.	% wt/wt			
Aliphatic Amines	Not Available	Trade Secret	40 - 60			
1,3-Benzenedimethanamine	Not Available	1477-55-0	40 - 60			

### **SECTION 4: FIRST AID MEASURES**

Inhalation: If inhaled: Remove person to fresh air and keep comfortable for

breathing.

If experiencing respiratory symptoms call poison center or doctor.

**Eye Contact:** If in eyes: Rinse cautiously with water for at least 30 minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. Immediately

call a poison center or doctor.

**Skin Contact:** If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower for at least 15 minutes. Immediately call a poison center or doctor if irritation develops. Wash contaminated clothing

before reuse.



Date Revised: 08/24/2022

Supersedes: 02/18/2019

**Ingestion:** If swallowed: Rinse mouth. Do NOT induce vomiting. Immediately call a

poison center or doctor. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Never give anything by mouth

to an unconscious person.

**General Advice:** In case of accident or if you feel unwell, seek medical advice immediately

(show the label or SDS where possible).

**Note to Physicians:** Symptoms may not appear immediately.

### **SECTION 5: FIRE-FIGHTING MEASURES**

Flammability and Explosion

Information:

Not flammable or combustible by OSHA/WHMIS criteria

Sensitivity to Mechanical

Impact:

This material is not sensitive to mechanical impact.

**Sensitivity to Static** 

Discharge:

This material is sensitive to static discharge at temperatures at or

above the flash point.

**MEANS OF EXTINCTION** 

**Suitable Extinguishing Media:** Small Fire: Dry chemical, CO2, or water spray.

Large Fire: Dry chemical, CO2, alcohol-resistant foam or water spray. Move containers from fire area if you can do it without risk. Dike fire-

control water for later disposal; do not scatter the material.

**Unsuitable Extinguishing** 

Media:

Not Applicable

**Product of Combustion:** 

Carbon monoxide. Oxides of nitrogen.

**Protection of Firefighters:** 

TOXIC; inhalation, ingestion or skin contact with material may cause severe injury or death. Contact with molten substance may cause severe burns to skin and eyes. Avoid any skin contact. Effects of contact or inhalation may be delayed. Fire may produce irritating, corrosive and/or toxic gases. Runoff from fire control or dilution water may be corrosive and/or toxic and cause pollution. Wear positive pressure self-contained breathing apparatus (SCBA). Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection. Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

Emergency Procedures: As an immediate precautionary measure, isolate spill or leak area in all

directions for at least 50 meters (150 ft). Stay upwind. Keep out of low areas. Ventilate enclosed areas. ELIMINATE all ignition sources (no

smoking, flares, sparks, or flames in immediate area).

Personal Precautions: Do not touch damaged containers or spilled material unless wearing

appropriate protective clothing. Use personal protection recommended

in Section 8.



Date Revised: 08/24/2022

Supersedes: 02/18/2019

**Environmental Precautions:** Prevent entry into waterway, sewers, basements, or confined areas.

**Methods for Containment:** Stop leak if you can do it without risk.

**Methods for Cleanup:** Absorb or cover with dry earth, sand, or other non-combustible material

and transfer to containers.

**Other Information:** See Section 13 for disposal considerations.

#### **SECTION 7: HANDLING AND STORAGE**

**Handling:** Do not swallow. Do not breathe mist, vapors, or spray. Do not get in

eyes, on skin, or on clothing. Wash thoroughly after handling. Do not eat, drink, or smoke when using this product. Contaminated work clothing should not be allowed out of workplace. See Section 8 for

information on Personal Protective Equipment.

**Storage:** Store locked up. Store away from incompatible materials. See Section

10 for information on incompatible materials. Keep out of reach of

children.

#### **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

### **Exposure Guidelines**

Component	CAS No.	ACGIH	OSHA
Aliphatic Amines	Trade Secret	No TLV established.	1.0 mg/m³(PEL)
1,3-Benzenedimethanamine	1477-55-0	No TLV established.	0.1 mg/m³(PEL)

PEL: Permissible Exposure Limit TLV: Threshold Limit Value.

**Engineering Controls:** Not normally required.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

**Eye/Face Protection:** Wear chemical safety goggles and full face shield. Ensure that eyewash

stations and safety showers are close to the workstation location. Use equipment for eye protection that meets the standards referenced for OSHA regulations in 29 CFR 1910.133 for Personal Protective

Equipment.

**Hand Protection:** Wear protective gloves. Rubber or polyethylene material is

recommended. Consult manufacturer specifications for further

information.

**Skin and Body Protection:** Wear protective clothing. Clothing with full length sleeves and pants

should be worn.

**Respiratory Protection:** Wear respiratory protection. If engineering controls and ventilation are

not sufficient to control exposure to below the allowable limits then an appropriate NIOSH/MSHA approved air-purifying respirator with organic vapor cartridge, or self- contained breathing apparatus must be used.



Date Revised: 08/24/2022

Supersedes: 02/18/2019

Supplied air breathing apparatus must be used when oxygen concentrations are low or if airborne concentrations exceed the limits of the air-purifying respirators.

General Hygiene Considerations:

Handle according to established industrial hygiene and safety practices.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES				
Appearance:	Liquid			
Color:	Straw Yellow			
Odor:	Ammoniacal			
Odor Threshold:	Not Available			
Physical State:	Liquid			
pH:	alkaline			
Melting Point / Freezing Point:	Liquid			
Initial Boiling Point:	245°C (473°F)			
Boiling Point:	245°C (473°C)			
Flash Point:	134°C (273°F)			
Evaporation Rate:	< 1; butyl acetate = 1			
Flammability (solid, gas):	Not Available			
Lower Flammability Limit:	Not Available			
Upper Flammability Limit:	Not Available			
Vapor Pressure:	15 mm Hg @ 148°C (298°F)			
Vapor Density:	Not Available			
Relative Density:	1.00			
Solubility:	Not Available			
Partition Coefficient: n-Octanol/Water:	Not Available			
Auto-ignition Temperature:	Not Available			
Decomposition Temperature:	Not Available			
Viscosity:	50 – 80 cps			
Percent Volatile, wt.%:	0%			
VOC Content, wt.%:	0%			
Density:	1.0			
Coefficient of Water/Oil Distribution:	Not Available			



Date Revised: 08/24/2022

Supersedes: 02/18/2019

#### **SECTION 10: STABILITY AND REACTIVITY**

Chemical Stability: Stable

**Possibility of Hazardous** 

**Reactions:** CO<sub>2</sub>, smoke, toxic vapors.

**Conditions to Avoid:** Avoid peroxides and acids.

**Incompatible Materials:** Epoxy resins under uncontrolled conditions.

#### **SECTION 11: TOXICOLOGICAL INFORMATION**

**Acute Toxicity** 

**Primary Irritant Effect** 

**On the Skin:** Irritant to skin and mucous membranes.

**Primary Irritant Effect** 

On the Eye: Irritating effect

**Sensitization:** Sensitization possible through skin contact.

Sensitizing effect through inhalation is possible by prolonged exposure.

**Additional Toxicological** 

Information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for

Preparations as issued in the latest version:

Irritant

Danger through skin adsorption.

Toxic and/or corrosive effects may be delayed up to 24 hours.

**Sensitization:** Sensitization possible by inhalation and/or dermal contact.

**Repeated Dose Toxicity:** Repeated exposures may result in skin and/or respiratory sensitivity.

#### **SECTION 12: ECOLOGICAL INFORMATION**

**Toxicity** 

**Aquatic Toxicity:** The material is harmful to the environment.

Persistence and

**Degradability:** The product is partly biodegradable. Significant residuals remain.

**Bio-accumulative Potential:** Does not accumulate in organisms.

**Mobility in Soil:** No further relevant information available.

**Ecotoxical Effects** 

**Remark:** Toxic for fish

**Additional Ecological Information** 

**General Notes:** This statement was deduced from products with a similar structure or



Date Revised: 08/24/2022

Supersedes: 02/18/2019

composition. Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the

environment cannot be excluded.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms.

PBT Assessment: Not applicable. vPvB Assessment: Not applicable.

**Other Adverse Effects:** No further relevant information available.

#### **SECTION 13: DISPOSAL CONSIDERATIONS**

#### **Waste Treatment Methods**

**Recommendation:** Must not be disposed together with household garbage. Do not allow

product to reach sewage system.

Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and

adhering to the necessary technical regulations.

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical

regulations.

Uncleaned Packaging

**Recommendation:** Disposal must be made according to official regulations.

#### **SECTION 14: TRANSPORT INFORMATION**

**US DEPARTMENT of** 

**TRANSPORTATION (DOT)** Corrosive Liquid, Basic, Organic, NOS

**Proper Shipping Name:** (1,3-Benzenedimethanamine)

Class: 8

**UN #:** UN3267

Packing Group: II

CANADA Transportation of

**Dangerous Goods (TDG)**Corrosive Liquid, Basic, Organic, NOS

**Proper Shipping Name:** (1,3-Benzenedimethanamine)

Class:

**UN #:** UN3267

Packing Group: II

Air Transport (ICAO-

IATA/DGR) Proper Shipping Corrosive Liquid, Basic, Organic, NOS

Name: (1,3-Benzenedimethanamine)

Class: 8



Date Revised: 08/24/2022

Supersedes: 02/18/2019

**UN #:** UN3267

Packing Group: II

Sea Transport (IMDG-Code/GGVSee)

**UN #:** 3267

Proper Shipping Name: Corrosive Liquid, Basic, Organic, NOS

(1,3-Benzenedimethanamine)

Class: 8

Packing Group: II

Marine Pollutant: No

**Special Provision(s):** Not Applicable

### **SECTION 15: REGULATORY INFORMATION**

**CHEMICAL INVENTORIES** 

**US (TSCA):** The components of this product are in compliance with the chemical

notification requirements of TSCA.

**CANADA (DSL):** The components of this product are in compliance with the chemical

notification requirements of the NSN Regulations under CEPA, 1999.

**FEDERAL REGULATIONS** 

**CANADA:** This product has been classified in accordance with the hazard

criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products

Regulations.

WHMIS Classification: Class D1B - Toxic Material

Class D2A - Respiratory sensitization

Class D2B - Skin sensitization Class E - Corrosive Material

**UNITED STATES:** This SDS had been prepared to meet the U.S. OSHA Hazard

Communication Standard, 29 CFR 1910.1200

**SARA Title III:** No components are listed.

**STATE REGULATIONS** 

Massachusetts US Massachusetts Commonwealth's Right-to-Know Las (Appendix A to

105 Code of Massachusetts Regulations Section 670.000).

Component:CAS No.RTK List:Aliphatic AminesTrade SecretListed



Date Revised: 08/24/2022

Supersedes: 02/18/2019

New Jersey US New Jersey Worker and Community Right-to-Know Act (New Jersey

Statute Annotated Section 34:5A-5).

Component:CAS No.RTK List:Aliphatic AminesTrade SecretListed

Pennsylvania US Pennsylvania Worker and Community Right-to-Know Law (34 Pa.

Code Chap. 301-323).

ComponentCAS No.RTK List:Aliphatic AminesTrade SecretListed

California

**California Prop 65:** 

This product contains the following Proposition 65 chemical:

Aliphatic Amines, Prop 65: Developmental

#### **SECTION 16: OTHER INFORMATION**

HMIS Rating:	Health	Flammability	Physical Hazard	Personal Protection
	3	1	0	X, E

**Disclaimer:** This information is furnished without warranty of any kind, expressed or

implied. Five Star Products, Inc. bases the information and recommendations in this document on data believed to be current and

accurate.