

Date Revised: 06/21/2018

Supersedes: 04/18/2018

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name(s): Five Star® Pile Jacket Epoxy Grout LV / Component C Aggregate

Five Star® Pile Jacket Epoxy Grout LPL / Component C Aggregate

Five Star® Epoxy Chock EX / Component C Aggregate

Synonyms: Pile Jacket Sand

Product Use: Aggregate for reactive polymer construction products. Designed for use

with appropriate hardener and resin.

Restrictions on Use: Use per Five Star Products recommendations

Manufacturer/Supplier Five Star Products, Inc.

60 Parrott Drive

Shelton, CT 06484 USA

Phone #: 203-336-7900

Emergency Phone #: CHEM-TEL 1-800-255-3924

(Outside the U.S. 1-813-248-0585)

SECTION 2: HAZARD(S) IDENTIFICATION-GHS INFORMATION

Classification: Carcinogenicity – Category 1A

Specific Target Organ Toxicity (Single Exposure) – Cat 3 Specific Target Organ Toxicity (Repeated Exposure) – Cat 2

Label Elements/Hazard Pictograms:





Signal Word: Danger

Hazard Statements: H335 May cause respiratory irritation

H350 May cause cancer by inhalation

H373 May cause damage to organs through prolonged or repeat

exposure

Precautionary P260 Do not breathe dust, fume, gas, mist, vapors, or spray.

Statements/Prevention: P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and

understood.

P280 Wear protective gloves, protective clothing, eye protection and

face protection.

P271 Use only outdoors or in a well-ventilated area.



Date Revised: 06/21/2018

Supersedes: 04/18/2018

Response: P330, P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P340 If inhaled: Remove person to fresh air and keep comfortable for

breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.
P314 Get medical advice and attention if you feel unwell.

P351 If in eyes: Rinse cautiously with water for several minutes. P338 Remove contact lenses, if present and easy to do. Continue rinsing.

Storage: Store locked up. Store in a well-ventilated place. Keep container

tightly closed.

Disposal: Dispose of contents/container in accordance with applicable regional,

national, and local laws and regulations.

Hazards Not Otherwise

Classified: Not applicable

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS				
Hazardous Common Ingredient(s) Name/Synonyms		CAS No.	% wt/wt	
Quartz	Silicon Dioxide, Silica Sand, Crystalline Silica	14808-60-7	99-100	

SECTION 4: FIRST AID MEASURES

Inhalation: If inhaled: Remove person to fresh air and keep comfortable for

breathing.

If experiencing respiratory symptoms call poison center or doctor.

Eye Contact: If in eyes: Immediately rinse with water for a prolonged period while

holding the eyelids wide open. Seek medical attention if material is embedded in eye. If eye irritation persists: Get medical advice and

attention.

Skin Contact: Rinse immediately with plenty of water. Gently wash with plenty of soap

and water. Obtain medical attention if irritation persists.

Ingestion: If swallowed: Do not induce vomiting: seek medical advice immediately

and show this container or label. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Never give anything

by mouth to an unconscious person.

General Advice: If medical advice is needed, have product container or label at hand. In

case of accident or if you feel unwell, seek medical advice immediately

(show the label or SDS where possible).

Note to Physicians: Symptoms may not appear immediately. Treat symptomatically.



Date Revised: 06/21/2018

Supersedes: 04/18/2018

SECTION 5: FIRE-FIGHTING MEASURES

Flammability and Explosion

Information: Not flammable or combustible by OSHA/WHMIS criteria.

Sensitivity to Mechanical

Impact: This material is not sensitive to mechanical impact.

Sensitivity to Static

Discharge: This material is not sensitive to static discharge.

MEANS OF EXTINCTION

Suitable Extinguishing Media: Small Fire: Dry chemical, CO2, or water spray.

Large Fire: Dry chemical, CO2, alcohol-resistant foam or water spray. Move containers from fire area if you can do it without risk. Dike fire-

control water for later disposal; do not scatter the material.

Unsuitable Extinguishing

Media: None known

Product of Combustion: Non-combustible

Protection of Firefighters: As in any fire, wear self-contained breathing apparatus pressure-

demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Emergency Procedures: Use personal protective equipment. Ensure adequate ventilation. Keep

people from spill. Avoid dust formation.

Personal Precautions: Avoid inhalation of dust. Do not get into eyes, on skin, or clothing.

Environmental Precautions: The environmental impact of this product has not been fully investigated.

Methods for Containment: Cover powder spill with plastic sheet or tarp to minimize spreading.

Collect this material into a disposal container by sucking or sweeping up.

Methods for Cleanup: Pick up and transfer to properly labeled containers.

Other Information: See Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

Handling: Wear personal protective equipment. Ensure adequate ventilation. Avoid

dust formation. Do not breathe dust. Prevent contact with skin, eyes,

and clothing. Wash thoroughly after handling.

Storage: Keep containers tightly closed in a cool, dry, and well-ventilated place.

Store locked up.



Date Revised: 06/21/2018

Supersedes: 04/18/2018

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Component	CAS No.	ACGIH TLV	OSHA PEL
Quartz**	14808-60-7	TWA: 0.025mg/m ³ respirable fraction	TWA: 0.050 mg/m ³ AL: 0.025 mg/m ³

PEL: Permissible Exposure Limit TLV: Threshold Limit Value AL: Actionable Level

Engineering Controls: Ensure adequate ventilation, especially in confined areas. Avoid dust

protection.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

Eye/Face Protection: Tightly fitting safety goggles

Hand Protection: Impervious gloves. Impervious clothing.

Skin and Body Protection: Impervious gloves. Impervious clothing. Handle in accordance with good

industrial hygiene and safety practice. Always wash your hands immediately after handling this product, and once again before leaving the workplace. Wear suitable protective clothing. Wash contaminated

clothing before reuse.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA

approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance

with current local regulations.

General Hygiene

Considerations: Handle according to established industrial hygiene and safety practices.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES		
Appearance:	Granular	
Color:	Gray, Tan	
Odor:	None	
Odor Threshold:	None	
Physical State:	Solid	
pH:	Not Applicable	
Melting Point / Freezing Point:	Not Applicable	
Initial Boiling Point:	Not Applicable	
Boiling Point:	Not Applicable	
Flash Point:	Not Applicable	

^{**} Respirable(< 6 micron) fraction for product is < 0.1%.



Date Revised: 06/21/2018

Supersedes: 04/18/2018

Evaporation Rate:	Not Applicable
Flammability (solid, gas):	Not Applicable
Lower Flammability Limit:	Not Applicable
Upper Flammability Limit:	Not Applicable
Vapor Pressure:	Not Applicable
Vapor Density:	Not Applicable
Relative Density:	2.5-2.8
Solubility:	Negligible
Partition Coefficient: n-Octanol/Water:	Not Applicable
Auto-ignition Temperature:	Not Applicable
Decomposition Temperature:	>3,000°F (1649°C)
Viscosity:	Not Applicable
Percent Volatile, wt.%:	Not Applicable
VOC Content, wt.%:	Not Applicable
Density:	2.5-2.8 g/cc
Coefficient of Water/Oil Distribution:	Not Applicable

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability: Stable under recommended storage conditions.

Possibility of Hazardous

Reactions: None under normal processing.

Conditions to Avoid: Exposure to water – product may harden on contact with water.

Incompatible Materials: Strong oxidizers.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation: Repeated inhalation of respirable crystalline silica (quartz) may cause

silicosis, a fibrosis (scarring) of the lungs. Silicosis is irreversible and may be fatal. Silicosis increases the risk of contracting pulmonary tuberculosis. Some studies suggest that repeated inhalation of respirable crystalline silica may cause other adverse health effects

including lung and kidney cancer.

Eye Contact: Contact may cause mechanical irritation and possible injury.

Skin Contact: No adverse effects expected.



Date Revised: 06/21/2018

Supersedes: 04/18/2018

Ingestion: No adverse effects expected for incidental ingestion.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Quartz	500 – 22,500 mg/kg (Rat)	Not Established	Not Established*

^{*}LCL50: 0.3 mg/m3 / 10Y (Human)

Symptoms related to the physical, chemical and

toxicological characteristics: No information available.

Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization: May cause sensitization by skin contact.

Mutagenic Effects: No information available.

Carcinogenicity: The table below indicates whether each agency has listed any ingredient

as a carcinogen. Crystalline silica (quartz) has been classified by the International Agency for Research on Cancer (IARC) as a known human

carcinogen (Group 1). May cause cancer by inhalation.

Chemical Name	ACGIH	IARC	NTP	OSHA
Quartz	A2*	Group 1	Known	X

^{*}The respirable fraction as a whole is less than 0.1% and anticipated usage would generate far less than 0.1% as a respirable quantity above exposure guidelines as noted in Section 8.

ACGIH: (American Conference of Governmental Industrial

Hygienists): A2 - Suspected Human Carcinogen

IARC: (International Agency

for Research on Cancer): Group 1 - Carcinogenic to Humans

NTP: (National Toxicity

Program): Known Carcinogen

OSHA: (Occupational Safety &

Health Administration): X - Present

Reproductive Toxicity: No information available.

STOT - single exposure: May cause respiratory irritation.

STOT - repeated exposure: Causes damage to organs through prolonged or repeated exposure if

inhaled. Lungs.

Chronic Toxicity: Inhalation overexposure to free crystalline silica may cause delayed lung

injury including silicosis, a disabling and potentially fatal lung disease.

Aspiration Hazard: No information available.

Numerical measures of toxicity - Product

The following values are calculated based on chapter 3.1 of the GHS document:

LD 50 Oral: 500 mg/kg; Acute toxicity estimate



Date Revised: 06/21/2018

Supersedes: 04/18/2018

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Aquatic Toxicity: Not Applicable

Persistence and

Degradability: Not Applicable

Bio-accumulative Potential: Not Applicable

Mobility in Soil: No further relevant information available

Ecotoxical Effects

Remark: Not Applicable

Additional Ecological

Information: Not Applicable

General Notes: No ecological effects are known other than to occupy volume as fill.

PBT Assessment: Not Applicable

vPvB Assessment: Not Applicable

Other Adverse Effects: No further relevant information known

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Recommendation: This material as supplied is not a hazardous waste according to Federal

regulations (40CFR261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is

processed or otherwise altered.

Uncleaned Packaging

Recommendation:

Disposal must be made according to official regulations. Do not re-use

empty containers.

SECTION 14: TRANSPORT INFORMATION

US DEPARTMENT of TRANSPORTATION (DOT)

Proper Shipping Name: Not Regulated

Class: Not Applicable

UN #: Not Applicable

Packing Group: Not Applicable

Air Transport: ICAO-

IATA/DGR (Cargo) Proper

Shipping Name: Not Regulated

Class: Not Applicable



Date Revised: 06/21/2018

Supersedes: 04/18/2018

UN#: Not Applicable

Packing Group: Not Applicable

Sea Transport: (IMDG-

Code/GGVSee): Not Regulated

Class: Not Applicable

UN #: Not Applicable

Packing Group: Not Applicable

CANADA Transportation of Dangerous Goods (TDG)

Proper Shipping Name: Not Regulated

Class: Not Applicable

UN #: Not Applicable

Packing Group: Not Applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Other:

Code.

SECTION 15: REGULATORY INFORMATION

CHEMICAL INVENTORIES

US (TSCA): The components of this product are in compliance with the chemical

notification requirements of TSCA.

The components of this product are in compliance with the chemical CANADA (DSL):

notification requirements of NSN Regulations under CEPA, 1999.

U.S. FEDERAL REGULATIONS: Section 313 of Title III of the Superfund Amendments and

> Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and

Title 40 of the CFR, Part 372.

UNITED STATES: This SDS has been prepared to meet the US OSHA Hazard Communication

Standard, 29 CFR 1910.1200

SARA 311/312 Hazard

Acute health hazard - Yes Categories: Chronic Health hazard - Yes

Fire Hazard - No

Sudden Release of Pressure - No

Reactive Hazard - No

US STATE Right to Know

Regulations

Chemical Name	NJ	MA	PA	IL	RI
Quartz	X	X	X		X

California This product contains the following Proposition 65 chemicals.

California Prop 65: Chemical Name: Quartz CAS-No: 14808-60-7 CA Prop. 65: Carcinogen



Date Revised: 06/21/2018

Supersedes: 04/18/2018

SECTION 16: OTHER INFORMATION

HMIS (Hazardous Material Information System:

Health	Flammability	Physical Hazard	Personal Protection
1	0	0	E, X

Disclaimer:

This information is furnished without warranty of any kind, expressed or implied. Five Star Products, Inc. bases the information and recommendations in this document on data believed to be current and accurate.