

Date Revised: 08/24/2022

Supersedes: 10/22/2015

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name(s): Five Star® Rapid Epoxy Grout /Component B Hardener

Synonyms: Rapid Epoxy Hardener

Product Use: High Performance machinery grouting. For use with Rapid Epoxy

Aggregate and Rapid Epoxy Resin.

Restrictions on Use: Should be used with Epoxy Aggregate and Rapid Epoxy Resin

Manufacturer/Supplier Five Star Products, Inc.

> 2 Enterprise Drive, Suite 303 Shelton, CT 06484 USA

Phone #: 203-336-7900

Emergency Phone #: VelocityEHS 1-800-255-3924

(Outside the U.S. 1-813-248-0585)

SECTION 2: HAZARD(S) IDENTIFICATION-GHS INFORMATION

Classification: Acute Toxicity - Oral Category 4

Acute Toxicity - Dermal, Category 3

Skin Corrosion, Category 1 Eye Damage, Category 1

Sensitization - Respiratory, Category 1

Sensitization - Skin, Category 1

Label Elements/Hazard

Pictograms:





Signal Word: Danger

Hazard Statements: Harmful if swallowed, H302.

Harmful in contact with skin, H312.

Causes severe skin burns and eye damage, H314.

May cause respiratory irritation, H335. May cause an allergic skin reaction, H317.

Precautionary

Do not breathe dust, fume, gas, mist, vapors, or spray, P260. **Statements/Prevention:**

Wash thoroughly after handling, P264.

Do not eat, drink or smoke when using this product, P270.

Contaminated work clothing should not be allowed out of the workplace,

P272.

Wear protective gloves, protective clothing, eye protection and face

protection, P280.

Wear respiratory protection, P284.



Date Revised: 08/24/2022

Supersedes: 10/22/2015

Response: If swallowed: Rinse mouth. Do NOT induce vomiting, P330, P331.

If on skin (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower, P361, P353.

If inhaled: Remove person to fresh air and keep comfortable for

breathing, P340.

If in eyes: Rinse cautiously with water for several minutes, P351. Remove contact lenses, if present and easy to do. Continue rinsing,

P338.

Immediately call a poison center or doctor, P310.

If skin irritation or rash occurs, P333: Get medical advice/attention,

P313.

If experiencing respiratory symptoms, P342: Call a poison center or doctor, P310. Wash contaminated clothing before reuse, P363.

Storage: Store locked up.

Disposal: Dispose of contents/container in accordance with applicable regional,

national, and local laws and regulations.

Hazards Not Otherwise

Classified:

N/A

Ingredients with Unknown

Toxicity:

Some of this product mixture may contain ingredients of unknown

acute toxicity.

| SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS | | | | |
|---|-------------------------|----------|---------|--|
| Hazardous Ingredient(s) | Common Name/Synonyms | CAS No. | % wt/wt | |
| Triethylenetetramine | Not available | 112-24-3 | 80-95 | |
| Tris-2,4,6- (Dimethylaminomethyl) Phenol | Not available | 90-72-2 | 5-20 | |

SECTION 4: FIRST AID MEASURES

Inhalation: If inhaled: Remove person to fresh air and keep comfortable for

breathing.

If experiencing respiratory symptoms call poison center or doctor.

Eye Contact: If in eyes: Rinse cautiously with water for at least 30 minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center or doctor.

Skin Contact: If on skin (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower for at least 15 minutes. Immediately call a poison center or doctor if irritation develops. Wash contaminated

clothing before reuse.



Date Revised: 08/24/2022

Supersedes: 10/22/2015

Ingestion: If swallowed: Rinse mouth. Do NOT induce vomiting. Immediately call

a poison center or doctor. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Never give anything by mouth

to an unconscious person.

General Advice: In case of accident or if you feel unwell, seek medical advice

immediately (show the label or SDS where possible).

Note to Physicians: Symptoms may not appear immediately.

SECTION 5: FIRE-FIGHTING MEASURES

Flammability and Explosion

Information:

Not flammable or combustible by OSHA/WHMIS criteria

Sensitivity to Mechanical

Impact:

This material is not sensitive to mechanical impact.

Sensitivity to Static

Discharge:

This material is sensitive to static discharge at temperatures at or

above the flash point.

MEANS OF EXTINCTION

Suitable Extinguishing Media: Small Fire: Dry chemical, CO2, or water spray.

Large Fire: Dry chemical, CO2, alcohol-resistant foam or water spray. Move containers from fire area if you can do it without risk. Dike fire-

control water for later disposal; do not scatter the material.

Unsuitable Extinguishing

Media:

N/A

Product of Combustion: Carbon monoxide. Oxides of nitrogen.

Protection of Firefighters: TOXIC; inhalation, ingestion or skin contact with material may cause

severe injury or death. Contact with molten substance may cause severe burns to skin and eyes. Avoid any skin contact. Effects of contact or inhalation may be delayed. Fire may produce irritating, corrosive and/or toxic gases. Runoff from fire control or dilution water may be corrosive and/or toxic and cause pollution. Wear positive pressure self-contained breathing apparatus (SCBA). Wear chemical

protective clothing that is specifically recommended by the

manufacturer. It may provide little or no thermal protection. Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct

contact with the substance is possible.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Emergency Procedures: As an immediate precautionary measure, isolate spill or leak area in all

directions for at least 50 meters (150 ft). Stay upwind. Keep out of low areas. Ventilate enclosed areas. ELIMINATE all ignition sources (no

smoking, flares, sparks, or flames in immediate area).

Personal Precautions: Do not touch damaged containers or spilled material unless wearing

appropriate protective clothing. Use personal protection recommended

in Section 8.

Environmental Precautions: Prevent entry into waterway, sewers, basements, or confined areas.



Date Revised: 08/24/2022

Supersedes: 10/22/2015

Methods for Containment: Stop leak if you can do it without risk.

Methods for Cleanup: Absorb or cover with dry earth, sand, or other non-combustible

material and transfer to containers.

Other Information: See Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

Handling: Do not swallow. Do not breathe mist, vapors, or spray. Do not get in

eyes, on skin, or on clothing. Wash thoroughly after handling. Do not eat, drink, or smoke when using this product. Contaminated work clothing should not be allowed out of workplace. See Section 8 for

information on Personal Protective Equipment.

Storage: Store locked up. Store away from incompatible materials. See Section

10 for information on incompatible materials. Keep out of reach of

children.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Engineering Controls:

| Component | CAS No. | ACGIH | OSHA |
|--|----------|---------------------|---------------------|
| Triethylenetetramine | 112-24-3 | No TLV established. | No PEL established. |
| Tris-2,4,6- (Dimethylaminomethyl) Phenol | 90-72-2 | No TLV established. | No PEL established. |

PEL: Permissible Exposure Limit TLV: Threshold Limit Value.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

Eye/Face Protection: Wear chemical safety goggles and full face shield. Ensure that eyewash

stations and safety showers are close to the workstation location. Use equipment for eye protection that meets the standards referenced for OSHA regulations in 29 CFR 1910.133 for Personal Protective

Equipment.

Hand Protection: Wear protective gloves. Rubber or polyethylene material is

Not normally required.

recommended. Consult manufacturer specifications for further

information.

Skin and Body Protection: Wear protective clothing. Clothing with full length sleeves and pants

should be worn.

Respiratory Protection: Wear respiratory protection. If engineering controls and ventilation are

not sufficient to control exposure to below the allowable limits then an appropriate NIOSH/OSHA approved air-purifying respirator with organic vapor cartridge, or self-contained breathing apparatus must be used.



Date Revised: 08/24/2022

Supersedes: 10/22/2015

Supplied air breathing apparatus must be used when oxygen concentrations are low or if airborne concentrations exceed the limits of the air-purifying respirators.

General Hygiene Considerations:

Handle according to established industrial hygiene and safety practices.

| SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES | | | | |
|---|--|--|--|--|
| Appearance: | Liquid | | | |
| Color: | Yellow or White | | | |
| Odor: | Fishy, Ammoniacal | | | |
| Odor Threshold: | Not available | | | |
| Physical State: | Liquid | | | |
| pH: | Not applicable | | | |
| Melting Point / Freezing Point: | Liquid | | | |
| Initial Boiling Point: | > 100 °C (212 °F) | | | |
| Boiling Point: | Not available | | | |
| Flash Point: | 400 °F(204 °C) | | | |
| Evaporation Rate: | Not applicable | | | |
| Flammability (solid, gas): | Not applicable | | | |
| Lower Flammability Limit: | Not applicable | | | |
| Upper Flammability Limit: | Not applicable | | | |
| Vapor Pressure: | Not available | | | |
| Vapor Density: | Not available | | | |
| Relative Density: | 0.98 | | | |
| Solubility: | Partial | | | |
| Partition Coefficient: n-Octanol/Water: | Not available | | | |
| Auto-ignition Temperature: | Can autoignite in air at approximately 676°F | | | |
| Decomposition Temperature: | Not available | | | |
| Viscosity: | 60-80 | | | |
| Percent Volatile, wt.%: | 0% | | | |
| VOC Content, wt.%: | 0% | | | |
| Density: | 0.98 g/cc | | | |
| Coefficient of Water/Oil Distribution: | Not available | | | |



Date Revised: 08/24/2022

Supersedes: 10/22/2015

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability: Stable

Possibility of Hazardous

Reactions: CO₂, smoke, toxic vapors. **Conditions to Avoid:** Avoid peroxides and acids.

Incompatible Materials: Epoxy resins under uncontrolled conditions, acid, oxidizing material,

halogenated, organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute Toxicity: LD50(CAS# 112-24-3) 2500 mg/kg(oral-rat); LD50(CAS# 90-72-2)

1670 mg/kg(oral-rat)

Primary Irritant Effect

On the Skin: Irritant to skin and mucous membranes.

Primary Irritant Effect

On the Eye: Irritating effect.

Sensitization: Sensitization possible through skin contact.

Sensitizing effect through inhalation is possible by prolonged exposure.

Additional Toxicological

Information:

The product shows the following dangers according to the

calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

Danger through skin adsorption.

Toxic and/or corrosive effects may be delayed up to 24 hours.

Sensitization: Sensitization possible by inhalation and/or dermal contact.

Repeated Dose Toxicity: Repeated exposures may result in skin and/or respiratory sensitivity.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Aquatic Toxicity: The material is harmful to the environment.

Persistence and

Degradability: The product is partly biodegradable. Significant residuals remain.

Bio-accumulative Potential: Does not accumulate in organisms.

Mobility in Soil: No further relevant information available.

Ecotoxical Effects

Remark: Toxic for fish.

Additional Ecological Information



Date Revised: 08/24/2022

Supersedes: 10/22/2015

General Notes: This statement was deduced from products with a similar structure or

composition. Due to available data on eliminability/decomposition

and bioaccumulation potential prolonged term damage of the

environment cannot be excluded.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms.

PBT Assessment: PBT: Not applicable.

vPvB Assessment: vPvB: Not applicable.

Other Adverse Effects: No further relevant information available.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Recommendation: Must NOT be disposed together with household garbage. Do not allow

product to reach sewage system.

Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and

adhering to the necessary technical regulations.

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical

regulations.

Uncleaned Packaging Recommendation:

Disposal must be made according to official regulations.

SECTION 14: TRANSPORT INFORMATION

US DEPARTMENT of

TRANSPORTATION (DOT) UN2735, Amines, Liquid, Corrosive, NOS

Proper Shipping Name: (Triethylenetetramine/Tris-2,4,6-(Dimethylaminomethyl) Phenol)

Class: 8

UN #: UN2735

Packing Group: II

Air Transport: ICAO-

IATA/DGR (Cargo) Proper UN2735, AMINES, LIQUID, CORROSIVE, NOS

Shipping Name: (Triethylenetetramine/Tris-2,4,6-(Dimethylaminomethyl)Phenol)

Class: 8

UN#: UN2735

Packing Group: II

Sea Transport UN2735, AMINES, LIQUID, CORROSIVE, NOS

(IMDG-Code/GGVSee): (Triethylenetetramine/Tris-2,4,6-(Dimethylaminomethyl)Phenol)

Class: 8



Date Revised: 08/24/2022

Supersedes: 10/22/2015

UN #: UN2735

Packing Group: II

CANADA Transportation of Dangerous Goods (TDG)

Proper Shipping Name:

UN2735, Amines, Liquid, Corrosive, NOS

(Triethylenetetramine/Tris-2,4,6-(Dimethylaminomethyl)Phenol)

Class: 8

UN #: UN2735

Packing Group: II

SECTION 15: REGULATORY INFORMATION

CHEMICAL INVENTORIES

US (TSCA): The components of this product are in compliance with the chemical

notification requirements of TSCA.

CANADA (DSL): The components of this product are in compliance with the chemical

notification requirements of the NSN Regulations under CEPA, 1999.

FEDERAL REGULATIONS

CANADA: This product has been classified in accordance with the hazard

criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products

Regulations.

WHMIS Classification: Class D1B - Toxic Material.

Class D2A - Respiratory sensitization.

Class D2B - Skin sensitization. Class E - Corrosive Material.

HAZARD SYMBOLS:



UNITED STATES: This SDS had been prepared to meet the U.S. OSHA Hazard

Communication Standard, 29 CFR 1910.1200

SARA Title III: No components are listed.

STATE REGULATIONS

Massachusetts US Massachusetts Commonwealth's Right-to-Know Las (Appendix A to

105 Code of Massachusetts Regulations Section 670.000).

Component:CAS No.RTK List:Triethylenetetramine112-24-3Listed



Date Revised: 08/24/2022

Supersedes: 10/22/2015

New Jersey US New Jersey Worker and Community Right-to-Know Act (New Jersey

Statute Annotated Section 34:5A-5).

Component:CAS No.RTK List:Triethylenetetramine112-24-3Listed

Pennsylvania US Pennsylvania Worker and Community Right-to-Know Law (34 Pa.

Code Chap. 301-323).

ComponentCAS No.RTK List:Triethylenetetramine112-24-3Listed

California This product does not contain chemicals known to the State of

California Prop 65: California to be Carcinogenic.

SECTION 16: OTHER INFORMATION

HMIS Information:

Health Flammability Physical Hazard Personal Protection

3 1 1 E

Disclaimer: This information is furnished without warranty of any kind, expressed or

implied. Five Star Products, Inc. bases the information and

recommendations in this document on data believed to be current and

accurate.