

# REDUCE DOWNTIME!



RAPID SURFACE REPAIR

## EASY MIX™

**For Rapid Repair of Concrete and Asphaltic Surfaces, Potholes, & Spalls**

- SAVE TIME AND MONEY BY REDUCING DOWNTIME
- HEAVY TRAFFIC READY IN AS LITTLE AS 30 MINUTES\*
- SIMPLE BUCKET MIX
- HIGH COMPRESSIVE STRENGTH
- MAKE REPAIRS YEAR ROUND

\*Dependent upon air and substrate temperatures

For information 1-800-243-2206 • [FiveStarProducts.com](http://FiveStarProducts.com)



No "off-season," with placements down to 0°F (-18°C)



**Build on our strength**

RAPID SURFACE REPAIR

# EASY MIX™

Fast turnaround repair for concrete, asphalt, runways & bridges



## FIVE STAR



### Innovation

- Traffic ready in as little as 30 minutes\*
- Make repairs year round - hot or cold
- No priming required to bond to concrete, asphalt, steel, or wood
- Waterproof, chemically resistant membrane protects substrates from freeze thaw spalling

Conveniently formulated for bucket mixing, this product is a self-leveling, low viscosity, two-part liquid polyurethane-hybrid polymer used to make an impact and traffic resistant polymer concrete.

When supplemented with its proprietary blended aggregate, it is used to repair and rehabilitate concrete and asphaltic pavements and can be installed at temperatures down to 0 °F (-18 °C). Within minutes of placement, durable, long-lasting repairs are able to handle vibration, heavy traffic, and thermal movement.

\*Dependent upon air and substrate temperatures



**Expansion Joint and Bridge Header Reconstruction**

**Control Joint Filler**

**Airport Runways**

**Walkways, Warehouse Floors, Parking Lots**

**Conduit Channels**

### TYPICAL PROPERTIES AT 77 °F (25 °C)

| Mix Ratio by Volume                | (1) Part A : (1) Part B |
|------------------------------------|-------------------------|
| Viscosity @ 77 °F (25 °C) - mixed  | 60 cps                  |
| Gel Time, Neat                     | 2 to 3 minutes          |
| Working time with Aggregate        | Approx. 5 minutes       |
| Cured                              |                         |
| Color                              | Dark Grey               |
| Cure Time (reopen to traffic)      | 30 minutes              |
| Hardness, Durometer D, ASTM D-2240 | 70                      |
| Tensile Strength, ASTM D-412       | 3,000 psi (20.7 MPa)    |
| Compressive Strength, ASTM C-579B  |                         |
| 1 hour                             | 2,000 psi (13.8 MPa)    |
| 1 day                              | 6,000 psi (41.3 MPa)    |
| 7 days                             | 7,000 psi (48.2 MPa)    |
| 28 days                            | 8,000 psi (55.1 MPa)    |
| Elongation, ASTM D-638             | 10 - 15%                |
| Bond Strength, ASTM C-882          | 2,000 psi (13.8 MPa)    |

SEE PRODUCT DATASHEET FOR COMPLETE SPECIFICATIONS



**FIVE STAR PRODUCTS, INC.**  
2 Enterprise Drive • Suite 303 • Shelton, CT 06484-4656 USA  
Phone: +1 203-336-7900 • Sales/Support: 1-800-243-2206  
**FiveStarProducts.com**

© 2023 Five Star Products, Inc.  
na13070eng Rev B • Printed in the U.S.A.