



---

**SECTION 1: PRODUCT AND COMPANY INFORMATION**

---

**PRODUCT NAME:** EverGuard PVC Membrane Conditioner  
**TRADE NAME:** N/A  
**CHEMICAL NAME /  
SYNONYM:** Solvent  
**CHEMICAL FAMILY:** N/A  
**MANUFACTURER:** GAF Materials Corporation  
**ADDRESS:** 1 Campus Drive, Parsippany, NJ 07054  
**24-HOUR EMERGENCY  
PHONE (CHEMTREC):** 800 – 424 – 9300  
**INFORMATION ONLY:** 800 – 766 – 3411  
**PREPARED BY:** Corporate EHS  
**APPROVED BY:** Corporate EHS

---

**SECTION 2: HAZARD IDENTIFICATION**

---

**NFPA and HMIS RATINGS:**

	NFPA Hazard Rating		HMIS Hazard Rating
Health	1	Health	1
Flammable	3	Flammable	3
Reactive	0	Reactive	0
Special Hazards	-	Personal Protection	X

**GHS LABEL ELEMENTS:**

**GHS  
CLASSIFICATION:** Flammable Liquid - Category 2  
Eye Irritant - Category 2A  
Target Organ (SE) - Category 3

GHS  
PICTOGRAMS:



SIGNAL  
WORD: Danger

HAZARD  
STATEMENTS: Highly flammable liquid and vapor.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.

**ADDITIONAL HAZARD IDENTIFICATION INFORMATION:**

**PRIMARY ROUTE OF EXPOSURE:** Inhalation, Skin Contact, Eye Contact, Ingestion

**SIGNS & SYMPTOMS OF EXPOSURE**

- EYES:** May cause severe eye irritation.
- SKIN:** May cause drying of skin resulting in skin irritation and dermatitis.
- INGESTION:** Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be harmful if swallowed.
- INHALATION:** Inhalation may cause central nervous system effects. May cause drowsiness or dizziness. May cause irritation to the respiratory tract. May be harmful if inhaled.

**ACUTE HEALTH HAZARDS:** See above.

**CHRONIC HEALTH HAZARDS:** May cause central nervous system depression (weakness, fatigue, dizziness, drowsiness, nausea, headache, and/or unconsciousness). Experiments for acetone have shown reproductive toxicity effects on laboratory animals. May cause adverse effects to liver or kidney.

See section 11 for additional toxicological information.

**CARCINOGENICITY:** N/A

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

CHEMICAL NAME	CAS #	% (BY WT)	OCCUPATIONAL EXPOSURE LIMITS		
			OSHA	ACGIH	OTHER
Acetone	67-64-1	100%	TWA (vacated): 750 ppm STEL(vacated): 1000 ppm	TWA: 500 ppm STEL: 750 ppm	NIOSH IDLH: 2500 ppm TWA: 250 ppm

			TWA: 1000 ppm		
--	--	--	---------------	--	--

**SECTION 4: FIRST AID MEASURES**

**FIRST AID PROCEDURES**

- EYES:** Flush with warm water for 15 minutes and seek immediate medical attention.
- SKIN:** Wash with soap and water for 15 minutes. If irritation persists, contact a physician.
- INHALATION:** Move victim to fresh air. If breathing has stopped, give artificial respiration. Seek immediate medical attention.
- INGESTION:** Do not induce vomiting. Get medical attention and advise the physician of the nature of the material.

**NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:** Treat symptomatically.

**SECTION 5: FIRE FIGHTING PROCEDURES**

- SUITABLE EXTINGUISHING MEDIA:** Foam, dry chemical, carbon dioxide, water spray.
- HAZARDOUS COMBUSTION PRODUCTS:** Carbon dioxide, carbon monoxide, chlorine compounds, fluoride compounds and hydrocarbons.
- RECOMMENDED FIRE FIGHTING PROCEDURES:** Wear self-contained breathing apparatus with pressure-demand, full face piece SCBA and full protective gear.
- UNUSUAL FIRE & EXPLOSION HAZARDS:** If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors may ignite and/or cause flash fires. Never use welding or cutting torch on or near container (even empty) because product (even just residue) can ignite explosively. Vapors are invisible, flammable, and heavier than air, and may accumulate in low areas and spread long distances. Keep away from heat/spark/open flame/hot surfaces.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**ACCIDENTAL RELEASE MEASURES:** Stay upwind, out of low areas, and ventilate closed spaces before entering. Eliminate all ignition sources (flames, hot surfaces and

sources of electrical sparks). Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered containers for recovery or disposal, or remove with inert absorbent. Use only non-sparking tools. Place absorbent diking materials in covered containers for disposal. Prevent contamination of sewers, streams and groundwater with spilled material or used absorbent.

---

**SECTION 7: HANDLING AND STORAGE**

---

**HANDLING AND STORAGE:**

Keep container closed when not in use. Store in a cool, dry, and well-ventilated place. Keep away from heat and all sources of ignition. Do not smoke while using this product.

**OTHER PRECAUTIONS:**

Containers may be hazardous when empty. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers.

---

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

---

**ENGINEERING CONTROLS /  
VENTILATION:**

Provide sufficient mechanical ventilation to maintain exposure below exposure limits.

**RESPIRATORY PROTECTION:**

If personal exposure concentrations cannot be maintained below the appropriate exposure limits using engineering controls, a NIOSH/MSHA approved organic vapor air purifying respirator may be appropriate based on employer-determined exposure levels. Air supplied or SCBA respirators may be required when the measured chemical concentration exceeds the capacity of the air purifying respirator or when personal exposure levels are unknown.

**EYE PROTECTION:**

Wear safety glasses with side shields or chemical goggles; face shield if there is a potential for splashing.

**SKIN PROTECTION:**

Wear chemical resistant gloves when handling this product to avoid prolonged skin contact.

**OTHER PROTECTIVE EQUIPMENT:**

Various application methods can dictate the use of additional protective safety equipment such as chemical resistant boots, impermeable aprons, etc. when handling this product to avoid prolonged skin contact.

**WORK HYGIENIC PRACTICES:**

Wash exposed skin prior to eating, drinking or smoking and at the end of each shift. Wash contaminated clothing prior to reuse. A source of clean water should be available to flush eyes and skin.



**SECTION 12: ECOLOGICAL INFORMATION****ECOLOGICAL INFORMATION:**

Chemical Name	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Acetone	Not listed	Leuciscus idus: LC50 = 11300 mg/L/48h Salmo gairdneri: LC50 = 6100 mg/L/24h	EC50 = 14500 mg/L/15 min	EC50 = 39 mg/L/48h EC50 = 12700 mg/L/48h EC50 = 12600 mg/L/48h

**SECTION 13: DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL METHOD:** This product, as supplied, is regulated as a hazardous waste by the U.S. Environmental Protection Agency (EPA) under Resource Conservation and Recovery Act (RCRA) regulations. If discarded in its purchased form, this product is a RCRA hazardous waste. It is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or residue of the product remains classified a hazardous waste as per 40 CFR 261, Subpart C. State or local regulations may also apply if they differ from the federal regulation.

**RCRA HAZARD CLASS:** D001, Ignitable Hazardous Waste

**SECTION 14: TRANSPORTATION INFORMATION****U.S. DOT TRANSPORTATION**

**PROPER SHIPPING NAME:** Acetone

**HAZARD CLASS:** 3

**ID NUMBER:** UN1090

**PACKING GROUP:** II

**DOT LABEL REQUIRED:** Flammable Liquids

**OTHER:** N/A

## IATA/IMDG/IMO

**PROPER SHIPPING NAME:** Acetone  
**HAZARD CLASS:** 3  
**ID NUMBER:** UN1090  
**PACKING GROUP:** II

**SECTION 15: REGULATORY INFORMATION****U.S. FEDERAL REGULATIONS**

**TSCA:** This product and its components are not listed on the TSCA 8(b) inventory.

**CERCLA:** This material, as supplied contains one or more substances regulated as a hazardous substance under CERCLA (40 CFR 302)

Component	Hazardous Substance RQs	CERCLA EHS RQs
Acetone	5000 lb	-

**SARA**

**311/312 HAZARD CATEGORIES:** Fire Hazard, Acute Health Hazard

**313 REPORTABLE INGREDIENTS:** None

**CALIFORNIA PROPOSITION 65:** None

Other state regulations may apply. Check individual state requirements. The following components appear on one or more of the following state hazardous substances lists:

Chemical Name	CAS #	CA	MA	MN	NJ	PA	RI
Acetone	67-64-1	Yes	Yes	Yes	Yes	Yes	Yes

**SECTION 16: OTHER INFORMATION**

---

**ADDITIONAL COMMENTS:** N/A

**DATE OF PREVIOUS SDS:** New Product

**CHANGES SINCE PREVIOUS SDS:** N/A

---

This information relates to the specific material designated and may not be valid for such material used on combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.